

BAGGAGE CARTS



LINEMA SERIES LZ



MAIN NOTES

- Transport of palletised or/and non palletised goods in airport ground operations.
- Load capacity that ranges from 800 to 2 000 kg enables to mach units to specific operation conditions and requirements.
- Have the same chassis frame design of different measures, while superstructure can be modified according to customer requirements.
- Are easy to handle with, and require minimum maintenance.
- Modular design enables reduction of maintenance costs.
- $\bullet \ \ \mathsf{Baggage}\,\mathsf{carts}\,\mathsf{are}\,\mathsf{safe}\,\mathsf{to}\,\mathsf{operate}, \mathsf{and}\,\mathsf{meet}\,\mathsf{all}\,\mathsf{IATA}\,\mathsf{AHM}\,\mathsf{requirements}.$

CAPACITY PARAMETERS

| | LZ08 | LZ15 | LZ20 |
|---|----------|----------|----------|
| WEIGHT APPROX. | 379 kg | 390 kg | 431 kg |
| LOAD CAPACITY | 800 kg | 1 500 kg | 2 000 kg |
| LOAD PLATFORM LENGTH | 2 000 mm | 2 200 mm | 2 500 mm |
| LOAD PALTFORM EIDTH | 1 200 mm | 1 300 mm | 1 600 mm |
| HEIGHT OF LOADING PALTFORMABOVE SURFACE | 600 mm | 600 mm | 600 mm |