



Revision Dates	
1	08.15.24
2	01.01.25

SHEET TITLE
Foundation

Drawing Date 08.27.26

Check By

Drawn By FRANCIS N.

Scale

Job Number 022225

Sheet Number



1. ALL OTHER SPECIFICATION FOR STANDARD HOLD DOWN TO COMPLY WITH SIMPSON REQUIREMENTS
2. ALL HOLD DOWN MUST BE TIED INTO PLACE PRIOR TO FOUNDATION INSPECTION
3. DEPTH SPECIFIED ON SCHEDULE
4. ALL ANCHOR BOLTS SHALL HAVE A 3" 3" .229" MIN. WASHER ON TOP OF SILL PLATES

SHEAR WALL SCHEDULE										
NO.	SHEATING	EDGE NAILING	FEILD NAILING	FRAMING MEMBER	CONNECTION AT TOP PLATE	FOUNDATION ANCHORAGE	SILL PLATE NAILING TO WOOD FLOOR	CAPACITY (plf)	POST-HOL DOWN	SIMPSON HOLDOWN
1	23/32 OSB	8d @ 6"	8d @ 12"	2x	A-35 @ 16"	5/8" ∅ @ 48"	16d @ 5"	260	4x4 OR (2) 2X4	HDU5