ENGINEERING REFERENCE & SPECIFICATION

SwiftGet

Enterprise Download Accelerator, BitTorrent Client & Browser Integration Engine

Comprehensive Architectural Blueprint, Turbo Network Scheduler Specifications, Browser Protocol Handoff, BitTorrent Engine Integration, IDM Parity Verification, and Operational Deployment Manual.

System Version: 1.0.0 Stable (WinUI 3 / .NET 8 / C# 12)

Target Platform: Windows 10 (19041+) and Windows 11 (x64 / ARM64)

Build Artifacts: WiX v4 MSI Installer, Chromium MV3 Extension, Firefox MV3 Extension

Publication Date: November 2026

Classification: High-Throughput Production Software Specification

Table of Contents

1. Executive Overview & Mission Statement **Page 3**

1.1 Architectural Philosophy & Zero-Merge Invariant 3

1.2 System Technology Stack & Solution Topology 4

1.3 IDM & FDM Comparative Parity Matrix 5

2. Core System Architecture **Page 6**

2.1 Component Layering & Subsystem Isolation 6

2.2 Inter-Process Communication & Single-Instance Flow 7

2.3 Data Storage Architecture (SQLite WAL Engine) 8

3. The SwiftGet Turbo Engine **Page 10**

3.1 SparseFileWriter: Zero-Overhead Direct Offset Allocation 10

3.2 Dynamic Midpoint Connection Splitting (1-32 Connections) 11

3.3 BBR-Style Link Capacity & Bottleneck Estimator 12

3.4 HTTP/2 Connection Trap Mitigation & ALPN Negotiation 13

3.5 Token-Bucket Bandwidth Shaping & Rate Limiter 14

4. File Name Resolution & Compound Extension Recovery **Page 15**

4.1 Single Source of Truth: IFileNameResolver Protocol 15

4.2 RFC 6266 & RFC 5987 Content-Disposition Grammar 16

4.3 Multi-Dot Compound Extension Engine (.tar.gz, .iso, .zip) 17

4.4 User Lock Precedence & Magic-Byte Recovery 18

5. Browser Integration & Native Messaging Bridge **Page 19**

5.1 Chromium MV3 Service Worker Interception Flow 19

5.2 Mozilla Firefox MV3 Non-Suspended Architecture 20

5.3 Native Messaging Host Protocol (32-bit LE stdio) 21

5.4 Authenticated Loopback REST & WebSocket API (:52384) 22

5.5 Window Foreground Takeover: AllowSetForegroundWindow 23

5.6 Keyboard Interception Modifiers (Alt Bypass, Insert Force) 24

6. BitTorrent Engine Subsystem **Page 25**

6.1 MonoTorrent Architecture & Distributed Hash Table (DHT) 25

6.2 Magnet URI Parsing & BEP 9 Metadata Probing 26
6.3 Piece Map Visualization & Sequential Media Mode 27
6.4 Swarm Optimization, Anti-Stall & Port Forwarding 28
7. Streaming Media Sniffing & Sidecar Orchestration Page 29
7.1 DOM & Network Media Sniffer Floating Overlay 29
7.2 Signature-Verified yt-dlp & ffmpeg Sidecars 30
7.3 HLS / DASH Multi-Bitrate Recording & Lossless Muxing 31
7.4 DRM Detection & Strict Non-Circumvention Policy 32
8. Desktop Interface & User Manual Page 33
8.1 Main Window: Virtualized ItemsRepeater & Ribbon Toolbar 33
8.2 Download File Info Dialog & Category Auto-Assignment 34
8.3 Download Progress Dialog & Live Telemetry Grid 35
8.4 Download Complete Dialog & Post-Download Actions 36
8.5 Batch Downloader & Pattern Generator ([001-100]) 37
8.6 Recursive Site Grabber & Depth Crawler 38
8.7 Floating Drop Box Widget & Clipboard Monitor 39
9. Security Invariants & Threat Mitigation Page 40
9.1 Path Traversal Guard (CVE-Class Defenses) 40
9.2 Mark-of-the-Web (Zone.Identifier) & Antivirus Scanner Hooks 41
9.3 Cryptographic Token Security & Constant-Time Validation 42
10. Packaging, Deployment & CLI Reference Page 43
10.1 WiX Toolset v4/v5 Release Packaging 43
10.2 Command-Line Interface Reference Table 44
10.3 Diagnostic Bundles & Troubleshooting Matrix 45

1. Executive Overview & Mission Statement

1.1 Architectural Philosophy & Zero-Merge Invariant

SwiftGet is engineered as a modern, high-throughput, IDM-class download accelerator designed for Windows 10 and 11. It matches and exceeds the raw transfer performance, visual conventions, and browser takeover responsiveness of legacy Win32 utilities such as Internet Download Manager (IDM) and Free Download Manager (FDM), while delivering a 100% modern, secure, and clean architecture implemented in C# 12 and .NET 8 with WinUI 3.

> **The SwiftGet Core Architectural Invariant: "No-Merge Direct Sparse Allocation"**
> Legacy download managers typically download chunks into separate temporary files on disk (e.g. `part001.tmp`, `part002.tmp`). Upon reaching 100%, they execute an expensive, disk-thrashing concatenation merge. For a 50 GB file, this consumes 100 GB of temporary disk space and freezes the user's computer for several minutes. SwiftGet operates strictly on pre-allocated sparse files: all concurrent HTTP range streams and BitTorrent workers write directly to their assigned byte offsets via atomic `RandomAccess.WriteAsync`. When the last byte arrives, zero merge is required—the file is immediately finalized and closed.

1.2 System Technology Stack & Solution Topology

The SwiftGet codebase is strictly structured into modular components to ensure clean boundaries, headless testing capabilities, and long-term maintainability:


Project Assembly	Target Framework	Primary Responsibilities	Key Technologies
SwiftGet.Core	.NET 8.0 AnyCPU	Data models, SQLite schema, PathResolver, FileNameResolver, MimeTypeMap	Microsoft.Data.Sqlite, System.Text.Json
SwiftGet.Engine	.NET 8.0 AnyCPU	Turbo scheduler, HTTP probing, dynamic connection splitter, BitTorrent engine, loopback API	SocketsHttpHandler, MonoTorrent, SparseFileWriter
SwiftGet.Media	.NET 8.0 AnyCPU	Managed sidecar orchestrator, HLS/DASH recorder, stream muxing, DRM detection	yt-dlp, ffmpeg sidecars, process isolation
SwiftGet.NativeHost	.NET 8.0 win-x64	Stdio binary bridge for Chrome/Edge/Firefox native messaging	Native stdio framing, SingleInstanceIpc
SwiftGet.App	.NET 8.0 win-x64 (WinAppSDK)	IDM-parity desktop GUI, virtualized items repeater, segmented dialogs	WinUI 3, CommunityToolkit.Mvvm, WinRT Interop
extension/	WebExtension MV3	Chrome, Edge, Brave, Opera, and Firefox interception extensions	Service worker, native messaging, webRequest

1.3 IDM & FDM Comparative Parity Matrix

Feature Capability	Internet Download Manager (IDM)	Free Download Manager (FDM)	SwiftGet Implementation
Dynamic Connection Splitting	Up to 32 connections, midpoint split	Static chunking (fixed count)	Adaptive Concurrency (1-32), BBR link capacity estimation
File Finalization Architecture	Temporary part files + merge step	Sparse / Direct write	Direct Sparse Write-At (Zero merge step, instant finish)
BitTorrent & Magnet Links	Unsupported (HTTP/FTP only)	Full BitTorrent integration	Full MonoTorrent integration (DHT, PeX, Piece Map visualizer)
Browser Interception (MV3)	Proprietary injected DLL / Hook	Native messaging	MV3 Service Worker + Stdio Native Host + Fast Foreground Takeover
Media Sniffing & Capture	In-browser video panel	Built-in video downloader	Multi-format sniffing panel + HLS/DASH lossless recording
Modern High-DPI UI	Legacy GDI / Win32 (Bitmap scaling)	Qt Framework	Modern WinUI 3 (Fluent Design, Mica, 60fps virtualization)

2. Core System Architecture

2.1 Component Layering & Subsystem Isolation



2.2 Inter-Process Communication & Single-Instance Flow

SwiftGet guarantees that only one desktop UI process runs at any time. When a secondary download command is launched from the Windows command line, browser extension, or file association, the second process transfers the request payload to the running primary instance over the Windows Named Pipe: `\\.\pipe\SwiftGet.SingleInstance.<Username>`.

The message format is serialized as UTF-8 JSON containing the URL, initial filename, target directory, category, session cookies, referrers, custom headers, and browser window coordinate bounding boxes.

2.3 Data Storage Architecture (SQLite WAL Engine)

Download state persistence is managed by `SqliteDatabase.cs` in `SwiftGet.Core`. It is configured strictly with SQLite Write-Ahead Logging (WAL) to provide zero-lock contention between concurrent thread workers writing chunk telemetry and the UI reading items for display:

```
PRAGMA journal_mode = WAL;
PRAGMA synchronous = NORMAL;
PRAGMA foreign_keys = ON;
PRAGMA busy_timeout = 5000;
```

3. The SwiftGet Turbo Engine

3.1 SparseFileWriter: Zero-Overhead Direct Offset Allocation

The `SparseFileWriter` is a specialized unmanaged file wrapper implemented in `SwiftGet.Engine.IO`. It eliminates file fragmentation and guarantees instantaneous finalization:

1. **Sparse Flag Activation:** Invokes Windows API `DeviceIoControl` with control code `FSCTL_SET_SPARSE` on NTFS/ReFS volumes. This allows the OS file system to allocate file ranges dynamically without requiring the disk to zero-fill gigabytes of space upfront.
2. **Direct Offset Streaming:** Each connection worker maintains an asynchronous pipeline. Upon reading a chunk of network data (typically 64 KB to 256 KB), it executes:

   ```
   await RandomAccess.WriteAsync(_fileHandle, buffer, fileOffset, cancellationToken);
   ```

3. **Instant Finalization:** When all workers complete, the file length is truncated to the exact `TotalBytes` and the handle is flushed and closed. The file is immediately available on disk with zero merge delay.

3.2 Dynamic Midpoint Connection Splitting (1-32 Connections)

Traditional multi-threaded downloaders assign fixed chunk boundaries at the beginning of the transfer. If connection 1 encounters network congestion, the overall download stalls waiting for that single thread.

The SwiftGet `DynamicRangeScheduler` implements continuous dynamic midpoint splitting:

- When a connection completes its assigned byte range, it does not terminate.
- The scheduler scans all active connections and identifies the segment with the largest remaining byte distance:

  ```
  remainingBytes = segment.EndOffset - segment.CurrentOffset + 1;
  ```

- If `remainingBytes >= minSplitSize` (default: 1 MB), the remaining range is split at the midpoint:

  ```
  splitPoint = segment.CurrentOffset + (remainingBytes / 2);
  var oldEnd = segment.EndOffset;
  segment.EndOffset = splitPoint - 1;

  // Spawn new worker for second half
  var newSegment = new DownloadSegment(splitPoint, oldEnd);
  SpawnConnectionWorker(newSegment);
  ```

- This guarantees that all available TCP connections remain 100% saturated until the entire file has finished transferring.

3.3 BBR-Style Link Capacity & Bottleneck Estimator

Implemented in `CapacityEstimator.cs`, SwiftGet continuously calculates:

- **Bottleneck Bandwidth (BtlBw):** Windowed max-filter tracking delivered bytes over a 10-sample sliding window.
- **Minimum Round-Trip Time (RTprop):** Windowed min-filter tracking TCP handshake latency and time-to-first-byte (TTFB).
- **Bottleneck Identification:** Identifies whether the transfer is constrained by the local network adapter, ISP line throttling, or remote server per-connection bandwidth limits. When per-connection limits are detected, the concurrency controller scales up connections up to 32 to maximize throughput.

3.4 HTTP/2 Connection Trap Mitigation & ALPN Negotiation

Critical Performance Hazard: The HTTP/2 Multiplexing Bottleneck

Under standard .NET `SocketsHttpHandler`, if an HTTP/2 connection is negotiated, all subsequent range requests to the same host are multiplexed over a *single TCP connection*. This defeats multi-connection acceleration because all streams share one congestion window (cwnd). SwiftGet explicitly sets:

```
handler.EnableMultipleHttp2Connections = true;
```

Furthermore, for multi-connection segmented downloads, SwiftGet configures HTTP version policy to `RequestVersionOrLower` with HTTP/1.1 prioritized, ensuring distinct parallel TCP sockets are established to bypass server-side per-connection traffic policing.

4. File Name Resolution & Compound Extension Recovery

4.1 Single Source of Truth: IFileNameResolver Protocol

A classic flaw in download managers is disjointed filename resolution: the initial dialog determines a filename from a URL slug, while the background engine writes to a different filename or loses the file extension.

SwiftGet unifies all filename logic into a single authoritative service: `IFileNameResolver` in `SwiftGet.Core.IO`.

4.2 Resolution Priority Matrix

When downloading a file, SwiftGet evaluates filename candidates strictly in order of descending authority:

Priority Level	Source	Condition	Example Output
1 (Highest)	**User Lock**	User explicitly edited the filename in the dialog	`MyCustomName.zip`
2	**Content-Disposition**	RFC 6266 / RFC 5987 header returned by server	`Wondershare_UniConverter_18.zip`
3	**Final Redirect URL**	Filename present in redirected URI path	`ubuntu-26.04-desktop.iso`
4	**Query-String Hint**	URL parameter hints (e.g. `?filename=...`)	`setup_installer.exe`
5	**Content-Type MIME Map**	Recover extension from MIME header	`download.tar.gz`
6	**Magic Byte Sniffer**	First 8 KB payload signature inspection	`archive.zip` (PK header)
7 (Lowest)	**Fallback Slug**	URL path segment or generic placeholder	`download_a1b2c3d4.bin`

4.3 Multi-Dot Compound Extension Engine

Standard .NET `Path.GetExtension("archive.tar.gz")` returns only `.gz`, which causes utilities to incorrectly categorize tarballs or corrupt complex archives upon renaming. SwiftGet includes an intelligent compound extension parser:

```
// Correctly extracts compound archives
resolver.GetCompoundExtension("archive.tar.gz")  // Returns ".tar.gz"
resolver.GetCompoundExtension("data.tar.bz2")   // Returns ".tar.bz2"
resolver.GetCompoundExtension("backup.tar.xz")  // Returns ".tar.xz"
resolver.GetCompoundExtension("disc.iso")       // Returns ".iso"
```

5. Browser Integration & Native Messaging Bridge

5.1 Chromium MV3 & Firefox Interception Architecture

SwiftGet ships with custom extensions for Chromium (Google Chrome, Microsoft Edge, Brave, Opera, Vivaldi) and Mozilla Firefox built to Manifest V3 standards:

- **Chromium (MV3):** Because Manifest V3 deprecates blocking `webRequest` in service workers, SwiftGet intercepts downloads using `chrome.downloads.onCreated` and `onDeterminingFilename`. The extension captures URL, session cookies, referrers, and user agents, instantly cancels and erases the browser's internal download item, and forwards the transfer payload to SwiftGet.
- **Firefox (MV3):** Leverages Firefox's native support for blocking `webRequest.onHeadersReceived`, intercepting the request *before* the browser initiates disk allocation.
- **Wake-Up & Heartbeat:** To prevent MV3 service workers from suspending during user clicks, the extension utilizes keep-alive alarms and reconnects on every download event.

5.2 Native Messaging Host Protocol (32-bit LE stdio)

The native messaging host (`SwiftGet.NativeHost.exe`) communicates with the browser via standard input and standard output. The framing protocol adheres strictly to browser specifications:

```
+-------------------------+-------------------------------------------------------------+
| Length Header (4 Bytes) | Message Payload (N Bytes UTF-8 JSON)                        |
| 32-bit Little-Endian    | {"action":"interceptDownload","url":"https://...","...":""} |
+-------------------------+-------------------------------------------------------------+
```

5.3 Window Foreground Takeover: AllowSetForegroundWindow

> **Windows OS Restriction: Foreground Window Management**
>
> Windows restricts background processes from stealing focus via `SetForegroundWindow`. If a background process calls it directly, Windows merely flashes the taskbar icon.
>
> SwiftGet solves this natively:
>
> 1. When the user clicks a download in Chrome, Chrome is the current foreground process.
> 2. Chrome spawns `SwiftGet.NativeHost.exe`, inheriting foreground privileges.
> 3. The Native Host calls Win32 `AllowSetForegroundWindow(swiftGetAppPid)`.
> 4. `WindowActivator.cs` in `SwiftGet.App` uses `AttachThreadInput` and `SetWindowPos(HWND_TOPMOST)` to reliably pop the "Download File Info" dialog in front of the user immediately.

5.4 Keyboard Interception Modifiers

SwiftGet replicates the classic IDM keyboard modifier conventions:

- **Holding `Alt` (Bypass Switch):** Completely disables SwiftGet interception for the clicked link, allowing the browser's built-in download manager to handle the file.
- **Holding `Insert` (Force Switch):** Forces SwiftGet to capture the clicked link immediately, even if the file extension or MIME type is not on the automatic interception list.

6. BitTorrent Engine Subsystem

6.1 MonoTorrent Engine Integration

SwiftGet integrates a fully managed BitTorrent client engine built upon `MonoTorrent` in `SwiftGet.Engine.Torrent`:

- **DHT (Distributed Hash Table):** Connects to bootstrap nodes (router.bittorrent.com, dht.transmissionbt.com) allowing trackerless torrent discovery.
- **Peer Exchange (PeX) & Local Peer Discovery (LSD):** Automatically discovers swarm peers across local subnets and active swarms.
- **UPnP and NAT-PMP:** Automatically maps external router ports dynamically for incoming peer connections.
- **Protocol Encryption:** Enforces `EncryptionTypes.All` (PreferEncryption / RequireEncryption) to prevent ISP bandwidth throttling.

6.2 Magnet URI Protocol & BEP 9 Metadata Probing

When a magnet link (`magnet:?xt=urn:btih:...`) is captured:

1. SwiftGet extracts the info-hash and display name using `MagnetUriParser`.
2. The engine joins the DHT swarm and requests torrent metadata from active peers using BEP 9 (Extension for Transfer of Metadata).
3. The "Add Torrent" dialog displays the complete file list, total sizes, and piece layout before the user confirms the download location.

6.3 Piece Map Visualization & Sequential Media Mode

SwiftGet features an interactive, real-time Piece Map control (`PieceMapControl.xaml`):

- Downsamples swarms of 5,000+ pieces into visual 2D block arrays using `PieceGridDownsampler.cs`.
- Colors blocks dynamically: *Available* (gray), *Downloading* (blue), *Complete & Verified* (green).
- **Sequential Mode:** When enabled, pieces are prioritized from index `0` to `N` sequentially rather than rarest-first, allowing users to play video and audio files while the download is actively in progress.

7. Streaming Media Sniffing & Sidecar Orchestration

7.1 DOM & Network Media Sniffer Floating Overlay

SwiftGet's browser extension includes an active media observer (`content.js` , `sniffer.css`):

- Monitors HTML5 `<video>` and `<audio>` elements as well as network stream requests (`.m3u8` , `.mpd` , `.mp4` , `.webm`).
- Renders a floating, non-intrusive "Download Video" overlay badge adjacent to the active player.
- Provides a quick multi-bitrate resolution picker (1080p, 720p, 480p, Audio Only).

7.2 Managed Sidecars: yt-dlp & ffmpeg

Media streaming extraction and transmuxing are delegated to isolated, managed sidecar executables:

```
SwiftGet/
  sidecars/
    yt-dlp.exe    (CLI JSON stream metadata extractor)
    ffmpeg.exe    (Multi-stream audio/video lossless remuxer)
```

All sidecars are verified against cryptographic SHA-256 signatures before execution. Command arguments are sanitized against injection vulnerabilities using `SidecarCommandSanitizer.cs` .

7.3 DRM Detection & Strict Non-Circumvention Policy

> **Legal & Security Policy: DRM Protected Content**
>
> SwiftGet strictly adheres to digital copyright laws and anti-circumvention standards. If a stream contains Widevine, PlayReady, or FairPlay DRM encryption (detected via stream manifest headers `pssh` or `_has_drm` flags), SwiftGet immediately halts extraction and displays an informative notification that protected DRM streams cannot be captured.

8. Desktop Interface & User Manual

8.1 Main Window Layout

The main window is designed for maximum information density, instant responsiveness, and adherence to classic IDM layout paradigms:

- **Ribbon Toolbar:** Quick action buttons for *Add URL*, *Resume*, *Stop*, *Stop All*, *Delete*, *Delete Completed*, *Options*, *Scheduler*, and *Start Queue*.
- **Category Sidebar:** Quick filtering by file type: *All Downloads*, *Compressed*, *Programs*, *Video*, *Audio*, *Documents*, and *Torrents*, with live count badges.
- **Virtualized Downloads Table:** Built using WinUI 3 `ItemsRepeater`. Handles over 10,000 active and completed downloads with smooth 60fps scrolling and sub-millisecond memory updates.
- **Status Bar:** Displays current active connection count, aggregate download speed, bandwidth priority mode, and available disk space on the primary storage drive.

8.2 Download Progress Dialog & Live Telemetry Grid

When a download is active, double-clicking or selecting it opens the `DownloadProgressDialog`:

```
+-------------------------------------------------------------------------------------+
| SwiftGet - Wondershare UniConverter 18.0.1.66 (x64) Multilingual [FileCR].zip       |
+-------------------------------------------------------------------------------------+
| Status: Downloading (63.7%)           Time Left: 00:00:08                           |
| File Size: 405.66 MB                  Downloaded: 258.21 MB                         |
| Transfer Rate: 16.77 MB/s             Resume Capability: Yes                        |
+-------------------------------------------------------------------------------------+
| [========================== PROGRESS BAR 63.7% ==================================] |
+-------------------------------------------------------------------------------------+
| Active Connections:                                                                 |
|   #   |   Status   |      Offset / Range       |   Downloaded   |    Transfer Rate    |
|   1   | Receiving  |        0 - 106,341,281    |     68.12 MB   |        4.21 MB/s    |
|   2   | Receiving  |  106,341,282 - 212,682,563|     65.40 MB   |        4.18 MB/s    |
|   3   | Receiving  |  212,682,564 - 319,023,845|     64.20 MB   |        4.15 MB/s    |
|   4   | Receiving  |  319,023,846 - 425,365,126|     60.49 MB   |        4.23 MB/s    |
+-------------------------------------------------------------------------------------+
| [Hide Details]                        [ Speed Limiter ]             [Pause] [Cancel] |
+-------------------------------------------------------------------------------------+
```

8.3 Batch URL Downloader & Recursive Site Grabber

- **Batch Downloader (`BatchDownloadDialog.xaml`):** Allows expanding formatted numeric or alphabetical URL ranges (e.g. `https://example.com/images/img_[001-100].jpg`) with zero memory bloat, automatically generating 100 queued items.
- **Site Grabber (`GrabberWizardDialog.xaml`):** A multi-stage recursive crawler that parses entire websites up to configurable hyperlink depths, filtering targets by file extension (e.g. download all `.pdf` manuals or `.png` assets from a documentation portal).

9. Security Invariants & Threat Mitigation

9.1 Path Traversal Guard (CVE-Class Defenses)

Remote servers can attempt directory traversal attacks by supplying malicious filenames in `Content-Disposition` headers (e.g. `filename="../../Windows/System32/evil.dll"`).

SwiftGet passes all paths through `PathTraversalGuard.EnsureSafePath()` in `SwiftGet.Core.IO`:

```
// Strips directory separators, URL encodings, and verifies boundary
string safeFileName = Path.GetFileName(rawFileName);
string fullPath = Path.GetFullPath(Path.Combine(baseDirectory, safeFileName));
if (!fullPath.StartsWith(Path.GetFullPath(baseDirectory), StringComparison.OrdinalIgnoreCase))
{
    throw new SecurityException("Directory traversal attempt blocked.");
}
```

9.2 Mark-of-the-Web (Zone.Identifier) & Antivirus Hooks

Files downloaded from the public internet must be tagged to ensure the Windows security subsystem protects the user:

- **NTFS Alternate Data Streams (ADS):** Upon completion, `MarkOfTheWeb.cs` attaches a `Zone.Identifier` stream indicating `ZoneId=3` (Internet Zone).
- **Antivirus Scanning Hook:** Automatically queries the Windows IAttachmentExecute API or launches the user's configured antivirus executable (Windows Defender, ESET, Bitdefender) against the completed file.

10. Packaging, Deployment & CLI Reference

10.1 WiX Toolset v4/v5 Release Packaging

SwiftGet is compiled and distributed as an enterprise WiX MSI installer:

- **Binary Output:** `dist/SwiftGet-1.0.0-x64.msi` (205 MB self-contained).
- **Native Registry Configuration:** Automatically writes browser native messaging host keys to `HKCU\Software\Google\Chrome\NativeMessagingHosts\com.swiftget.native` and `HKCU\Software\Mozilla\NativeMessagingHosts\com.swiftget.native`.
- **Clean Uninstall:** Full uninstallation support removing all program files, shortcuts, and native messaging registrations cleanly without registry pollution.

10.2 Command-Line Interface (CLI) Reference

SwiftGet features full command-line interoperability matching classic IDM syntax:

CLI Flag	Syntax Example	Operational Description
`/d <URL>`	`SwiftGet.exe /d "https://ex.com/f.zip"`	Adds the specified download URL to the queue.
`/s`	`SwiftGet.exe /s`	Starts processing the active transfer queue immediately.
`/p <Path>`	`SwiftGet.exe /d "..." /p "D:\Files"`	Overrides the local target save directory.
`/f <FileName>`	`SwiftGet.exe /d "..." /f "setup.exe"`	Overrides the local destination filename.
`/q`	`SwiftGet.exe /d "..." /q`	Enqueues download silently without popping the confirmation dialog.
`/h`	`SwiftGet.exe /h`	Disconnects/hangs up dial-up or active network connections on finish.
`/a`	`SwiftGet.exe /d "..." /a`	Adds to download queue in paused state without starting transfer.

10.3 Diagnostic Bundles & Troubleshooting Matrix

Observed Symptom	Probable Root Cause	Remediation / Diagnostic Action
Browser download bubble appears instead of SwiftGet	Extension disabled or Native Host registry unpinned	Reinstall extension from `dist/extension/` or run `scripts/register-native-host.ps1`.
Download starts at single-connection speed	Remote server lacks `Accept-Ranges: bytes` header	Check dialog "Resume Capability: No". Server does not permit multi-connection segmentation.
HTTP 403 Forbidden on resume	Signed download URL has expired (CDN token expiry)	Right-click download -> "Refresh Download Address" to re-authenticate with the browser.
Progress dialog fails to focus in front	Windows OS foreground restrictions	Verify Native Host is registered and executing `AllowSetForegroundWindow`.

SwiftGet Production Release Seal

This document serves as the formal specification and technical manual for SwiftGet Version 1.0.0. All architecture modules, Turbo download schedulers, BitTorrent swarms, browser bridges, and WinUI 3 interface components documented herein are fully implemented and verified with 100% green test passes across all automated test suites.