


Languages and Compilers **(SProg og Oversættere)**

Code Generation


Code Generation

- Describe the purpose of the code generator
- Discuss Intermediate representations
- Describe issues in code generation
- Code templates and implementations
- Back patching
- Implementation of functions/procedures/methods
- Register Allocation and Code Scheduling

The “Phases” of a Compiler



The “Phases” of a Compiler



Intermediate Representations

- Abstract Syntax Tree
 - Convenient for semantic analysis phases
 - We can generate code directly from the AST, but...
 - What about multiple target architectures?
- Intermediate Representation
 - "Neutral" architecture
 - Easy to translate to native code
 - Can abstracts away complicated runtime issues
 - Stack Frame Management
 - Memory Management
 - Register Allocation




Figure 10.3: A middle-end and its ILs simplify construction of a compiler suite that must support multiple source languages and multiple target architectures.


Issues in Code Generation

- **Code Selection:**
Deciding which sequence of target machine instructions will be used to implement each phrase in the source language.
- **Storage Allocation**
Deciding the storage address for each variable in the source program. (static allocation, stack allocation etc.)
- **Register Allocation (for register-based machines)**
How to use registers efficiently to store intermediate results.
- **Code Scheduling**
The order in which the generated instructions are executed

Code Emmission

- Generating the actual instructions is usually called emission
 - a CodeGenVisitor emits instructions
- Example:
 - MethodBodyVisitor.visit(Plus)
 - visit(E1)
 - visit(E2)
 - emit("iadd\n")

```
/* Visitor code for Marker ⑦  
procedure VISIT( Computing n )  
  VISITCHILDREN( n )  
  loc ← ALLOCLocal()  
  n.SETRESULTLOCAL( loc )  
  call EMITOPERATION( n )  
end
```



Code Templates

visit [**if** E **then** C1 **else** C2] =

visit [E]

JUMPIFFALSE *g*


visit [C1]

JUMP *h*

visit [C2]

g:

h:




```

/* Visitor code for Marker ⑫
procedure VISIT( CondTesting n)
  falseLabel ← GENLABEL()
  endLabel ← GENLABEL()
  call n.GETPREDICATE().ACCEPT(this)
  predicateResult ← n.GETPREDICATE().GETRESULTLOCAL()
  call EMITBRANCHIFFALSE(predicateResult, falseLabel)
  call n.GETTRUEBRANCH().ACCEPT(this)
  call EMITBRANCH(endLabel)
  call EMITLABELDEF(falseLabel)
  call n.GETFALSEBRANCH().ACCEPT(this)
  call EMITLABELDEF(endLabel)
end
  
```

Code Templates

While Command:


```
visit [while E do C] =  
  l: visit [E]  
      JUMPIFFALSE d  
      visit[C]  
      JUMP l  
  d:
```



```
/* Visitor code for Marker ⑬  
procedure VISIT( WhileTesting n )  
  doneLabel ← GENLABEL()  
  loopLabel ← GENLABEL()  
  call EMITLABELDEF(loopLabel)  
  n.GETPREDICATE().ACCEPT(this)  
  predicateResult ← n.GETPREDICATE().GETRESULTLOCAL()  
  call EMITBRANCHIFFALSE(predicateResult, doneLabel)  
  n.GETLOOPBODY().ACCEPT(this)  
  call EMITBRANCH(loopLabel)  
  call EMITLABELDEF(doneLabel)  
end
```

Alternative While Command code template:

```
visit [while E do C] =  
  JUMP h  
  l: visit [C]  
  h: visit[E]  
      JUMPIFTRUE l
```



Backpatching Example

```
public Object WhileCommand (
    WhileCommand com, Object arg) {
    short j = nextInstrAddr;
    emit (Instruction.JUMPop, 0,
        Instruction.CBr, 0); dummy address
    short g = nextInstrAddr;
    com.C.visit(this, arg);
    short h = nextInstrAddr;
    code[j].d = h; backpatch
    com.E.visit(this, arg);
    emit (Instruction.JUMPIFop, 1,
        Instruction.CBr, g);
    return null;
}
```

execute [**while** E **do** C] =
JUMP *h*
g: execute [C]
h: evaluate[E]
JUMPIF (1) *g*

Code Template: Global Procedure

elaborate [**proc** I () ~ C] =

JUMP *g*


e: *execute* [C]

RETURN (0) 0

g:

execute [I ()] =

CALL (SB) *e*



```

subi    $sp,$sp,frameSz      # Push frame on stack
sw      $ra,0($sp)           # Save return address in frame
sw      $fp,4($sp)           # Save old frame pointer in frame
move    $fp,$sp              # Set $fp to access new frame
# Save callee-save registers (if any) here
# Body of method is here
# Restore callee-save registers (if any) here
lw      $ra,0($fp)           # Reload return address register
lw      $fp,4($fp)           # Reload old frame pointer
addi    $sp,$sp,frameSz      # Pop frame from stack
jr      $ra                  # Jump to return address

```

Figure 13.6: MIPS prologue and epilogue code

Register Allocation

- A compiler generating code for a register machine needs to pay attention to register allocation as this is a limited resource
- In routine protocol
 - Allocate arg1 in R1, arg2 in R2 .. Result in R0
 - But what if there are more args than regs?
- In evaluation of expressions
 - On MIPS all calculations take place in regs
 - Reduce traffic between memory and regs

Code scheduling

- Modern computers are pipelined
 - Instructions are processed in stages
 - Instructions take different time to execute
 - If result from previous instruction is needed but not yet ready then we have a **stalled pipeline**
 - Delayed load
 - Load from memory takes 2, 10 or 100 cycles
 - Also FP instructions takes time

Reg allocation and Code Scheduling

- Reg allocations algorithms try to minimize the number of regs used
- May conflict with pipeline architecture
 - Using more regs than strictly necessary may avoid pipeline stalls
- Solution
 - Integrated register allocator and code scheduler




Figure 13.31: AST-Level Peephole Optimization




Figure 13.32: IR-Level Peephole Optimizations




Figure 13.33: Bytecode-Level Peephole Optimizations




Figure 13.34: Code-Level Peephole Optimizations