## M4-L1-P2

October 1, 2023

# 1 Problem 2 (5 points)

The UCI Machine Learning Repository (https://archive.ics.uci.edu/ml/index.php) contains hundreds of public datasets donated by researchers to test machine learning/statistical methods. Here we will look at a curated version of one of these datasets and try to perform classification using SVM.

Tsanas and Xifara, cited below, performed simulations of buildings using a program called Ecotect. They modified 8 building features, and measured energy efficiency with 2 metrics: heating load requirement and cooling load requirement. For the purpose of demonstration, we have truncated the dataset to only look at a subset of the data points and building attributes.

You will be training an SVM (with sklearn) to use "relative compactness" and "wall area" to classify whether "heating load" is high (>20) or low (<=20).

#### Dataset source:

A. Tsanas, A. Xifara: 'Accurate quantitative estimation of energy performance of residential box Run the following cell to perform the necessary imports and load the data:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.svm import SVC
from matplotlib.colors import ListedColormap

def plot_data(x,y,e=0.1):
    x1min, x1max = min(x[:,0]), max(x[:,0])
    x2min, x2max = min(x[:,1]), max(x[:,1])

xb = np.linspace(x1min,x1max)

cmap = ListedColormap(["blue","red"])

plt.scatter(x[:,0],x[:,1],c=y,cmap=cmap)
plt.colorbar()

plt.xlabel('$x_1$')
plt.ylabel('$x_2$')
```

```
plt.axis((x1min-e,x1max+e,x2min-e,x2max+e))
def plot_SV_decision_boundary(svm, extend=True):
   ax = plt.gca()
   xlim = ax.get_xlim()
   ylim = ax.get_ylim()
   xrange = xlim[1] - xlim[0]
   yrange = ylim[1] - ylim[0]
   x = np.linspace(xlim[0] - extend*xrange, xlim[1] + extend*xrange, 100)
   y = np.linspace(ylim[0] - extend*yrange, ylim[1] + extend*yrange, 100)
   X,Y = np.meshgrid(x,y)
   xy = np.vstack([X.ravel(), Y.ravel()]).T
   P = svm.decision_function(xy)
   P = P.reshape(X.shape)
   ax.contour(X, Y, P, colors='k',levels=[0],linestyles=['-'])
   ax.contour(X, Y, P, colors='k',levels=[-1, 1], alpha=0.6,linestyles=['--'])
   plt.xlim(xlim)
   plt.ylim(ylim)
relative_compactness = np.array([0.98, 0.9, 0.86, 0.82, 0.79, 0.76, 0.74, 0.
 471, 0.69, 0.66, 0.64,
      0.62])
318.5, 343., 367.5])
heating_load = np.array([24.58, 29.03, 26.28, 23.53, 35.56, 32.96, 10.36, 10.
 <sup>4</sup>71, 11.11,
      11.68, 15.41, 12.96])
```

### 1.1 Train an SVM in sklearn

Perform the following steps: - Combine relative\_compactness and wall\_area into one 2-column input feature array - Transform heating\_load into an array of classes with -1 where heating\_load entries are less than 20, and +1 otherwise. - Create a Support Vector Classification model in sklearn. Make sure to use a "linear" kernel! Also set the argument "C" to a large number, like 1e5. - Fit the SVC to your data

```
print(X)
    model = SVC(kernel='linear', C=1e5)
    model.fit(X, y)
    [[ 0.98 294. ]
     [ 0.9 318.5]
     [ 0.86 294. ]
     [ 0.82 318.5 ]
     [ 0.79 343. ]
     [ 0.76 416.5 ]
     [ 0.74 245. ]
     [ 0.71 269.5 ]
     [ 0.69 294. ]
     [ 0.66 318.5 ]
     [ 0.64 343. ]
     [ 0.62 367.5 ]]
[]: SVC(C=100000.0, kernel='linear')
```

### 1.2 Plotting results

You can make predictions on any X data using the .predict(X) method of your SVC model. The .decision\_function() method will return a continuous class evaluation, 0 at the boundary and 1 or -1 at the margin edges.

Now use the provided function plot\_SV\_decision\_boundary(), which takes an sklearn model as its input, to plot the decision boundary.

```
[]: plt.figure(figsize=(6,4),dpi=150)
plot_data(X,y)

plot_SV_decision_boundary(model)

plt.xlabel("Relative Compactness")
plt.ylabel("Wall Area")
plt.title("Heating Load High/Low")
plt.show()
```

