2-Port Antenna Y1
Frequency Range 1710–2690
HPBW 65°

KATHREIN

2-Port Antenna HB 1.7m 65° | 1710–2690 19dBi

Type No.		80010651			
Highband		Y1			
		1710–2690			
Frequency range	MHz	1710 – 1990	1920 – 2170	2170 – 2490	2490 – 2690
Polarization	°	+45, −45	+45, −45	+45, −45	+45, −45
Gain at 0° tilt	dB	18.5	19.0	19.4	19.5
Horizontal Pattern:					
Half-power beam width	°	67	63	60	58
Front-to-back ratio (180°±30°)	dB	> 28	> 28	> 25	> 25
Cross polar ratio 0° Sector ±60°	dB	Typically: 25 > 10	Typically: 25 > 10	Typically: 25 > 10	Typically: 28 > 10
Tracking, Avg.	dB	1.5			
Squint	°	±3			
Vertical Pattern:					
Half-power beam width	°	5.4	4.9	4.3	4.0
Electrical tilt	°	0–6, continuously adjustable			
Sidelobe supression for first sidelobe above main beam	°T dB	0 ... 3 ... 6 ≥ 18 ... 18 ... 17	0 ... 3 ... 6 ≥ 18 ... 18 ... 16	0 ... 3 ... 6 ≥ 18 ... 18 ... 16	0 ... 3 ... 6 ≥ 18 ... 18 ... 17
Impedance	Ω	50			
VSWR		< 1.5			
Isolation, between ports	dB	> 30			
Intermodulation IM3	dBc	< −150 (2 x 43 dBm carrier)			
Max. power per input	W	300 (at 50 °C ambient temperature)			



Mechanical specifications		
Input		2 x 7-16 female
Connector position		Bottom
Adjustment mechanism		1x, Position bottom continuously adjustable
Wind load (at Rated Wind Speed: 150 km/h)	N | lbf	Frontal: 295 | 66 Maximal: 325 | 73
Max. wind velocity	km/h mph	200 124
Height/width/depth	mm inches	1670 / 155 / 70 65.7 / 6.1 / 2.8
Category of mounting hardware		M (Medium)
Weight	kg lb	7 / 9.2 (clamps incl.) 15.4 / 20.3 (clamps incl.)
Packing size	mm inches	1934 x 172 x 92 76.1 x 6.8 x 3.6
Scope of supply		Panel and 2 units of clamps for 42–115 mm | 1.7–4.5 inches diameter

For more information about additional mounting accessories please refer to page 305