

AIRCRAFT AND SIMULATOR SETUP

1. Time / Weather / A/C Position **As Chosen**
 - IF FLYING ON IVAO ---
 - a. A/C Position **Free of other traffic**
 - b. IVAO Pilot Client **Connect**
2. A/C Fuel & Weights **Set**

Cockpit Preparation

1. Rear Pilot Seat
 - a. ENG START SW **On**
 - b. TAILPLANE TRIM STANDBY COVER **Confirm Down**
 - c. Anti Skid SW **On**
 - d. STBY UHF SW **MAIN**
 - e. Landing Gear Transfer Button **Pushed In**
 - f. Flap Selector **Pupil**
 - g. Lights **Off**
 - h. Oxygen Selector **On**
2. Front Pilot Seat
 - a. Landing Gear Selector **DOWN**
 - b. Batt 1 & 2 **OFF**
 - c. Oxygen Selector **On**

Strapping-In

1. Canopy **Closed & Latched**
2. Rudder Pedal Lock **Off**
3. Batt 1 & 2 **Check Voltage >= 23V**
4. Batt 1 & 2 **ON**
5. Nav Light **On**
6. Anti-Collision Lights **Both Red**
7. AMP Selector **NORM**
8. Parking Brake **Confirm ON**

Internal

1. LP Fuel Cock	ON (Level Pointing Down)
2. ENG START SW	Confirm Off
3. Fuel Pump	On
4. Pitot ht	Off
5. Tailplane Trim Standby Cover	Confirm Down
6. ENG Ignition SW	Normal
7. Throttle	Check full & free movement
8. Throttle	Set Idle Stop Lever
9. Anti Skid	Off
10. Standby UHF SW	Main
11. Brake Pressure	Confirm Normal
12. Flap & Undercarriage Standby Handles	Confirm NOT pulled
13. Landing Gear Indicator	3 Green
14. Flaps	Up
15. UHF Radio	Both
16. Flight Instruments	Check
17. G-Meter	Reset
18. AHRS Control Unit	SLV
19. ILS Marker Light	Test
20. UHF Power	Normal
21. Standby Instrument Power SW	Normal
22. Oxygen Light	Confirm Out
23. Oxygen Qty	Confirm Sufficient
24. Oxygen Flow	Confirm
25. Fuel Qty	Confirm Sufficient
26. Rotation & GTS Indicators	Confirm Black
27. CWP	Test
28. Internal Lighting	As Required
29. VHF Radio	TR+G
30. VHF Freq Mode Selector	MAN
31. Air Conditioning	Normal
32. Temperature Control SW	AUTO
33. IFF XPDR	STBY

Internal - CONTINUED

34. TACAN TX/RX

35. ILS Receiver Set as Required

Pre-Start

1. ENG START SW On

Engine Start

1. Throttle Relight Button Press

Once GTS Indicator Green

2. ENG START SW Start

a. Rotation Indicator Shows Green

Once RPM between 15 and 20

3. Throttle Lever Idle

a. Monitor RPM and TGT

At 45 RPM

4. Rotation & GTS Lights Confirm Black

Once RPM Stabilizes at 50 to 55

5. CWP Confirm only HYD.2 and SKID Lights On

6. Flight Controls Full & Free Movement

7. Hyd 2 Reset Button Push

After Start

1. Trims **Confirm Neutral**
2. Airbrake **Test**
 - a. Airbrake Test SW **On**
 - b. Airbrake SW **On**
 - c. Airbrake Indicator **Confirm White**
 - d. Airbrake SW **Off**
 - e. Airbrake Indicator **Confirm Black**
 - f. Airbrake Test SW **Off**
3. Pitot hat **On**
4. Flaps **Mid position**
5. Ground Equipment **Remove**
6. Hyd. & Brake Pressure **Confirm within Limits**
7. Altimeter Test **Perform**
8. Flight Instruments **Check**
9. AHRS **Confirm Synced**
10. IFF XPDR **NORM**

Taxi

1. Land Taxi Light **On**
2. GPS Unit **On**
3. Parking Brake **Release**
4. Brake Test **Perform**

Before Takeoff

1. Trims **Confirm Neutral**
2. Pitot hat **Confirm On**
3. Anti Skid **On**
4. CWP **Confirm no lights**
5. Flaps **Confirm Mid**
6. Anti-Collision Lights **Both White (Strobe)**
7. Landing Light **On**
8. IFF XPDR **As Required**
9. Altimeters **Set as Required**

Takeoff

1. Gear and Flaps **Up (before 200 kt)**