

Sim Setup

1. Time / Weather / A/C Position **As Chosen**
- IF FLYING ON IVAO ---**
- a. A/C Position **Free of other traffic**
- b. IVAO Pilot Client **Connect**

Electrical Power-Up

1. Gear Selector **DOWN & Synced**
2. Engine Levers **SHUT OFF**
3. Speedbrake **UP & Synced**
4. Flaps **UP & Synced**
5. Battery Master **ON**
6. Power **EXT or APU, As Required**
- IF MCDU NOT SYNCED TO HARDWARE ---**
- a. Cockpit MCDU BRT **Turn**
7. IRS 1 & 2 **NAV**

APU Start Procedure

1. APU PWR FUEL **Push**
2. APU START / STOP **START**
3. APU GEN **Confirm AUTO**
4. BLEED SOURCE **APU**
5. L PACK **ON**
6. RECIRC FAN **ON**

Cockpit Setup

1. NAV & LOGO Lights	ON
2. WSHLD Heats LH & RH	LOW
3. EMER LTS	ARM
4. NO SMKG & SEAT BLTS	ON
5. N/W STRG	OFF
6. HYDRAULIC	AUTO & ON
7. ELT	Confirm ARM
8. Baro	Set Local QNH
9. Frequencies	Set As Required
10. ANTI SKID	Confirm ARMED
11. ENGINE SYNCH	Confirm N1 SYNCH
12. SPOILERS	AUTO
13. THRUST REVERSERS	OFF
14. LIGHTING	As Required
15. STAB & MACH TRIM	ON
16. YAW DAMPERS	ON

MDCU Setup

1. STATUS Page **Check Information Correct**
2. POS INIT Page **Setup**
 - a. Enter Airport
 - b. SET POS **Use GNSS1**
3. FPLN Page (RTE) **Enter Information**
 - a. Can also be send from EFB
 - b. EXEC
4. DEP ARR Page **Enter Departure, Route, then Arrival**
 - a. EXEC
5. PERF INIT Page **Enter Information**
 - a. EXEC
6. VNAV Setup Page **Set TA**
 - a. EXEC
7. EFB **Calculate TO Performance**
 - a. Flaps 8
 - b. V Speeds **Set (EFB or manually knobs right of EFB)**
 - c. TRIM **Set**
8. MFD MENU Page (LONG MENU) **Show VNAV As Required**

A/P Setup

1. Altitude **Set**
2. HDG **Set RWY HDG**
3. TFC **Confirm Shown on ND**
4. Landing Elevation **Set**

Before Start

1. APU	ON
2. EXT PWR	OFF
3. L & R PACKS	ON
4. RECIRC FAN	ON
5. Parking Brake	SET
6. Chocks	Removed
7. XPDR	As Required
a. Squawk	Set

Engine Start

1. BEACON	ON
2. Pushback	Perform
3. L & R FUEL BOOST PUMPS	ON
4. ENG L START	HOLD until START illuminates
ONCE N2 Above 20	
5. L THRUST LEVER	IDLE
6. Repeat for R Engine	

Before Taxi

1. GENERATORS	AUTO
2. APU	OFF
3. BLEED SOURCE	BOTH ENG
4. RECIRC FANS	ON
5. Flaps	Set for TO
6. NAV Source	Select FMS1
7. TOGA Button	Push
8. N/W STRG	ARMED
9. Flight Controls	Checked
10. TRIM	Checked
11. WXR	ON
12. TAXI Lights	ON
13. ANTI-ICE	As Required

Taxi

1. THRUST REVERSERS LH & RH	ARM
2. APU	DEPOWER
3. PROBES	ON

Before Takeoff

1. XPDR	ON
2. TCAS	ON
3. STROBE Lights	ON
4. LANDING LIGHTS	ON

Takeoff

1. Thrust	50
ONCE ENGINES STABILIZED	
2. Thrust	TOGA

After Takeoff

1. NAV & SPEED Modes	Activate
2. THRUST REVERSERS	OFF
3. CAS	Check for Warnings

Before Descend

1. Arrival Information	Check
2. Destination Weather	Obtained
3. VNAV TRL	Set
4. Landing Performance	Calculate
5. ND	Confirm VNAV Shown (MFD Menu)

Descent

1. LDG ELEV	Checked
2. Approach	Loaded and Correct
ONCE PASSING FL100	
3. LDG & TAXI LIGHTS	ON
4. SEAT BLTS	ON
AT TRANSITION LEVEL	
5. Baro	Set Local QNH
6. NAV Frequency	Check
ONCE VECTORED ONTO ILS	
7. NAV Source	Switch to LOC1

Before Landing

1. THRUST REVERSERS	ARMED
2. LDG GEAR	Down
3. Slats / Flaps	As Required / Full

After Landing

1. Flaps	Up
2. WXR	OFF
3. THRUST REVERSE	OFF
4. APU	Start
5. XPDR	As Required
6. STROBE	OFF
7. LDG LIGHTS	OFF
8. PROBES	OFF

Shutdown

1. Parking Brake	Set
2. SEAT BLTS	OFF
3. Thrust Levers	Shut Off
4. ANTI-ICE	OFF
5. Fuel Pumps	OFF
6. BEACON	OFF
7. N/W STRG	OFF

Securing

1. Chocks	ON
2. Brakes	OFF
3. IRS	OFF
4. EMER LTS	OFF
5. ANTI-ICE	OFF
6. HYDRAULIC PUMPS	OFF
7. EXTERNAL LTS	OFF
8. APU	OFF
9. BATTERY MASTER	OFF
10. Cockpit Lights .	OFF