```
mysql> create database my_database;
Query OK, 1 row affected (0.03 sec)

mysql> use my_database;
Database changed
mysql> CREATE TABLE departments (dept_id INT PRIMARY KEY, dept_name VARCHAR(50));
Query OK, 0 rows affected (0.08 sec)

mysql> CREATE TABLE employees (emp_id INT PRIMARY KEY, first_name VARCHAR(30),
salary DECIMAL(10,2));
Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE projects (project_id INT PRIMARY KEY, project_name VARCHAR(100),
start_date DATE);
Query OK, 0 rows affected (0.10 sec)

mysql> CREATE TABLE audit_logs (log_id INT PRIMARY KEY, action TEXT, created_at
TIMESTAMP);
Query OK, 0 rows affected (0.03 sec)

mysql> CREATE TABLE products (product_id INT PRIMARY KEY, product_name VARCHAR(50),
is_available BOOLEAN);
Query OK, 0 rows affected (0.02 sec)

mysql> CREATE TABLE system_settings (setting_id SMALLINT PRIMARY KEY, setting_key
VARCHAR(50), setting_value VARCHAR(100));
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> ALTER TABLE employees ADD COLUMN email VARCHAR(100);
Query OK, 0 rows affected (0.11 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> ALTER TABLE products DROP COLUMN is_available;
Query OK, 0 rows affected (0.07 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> RENAME TABLE departments TO dept_units;
Query OK, 0 rows affected (0.06 sec)

mysql> TRUNCATE TABLE audit_logs;
Query OK, 0 rows affected (0.02 sec)

mysql> CREATE TABLE user_profiles (user_id INT PRIMARY KEY, bio TEXT, profile_pic BLOB);
Query OK, 0 rows affected (0.02 sec)

mysql> CREATE TABLE ticket_orders (ticket_id INT PRIMARY KEY, priority_level
ENUM('Low','Medium','High'));
Query OK, 0 rows affected (0.09 sec)

mysql> DROP TABLE products;
Query OK, 0 rows affected (0.02 sec)

mysql> ALTER TABLE employees MODIFY COLUMN email VARCHAR(150);
Query OK, 0 rows affected (0.04 sec)
Records: 0  Duplicates: 0  Warnings: 0
```

```
mysql> CREATE TABLE sensor_data (read_id BIGINT PRIMARY KEY, temperature FLOAT);
Query OK, 0 rows affected (0.02 sec)

mysql> ALTER TABLE student_courses ADD PRIMARY KEY (student_id, course_id);
ERROR 1146 (42S02): Table 'my_database.student_courses' doesn't exist
mysql> ALTER TABLE employees RENAME COLUMN first_name TO given_name;
Query OK, 0 rows affected (0.01 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> ALTER TABLE system_settings DROP PRIMARY KEY;
Query OK, 0 rows affected (0.08 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> CREATE TABLE clients (client_id INT PRIMARY KEY, registration_time TIME);
Query OK, 0 rows affected (0.05 sec)

mysql> ALTER TABLE clients ADD PRIMARY KEY (client_id);
ERROR 1068 (42000): Multiple primary key defined
mysql> CREATE TABLE order_items (order_id INT, item_id INT, quantity INT, unit_price
DECIMAL(8,2), PRIMARY KEY (order_id, item_id));
Query OK, 0 rows affected (0.07 sec)

mysql> CREATE TABLE event_schedules (event_id INT, venue_id INT, event_date DATE,
duration_hours TINYINT, PRIMARY KEY (event_id, venue_id));
Query OK, 0 rows affected (0.08 sec)

mysql> ALTER TABLE employees ADD COLUMN hire_date DATE, ADD COLUMN is_active
BOOLEAN;
```

Query OK, 0 rows affected (0.10 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> ALTER TABLE employees DROP COLUMN email, MODIFY COLUMN salary DECIMAL(12,2);

Query OK, 0 rows affected (0.08 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> ALTER TABLE inventory ADD PRIMARY KEY (warehouse_id, sku);

ERROR 1146 (42S02): Table 'my_database.inventory' doesn't exist

mysql> ALTER TABLE user_profiles MODIFY COLUMN bio MEDIUMTEXT;

Query OK, 0 rows affected (0.04 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> ALTER TABLE employees ADD COLUMN middle_name VARCHAR(30) AFTER given_name;

Query OK, 0 rows affected (0.07 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> CREATE TABLE geolocations (location_id INT PRIMARY KEY, latitude DECIMAL(9,6), longitude DECIMAL(9,6));

Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE user_accounts (user_id BIGINT PRIMARY KEY, account_type ENUM('Standard','Premium','Admin'), created_timestamp TIMESTAMP);

Query OK, 0 rows affected (0.01 sec)

mysql> CREATE TABLE device_logs (log_id BIGINT PRIMARY KEY, ip_address VARCHAR(45), payload LONGBLOB);

Query OK, 0 rows affected (0.08 sec)

mysql> ALTER TABLE order_items DROP PRIMARY KEY, ADD COLUMN order_item_id INT FIRST, ADD PRIMARY KEY (order_item_id);

Query OK, 0 rows affected (0.07 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> ALTER TABLE projects CHANGE COLUMN start_date project_year YEAR;

Query OK, 0 rows affected (0.07 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> CREATE TABLE document_store (doc_id INT PRIMARY KEY, doc_title VARCHAR(255), content LONGTEXT);

Query OK, 0 rows affected (0.07 sec)

mysql> ALTER TABLE document_store RENAME COLUMN content TO doc_body;

Query OK, 0 rows affected (0.04 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> CREATE TABLE employees_archive LIKE employees;

Query OK, 0 rows affected (0.02 sec)

mysql> DROP TABLE IF EXISTS employees_archive;

Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE financial_ledger (entry_id BIGINT PRIMARY KEY, debit DECIMAL(15,4), credit DECIMAL(15,4));

Query OK, 0 rows affected (0.14 sec)

```
mysql> ALTER TABLE financial_ledger ADD COLUMN transaction_date DATETIME FIRST;
Query OK, 0 rows affected (0.07 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> CREATE TABLE measurements (sample_id INT PRIMARY KEY, value DOUBLE);
Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE app_users (user_id INT PRIMARY KEY, status_code TINYINT);
Query OK, 0 rows affected (0.05 sec)

mysql> CREATE TABLE transactions (xact_id BIGINT PRIMARY KEY, user_id INT, amount
DECIMAL(10,2), channel ENUM('Web','Mobile','ATM'), status VARCHAR(20), xact_time
TIMESTAMP);
Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE system_events (event_id BIGINT, node_id SMALLINT, event_payload
TEXT, logged_time TIMESTAMP, PRIMARY KEY (event_id, node_id));
Query OK, 0 rows affected (0.02 sec)
```