CI-R1 - six stationary interfaces / source geometry contract

Nominal rear depths from the drawn rear flange shoulder. Termination and assembly access are additional.

NAC3MPXXA		30.4 mm; +6.4 mm beyond 24 Flange 26 x 31 mm; no wire/tool allowance
NAC3MPXXB		30.4 mm; +6.4 mm beyond 24 Flange 26 x 31 mm; no wire/tool allowance
NAC3MPX-TOP		31.2 mm; +7.2 mm beyond 24 Flange 26 x 31 mm; no wire/tool allowance
NAC3FPX-TOP		32.8 mm; +8.8 mm beyond 24 Flange 35.4 x 35.4 mm; no wire/tool allowance
5278-C		45.3 mm; +21.3 mm beyond 24 Flange Dia 63.5 mm; no wire/tool allowance
5279-C		43.6 mm; +19.6 mm beyond 24 Flange Dia 63.5 mm; no wire/tool allowance

All 24 mm rear allocations fail before termination allowance. NEMA flange Dia63.5 exceeds Dia48.

Source drawing depths are not installed plug projection. Mounting planes do not establish contact mating planes.

No production approval, electrical test, custom-contact design, or baseline change.

Mating map and actual CAD inspection limits

Classic: input NAC3MPXXA <- NAC3FXXA-W-S (A / blue).

Output NAC3MPXXB -> NAC3FXXB-W-S -- cord -- NAC3FXXA-W-S -> fixture blue A inlet.

B is not A. FXX + legacy inlet has no CBC; do not transfer XX/FXX load-break permission.

TRUE1: input NAC3MPX-TOP <- female NAC3FX-W-TOP.

Output female NAC3FPX-TOP -> male NAC3MX-W-TOP -- cord -- female NAC3FX-W-TOP -> male fixture inlet.

NEMA: input male 5278-C <- female 5269-C. Output female 5279-C -> male 5266-C cord / fixture plug.

Optional source-to-fixture extension has 5266-C at source, 5269-C at fixture. No default positive mains lock.

Flanged NEMA comparison does not qualify baseline molded pigtails or a cord connector as a custom panel insert.

Saved original-model inspection (0.03 mm mesh samples are not maximum tolerance envelopes):

NAC3MPXXA	sampled axial span	37.100 mm; valid=True; solids=1
NAC3MPXXB	sampled axial span	37.000 mm; valid=True; solids=1
NAC3MPX-TOP	sampled axial span	38.200 mm; valid=False; solids=1
NAC3FPX-TOP	sampled axial span	43.000 mm; valid=False; solids=1
5278-C	sampled axial span	47.244 mm; valid=True; solids=0
5279-C	sampled axial span	47.981 mm; valid=True; solids=1
NAC3FXXA-W-S	sampled axial span	79.250 mm; valid=True; solids=1
NAC3FXXB-W-S	sampled axial span	79.250 mm; valid=True; solids=1
NAC3FX-W-TOP	sampled axial span	77.600 mm; valid=True; solids=0
NAC3MX-W-TOP	sampled axial span	77.100 mm; valid=True; solids=0
5269-C	sampled axial span	70.104 mm; valid=True; solids=0
5266-C	sampled axial span	71.374 mm; valid=True; solids=1

Invalid TRUE1 chassis and open/surface models retained unchanged. CAD face IDs are import-version specific.

No installed mate/hand/cable bend plane, rear terminal sleeve/tool sweep, wall/seal/boss fit, or assembly is qualified.

Source URLs, hashes, model headers, panel face coordinates, static checks: source-manifest / contracts / cad-inspection JSON.

Original STEP + editable import library are private source-cache evaluation artifacts; no redistribution licence asserted.