CME-R1: installed mating envelopes remain HOLD

No defended rigid transform / installed length / latch motion envelope for any selected pair.

NAC3MPXXA + NAC3FXXA-W-S

Panel: +Z, Face460 at 0; bare rear 30.4 mm; standalone mate 79..82.5 mm.

Installed panel-to-mate extent, locked transverse envelope, terminal assembly depth: UNKNOWN.

NAC3MPXXB + NAC3FXXB-W-S

Panel: +Z, Face680 at 0; bare rear 30.4 mm; standalone mate 79..82.5 mm.

Installed panel-to-mate extent, locked transverse envelope, terminal assembly depth: UNKNOWN.

NAC3MPX-TOP + NAC3FX-W-TOP

Panel: +Y, Face178 at 0; bare rear 31.2 mm; standalone mate 77..80 mm.

Installed panel-to-mate extent, locked transverse envelope, terminal assembly depth: UNKNOWN.

NAC3FPX-TOP + NAC3MX-W-TOP

Panel: +Z, Face105 at 0; bare rear 32.8 mm; standalone mate 77..80 mm.

Installed panel-to-mate extent, locked transverse envelope, terminal assembly depth: UNKNOWN.

All four bare rear dimensions exceed the 24 mm blank; terminals, wiring and access are additional.

Panel shoulders are mounting references, not contact mating planes. Dimensions retain drawing tolerances.

Source hashes, model identities, exact URLs and face constraints: source-links.json / new-source-manifest.json.

Private editable reference: sources/unplaced-references.FCStd. No mated STEP issued.

No product fit, electrical engagement, energized assembly or manufacturing release.

CME-R1: geometric probes and missing datums

Axial body cylinders identify axes but leave axial translation and circumferential rotation unresolved.

Classic A: Face466 / mate Face247, analytical tZ=-1.65 mm: zero isolated planar overlap.

Classic A: Face337 / mate Face2435, tZ=-2.15 mm: 50.69984 mm2 overlap.

Classic A: Face560 / mate Face2435, tZ=+20.35 mm: 95.57412 mm2 overlap.

Positive plane overlap is not a valid assembly pose, electrical engagement or lock/stop proof.

Eight independent saved-reference probes are recorded; no whole-assembly Boolean or motion PASS.

Two TRUE1 chassis whole-shapes are invalid. Both TRUE1 cable models have zero closed solids.

No source shape was healed; all models remain in their original coordinates and configuration.

Required next: actual axial stop + panel datum; insertion and final locked key angles; contact overlap;

latch state/travel/tolerances; exact insulated rear terminal/sleeve profile and finite tool/cable bend space.

No defensible finite insertion-depth interval or arbitrary hand/bend/tool allowance is supplied.

New exact mate drawing versions: 20003815 / 20003817 (2022-06-21);

ST-NAC3FX-W-TOP / ST-NAC3MX-W-TOP (2018-05-03). Manufacturer: Neutrik.

Private equal-scale unplaced sections: sources/reference-atlas.html and sixteen SVGs.

The four exact drawing PDFs retain original maker title blocks/copyright in the ignored cache.