







































































PROTOTYPE: stationaryXM20-5/YPC input only. No mains/PE or module circuitry captured here. All physical source board parts shown.

U1 reverse-blocking input, UVLO/OVLO and latched circuit-breaker. U2 forcedPWM5.136V. PG enables U3 after unloaded startup: no firmware.

U3 CHG=REGSW. CHG_HI=GND:1.5A only. CC1/CC2 independent. No USBdata processing or PD voltage escalation.

J1 has16 contacts but12 shared signal lands +kshell stakes, per originalGCT8+. D+ and D- tied by copper: no invented separate ground/VBUS pads.

Bulk150uF+76uFceramic before cold socket switch. ESR/capacitance attemperature. startup/inrush/thermal/ripple/faults remain physical gates.

Shell tiedisolatedGND proposal. No rotatingPE: accessiblemetal bonding/mainsendcap/harness/safety remain parent scope.

R12=10k EN series per?11.1; R13=100ohm DVDT series per?7.3.5.1. C12max11nF. Connector maxheight3.46mm: no fit/release claim.

Sheet: /	
File: regulated-source.kicad_sch	
Title: NOVA rotating regulated 5V 1.5A source prototype	
Size: A1	Date:
Rev: AX-1	
KiCad E.D.A. 10.0.7	Id: 1/1