

Machine Learning in Benthic Habitat Mapping

Justin Ting — Honours Student

Simon O’Callaghan — NICTA Researcher

NICTA

SIT

2016-05-06

Machine Learning in Benthic Habitat Mapping

Machine Learning in Benthic Habitat Mapping

Justin Ting — Honours Student
Simon O’Callaghan — NICTA Researcher
NICTA
SIT

Introduction

- ▶ Less than 10% of the world's oceans are mapped compared to 99% of Earth's topology mapped (low resolution)¹
- ▶ To map more of the world's oceans at a high resolution, we employ benthic habitat mapping techniques
- ▶ Marine habitat mapping cuts across marine biology, geology, hydrography, oceanography, geophysics (Brown et al., 2011), along with habitat mapping

¹<http://www.wired.com/2009/06/nasa-satellite-maps-99-of-earths-topography/>

2016-05-06

└ Introduction

Introduction

- ▶ Less than 10% of the world's oceans are mapped compared to 99% of Earth's topology mapped (low resolution)¹
- ▶ To map more of the world's oceans at a high resolution, we employ benthic habitat mapping techniques
- ▶ Marine habitat mapping cuts across marine biology, geology, hydrography, oceanography, geophysics (Brown et al., 2011), along with habitat mapping

¹<http://www.wired.com/2009/06/nasa-satellite-maps-99-of-earths-topography/>

- 0.5 minutes
- What is benthic habitat mapping?
- Benthic - ecological region at the lowest level of a body of water
- benthos - things related to the benthic layer
- Habitat mapping - based on a small amount of high resolution data, and a considerably larger amount of lower resolution data, a relationship is created to correlate the data in overlapping regions, which is then projected to the regions without the high resolution data to create a 'habitat map'
- The high resolution data is generally actual sediment samples or organism samples at the benthos
- Low resolution data is generally some sort of acoustic data representing basic properties of the seafloor

Problem Statement

- ▶ Much research in benthic habitat mapping generates deterministic maps using as-is machine learning techniques/implementations
- ▶ We need to be able to monitor marine habitats on a large scale to assess human impact over time to be able to make informed management decisions

2016-05-06

└ Problem Statement

1 minute

Problem Statement

- ▶ Much research in benthic habitat mapping generates deterministic maps using as-is machine learning techniques/implementations
- ▶ We need to be able to monitor marine habitats on a large scale to assess human impact over time to be able to make informed management decisions

Solution - Overview

- ▶ We will use Gaussian Processes to obtain distributions of likely habitat maps
- ▶ Probabilistic approach allows us to state certainty about a particular mapped area
- ▶ Use of Gaussian Processes requires a matrix inversion step with $O(n^3)$ complexity - attempt to overcome this by making our covariance matrix sparse and hence the inversion step computationally feasible for large datasets

2016-05-06

└ Solution - Overview

2.5 minutes

Solution - Overview

- ▶ We will use Gaussian Processes to obtain distributions of likely habitat maps
- ▶ Probabilistic approach allows us to state certainty about a particular mapped area
- ▶ Use of Gaussian Processes requires a matrix inversion step with $O(n^3)$ complexity - attempt to overcome this by making our covariance matrix sparse and hence the inversion step computationally feasible for large datasets

Solution - Gaussian Processes

TODO - a few slides providing an overview of Gaussian Processes here (may not include in the 10 minute presentation if time doesn't allow - will time once slides have been written out)

2016-05-06

└ Solution - Gaussian Processes

Solution - Gaussian Processes

TODO - a few slides providing an overview of Gaussian Processes here (may not include in the 10 minute presentation if time doesn't allow - will time once slides have been written out)

We would like to compare the results obtainable from use of Gaussian Processes in generating habitat maps to those of more naive methods. Note that measurements are taken by averaging over 10-fold cross validations.

This first set of results is using 24 separate habitat classes as the labels.

Algorithm	F1 score	Accuracy
KNN (5)	0.04823	0.14192
Logistic Regression	0.00900	0.17119
Random Forest	0.04960	0.15240
SVM	0.00890	0.17119

2016-05-06

Results

We would like to compare the results obtainable from use of Gaussian Processes in generating habitat maps to those of more naive methods. Note that measurements are taken by averaging over 10-fold cross validations.

This first set of results is using 24 separate habitat classes as the labels.

Algorithm	F1 score	Accuracy
KNN (5)	0.04823	0.14192
Logistic Regression	0.00900	0.17119
Random Forest	0.04960	0.15240
SVM	0.00890	0.17119

Results

This second set of results is using a higher level mapping of the habitats created in collaboration with an expert - bringing the number of classes down to 5. The accuracy increases notably when the aggregation of visually matching habitat classes is performed.

Algorithm	F1 score	Accuracy
KNN (5)	0.33278	0.62459
Logistic Regression	0.20285	0.682705
Random Forest	0.20283	0.68258
SVM	0.20284	0.68270

2016-05-06

Results

Results

This second set of results is using a higher level mapping of the habitats created in collaboration with an expert - bringing the number of classes down to 5. The accuracy increases notably when the aggregation of visually matching habitat classes is performed.

Algorithm	F1 score	Accuracy
KNN (5)	0.33278	0.62459
Logistic Regression	0.20285	0.682705
Random Forest	0.20283	0.68258
SVM	0.20284	0.68270

These final two set of results are using Gaussian processes with the granular and aggregated habitat classes, respectively.

Algorithm	F1 score	Accuracy
KNN (5)	0	0
Logistic Regression	0	0
Random Forest	0	0
SVM	0	0

Algorithm	F1 score	Accuracy
KNN (5)	0	0
Logistic Regression	0	0
Random Forest	0	0
SVM	0	0

2016-05-06

2 minutes for all results

These final two set of results are using Gaussian processes with the granular and aggregated habitat classes, respectively.

Algorithm	F1 score	Accuracy
KNN (5)	0	0
Logistic Regression	0	0
Random Forest	0	0
SVM	0	0

Algorithm	F1 score	Accuracy
KNN (5)	0	0
Logistic Regression	0	0
Random Forest	0	0
SVM	0	0

Discussion and Analysis

► stuff

2016-05-06

└ Discussion and Analysis

► stuff

Craig Brown, Stephen J Smith, and Peter Lawton. Benthic habitat mapping: A review of progress towards improved understanding of the spatial ecology of the seafloor using acoustic techniques. *Estuarine, Coastal and Shelf Science*, 92, 2011.

2016-05-06

└ Bibliography

2 minutes