Olex-Flexs Flexible PVC Earth

One core flexible multiple stranded plain annealed copper, 0.6/1 kV, PVC insulated flexible earth cable. Best Practice Guidelines.

STANDARDS

Product AS/NZS 1125; AS/NZS 5000.1

One core flexible multiple stranded plain annealed copper, 0.6/1 kV, V-90 PVC, insulated flexible earth cable.

For use with flexible Versolex and other PVC single core cables

CONTACT

Sales
Phone: 1300 CABLES
olex.customerservice@nexans.com

CHARACTERISTICS

Construction characteristics	
Colour	Green / yellow
Conductor flexibility	Class 5
Conductor material	Copper
Conductor shape	Circular
Insulation	V-90
Type of conductor	Stranded flexible
Electrical characteristics	
Rated Voltage Uo/U (Um)	0,6/1 kV
Mechanical characteristics	
Cable flexibility	Flexible

Conductor flexibility
Class 5

Rated Voltage Uo/U (Um)
0,6/1 kV

Cable flexibility
Flexible

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

FLEXIBLE PVC EARTH

Cross section [mm²]	Nom. overall diam. [mm]	Approx. weight [kg/100m]	Max. pulling tension [kN]	Min. bend. rad. during instal. [mm]	Min. bend. rad. installed [mm]	Nexans Ref.
10	6.3	10.6	0.2	38	19	BAAX01AA001AAHT
16	7.3	15.9	0.32	44	22	BAAX02AA001AAHT
25	9.0	24.7	0.5	54	27	BAAX03AA001AAHT
35	10.2	33.0	0.7	61	31	BAAX04AA001AAHT
50	12.2	48.5	1	73	49	BAAX05AA001AAHT
70	13.9	69.0	1.4	83	56	BAAX63AA001AAHT
95	16.0	94.2	1.9	96	64	BAAX64AA001AAHT
120	18.2	111.0	2.4	109	73	BAAE87AA001AAHT
150	20.1	138.0	3	121	80	BAAE88AA001AAHT
185	22.4	169.0	3.7	134	90	BAAE89AA001AAHT
240	25.4	220.0	4.8	229	152	BAAE90AA001AAHT
300	28.3	275.0	6	255	170	BAAE91AA001AAHT
400	32.0	357.0	8	288	192	BAAE92AA001AAHT

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

PVC INSULATED - CURRENT CARRYING CAPACITY TABLE THREE PHASE (IN AMPS)

Copper Conductor Insulation PVC Maximum Conductor Temperature 75C

Conductor cross-section [mm²]	Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu
1	16	14	13	12	10	6	16	19
1.5	20	17	16	15	12	8	20	24
2.5	29	25	23	21	17	12	27	33
4	38	33	31	28	23	16	36	43
6	49	42	40	35	28	20	45	53
10	67	58	54	47	37	27	59	70
16	89	77	72	62	50	36	78	90
25	120	103	97	81	64	48	100	117
35	148	127	119	100	80	59	122	140
50	181	156	146	119	95	-	144	168
70	230	197	184	152	122	-	180	205
95	287	246	230	183	147	-	217	250
120	335	287	267	217	173	-	252	283
150	385	330	308	244	195	-	283	317
185	447	383	357	284	227	-	325	365
240	535	457	426	331	265	-	377	422
300	620	529	492	388	311	-	434	488
400	726	615	573	442	353	-	492	553
500	846	710	661	523	418	-	571	641
630	990	817	760	588	471	-	639	723

Unenclosed spaced
Unenclosed spaced from surface
Unenclosed touching
Enclosed conduit in air
Thermal insulation, partially surrounded by thermal insulation
Thermal Insulation, completely surrounded by thermal insulation
Underground ducts A - Undergound Wiring Enclosure
Underground ducts B - Individual Wiring Enclosure

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

PVC INSULATED - CURRENT CARRYING CAPACITY TABLE SINGLE PHASE (IN AMPS)

Copper Conductor Insulation PVC Maximum Conductor Temperature 75C

Conductor cross-section [mm^2]	Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu
1	16	16	13	13	11	6	18	21
1.5	21	21	16	18	14	8	23	26
2.5	30	29	23	24	20	12	32	36
4	40	39	31	32	25	16	41	47
6	51	49	40	41	33	20	52	58
10	69	67	54	54	44	27	69	77
16	92	89	72	70	56	36	89	99
25	124	119	97	94	75	48	116	129
35	153	145	119	112	90	59	139	155
50	187	177	146	138	110	-	168	186
70	238	223	184	170	136	-	206	228
95	295	276	230	212	169	-	252	278
120	344	321	267	242	193	-	287	316
150	395	367	308	282	225	-	329	354
185	459	424	358	320	256	-	373	408
240	549	505	428	381	305	-	438	472
300	636	582	495	-	-	-	496	546
400	744	676	577	-	-	-	575	621
500	867	780	668	-	-	-	649	721
630	1014	897	770	-	-	-	750	816

Unenclosed spaced

Unenclosed spaced from surface

Unenclosed touching

Enclosed conduit in air

Thermal insulation, partially surrounded by thermal insulation

Thermal Insulation, completely surrounded by thermal insulation

Underground ducts A - Undergound Wiring Enclosure

Underground ducts B - Individual Wiring Enclosure

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.