

Summary of FSAE-I Rules Changes 2025 versus 2024 and Comments

This document lists the Clause Numbers from the US 2025 Rules REVISION SUMMARY, with added comment on the changes to assist local teams and officials.

Note: This summary is issued as a courtesy only and may not contain all of the minor changes in the rules. Teams must ensure they are thoroughly familiar with, and comply with, all of the detailed current year rules.

The majority of the revisions are mainly word changes and clarifications with the most significant revisions relating to monocoque layup, testing and SES inputs (F.4.2.6; F.4.3); added requirements for Accumulator Container Covers/Lids and Segment Retention and stricter Rear Impact Protection requirements; and changes to require separate Ready to Move and Tractive System Status lights instead of the prior single TSAL (EV.5.10; EV.5.11).

With the 2025 rules revisions, some of the 2024 Local Addendum clauses have been eliminated due an item being revised or covered in the 2025 FSAE-I Rules. Some additional clauses are added to the Local Addendum for EV's to clarify some items that arose during EV Technical Inspection at the 2024 event.

DR -Documentation Requirements

DR3.3.1 – Relates to US event only with earlier application of penalty for some late submissions.

V -Vehicle Requirements

V.1.4.2 – Adds mandatory requirement that distance to ground below the Lower SIS must be 90mm or less and should be 75 mm or less.

F – Chassis and Structural

F.4.2.6 and **F.4.3** – Deletes the reference to Quasi-Isotropic layups and revises the rules words to correlate with the SES. Adds requirement that unidirectional plies be enclosed by balanced plies and unidirectional should not be next to the core. The two clauses in the 2024 Local Addendum are no longer required and deleted in the 2025 Addendum.

F.5.6.3 – Clarifies where triangulation bracing is required for bends in the Main Roll Hoop below the Main Hoop Bracing in front and side view. Local Addendum Clause relating to this is modified accordingly..

F.5.11 – This modifies the definition of External Items and expands the allowable methods for related support to the Main Hoop and MH Brace. This should not present any new issues for teams.

Summary of FSAE-I Rules Changes 2025 versus 2024 and Comments

F.6.4.4.b – Upper Side Impact Member. Defines the vertical location zone relative to the upper top surface of the member rather than the location of the whole member. Not a major change and net result is similar.

F.5.7.5.1 – Side Impact Zone for monocoques. Redefines the reference height measurements with a minimum vertical dimension 290 mm for the height of the zone above the bottom of the monocoque floor. Should not create any significant issues.

F.8.5.6 – Impact Attenuator Location. Reduces the allowable height for the bottom leading edge of the Attenuator from 220 mm above to 150 mm above the lowest point on the top of the Lower Side Impact structure.

F.10.2 and **F.10.3** – Accumulator Container Structure and Cells/Segment. Layout order of paragraphs revised for better grouping. Major change is Covers/Lids no longer have a specified minimum number of Fasteners but must be mechanically attached with Positive Locking Mechanisms and Segments must be retained either by Covers/Lid with the Attachments showing equivalent strength to defined welds or Mechanical Segment Attachments that must be shown to meet the defined accelerations loads in the direction of removal.

F.11.3 – Tractive System Rear Impact Protection. This clause replaces 11.2.2 of 2024. More specific definitions of height requirements are included as well as other added requirements. The Top of the Rear Impact Protection (RIP) must be vertically above the Bottom of the RIP. A diagonal structure or X Brace must provide protection in the rear view. Some vehicles meeting the 2024 Rules may need Modification to comply with the 2025 rules, in particular if tube frame rear structure is employed.

F.11.4 – Separate clause added to better clarify requirements for clearances and Non-Crushable items. No new requirements.

T – Technical Aspects

T.1.8 – Firewall. Revised wording layout to combine sealing requirements into the same section. No significant change.

T.2.4 – Harness Installation. No major change but more exact requirements noted for tabs and brackets and new section added relating to use of Eye Bolts and Weld Eyes. Note typo in T.2.4.6 where it should say “For the bolt itself ---” not the “For the belt itself ---”.

T.8.3.3 - Positive Locking Mechanisms. New clause added noting requirements for where prevailing torque lock nuts are used.

EV – Electric Vehicles

EV.3.2.4 – Revised words relating to teams downloading their energy data. Not applicable to our event.

EV.5.4 – Accumulator Isolation Relays changed name to Isolation Relays. No change in functional requirements.

Summary of FSAE-I Rules Changes 2025 versus 2024 and Comments

EV.5.5 – High Voltage Disconnect name changed to Manual Service Disconnect with related labelling changes. No change to functional requirements.

EV.5.6.1 – Precharge and Discharge Circuits. Deletes sub clause c that stated circuits must not be fused.

EV.5.6.2 – Control of end of Precharge. Deletes the option of using time based control and must now only be via feedback of voltage monitoring in the Intermediate Circuit.

EV.5.9 – Connectors. New clause. Connectors outside of a housing must contain an interlock.

EV.5.10 and **EV.5.11** – Major change with the prior TSAL replaced by two separate lights as defined in each clause; a Ready to Move Light and a Tractive System Status Indicator. Refer to the clause details for the new requirements.

EV.7.3 – Accumulator Management System name changed to Battery Management system with related rewording of clauses but no change to functional requirements.

EV.7.5.4 – Minor word change for the temperature sensor to be less than 10 mm from the spotweld or clamping source on the negative cell terminal rather than from the cell terminal.

EV.7.8.4 – Physical separation of interlock circuits. Adds defined conditions for when physical separation is not required.