

AI.2.2 HV GLOVES

1. AS2225, Tested within 12mths, Labelled w/ voltage
(datasheet)

AI.2.3 ISOLATING BLANKET

2. 0.83m², Labelled w/ voltage (datasheet)

AI.2.4 INSULATED TOOLS

1. Fluke test leads, CAT III 600V or better (datasheet)
2. (photos)

AI.2.5 ADDITIONAL TOOLS

3. (photos)

AI.3.1 HAND CART WHEELS

1. (datasheet)

AI.4.2 CHARGER WIRING

1. Plug rated to AS/NZS 3123 (datasheet)

AI.4.3

CHARGER WIRING

1. Charger cable (datasheet)
2. 2.5mm² cable marked with gauge, temp and voltage;
and/or serial number (datasheet)
3. 16mm² + 25mm² cable marked with gauge, temp and
voltage; and/or serial number (datasheets)
4. (photos)

AI.4.4

CHARGER WIRING

1. 22AWG w/ suitable temp, current and voltage
(datasheets)
2. 16AWG w/ suitable temp, current and voltage
(datasheets)

AI.4.6

CHARGER WIRING

1. RCBO (4P) w/ trip sensitivity $\leq 30\text{mA}$ (datasheet)
2. RCBO (1P) w/ trip sensitivity $\leq 30\text{mA}$ (datasheet)
3. Charger HV (schematic)

AI.4.7 CHARGER WIRING

1. Orange HV charging cable (datasheet)

AI.4.8 CHARGER MEASURING POINTS

1. (Schematic)

AI.4.10 CHARGER MEASURING POINTS

2. 4mm banana jack (datasheet)
3. Test point covers (datasheet)

AI.4.11 CHARGING MEASURING POINTS

1. Body Protection Resistors 15kohm (datasheet)
2. (schematic)

AI.4.14 CHARGER EMERGENCY STOP

1. Positive switching shutdown circuit (schematic)

AI.4.16

CHARGER EARTHING

1. Earth cabling (photo)
2. Yellow/green 2.5mm² Earth cable (datasheet)

AI.4.17

CHARGER GALVANIC ISOLATION

1. DC Power Supply CHARGER (datasheet)
2. PFC Function Power Supply (datasheet)
3. Overview schematic (schematic)

AI.5.3

ACCUMULATOR CONSTRUCTION

1. Bottom thickness > 3.2mm. Wall thickness > 2.3mm (cad)
2. Internal wall thickness > 2.3mm (photo)

AI.5.6 ACCUMULATOR CONSTRUCTION

1. Reinforced lid strength calcs (datasheet, cad, photos)
2. Top view of cells (photo)
3. Segment housing design (photos)

AI.5.7 ACCUMULATOR CONSTRUCTION

4. Internal walls robustly fastened (photos)

AI.5.8

ACCUMULATOR CONSTRUCTION

1. Nomex insulation (datasheet)
2. Nomex installation (photos)
3. CANaMon PCB FR4 (datasheet)
4. PEEK – NAT/BLK (datasheet)
5. Kapton Tape (datasheet)
6. 9200FR Structural Adhesive (datasheet)

AI.5.9

ACCUMULATOR CONSTRUCTION

1. Ventilation holes < 10mm dia. (photos)
2. Ventilation holes DO NOT face driver (photos)

AI.5.11 CELL CONNECTION

1. Connecting single cells via solder is prohibited (photo)

AI.5.12 CELL CONNECTION

2. Adequately supported busbar connections to cell tabs
(photo)

AI.5.13

IR/ MAIN FUSE

1. Insulation relays (datasheet)
2. HRC Main fuse (datasheet)
3. PEEK – NAT/BLK (datasheet)

1. Top plate fuses ADP (datasheet)
2. Top plate fuse holders (datasheet)
3. CANaMon Fuse (datasheet)
4. CANaMon schematic (schematic)

5. AIL fuses ceramic tube cartridge (datasheet)
6. AIL fuse holders (datasheet)
7. PCB surface mount fuses (datasheet)
8. PCB surface mount fuse holders (datasheet)

AI.5.14

FUSES CONT.

1. 9. Precharge (schematic)
2. 10. LVD (schematic)
3. 11. AIL (schematic)

AI.5.15

MAINTENANCE PLUGS

1. Li-ion building block (datasheet)
2. Methode Embedded Bud Connector (datasheet)

1. UltraFuse ABS FR black Filament (datasheet)
2. PEEK – NAT/BLK (datasheet)
3. Nomex insulation (datasheet)
4. Segment stack housing (photos)

AI.5.17 CONTAINER CONNECTORS

1. SD and LVD overview schematics (schematic)

AI.5.18 INDICATOR LIGHT/ VOLTMETER

2. AIL schematic (schematic - A3 folder)

1. Methode Embedded Bud Connectors (datasheet)
2. Molex, Microfit (datasheet)

3. AT-Series Amphenol Connector (datasheet)
4. RADLOK Amphenol Connectors (datasheet)
5. E-Power Lite Amphenol Connector (datasheet)

AI.5.21

PRECHARGE AND DISCHARGE RESISTORS

1. Precharge resistor (datasheet, schematic)
2. Discharge resistor (inside HIP) (datasheet)

AI.5.22 INTERNAL WIRING

1. 22 AWG (datasheet)
2. 16 AWG (datasheet)
3. 10mm², 16mm², 25mm² (datasheet)

AI.6.1

PLASTIC AND 3D PRINT COMPONENTS

1. PolyMax PC-FR Filament (datasheet)
2. UltraFuse ABS FR black Filament (datasheet)
3. Busbar operating temp calc (datasheet)