



ADDEVMATERIALS

TAPES & FOAMS

TAPES



TDSAM-0032

► **PRODUCT DESCRIPTION**

MICROL N80A

A Nomex® single sided tape

50m standard length

Used for demanding electrical insulation applications.

Thermal class 155°C

Carrier : Nomex® 80 µm

► **CHARACTERISTICS & APPLICATIONS**

Suitable for electrical insulation in automotive, railway, electronics and power industries.

► **PERFORMANCE**

Test methods : AFERA, IEC 60 454-2





TAPES & FOAMS

TAPES

**TDSAM-0032**

► PROPERTIES

	VALUES	TEST
PHYSICAL PROPERTIES		
Construction		
Liner		
Adhesive mass		
Carrier	Nomex®	
Adhesive mass	Acrylic	
Liner		
Dimensions		
Length	50 m	
Width	On request	
Others physical properties		
Thickness	120 µm	
Color	Cream	
Curing		
Pression		
Density		
Curing conditions		
Compression rate		
Compression strength		
Shore hardness		
Electrical conductivity		
THERMAL PROPERTIES		
T° resistance (service)	155°C	
T° resistance (pic)		
Thermal conductivity		
CTE (coefficient of thermal expansion)		

	VALUES	TEST
MECHANICAL PROPERTIES		
Tensile strength at break	60 N/cm	
Static shear strength		
Shear strength		
Peel strength	3.5 N/cm	
Elongation at break	5%	
AGEING		
Chemical resistance		
Weather		
UV resistance		
INSTRUCTIONS FOR USE		
Surface preparation		
Application		
ELECTRICAL PROPERTIES		
Breakdown voltage	1.4 kV	
PERFORMANCES ADHESION		
Tack		
Adhesion on steel	3.5 N/cm	
STORAGE		
Storage conditions	20-30°C	50% humidity
Expiration date	12 month	
MEET STANDARDS		
Storage conditions		
LIABILITY		
Because varied and numerous applications escape our control, this information is only given as an indicative title and without any commitment on our part. Also, it is compulsory to carry out tests before hand. A wrong application is not the responsibility of the manufacturer.		

