

Task 3.9: Common Table Expressions

1) Step 1:

CTE:	Explanation:
<pre>WITH average_total_amount_paid_cte(customer_id, first_name, last_name, city, country, total_amount_paid) AS (SELECT A.customer_id, A.first_name, A.last_name, D.city, E.country, SUM(B.amount) AS total_amount_paid FROM customer A INNER JOIN payment B on A.customer_id = B.customer_id INNER JOIN address C on A.address_id = C.address_id INNER JOIN city D on C.city_id = D.city_id INNER JOIN country E on D.country_id = E.country_id WHERE D.city IN ('Aurora', 'Atlixco', 'Xintai', 'Adoni', 'Dhule (Dhulia)', 'Kurashiki', 'Pingxiang', 'Sivas', 'Celaya', 'So Leopoldo') GROUP BY A.customer_id, A.first_name, A.last_name, D.city, E.country ORDER BY total_amount_paid DESC limit 5) SELECT AVG(total_amount_paid) AS average_amount_paid FROM average_total_amount_paid_cte</pre>	<p>First, I copied and pasted the query from step in in 3.8. Then, I removed the outer query and rewrote it as CTE by using the WITH and naming it AS the inner query. Lastly, I added the SELECT AVG(total_amount_paid) AS average_amount_paid FROM average_total_amount_paid_cte.</p>

Data outputMessagesNotifications

average\_amount\_paid

numeric

1

107.354000000000000000

Server connected.

Total rows: 1 of 1

Query complete 00:00:00.066

Ln 35, Col 35

Step 2:

CTE:	Explanation:
------	--------------

```
WITH top_customer_count_cte(amount,
customer_id, first_name, last_name, city, country,
total_amount_paid) AS
(SELECT A.amount, B.customer_id, B.first_name,
B.last_name, D.city, E.country),
SUM(amount) AS total_amount_paid
FROM payment A
INNER JOIN customer B on
A.customer_id=B.customer_id
INNER JOIN address C on
B.address_id=C.address_id
INNER JOIN city D on C.city_id=D.city_id
INNER JOIN country E on
D.country_id=E.country_id
WHERE city IN ('Aurora', 'Atlixco', 'Xintai',
'Adoni', 'Dhule (Dhulia)', 'Kurashiki', 'Pingxiang',
'Sivas', 'Celaya', 'So Leopoldo')
GROUP BY A.amount, B.customer_id,
B.first_name, B.last_name, D.city, E.country
ORDER BY SUM (amount) DESC limit 5),
customer_count_cte AS (SELECT D.country,
COUNT(DISTINCT A.customer_id) AS
all_customer_count,
COUNT(DISTINCT D.country) AS
top_customer_count
FROM customer A
INNER JOIN address B on
A.address_id=B.address_id
INNER JOIN city C on B.city_id=C.city_id
INNER JOIN country D on
C.country_id=D.country_id
GROUP BY D.country)
SELECT D.country, COUNT(DISTINCT
A.customer_id) AS all_customer_count,
COUNT(DISTINCT
top_customer_count_cte.customer_id) AS
top_customer_count
FROM customer A
INNER JOIN address B on
A.address_id=B.address_id
INNER JOIN city C on B.city_id=C.city_id
INNER JOIN country D on
C.country_id=D.country_id
LEFT JOIN top_customer_count_cte ON
D.country=top_customer_count_cte.country
GROUP BY D.country
ORDER BY top_customer_count DESC
LIMIT 5;
```

The steps for step 2 was similar to step 1 except this time I added 2 CTE's: one for all customer count and another for top customer count. Also, I used LEFT JOIN to combine the payment and customer tables.

Data outputMessagesNotifications

	country character varying (50)	all_customer_count bigint	top_customer_count bigint	
1	Mexico	30	1	
2	Turkey	15	1	
3	India	60	1	
4	Japan	31	1	
5	United States	36	1	

Total rows: 5 of 5Query complete 00:00:00.268Ln 26, Col 77

2)

Step 1 Subquery Query Plan:	Step 1 CTE Query Plan:																																																
<p>Dashboard Properties SQL Statistics Dependencies Dependents <b>Rockbuster/postgres@PostgreSQL 14</b></p> <p>Rockbuster/postgres@PostgreSQL 14</p> <p>Data output Messages <b>Explain</b> Notifications</p> <p>Graphical <b>Analysis</b> Statistics</p> <table border="1"> <thead> <tr> <th>#</th> <th>Node</th> </tr> </thead> <tbody> <tr><td>1.</td><td>→ Aggregate (cost=64.45..64.46 rows=1 width=32)</td></tr> <tr><td>2.</td><td>→ Limit (cost=64.37..64.39 rows=5 width=67)</td></tr> <tr><td>3.</td><td>→ Sort (cost=64.37..64.98 rows=243 width=67)</td></tr> <tr><td>4.</td><td>→ Aggregate (cost=57.3..60.34 rows=243 width=67)</td></tr> <tr><td>5.</td><td>→ Nested Loop Inner Join (cost=18.16..54.87 rows=243 width=67)</td></tr> <tr><td>6.</td><td>→ Hash Inner Join (cost=17.88..37.14 rows=10 width=67) Hash Cond: (d.country_id = e.country_id)</td></tr> <tr><td>7.</td><td>→ Nested Loop Inner Join (cost=14.43..33.14 rows=243 width=67)</td></tr> <tr><td>8.</td><td>→ Hash Inner Join (cost=14.15..29.77 rows=243 width=67) Hash Cond: (c.city_id = d.city_id)</td></tr> <tr><td>9.</td><td>→ Seq Scan on address as c (cost=0..14.03 rows=243 width=67)</td></tr> <tr><td>10.</td><td>→ Hash (cost=14.03..14.03 rows=243 width=67)</td></tr> <tr><td>11.</td><td>→ Seq Scan on city as d (cost=0..14.03 rows=243 width=67)</td></tr> </tbody> </table> <p>Total rows: 1 of 1 Query complete 00:00:00.051</p>	#	Node	1.	→ Aggregate (cost=64.45..64.46 rows=1 width=32)	2.	→ Limit (cost=64.37..64.39 rows=5 width=67)	3.	→ Sort (cost=64.37..64.98 rows=243 width=67)	4.	→ Aggregate (cost=57.3..60.34 rows=243 width=67)	5.	→ Nested Loop Inner Join (cost=18.16..54.87 rows=243 width=67)	6.	→ Hash Inner Join (cost=17.88..37.14 rows=10 width=67) Hash Cond: (d.country_id = e.country_id)	7.	→ Nested Loop Inner Join (cost=14.43..33.14 rows=243 width=67)	8.	→ Hash Inner Join (cost=14.15..29.77 rows=243 width=67) Hash Cond: (c.city_id = d.city_id)	9.	→ Seq Scan on address as c (cost=0..14.03 rows=243 width=67)	10.	→ Hash (cost=14.03..14.03 rows=243 width=67)	11.	→ Seq Scan on city as d (cost=0..14.03 rows=243 width=67)	<p>Dashboard Properties SQL Statistics Dependencies Dependents <b>Rockbuster/postgres@PostgreSQL 14</b></p> <p>Rockbuster/postgres@PostgreSQL 14</p> <p>Data output Messages <b>Explain</b> Notifications</p> <p>Graphical <b>Analysis</b> Statistics</p> <table border="1"> <thead> <tr> <th>#</th> <th>Node</th> </tr> </thead> <tbody> <tr><td>1.</td><td>→ Aggregate (cost=64.45..64.46 rows=1 width=32)</td></tr> <tr><td>2.</td><td>→ Limit (cost=64.37..64.39 rows=5 width=67)</td></tr> <tr><td>3.</td><td>→ Sort (cost=64.37..64.98 rows=243 width=67)</td></tr> <tr><td>4.</td><td>→ Aggregate (cost=57.3..60.34 rows=243 width=67)</td></tr> <tr><td>5.</td><td>→ Nested Loop Inner Join (cost=18.16..54.87 rows=243 width=67)</td></tr> <tr><td>6.</td><td>→ Hash Inner Join (cost=17.88..37.14 rows=10 width=67) Hash Cond: (d.country_id = e.country_id)</td></tr> <tr><td>7.</td><td>→ Nested Loop Inner Join (cost=14.43..33.14 rows=243 width=67)</td></tr> <tr><td>8.</td><td>→ Hash Inner Join (cost=14.15..29.77 rows=243 width=67) Hash Cond: (c.city_id = d.city_id)</td></tr> <tr><td>9.</td><td>→ Seq Scan on address as c (cost=0..14.03 rows=243 width=67)</td></tr> <tr><td>10.</td><td>→ Hash (cost=14.03..14.03 rows=243 width=67)</td></tr> <tr><td>11.</td><td>→ Seq Scan on city as d (cost=0..14.03 rows=243 width=67) Filter: ((city)::text = ANY ('A'))</td></tr> </tbody> </table> <p>Total rows: 1 of 1 Query complete 00:00:00.066</p>	#	Node	1.	→ Aggregate (cost=64.45..64.46 rows=1 width=32)	2.	→ Limit (cost=64.37..64.39 rows=5 width=67)	3.	→ Sort (cost=64.37..64.98 rows=243 width=67)	4.	→ Aggregate (cost=57.3..60.34 rows=243 width=67)	5.	→ Nested Loop Inner Join (cost=18.16..54.87 rows=243 width=67)	6.	→ Hash Inner Join (cost=17.88..37.14 rows=10 width=67) Hash Cond: (d.country_id = e.country_id)	7.	→ Nested Loop Inner Join (cost=14.43..33.14 rows=243 width=67)	8.	→ Hash Inner Join (cost=14.15..29.77 rows=243 width=67) Hash Cond: (c.city_id = d.city_id)	9.	→ Seq Scan on address as c (cost=0..14.03 rows=243 width=67)	10.	→ Hash (cost=14.03..14.03 rows=243 width=67)	11.	→ Seq Scan on city as d (cost=0..14.03 rows=243 width=67) Filter: ((city)::text = ANY ('A'))
#	Node																																																
1.	→ Aggregate (cost=64.45..64.46 rows=1 width=32)																																																
2.	→ Limit (cost=64.37..64.39 rows=5 width=67)																																																
3.	→ Sort (cost=64.37..64.98 rows=243 width=67)																																																
4.	→ Aggregate (cost=57.3..60.34 rows=243 width=67)																																																
5.	→ Nested Loop Inner Join (cost=18.16..54.87 rows=243 width=67)																																																
6.	→ Hash Inner Join (cost=17.88..37.14 rows=10 width=67) Hash Cond: (d.country_id = e.country_id)																																																
7.	→ Nested Loop Inner Join (cost=14.43..33.14 rows=243 width=67)																																																
8.	→ Hash Inner Join (cost=14.15..29.77 rows=243 width=67) Hash Cond: (c.city_id = d.city_id)																																																
9.	→ Seq Scan on address as c (cost=0..14.03 rows=243 width=67)																																																
10.	→ Hash (cost=14.03..14.03 rows=243 width=67)																																																
11.	→ Seq Scan on city as d (cost=0..14.03 rows=243 width=67)																																																
#	Node																																																
1.	→ Aggregate (cost=64.45..64.46 rows=1 width=32)																																																
2.	→ Limit (cost=64.37..64.39 rows=5 width=67)																																																
3.	→ Sort (cost=64.37..64.98 rows=243 width=67)																																																
4.	→ Aggregate (cost=57.3..60.34 rows=243 width=67)																																																
5.	→ Nested Loop Inner Join (cost=18.16..54.87 rows=243 width=67)																																																
6.	→ Hash Inner Join (cost=17.88..37.14 rows=10 width=67) Hash Cond: (d.country_id = e.country_id)																																																
7.	→ Nested Loop Inner Join (cost=14.43..33.14 rows=243 width=67)																																																
8.	→ Hash Inner Join (cost=14.15..29.77 rows=243 width=67) Hash Cond: (c.city_id = d.city_id)																																																
9.	→ Seq Scan on address as c (cost=0..14.03 rows=243 width=67)																																																
10.	→ Hash (cost=14.03..14.03 rows=243 width=67)																																																
11.	→ Seq Scan on city as d (cost=0..14.03 rows=243 width=67) Filter: ((city)::text = ANY ('A'))																																																

The cost for Step 1 was the same. However, the speed of the subquery was faster than the speed of the CTE by 15 milliseconds.

Step 2 Subquery Query Plan:	Step 2 CTE Query Plan:																																														
<p>Dashboard Properties SQL Statistics Dependencies Dependents <b>Rockbuster/postgres@PostgreSQL 14</b></p> <p>Rockbuster/postgres@PostgreSQL 14</p> <p>Data output Messages <b>Explain</b> Notifications</p> <p>Graphical <b>Analysis</b> Statistics</p> <table border="1"> <thead> <tr> <th>#</th> <th>Node</th> </tr> </thead> <tbody> <tr><td>1.</td><td>→ Limit (cost=154.14..154.16 rows=5 width=84)</td></tr> <tr><td>2.</td><td>→ Sort (cost=154.14..155.51 rows=545 width=84)</td></tr> <tr><td>3.</td><td>→ Aggregate (cost=139.64..145.09 rows=545 width=84)</td></tr> <tr><td>4.</td><td>→ Aggregate (cost=122.62..135.55 rows=545 width=84)</td></tr> <tr><td>5.</td><td>→ Sort (cost=122.62..124.11 rows=599 width=72)</td></tr> <tr><td>6.</td><td>→ Hash Left Join (cost=72.68..94.98 rows=599 width=72) Hash Cond: ((a.country)::text = (top_5_customers.country)::text)</td></tr> <tr><td>7.</td><td>→ Hash Inner Join (cost=43.52..63.3 rows=599 width=13) Hash Cond: (b.country_id = a.country_id)</td></tr> <tr><td>8.</td><td>→ Hash Inner Join (cost=40.07..58.22 rows=599 width=6) Hash Cond: (c.city_id = b.city_id)</td></tr> <tr><td>9.</td><td>→ Hash Inner Join (cost=21.57..38.14 rows=599 width=6) Hash Cond: (d.address_id = c.address_id)</td></tr> <tr><td>10.</td><td>→ Seq Scan on customer as d (cost=0..14.03 rows=599 width=6)</td></tr> </tbody> </table> <p>Total rows: 1 of 1 Query complete 00:00:00.055</p>	#	Node	1.	→ Limit (cost=154.14..154.16 rows=5 width=84)	2.	→ Sort (cost=154.14..155.51 rows=545 width=84)	3.	→ Aggregate (cost=139.64..145.09 rows=545 width=84)	4.	→ Aggregate (cost=122.62..135.55 rows=545 width=84)	5.	→ Sort (cost=122.62..124.11 rows=599 width=72)	6.	→ Hash Left Join (cost=72.68..94.98 rows=599 width=72) Hash Cond: ((a.country)::text = (top_5_customers.country)::text)	7.	→ Hash Inner Join (cost=43.52..63.3 rows=599 width=13) Hash Cond: (b.country_id = a.country_id)	8.	→ Hash Inner Join (cost=40.07..58.22 rows=599 width=6) Hash Cond: (c.city_id = b.city_id)	9.	→ Hash Inner Join (cost=21.57..38.14 rows=599 width=6) Hash Cond: (d.address_id = c.address_id)	10.	→ Seq Scan on customer as d (cost=0..14.03 rows=599 width=6)	<p>Dashboard Properties SQL Statistics Dependencies Dependents <b>Rockbuster/postgres@PostgreSQL 14</b></p> <p>Rockbuster/postgres@PostgreSQL 14</p> <p>Data output Messages <b>Explain</b> Notifications</p> <p>Graphical <b>Analysis</b> Statistics</p> <table border="1"> <thead> <tr> <th>#</th> <th>Node</th> </tr> </thead> <tbody> <tr><td>1.</td><td>→ Limit (cost=166.83..166.85 rows=5 width=25)</td></tr> <tr><td>2.</td><td>→ Sort (cost=166.83..167.11 rows=109 width=25)</td></tr> <tr><td>3.</td><td>→ Aggregate (cost=156.04..165.02 rows=109 width=25)</td></tr> <tr><td>4.</td><td>→ Merge Left Join (cost=156.04..159.44 rows=599 width=17)</td></tr> <tr><td>5.</td><td>→ Sort (cost=90.94..92.44 rows=599 width=13)</td></tr> <tr><td>6.</td><td>→ Hash Inner Join (cost=43.52..63.3 rows=599 width=13) Hash Cond: (c.country_id = d.country_id)</td></tr> <tr><td>7.</td><td>→ Hash Inner Join (cost=40.07..58.22 rows=599 width=6) Hash Cond: (b.city_id = c.city_id)</td></tr> <tr><td>8.</td><td>→ Hash Inner Join (cost=21.57..38.14 rows=599 width=6) Hash Cond: (a.address_id = b.address_id)</td></tr> <tr><td>9.</td><td>→ Seq Scan on customer as a (cost=0..14.03 rows=599 width=6)</td></tr> <tr><td>10.</td><td>→ Hash (cost=14.03..14.03 rows=603 width=6)</td></tr> <tr><td>11.</td><td>→ Seq Scan on address as b (cost=0..14.03 rows=603 width=6)</td></tr> </tbody> </table> <p>Total rows: 1 of 1 Query complete 00:00:00.073</p>	#	Node	1.	→ Limit (cost=166.83..166.85 rows=5 width=25)	2.	→ Sort (cost=166.83..167.11 rows=109 width=25)	3.	→ Aggregate (cost=156.04..165.02 rows=109 width=25)	4.	→ Merge Left Join (cost=156.04..159.44 rows=599 width=17)	5.	→ Sort (cost=90.94..92.44 rows=599 width=13)	6.	→ Hash Inner Join (cost=43.52..63.3 rows=599 width=13) Hash Cond: (c.country_id = d.country_id)	7.	→ Hash Inner Join (cost=40.07..58.22 rows=599 width=6) Hash Cond: (b.city_id = c.city_id)	8.	→ Hash Inner Join (cost=21.57..38.14 rows=599 width=6) Hash Cond: (a.address_id = b.address_id)	9.	→ Seq Scan on customer as a (cost=0..14.03 rows=599 width=6)	10.	→ Hash (cost=14.03..14.03 rows=603 width=6)	11.	→ Seq Scan on address as b (cost=0..14.03 rows=603 width=6)
#	Node																																														
1.	→ Limit (cost=154.14..154.16 rows=5 width=84)																																														
2.	→ Sort (cost=154.14..155.51 rows=545 width=84)																																														
3.	→ Aggregate (cost=139.64..145.09 rows=545 width=84)																																														
4.	→ Aggregate (cost=122.62..135.55 rows=545 width=84)																																														
5.	→ Sort (cost=122.62..124.11 rows=599 width=72)																																														
6.	→ Hash Left Join (cost=72.68..94.98 rows=599 width=72) Hash Cond: ((a.country)::text = (top_5_customers.country)::text)																																														
7.	→ Hash Inner Join (cost=43.52..63.3 rows=599 width=13) Hash Cond: (b.country_id = a.country_id)																																														
8.	→ Hash Inner Join (cost=40.07..58.22 rows=599 width=6) Hash Cond: (c.city_id = b.city_id)																																														
9.	→ Hash Inner Join (cost=21.57..38.14 rows=599 width=6) Hash Cond: (d.address_id = c.address_id)																																														
10.	→ Seq Scan on customer as d (cost=0..14.03 rows=599 width=6)																																														
#	Node																																														
1.	→ Limit (cost=166.83..166.85 rows=5 width=25)																																														
2.	→ Sort (cost=166.83..167.11 rows=109 width=25)																																														
3.	→ Aggregate (cost=156.04..165.02 rows=109 width=25)																																														
4.	→ Merge Left Join (cost=156.04..159.44 rows=599 width=17)																																														
5.	→ Sort (cost=90.94..92.44 rows=599 width=13)																																														
6.	→ Hash Inner Join (cost=43.52..63.3 rows=599 width=13) Hash Cond: (c.country_id = d.country_id)																																														
7.	→ Hash Inner Join (cost=40.07..58.22 rows=599 width=6) Hash Cond: (b.city_id = c.city_id)																																														
8.	→ Hash Inner Join (cost=21.57..38.14 rows=599 width=6) Hash Cond: (a.address_id = b.address_id)																																														
9.	→ Seq Scan on customer as a (cost=0..14.03 rows=599 width=6)																																														
10.	→ Hash (cost=14.03..14.03 rows=603 width=6)																																														
11.	→ Seq Scan on address as b (cost=0..14.03 rows=603 width=6)																																														

The cost for Step 2 were different. The subquery cost was lower than the cost of the CTE. Also, the subquery was 18 milliseconds faster than the CTE.

**I thought the CTE approach would perform better because it was easier to read. However, the results surprised me because for both steps 1 and 2, the subquery was faster. It might be because the subquery is shorter than the CTE since it doesn't have as many clauses or inner statements.**

**Step 3:**

**For step 1, replacing the subquery with a CTE was manageable. It was simple and easy to understand. It might be because for step 1 only one table was utilized. However, replacing the subquery with a CTE for step 2 was extremely difficult. Because step 2 dealt with two tables to combine I needed to be meticulous and accurate with which columns needed to be extracted and combined. I also had to write 2 CTE's.**