

Problem Set I

1. (20%) Prove the properties of convolution. For all continuous function f , g , and h , the following axioms hold:
 - Associativity: $(f * g) * h = f * (g * h)$
 - Distributivity: $f * (g + h) = f * g + f * h$
 - Differentiation rule: $(f * g)' = f' * g = f * g'$
 - Convolution theorem: $\mathcal{F}(g * h) = \mathcal{F}(g)\mathcal{F}(h)$, where \mathcal{F} denotes Fourier transform
2. (25%) Frequency smoothing:
 - (a) Compute Fourier transform of the given image `lenaNoise.PNG` by using `fft2` function in Matlab and then center the low frequencies (`fftshift`).
 - (b) Keep different number of low frequencies (e.g., 10^2 , 20^2 , 40^2 and up to the full dimension), but set all other high frequencies to 0.
 - (c) Reconstruct the original image (`ifft2`) by using the new generated frequencies in step (b).

Submit the code and include the restored images with different number of low frequencies in your report.

3. (55%) Implement gradient decent algorithm for ROF model with total variation minimization. All codes and a two-page report including problem description, your solution, and experimental results (denoised image, convergence graph, etc.) with discussions should be submitted.

NOTE that

- The forward / backward difference for computing image gradient is given in `Dx.m` / `Dxt.m`. Feel free to use it or write your own.
- A detailed class note of deriving total variation, computing gradient term, and gradient decent algorithm can be downloaded from Canvas.