

```
1  /**
2   * \file
3   * Functions and types for CRC checks.
4   *
5   * Generated on Wed Sep 11 13:56:48 2019
6   * by pycrc v0.9.2, https://pycrc.org
7   * using the configuration:
8   * - Width      = 8
9   * - Poly       = 0x07
10  * - XorIn      = 0x00
11  * - ReflectIn  = False
12  * - XorOut     = 0x00
13  * - ReflectOut = False
14  * - Algorithm   = bit-by-bit-fast
15  *
16  * This file defines the functions crc_init(), crc_update() and crc_finalize().
17  *
18  * The crc_init() function returns the initial \c crc value and must be called
19  * before the first call to crc_update().
20  * Similarly, the crc_finalize() function must be called after the last call
21  * to crc_update(), before the \c crc is being used.
22  * is being used.
23  *
24  * The crc_update() function can be called any number of times (including zero
25  * times) in between the crc_init() and crc_finalize() calls.
26  *
27  * This pseudo-code shows an example usage of the API:
28  * \code{.c}
29  * crc_t crc;
30  * unsigned char data[MAX_DATA_LEN];
31  * size_t data_len;
32  *
33  * crc = crc_init();
34  * while ((data_len = read_data(data, MAX_DATA_LEN)) > 0) {
35  *     crc = crc_update(crc, data, data_len);
36  * }
37  * crc = crc_finalize(crc);
38  * \endcode
39  */
40 #ifndef CRC_H
41 #define CRC_H
42
43 #include <stdlib.h>
44 #include <stdint.h>
45
46 #ifdef __cplusplus
47 extern "C" {
48 #endif
49
50
51 /**
52  * The definition of the used algorithm.
```

```
53  *
54  * This is not used anywhere in the generated code, but it may be used by the
55  * application code to call algorithm-specific code, if desired.
56  */
57 #define CRC_ALGO_BIT_BY_BIT_FAST 1
58
59
60 /**
61  * The type of the CRC values.
62  *
63  * This type must be big enough to contain at least 8 bits.
64  */
65 typedef uint_fast8_t crc_t;
66
67
68 /**
69  * Calculate the initial crc value.
70  *
71  * \return      The initial crc value.
72  */
73 static inline crc_t crc_init(void)
74 {
75     return 0x00;
76 }
77
78
79 /**
80  * Update the crc value with new data.
81  *
82  * \param[in] crc      The current crc value.
83  * \param[in] data      Pointer to a buffer of \a data_len bytes.
84  * \param[in] data_len  Number of bytes in the \a data buffer.
85  * \return              The updated crc value.
86  */
87 crc_t crc_update(crc_t crc, const void *data, size_t data_len);
88
89
90 /**
91  * Calculate the final crc value.
92  *
93  * \param[in] crc  The current crc value.
94  * \return          The final crc value.
95  */
96 static inline crc_t crc_finalize(crc_t crc)
97 {
98     return crc;
99 }
100
101
102 #ifdef __cplusplus
103 } /* closing brace for extern "C" */
104 #endif
```

105

106 #endif       /\* CRC\_H \*/

107