

Package ‘edm1’

October 20, 2024

Title Simplify Complex Data Manipulation

Version 2.0.0.0

Description Provides complex sorting algorithms. Provides date manipulation algorithms. In addition to providing handy functions to discretize variables, an SQL joins alternatives, a set of function to work with geographical coordinates, and other functions to work with text mining.

License GPL (==3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Imports stringr,
stringi,
dplyr,
data.table,
openxlsx

Depends stringr,
stringi,
dplyr,
data.table,
openxlsx

Contents

all_concat	5
all_stat	6
and_bool1	7
and_bool2	7
any_join_datf	8
appndr	10
arroundr_mean	11
arroundr_min	11
better_match	12
better_split	13
better_split_any	13
better_sub	14
better_sub_mult	15
better_unique	16
bind_cols	17

bind_rows	18
can_be_num	18
closer_ptrn	19
closer_ptrn_adv	21
clusterizer_v	23
colins_datf	25
col_converter	26
col_to_row	27
converter_date	27
converter_format	28
cost_and_taxes	29
cumulated_rows	30
cumulated_rows_na	31
cutr_v	31
cut_v	32
data_gen	33
data_meshup	35
date_addr	36
date_converter_reverse	37
datf_appendr	38
datf_appendr2	38
datf_insertr	39
datf_row_appendr	40
datf_row_appendr2	40
dcr_untl	41
dcr_val	42
delta_normal	42
delta_unif	43
depth_pairs_findr	44
diff_datf	44
dynamic_idx_converter	45
edm1_normal_gen	46
edm1_random_val	47
edm1_random_val_spe	48
edm1_runif_deterministic	49
edm_arrangr	49
edm_arrangr2	50
edm_group_by1	51
edm_group_by2	53
edm_pert	54
edm_pivot_longer1	55
edm_pivot_longer2	58
edm_pivot_series	61
edm_pivot_wider1	62
edm_pivot_wider2	64
elements_equalifier	65
equalizer_v	66
extract_normal	67
extrt_only_v	73
fillr	74
fixer_nest_v	74
fold_rec	75

fold_rec2	75
format_date	76
geo_min	76
get_rec	77
globe	77
glue_groupv	78
grep_all	79
grep_all2	79
group_datf	80
gsub_mult	81
historic_sequence1	82
historic_sequence2	83
id_keepr	84
incr_fillr	85
infinite_char_seq	86
inner_all	86
insert_datf	87
intersect_all	88
intersect_mod	89
intersect_mod2	90
inter_max	91
inter_min	92
isnt_divisible	93
is_divisible	93
join_n_lvl	94
just_anything	95
just_anything2	95
just_anything3	96
just_chr	96
just_chr2	97
just_chr3	97
just_nb	98
just_nb2	98
just_nb3	99
just_not_anything	99
just_not_anything2	100
just_not_anything3	100
leap_yr	101
left_all	101
letter_to_nb	102
list_files	102
lst_flatnr	103
match_by	103
match_na_omit	104
multitud	104
mutate_vector	105
nb2_follow	106
nb_follow	107
nb_to_letter	107
nestr_datf1	109
nestr_datf2	110
nest_v	110

new_ordered	111
normal_dens	112
normal_offset_prob	112
normal_offset_val	113
occu	113
old_to_new_idx	114
or_bool1	114
or_bool2	115
pairs_findr	115
pairs_findr_merger	116
pairs_insertr	117
pairs_insertr2	119
paste_datf	120
paste_datf2	121
pattern_generator	121
pattern_gettr	122
pattern_tuning	123
power_to_char	124
pre_to_post_idx	124
ptrn_switchr	125
ptrn_twkr	125
read_edm_parser	126
rearangr_v	127
regex_spe_detect	128
regroupr	128
rm_na_rows	129
rm_rows	130
row_to_col	131
r_print	131
save_untl	132
see_datf	133
see_diff	134
see_diff_all	135
see_diff_detailed	135
see_file	136
see_idx	136
see_inside	137
see_in_grep	138
see_in_l	138
see_mode	139
selected_char	139
sequence_na_mean1	140
sequence_na_mean2	141
sequence_na_med1	142
sequence_na_med2	143
sort_date	144
sort_normal_qual	145
sort_normal_qual2	149
split_by_step	152
str_remove_untl	153
sub_mult	154
successive_diff	155

sum_group1	155
sum_group2	157
swipr	159
test_order	160
time_serie_equalizer	160
to_unique	162
union_all	163
union_keep	163
unique_datf	164
unique_ltr_from_v	165
unique_pos	165
unique_total	166
until_stnl	166
val_replacer	167
vector_replacor	167
vec_in_datf	168
vlookup_datf	169
wider_datf	170
wide_to_narrow_idx	171
write_edm_parser	172

Index	173
--------------	------------

all_concat	<i>all_concat</i>
------------	-------------------

Description

Output all the possible concatenations of elements in different vectors, see examples

Usage

```
all_concat(..., sep = "_")
```

Arguments

...	is all the vectors of the elements that will be concatenated, see examples
sep	is the separator to use between concatenated elements

Examples

```
print(all_concat(c("France", "Germany"), c("2012", "2013"), c(1:2), sep = "_"))
[1] "France_2012_1" "Germany_2012_1" "France_2013_1" "Germany_2013_1"
[5] "France_2012_2" "Germany_2012_2" "France_2013_2" "Germany_2013_2"
```

all_stat

*all_stat***Description**

Allow to see all the main statistics indicators (mean, median, variance, standard deviation, sum, max, min, quantile) of variables in a dataframe by the modality of a variable in a column of the input datarame. In addition to that, you can get the occurrence of other qualitative variables by your chosen qualitative variable, you have just to precise it in the vector "stat_var" where all the statistics indicators are given with "occu-var_you_want/".

Usage

```
all_stat(inpt_v, var_add = c(), stat_var = c(), inpt_datf)
```

Arguments

inpt_v is the modalities of the variables
var_add is the variables you want to get the stats from
stat_var is the stats indicators you want
inpt_datf is the input dataframe

Examples

```
datf <- data.frame("mod"=c("first", "seco", "seco", "first", "first", "third", "first"),
  "var1"=c(11, 22, 21, 22, 22, 11, 9),
  "var2"=c("d", "d", "z", "z", "z", "d", "z"),
  "var3"=c(45, 44, 43, 46, 45, 45, 42),
  "var4"=c("A", "A", "A", "A", "B", "C", "C"))

print(all_stat(inpt_v=c("first", "seco"), var_add = c("var1", "var2", "var3", "var4"),
  stat_var=c("sum", "mean", "median", "sd", "occu-var2/", "occu-var4/", "variance",
"quantile-0.75/"),
  inpt_datf=datf))

#   modal_v var_vector occu sum mean  med standard_devaition      variance
#1      first
#2          var1      64   16 16.5   6.97614984548545 48.66666666666667
#3          var2-d       1
#4          var2-z       3
#5          var3     178 44.5   45   1.73205080756888           3
#6          var4-A       2
#7          var4-B       1
#8          var4-C       1
#9      seco
#10         var1      43 21.5 21.5   0.707106781186548           0.5
#11         var2-d       1
#12         var2-z       1
#13         var3     87 43.5 43.5   0.707106781186548           0.5
#14         var4-A       2
#15         var4-B       0
#16         var4-C       0
#   quantile-0.75
```

```
#1
#2          22
#3
#4
#5          45.25
#6
#7
#8
#9
#10         21.75
#11
#12
#13         43.75
#14
#15
#16
```

`and_bool1`*and_bool1*

Description

Returns a boolean vector according to 'and' condition on boolean vector in a dataframe, each column represents a boolean vector, see examples

Usage

```
and_bool1(inpt_datf)
```

Examples

```
print(and_bool1(inpt_datf = data.frame("bool1" = c(TRUE, FALSE, FALSE, TRUE),
                                         "bool2" = c(TRUE, TRUE, FALSE, TRUE))))

[1]  TRUE FALSE FALSE  TRUE
```

`and_bool2`*and_bool2*

Description

Returns a boolean vector according to 'and' condition on boolean vector in a dataframe, each column represents a boolean vector, see examples, uses a different algorithm than and_bool1

Usage

```
and_bool2(inpt_datf)
```

Examples

```
print(and_bool2(inpt_datf = data.frame("bool1" = c(TRUE, FALSE, FALSE, TRUE),
                                         "bool2" = c(TRUE, TRUE, FALSE, TRUE))))

[1] TRUE FALSE FALSE TRUE
```

any_join_datf	<i>any_join_datf</i>
---------------	----------------------

Description

Allow to perform SQL joints with more features

Usage

```
any_join_datf(
  inpt_datf_l,
  join_type = "inner",
  join_spe = NA,
  id_v = c(),
  excl_col = c(),
  rtn_col = c(),
  d_val = NA
)
```

Arguments

<code>inpt_datf_l</code>	is a list containing all the dataframe
<code>join_type</code>	is the joint type. Defaults to inner but can be changed to a vector containing all the dataframes you want to take their ids to don external joints.
<code>join_spe</code>	can be equal to a vector to do an external joints on all the dataframes. In this case, <code>join_type</code> should not be equal to "inner"
<code>id_v</code>	is a vector containing all the ids name of the dataframes. The ids names can be changed to number of their columns taking in count their position in <code>inpt_datf_l</code> . It means that if my id is in the third column of the second dataframe and the first dataframe have 5 columns, the column number of the ids is $5 + 3 = 8$
<code>excl_col</code>	is a vector containing the column names to exclude, if this vector is filled so "rtn_col" should not be filled. You can also put the column number in the manner indicated for "id_v". Defaults to <code>c()</code>
<code>rtn_col</code>	is a vector containing the column names to retain, if this vector is filled so "excl_col" should not be filled. You can also put the column number in the manner indicated for "id_v". Defaults to <code>c()</code>
<code>d_val</code>	is the default val when here is no match

Examples

[illegible]

```
#10  a8 <NA> <NA>  <NA>      <NA>      4      a  oui      8      4      a  oui
#    second_ids
#1      13
#2      12
#3      <NA>
#4      <NA>
#5      <NA>
#6      <NA>
#7      <NA>
#8      11
#9      <NA>
#10     8
```

```
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type=c(1), id_v=c("ids"),
                    excl_col=c(), rtn_col=c()))
```

```
#ids val ids last second_ids val ids bool second_ids val ids last
#1  e  1  e  oui      13 <NA> <NA>  <NA>      <NA> <NA> <NA> <NA>
#2  a  1  a  oui      11  3   a  TRUE      13   1   a  oui
#3  z  2  z  non      12  7   z  FALSE     12   2   z  non
#4  a  4  a  oui       8  4   a  FALSE     34   9   a  oui
#    second_ids
#1      <NA>
#2      13
#3      12
#4      11
```

appndr	<i>appndr</i>
--------	---------------

Description

Append to a vector "inpt_v" a special value "val" n times "mmn". The appending begins at "strt" index.

Usage

```
appndr(inpt_v, val = NA, hmn, strt = "max")
```

Arguments

- inpt_v is the input vector
- val is the special value
- hmn is the number of special value element added
- strt is the index from which appending begins, defaults to max which means the end of "inpt_v"

Examples

```
print(appndr(inpt_v=c(1:3), val="oui", hmn=5))

#[1] "1"    "2"    "3"    "oui" "oui" "oui" "oui" "oui"

print(appndr(inpt_v=c(1:3), val="oui", hmn=5, strt=1))

#[1] "1"    "oui" "oui" "oui" "oui" "oui" "2"    "3"
```

arroundr_mean	<i>arroundr_mean</i>
---------------	----------------------

Description

Takes an ascendly int ordered vector as input and assigns each elements that are close enough to the same value accrdng to a step value (step_value), see examples.

Usage

```
arroundr_mean(inpt_v = c(), step_val)
```

Arguments

inpt_v	is the input vector
step_val	is the step_value

Examples

```
x <- arroundr_mean(inpt_v = c(-11:25), step_val = 5)
print(x)
print(length(x))

[1] -9.0 -9.0 -9.0 -9.0 -9.0 -4.0 -4.0 -4.0 -4.0 -4.0  1.0  1.0  1.0  1.0  1.0
[16]  6.0  6.0  6.0  6.0  6.0 11.0 11.0 11.0 11.0 11.0 16.0 16.0 16.0 16.0 16.0
[31] 21.0 21.0 21.0 21.0 21.0 23.8 23.8
[1] 37
```

arroundr_min	<i>arroundr_min</i>
--------------	---------------------

Description

Takes an ascendly int ordered vector as input and assigns each elements that are close enough to the same value accrdng to a step value (step_value), see examples.

Usage

```
arroundr_min(inpt_v = c(), step_val)
```

Arguments

inpt_v is the input vector
step_val is the step value

Examples

```
print(arroundr_min(inpt_v = c(-11:25), step_val = 5))  
  
[1] -11 -11 -11 -11 -11 -11 -11 -6 -6 -6 -6 -6 -1 -1 -1 -1 -1 4 4 4  
[20] 4 4 9 9 9 9 9 9 14 14 14 14 14 19 19 19 19 19 24
```

better_match	<i>better_match</i>
--------------	---------------------

Description

Allow to get the nth element matched in a vector

Usage

```
better_match(inpt_v = c(), ptrn, until = 1, nvr_here = NA)
```

Arguments

inpt_v is the input vector
ptrn is the pattern to be matched
until is the maximum number of matched pattern outputed
nvr_here is a value you are sure is not present in inpt_v

Examples

```
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=1))  
  
#[1] 3  
  
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=5))  
  
#[1] 3 13 16  
  
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=c(3, 4), until=5))  
  
[1] 3 13 16 4 14  
  
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=c(3, 4), until=c(1, 5)))  
  
[1] 3 4 14
```

better_split	<i>better_split</i>
--------------	---------------------

Description

Allows to split a string by multiple split, returns a vector and not a list.

Usage

```
better_split(inpt, split_v = c())
```

Arguments

inpt	is the input character
split_v	is the vector containing the splits

Examples

```
print(better_split(inpt = "o-u_i", split_v = c("-")))  
[1] "o"    "u_i"  
  
print(better_split(inpt = "o-u_i", split_v = c("-", "_")))  
[1] "o" "u" "i"
```

better_split_any	<i>better_split_any</i>
------------------	-------------------------

Description

Allows to split a string by multiple split regardless of their length, returns a vector and not a list.
Contrary to better_split, this functions keep the delimiters in the output.

Usage

```
better_split_any(inpt, split_v = c())
```

Arguments

inpt	is the input character
split_v	is the vector containing the splits

Examples

```
print(better_split_any(inpt = "o-u_i", split_v = c("-")))

[1] "o"  "-" "u_i"

print(better_split_any(inpt = "o-u_i", split_v = c("-", "_")))

[1] "o"  "-" "u"  "_" "i"

print(better_split_any(inpt = "--o--_/m/m/___opo-/m/-u_i_--", split_v = c("--", "_", "/"

[1] "--"      "o"      "--"      "_"      "/"      "m"      "/"      "m"      "/"
[10] "_"      "_"      "-opo-"   "/"      "m"      "/"      "-u"      "_"      "i-"
[19] "_"      "--"

print(better_split_any(inpt = "(ok(ee:56))(ok2(oui)(ee:4))", split_v = c("(", ")", ":")))

[1] "("      "ok"     "("      "ee"     ":"      "56"     ")"      ")"      "("      "ok2"    "("      "oui"
[13] ")"      "("      "ee"     ":"      "4"      ")"      ")"
```

better_sub

*better_sub***Description**

Allow to perform a sub operation to a given number of matched patterns, see examples

Usage

```
better_sub(inpt_v = c(), pattern, replacement, until_v = c())
```

Arguments

inpt_v	is a vector containing all the elements that contains expressions to be substituted
pattern	is the expression that will be substituted
replacement	is the expression that will substitute pattern
until_v	is a vector containing, for each element of inpt_v, the number of pattern that will be substituted

Examples

```
print(better_sub(inpt_v = c("yes NAME, i will call NAME and NAME",
                             "yes NAME, i will call NAME and NAME"),
               pattern = "NAME",
               replacement = "Kevin",
               until = c(2)))

[1] "yes Kevin, i will call Kevin and NAME"
[2] "yes Kevin, i will call Kevin and NAME"
```

```

print(better_sub(inp_v = c("yes NAME, i will call NAME and NAME",
                           "yes NAME, i will call NAME and NAME"),
      pattern = "NAME",
      replacement = "Kevin",
      until = c(2, 3)))

[1] "yes Kevin, i will call Kevin and NAME"
[2] "yes Kevin, i will call Kevin and Kevin"

print(better_sub(inp_v = c("yes NAME, i will call NAME and NAME",
                           "yes NAME, i will call NAME and NAME"),
      pattern = "NAME",
      replacement = "Kevin",
      until = c("max", 3)))

[1] "yes Kevin, i will call Kevin and Kevin"
[2] "yes Kevin, i will call Kevin and Kevin"

```

better_sub_mult	<i>better_sub_mult</i>
-----------------	------------------------

Description

Allow to perform a sub_mult operation to a given number of matched patterns, see examples

Usage

```

better_sub_mult(
  inp_v = c(),
  pattern_v = c(),
  replacement_v = c(),
  until_v = c()
)

```

Arguments

<code>inp_v</code>	is a vector containing all the elements that contains expressions to be substituted
<code>pattern_v</code>	is a vector containing all the patterns to be substituted in any elements of <code>inp_v</code>
<code>replacement_v</code>	is a vector containing the expression that are going to substitute those provided by <code>pattern_v</code>
<code>until_v</code>	is a vector containing, for each element of <code>inp_v</code> , the number of pattern that will be substituted

Examples

```

print(better_sub_mult(inp_v = c("yes NAME, i will call NAME and NAME2",
                                "yes NAME, i will call NAME and NAME2, especially NAME2"),
  pattern_v = c("NAME", "NAME2"),
  replacement_v = c("Kevin", "Paul"),
  until = c(1, 3)))

```

```

[1] "yes Kevin, i will call NAME and Paul"
[2] "yes Kevin, i will call NAME and Paul, especially Paul"

print(better_sub_mult(inpt_v = c("yes NAME, i will call NAME and NAME2",
                                "yes NAME, i will call NAME and NAME2, especially NAME2"),
                    pattern_v = c("NAME", "NAME2"),
                    replacement_v = c("Kevin", "Paul"),
                    until = c("max", 3)))

[1] "yes Kevin, i will call Kevin and Kevin2"
[2] "yes Kevin, i will call Kevin and Kevin2, especially Kevin2"

```

better_unique	<i>better_unique</i>
---------------	----------------------

Description

Returns the element that are not unique from the input vector

Usage

```
better_unique(inpt_v, occu = ">-1-")
```

Arguments

<code>inpt_v</code>	is the input vector containing the elements
<code>occu</code>	is a parameter that specifies the occurrence of the elements that must be returned, defaults to ">-1-" it means that the function will return all the elements that are present more than one time in <code>inpt_v</code> . The syntax is the following "comparaison_type-actual_value-". The comparaison type may be "==" or ">" or "<". Occu can also be a vector containing all the occurrence that must have the elements to be returned.

Examples

```

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non")))

#[1] "oui" "non"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu="=")

#[1] "oui"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=">")

#[1] "non"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=c("non", "peut", "peut1"))

#[1] "non" "peut" "peut1"

```



```
print(better_unique(inpt_v = c("a", "b", "c", "c"), occu = "=="-1-"))  
[1] "a" "b"  
  
print(better_unique(inpt_v = c("a", "b", "c", "c"), occu = "<-2-"))  
[1] "a" "b"
```

`bind_cols`*bind_cols*

Description

Allow to find the cols of a dataframe in an other dataframe, see examples

Usage

```
bind_cols(from_datf, in_datf)
```

Arguments

<code>from_datf</code>	is the dataframe that contains the cols to find among other cols
<code>in_datf</code>	is the dataframe that only contains the cols to find in from_datf

Examples

```
iris[, 5] <- as.character(iris[, 5])  
iris <- cbind(iris, iris[, 4])  
from_datf <- iris  
in_datf <- iris[, c(1, 2, 2, 2, 4)]  
bind_cols(from_datf = from_datf,  
          in_datf = in_datf)  
  
[[1]]  
[1] 1  
  
[[2]]  
[1] 2  
  
[[3]]  
[1] 2  
  
[[4]]  
[1] 2  
  
[[5]]  
[1] 4 6
```

bind_rows	<i>bind_rows</i>
-----------	------------------

Description

Allow to find the rows of a dataframe in an other dataframe, see examples

Usage

```
bind_rows(from_datf, in_datf)
```

Arguments

`from_datf` is the dataframe that contains the rows to find among other rows
`in_datf` is the dataframe that only contains the rows to find in `from_datf`

Examples

```
iris[, 5] <- as.character(iris[, 5])
from_datf <- iris
in_datf <- iris[c(4, 2, 23, 21, 11), ]

bind_rows(from_datf = from_datf,
          in_datf = in_datf)

[[1]]
[1] 4

[[2]]
[1] 2

[[3]]
[1] 23

[[4]]
[1] 21

[[5]]
[1] 11
```

can_be_num	<i>can_be_num</i>
------------	-------------------

Description

Return TRUE if a variable can be converted to a number and FALSE if not (supports float)

Usage

```
can_be_num(x)
```

Arguments

`x` is the input value

Examples

```
print(can_be_num("34.677"))
#[1] TRUE

print(can_be_num("34"))
#[1] TRUE

print(can_be_num("3rt4"))
#[1] FALSE

print(can_be_num(34))
#[1] TRUE
```

closer_ptrn

closer_ptrn

Description

Take a vector of patterns as input and output each chosen word with their closest patterns from chosen patterns.

Usage

```
closer_ptrn(
  inpt_v,
  base_v = c("?", letters),
  excl_v = c(),
  rtn_v = c(),
  sub_excl_v = c(),
  sub_rtn_v = c()
)
```

Arguments

<code>inpt_v</code>	is the input vector containing all the patterns
<code>base_v</code>	must contain all the characters that the patterns are susceptible to contain, defaults to <code>c("?", letters)</code> . "?" is necessary because it is internally the default value added to each element that does not have a sufficient length compared to the longest pattern in <code>inpt_v</code> . If set to NA, the function will find by itself the elements to be filled with but it may take an extra time
<code>excl_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to exclude for comparing them to others patterns. If this parameter is filled, so <code>"rtn_v"</code> must be empty.

`rtn_v` is the vector containing all the patterns from `inpt_v` to keep for comparing them to others patterns. If this parameter is filled, so `"rtn_v"` must be empty.

`sub_excl_v` is the vector containing all the patterns from `inpt_v` to exclude for using them to compare to another pattern. If this parameter is filled, so `"sub_rtn_v"` must be empty.

`sub_rtn_v` is the vector containing all the patterns from `inpt_v` to retain for using them to compare to another pattern. If this parameter is filled, so `"sub_excl_v"` must be empty.

Examples

```
print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir"),
  #[[1]]
  #[1] "bonjour"
  #
  #[[2]]
  #[1] "lpoerc"      "nonnour"      "bonnour"      "nonjour"      "aurevoir"
  #
  #[[3]]
  #[1] 1 1 2 7 8
  #
  #[[4]]
  #[1] "lpoerc"
  #
  #[[5]]
  #[1] "bonjour"      "nonnour"      "bonnour"      "nonjour"      "aurevoir"
  #
  #[[6]]
  #[1] 7 7 7 7 7
  #
  #[[7]]
  #[1] "nonnour"
  #
  #[[8]]
  #[1] "bonjour"      "lpoerc"      "bonnour"      "nonjour"      "aurevoir"
  #
  #[[9]]
  #[1] 1 1 2 7 8
  #
  #[[10]]
  #[1] "bonnour"
  #
  #[[11]]
  #[1] "bonjour"      "lpoerc"      "nonnour"      "nonjour"      "aurevoir"
  #
  #[[12]]
  #[1] 1 1 2 7 8
  #
  #[[13]]
  #[1] "nonjour"
  #
  #[[14]]
  #[1] "bonjour"      "lpoerc"      "nonnour"      "bonnour"      "aurevoir"
  #
  #[[15]]
```

```

#[1] 1 1 2 7 8
#
#[[16]]
#[1] "aurevoir"
#
#[[17]]
#[1] "bonjour" "lpoerc" "nonnour" "bonnour" "nonjour"
#
#[[18]]
#[1] 7 8 8 8 8

print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir", "nonjour"),
excl_v=c("nonnour", "nonjour"),
      sub_excl_v=c("nonnour")))

#[1] 3 5
#[[1]]
#[1] "bonjour"
#
#[[2]]
#[1] "lpoerc" "bonnour" "nonjour" "aurevoir"
#
#[[3]]
#[1] 1 1 7 8
#
#[[4]]
#[1] "lpoerc"
#
#[[5]]
#[1] "bonjour" "bonnour" "nonjour" "aurevoir"
#
#[[6]]
#[1] 7 7 7 7
#
#[[7]]
#[1] "bonnour"
#
#[[8]]
#[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"
#
#[[9]]
#[1] 0 1 2 7 8
#
#[[10]]
#[1] "aurevoir"
#
#[[11]]
#[1] "bonjour" "lpoerc" "nonjour" "aurevoir"
#
#[[12]]
#[1] 0 7 8 8

```

Description

Allow to find how patterns are far or near between each other relatively to a vector containing characters at each index ("base_v"). The function gets the sum of the indexes of each pattern letter relatively to the characters in base_v. So each pattern can be compared.

Usage

```
closer_ptrn_adv(
  inpt_v,
  res = "raw_stat",
  default_val = "?",
  base_v = c(default_val, letters),
  c_word = NA
)
```

Arguments

inpt_v	is the input vector containing all the patterns to be analyzed
res	is a parameter controlling the result. If set to "raw_stat", each word in inpt_v will come with its score (indexes of its letters relatively to base_v). If set to something else, so "c_word" parameter must be filled.
default_val	is the value that will be added to all patterns that do not equal the length of the longest pattern in inpt_v. Those get this value added to make all patterns equal in length so they can be compared, defaults to "?"
base_v	is the vector from which all pattern get its result (letters indexes for each pattern relatively to base_v), defaults to c("default_val", letters). "default_val" is another parameter and letters is all the western alphabetic letters in a vector
c_word	is a pattern from which the nearest to the farthest pattern in inpt_v will be compared

Examples

```
print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois", "bonjour"),
  res="word", c_word="bonjour"))

#[[1]]
#[1] 1 5 15 17 38 65
#
#[[2]]
#[1] "bonjour" "bonnour" "aurevoir" "nonnour" "mois" "fin"

print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois")))

#[[1]]
#[1] 117 107 119 37 64
#
#[[2]]
#[1] "aurevoir" "bonnour" "nonnour" "fin" "mois"
```

clusterizer_v	<i>clusterizer_v</i>
---------------	----------------------

Description

Allow to output clusters of elements. Takes as input a vector "inpt_v" containing a sequence of number. Can also take another vector "w_v" that has the same size of inpt_v because its elements are related to it. The way the clusters are made is related to an accuracy value which is "c_val". It means that if the difference between the values associated to 2 elements is superior to c_val, these two elements are in distinct clusters. The second element of the outputed list is the begin and end value of each cluster.

Usage

```
clusterizer_v(inpt_v, w_v = NA, c_val)
```

Arguments

inpt_v	is the vector containing the sequence of number
w_v	is the vector containing the elements related to inpt_v, defaults to NA
c_val	is the accuracy of the clusterization

Examples

```
print(clusterizer_v(inpt_v=sample.int(20, 26, replace=TRUE), w_v=NA, c_val=0.9))

# [[1]]
# [[1]] [[1]]
# [1] 1
#
# [[1]] [[2]]
# [1] 2
#
# [[1]] [[3]]
# [1] 3
#
# [[1]] [[4]]
# [1] 4
#
# [[1]] [[5]]
# [1] 5 5
#
# [[1]] [[6]]
# [1] 6 6 6 6
#
# [[1]] [[7]]
# [1] 7 7 7
#
# [[1]] [[8]]
# [1] 8 8 8
#
# [[1]] [[9]]
# [1] 9
```

```

#
#[[1]][[10]]
#[1] 10
#
#[[1]][[11]]
#[1] 12
#
#[[1]][[12]]
#[1] 13 13 13
#
#[[1]][[13]]
#[1] 18 18 18
#
#[[1]][[14]]
#[1] 20
#
#
#[[2]]
# [1] "1" "1" "-" "2" "2" "-" "3" "3" "-" "4" "4" "-" "5" "5" "-"
#[16] "6" "6" "-" "7" "7" "-" "8" "8" "-" "9" "9" "-" "10" "10" "-"
#[31] "12" "12" "-" "13" "13" "-" "18" "18" "-" "20" "20"

print(clusterizer_v(inpt_v=sample.int(40, 26, replace=TRUE), w_v=letters, c_val=0.29))

#[[1]]
#[[1]][[1]]
#[1] "a"
#
#[[1]][[2]]
#[1] "b"
#
#[[1]][[3]]
#[1] "c" "d"
#
#[[1]][[4]]
#[1] "e" "f"
#
#[[1]][[5]]
#[1] "g" "h" "i" "j"
#
#[[1]][[6]]
#[1] "k"
#
#[[1]][[7]]
#[1] "l"
#
#[[1]][[8]]
#[1] "m" "n"
#
#[[1]][[9]]
#[1] "o"
#
#[[1]][[10]]
#[1] "p"
#
#[[1]][[11]]
#[1] "q" "r"

```



```

#
#[[1]][[12]]
#[1] "s" "t" "u"
#
#[[1]][[13]]
#[1] "v"
#
#[[1]][[14]]
#[1] "w"
#
#[[1]][[15]]
#[1] "x"
#
#[[1]][[16]]
#[1] "y"
#
#[[1]][[17]]
#[1] "z"
#
#
#[[2]]
# [1] "13" "13" "-" "14" "14" "-" "15" "15" "-" "16" "16" "-" "17" "17" "-"
#[16] "19" "19" "-" "21" "21" "-" "22" "22" "-" "23" "23" "-" "25" "25" "-"
#[31] "27" "27" "-" "29" "29" "-" "30" "30" "-" "31" "31" "-" "34" "34" "-"
#[46] "35" "35" "-" "37" "37"

```

colins_datf

colins_datf

Description

Allow to insert vectors into a dataframe.

Usage

```
colins_datf(inpt_datf, target_col = list(), target_pos = list())
```

Arguments

inpt_datf	is the dataframe where vectors will be inserted
target_col	is a list containing all the vectors to be inserted
target_pos	is a list containing the vectors made of the columns names or numbers where the associated vectors from target_col will be inserted after

Examples

```

datf1 <- data.frame("frst_col"=c(1:5), "scd_col"=c(5:1))

print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
  c("u", "z", "z", "z", "u")),
  target_pos=list(c("frst_col", "scd_col"), c("scd_col"))))

```

```
#   first_col cur_col scd_col cur_col.1 cur_col
#1         1     oui      5         oui      u
#2         2     oui      4         oui      z
#3         3     oui      3         oui      z
#4         4     non      2         non      z
#5         5     non      1         non      u

print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
  c("u", "z", "z", "z", "u")),
  target_pos=list(c(1, 2), c("first_col"))))

#   first_col cur_col scd_col cur_col cur_col
#1         1     oui      5         u     oui
#2         2     oui      4         z     oui
#3         3     oui      3         z     oui
#4         4     non      2         z     non
#5         5     non      1         u     non
```

col_converttr

col_converttr

Description

Allow to convert all column that may be converted to a numeric, to a numeric, see examples

Usage

```
col_converttr(inpt_datf)
```

Arguments

inpt_datf is the input dataframe

Examples

```
datf <- mtcars
datf[, 3] <- as.character(datf[, 3])
datf[, 4] <- as.character(datf[, 4])
str(datf)

'data.frame': 32 obs. of 11 variables:
 $ mpg : num  21 21 22.8 21.4 18.7 18.1 14.3 24.4 22.8 19.2 ...
 $ cyl : num   6  6  4  6  8  6  8  4  4  6 ...
 $ disp: chr  "160" "160" "108" "258" ...
 $ hp  : chr  "110" "110" "93" "110" ...
 $ drat: num   3.9 3.9 3.85 3.08 3.15 2.76 3.21 3.69 3.92 3.92 ...
 $ wt  : num   2.62 2.88 2.32 3.21 3.44 ...
 $ qsec: num   16.5 17 18.6 19.4 17 ...
 $ vs  : num    0  0  1  1  0  1  0  1  1  1 ...
 $ am  : num    1  1  1  0  0  0  0  0  0  0 ...
 $ gear: num    4  4  4  3  3  3  3  4  4  4 ...
 $ carb: num    4  4  1  1  2  1  4  2  2  4 ...
```

```
datf <- col_converttr(inpt_datf = datf)

all(datf == mtcars)

[1] TRUE
```

col_to_row

col_to_row

Description

Allow to reverse a dataframe (cols become rows and rows become cols)

Usage

```
col_to_row(inpt_datf)
```

Arguments

inpt_datf is the inout dataframe

Examples

```
datf_test <- data.frame(c(1:11), c(11:1))

print(col_to_row(inpt_datf = datf_test))

  X1 X2 X3 X4 X5 X6 X7 X8 X9 X10 X11
1  1  2  3  4  5  6  7  8  9  10  11
2 11 10  9  8  7  6  5  4  3  2  1
```

converter_date

converter_date

Description

Allow to convert any date like second/minute/hour/day/month/year to either second, minute...year. The input date should not necessarily have all its time units (second, minute...) but all the time units according to a format. Example: "snhdmy" is for second, hour, minute, day, month, year. And "mdy" is for month, day, year.

Usage

```
converter_date(inpt_date, convert_to, frmt = "snhdmy", sep_ = "-")
```

Arguments

inpt_date	is the input date
convert_to	is the time unit the input date will be converted ("s", "n", "h", "d", "m", "y")
frmt	is the format of the input date
sep_	is the separator of the input date. For example this input date "12-07-2012" has "-" as a separator

Examples

```
print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="m"))
#[1] 24299.15

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="y"))
#[1] 2024.929

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="s"))
#[1] 63900626400

print(converter_date(inpt_date="63900626400", sep_="-", frmt="s", convert_to="y"))
#[1] 2024.929

print(converter_date(inpt_date="2024", sep_="-", frmt="y", convert_to="s"))
#[1] 63873964800
```

converter_format	converter_format
------------------	------------------

Description

Allow to convert a format to another

Usage

```
converter_format(inpt_val, sep_ = "-", inpt_frmt, frmt, default_val = "00")
```

Arguments

inpt_val	is the input value that is linked to the format
sep_	is the separator of the value in inpt_val
inpt_frmt	is the format of the input value
frmt	is the format you want to convert to
default_val	is the default value given to the units that are not present in the input format

Examples

```
print(converter_format(inpt_val="23-12-05-1567", sep="-",
                       inpt_frmt="shmy", frmt="snhdmy", default_val="00"))

#[1] "23-00-12-00-05-1567"

print(converter_format(inpt_val="23-12-05-1567", sep="-",
                       inpt_frmt="shmy", frmt="Pnhdmy", default_val="00"))

#[1] "00-00-12-00-05-1567"
```

cost_and_taxes	<i>cost_and_taxes</i>
----------------	-----------------------

Description

Allow to calculate basic variables related to cost and taxes from a bunch of products (elements). So put every variable you know in the following order:

Usage

```
cost_and_taxes(
  qte = NA,
  pu = NA,
  prix_ht = NA,
  tva = NA,
  prix_ttc = NA,
  prix_tva = NA,
  pu_ttc = NA,
  adjust = NA,
  prix_d_ht = NA,
  prix_d_ttc = NA,
  pu_d = NA,
  pu_d_ttc = NA
)
```

Arguments

qte	is the quantity of elements
pu	is the price of a single elements without taxes
prix_ht	is the duty-free price of the whole set of elements
tva	is the percentage of all taxes
prix_ttc	is the price of all the elements with taxes
prix_tva	is the cost of all the taxes
pu_ttc	is the price of a single element taxes included
adjust	is the discount percentage
prix_d_ht	is the free-duty price of an element after discount
prix_d_ttc	is the price with taxes of an element after discount
pu_d	is the price of a single element after discount and without taxes
pu_d_ttc	is the free-duty price of a single element after discount

Examples

```
print(cost_and_taxes(pu=45, prix_ttc=2111, qte=23))

# [1] 23.000000 45.000000 45.000000 1.039614 2111.000000 1076.000000
#[7] 45.000000 NA NA NA NA NA
```

cumulated_rows	<i>cumulated_rows</i>
----------------	-----------------------

Description

Output a vector of size that equals to the rows number of the input dataframe, with TRUE value at the indices corresponding to the row where at least a cell of any column is equal to one of the values inputed in values_v

Usage

```
cumulated_rows(inpt_datf, values_v = c())
```

Arguments

inpt_datf	is the input data.frame
values_v	is a vector containing all the values that a cell has to equal to return a TRUE value in the output vector at the index corresponding to the row of the cell

Examples

```
datf_teste <- data.frame(c(1:10), c(10:1))

print(datf_teste)

  c.1.10. c.10.1.
1      1      10
2      2       9
3      3       8
4      4       7
5      5       6
6      6       5
7      7       4
8      8       3
9      9       2
10     10       1

print(cumulated_rows(inpt_datf = datf_teste, values_v = c(2, 3)))

[1] FALSE TRUE TRUE FALSE FALSE FALSE FALSE TRUE TRUE FALSE
```

cumulated_rows_na	<i>cumulated_rows_na</i>
-------------------	--------------------------

Description

Output a vector of size that equals to the rows number of the input dataframe, with TRUE value at the indices corresponding to the row where at least a cell of any column is equal to NA.

Usage

```
cumulated_rows_na(inpt_datf)
```

Arguments

`inpt_datf` is the input data.frame

Examples

```
datf_teste <- data.frame(c(1, 2, 3, 4, 5, NA, 7), c(10, 9, 8, NA, 7, 6, NA))
print(datf_teste)

  c.1..2..3..4..5..NA..7. c.10..9..8..NA..7..6..NA.
1                        1                        10
2                        2                        9
3                        3                        8
4                        4                        NA
5                        5                        7
6                       NA                        6
7                        7                        NA

print(cumulated_rows_na(inpt_datf = datf_teste))

[1] FALSE FALSE FALSE  TRUE FALSE  TRUE  TRUE
```

cutr_v	<i>cutr_v</i>
--------	---------------

Description

Allow to reduce all the elements in a vector to a defined size of nchar

Usage

```
cutr_v(inpt_v, until = "min")
```

Arguments

`inpt_v` is the input vector

`until` is the maximum size of nchar authorized by an element, defaults to "min", it means the shortest element in the list

Examples

```
test_v <- c("oui", "nonon", "ez", "aa", "a", "dsfsdsds")

print(cutr_v(inpt_v=test_v, until="min"))

#[1] "o" "n" "e" "a" "a" "d"

print(cutr_v(inpt_v=test_v, until=3))

#[1] "oui" "non" "ez" "aa" "a" "dsf"
```

cut_v

*cut_v***Description**

Allow to convert a vector to a dataframe according to a separator.

Usage

```
cut_v(inpt_v, sep_ = "")
```

Arguments

`inpt_v` is the input vector

`sep_` is the separator of the elements in `inpt_v`, defaults to ""

Examples

```
print(cut_v(inpt_v=c("oui", "non", "oui", "non")))

#      X.o. X.u. X.i.
#oui "o" "u" "i"
#non "n" "o" "n"
#oui "o" "u" "i"
#non "n" "o" "n"

print(cut_v(inpt_v=c("ou-i", "n-on", "ou-i", "n-on"), sep_="-"))

#      X.ou. X.i.
#ou-i "ou" "i"
#n-on "n" "on"
#ou-i "ou" "i"
#n-on "n" "on"
```

data_gen	<i>data_gen</i>
----------	-----------------

Description

Allo to generate in a csv all kind of data you can imagine according to what you provide

Usage

```
data_gen(
  type_ = c("number", "mixed", "string"),
  strt_l = c(0, 0, 10),
  nb_r = c(50, 10, 40),
  output = NA,
  properties = c("1-5", "1-5", "1-5"),
  type_distri = c("random", "random", "random"),
  str_source = c("a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m",
    "o", "p", "q", "r", "s", "t", "u", "w", "x", "y", "z"),
  round_l = c(0, 0, 0),
  sep_ = ",",
)
```

Arguments

type_	is a vector. Its arguments designates a column, a column can be made of numbers ("number"), string ("string") or both ("mixed")
strt_l	is a vector containing for each column the row from which the data will begin to be generated
nb_r	is a vector containing for each column, the number of row full from generated data
output	is the name of the output csv file, defaults to NA so no csv will be outputted by default
properties	is linked to type_distri because it is the parameters ("min_val-max_val") for "random type", ("u-x") for the poisson distribution, ("u-d") for gaussian distribution
type_distri	is a vector which, for each column, associate a type of distribution ("random", "poisson", "gaussian"), it means that not only the number but also the length of the string will be randomly generated according to these distribution laws
str_source	is the source (vector) from which the character creating random string are (default set to the occidental alphabet)
round_l	is a vector which, for each column containing number, associate a round value, if the type of the value is numeric
sep_	is the separator used to write data in the csv

Value

new generated data in addition to saving it in the output

Examples

```

print(data_gen())

#   X1   X2   X3
#1   4   2  <NA>
#2   2   4  <NA>
#3   5   2  <NA>
#4   2 abcd  <NA>
#5   4 abcd  <NA>
#6   2   4  <NA>
#7   2  abc  <NA>
#8   4  abc  <NA>
#9   4   3  <NA>
#10  4  abc  abcd
#11  5 <NA>  abc
#12  4 <NA>  abc
#13  1 <NA>  ab
#14  1 <NA> abcde
#15  2 <NA>  abc
#16  4 <NA>   a
#17  1 <NA>  abcd
#18  4 <NA>  ab
#19  2 <NA>  abcd
#20  3 <NA>  ab
#21  3 <NA>  abcd
#22  2 <NA>   a
#23  4 <NA>  abc
#24  1 <NA>  abcd
#25  4 <NA>  abc
#26  4 <NA>  ab
#27  2 <NA>  abc
#28  5 <NA>  ab
#29  3 <NA>  abc
#30  5 <NA>  abcd
#31  2 <NA>  abc
#32  2 <NA>  abc
#33  1 <NA>  ab
#34  5 <NA>   a
#35  4 <NA>  ab
#36  1 <NA>  ab
#37  1 <NA> abcde
#38  5 <NA>  abc
#39  4 <NA>  ab
#40  5 <NA> abcde
#41  2 <NA>  ab
#42  3 <NA>  ab
#43  2 <NA>  ab
#44  4 <NA>  abcd
#45  5 <NA>  abcd
#46  3 <NA>  abcd
#47  2 <NA>  abcd
#48  3 <NA>  abcd
#49  3 <NA>  abcd
#50  4 <NA>   a

print(data_gen(strt_l=c(0, 0, 0), nb_r=c(5, 5, 5)))

```

```
# X1 X2 X3
#1 2 a abc
#2 3 abcde ab
#3 4 abcde a
#4 1 3 abc
#5 3 a abcd
```

data_mesgup

data_mesgup

Description

Allow to automatically arrange 1 dimensional data according to vector and parameters

Usage

```
data_mesgup(
  data,
  cols = NA,
  file_ = NA,
  sep_ = ";",
  organisation = c(2, 1, 0),
  unic_sep1 = "_",
  unic_sep2 = "-"
)
```

Arguments

data	is the data provided (vector) each column is separated by a unic separator and each dataset from the same column is separated by another unic separator (ex: <code>c("", c("d", "-", "e", "-", "f"), "", c("a", "a1", "-", "b", "-", "c", "c1"), "_")</code>)
cols	are the colnames of the data generated in a csv
file_	is the file to which the data will be outputed, defaults to NA which means that the functio will return the dataframe generated and won't write it to a csv file
sep_	is the separator of the csv outputed
organisation	is the way variables include themselves, for instance ,resuming precedent example, if organisation=c(1, 0) so the data output will be: d, a d, a1 e, c f, c f, c1
unic_sep1	is the unic separator between variables (default is "_")
unic_sep2	is the unic separator between datasets (default is "-")

Examples

```
print(data_mesgup(data=c("_", c("-", "d", "-", "e", "-", "f"), "_",
  c("-", "a", "a1", "-", "B", "r", "uy", "-", "c", "c1"), "_"), organisation=c(1, 0)))

# X1 X2
#1 d a
#2 d a1
#3 e B
```

```
#4 e r
#5 e uy
#6 f c
#7 f c1
```

date_addr	<i>date_addr</i>
-----------	------------------

Description

Allow to add or subtract two dates that have the same time unit or not

Usage

```
date_addr(  
  date1,  
  date2,  
  add = FALSE,  
  frmt1,  
  frmt2 = frmt1,  
  sep_ = "-",  
  convert_to = "dmy"  
)
```

Arguments

- date1 is the date from which the second date will be added or subtracted
- date2 is the date that will be added or will subtract date1
- add equals to FALSE if you want date1 - date2 and TRUE if you want date1 + date2
- frmt1 is the format of date1 (snhdmy) (second, minute, hour, day, monthn year)
- frmt2 is the format of date2 (snhdmy)
- sep_ is the separator of date1 and date2
- convert_to is the format of the outputed date

Examples

```
print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",  
  convert_to="dmy"))  
  
#[1] "18-2-0"  
  
print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",  
  convert_to="dmy", add=TRUE))  
  
#[1] "3-3-0"  
  
print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",  
  convert_to="dmy", add=TRUE))  
  
#[1] "27-3-2024"
```

```
print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="dmy", add=False))

#[1] "23-1-2024"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="n", add=False))

#[1] "1064596320"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="s", add=False))

#[1] "63875779200"
```

```
date_converter_reverse
      date_converter_reverse
```

Description

Allow to convert single date value like 2025.36 year to a date like second/minutehour/day/month/year (snhdmy)

Usage

```
date_converter_reverse(inpt_date, convert_to = "dmy", frmt = "y", sep_ = "-")
```

Arguments

inpt_date	is the input date
convert_to	is the date format the input date will be converted
frmt	is the time unit of the input date
sep_	is the separator of the outputed date

Examples

```
print(date_converter_reverse(inpt_date="2024.929", convert_to="hmy", frmt="y", sep_="-"))

#[1] "110-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dmy", frmt="y", sep_="-"))

#[1] "4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="hdmy", frmt="y", sep_="-"))

#[1] "14-4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dhym", frmt="y", sep_="-"))
```

```
#[1] "4-14-2024-11"
```

<code>datf_appendr</code>	<i>datf_appendr</i>
---------------------------	---------------------

Description

Allow to append all columns of a dataframe in a vector.

Usage

```
datf_appendr(inpt_datf)
```

Arguments

`inpt_datf` is the input dataframe

Examples

```
datf_teste <- data.frame("col1" = c(1:5), "col2" = c(5:1))

print(datf_appendr(inpt_datf = datf_teste))

[1] 1 2 3 4 5 5 4 3 2 1
```

<code>datf_appendr2</code>	<i>datf_appendr2</i>
----------------------------	----------------------

Description

Allow to append all columns of a dataframe in a vector, specifying the column types ("integer" or "character"), see examples

Usage

```
datf_appendr2(inpt_datf, chs_type = "integer")
```

Arguments

`inpt_datf` is the inout dataframe

Examples

```
datf_teste <- data.frame("col1" = c(1:5), "col2" = c(5:1),
  "col3" = c("oui", "oui", "oui", "non", "non"))

print(datf_appendr2(inpt_datf = datf_teste, chs_type = "integer"))

[1] 1 2 3 4 5 5 4 3 2 1

print(datf_appendr2(inpt_datf = datf_teste, chs_type = "character"))

[1] "oui" "oui" "oui" "non" "non"
```

datf_insertr	<i>datf_insertr</i>
--------------	---------------------

Description

Insert rows after certain indexes, see examples

Usage

```
datf_insertr(inpt_datf, ids_vec, val_l)
```

Arguments

inpt_datf	is the input dataframe
ids_vec	is the ids where the rows has to be inserted after
val_l	is a list containing all the rows (vector) to be inserted, linked to every index within ids_vec

Examples

```
datf <- data.frame(c(1:4), c(4:1))
print(datf)

  c.1.4. c.4.1.
1      1      4
2      2      3
3      3      2
4      4      1

print(datf_insertr(inpt_datf = datf, ids_vec = c(1, 3), val_l = list(c("non", "non"), c("oui", "oui"))))

  c.1.4. c.4.1.
1      1      4
2    non    non
21     2      3
3      3      2
5    oui    oui
4      4      1

print(datf_insertr(inpt_datf = datf, ids_vec = c(1, 3), val_l = list(c("non", "non"))))
```

	c.1.4.	c.4.1.
1	1	4
2	non	non
21	2	3
3	3	2
5	non	non
4	4	1

`datf_row_appendr` *datf_row_appendr*

Description

Allow to append all rows of a dataframe in a vector.

Usage

```
datf_row_appendr(inpt_datf)
```

Arguments

`inpt_datf` is the input dataframe

Examples

```
datf_teste <- data.frame("col1" = c(1:5), "col2" = c(5:1))

print(datf_appendr(inpt_datf = datf_teste))

col1 col2 col1 col2 col1 col2 col1 col2 col1 col2
   1    5    2    4    3    3    4    2    5    1
```

`datf_row_appendr2` *datf_row_appendr2*

Description

Allow to append all rows of a dataframe in a vector, specifying the column types ("integer" or "character"), see examples

Usage

```
datf_row_appendr2(inpt_datf, chs_type = "integer")
```

Arguments

`inpt_datf` is the inout dataframe

Examples

```
datf_teste <- data.frame("col1" = c(1:5), "col2" = c(5:1),
  "col3" = c("oui", "oui", "oui", "non", "non"))

print(datf_row_appendr2(inpt_datf = datf_teste, chs_type = "integer"))

NULL

print(datf_row_appendr2(inpt_datf = datf_teste, chs_type = "character"))

col1 col2 col3 col1 col2 col3 col1 col2 col3 col1 col2 col3 col1
"1" "5" "oui" "2" "4" "oui" "3" "3" "oui" "4" "2" "non" "5"
col2 col3
"1" "non"
```

dcr_untl	<i>dcr_untl</i>
----------	-----------------

Description

Allow to get the final value of a incremental or decremental loop.

Usage

```
dcr_untl(strt_val, cr_val, stop_val = 0)
```

Arguments

- strt_val is the start value
- cr_val is the incremental (or decremental value)
- stop_val is the value where the loop has to stop

Examples

```
print(dcr_untl(strt_val=50, cr_val=-5, stop_val=5))

#[1] 9

print(dcr_untl(strt_val=50, cr_val=5, stop_val=450))

#[1] 80
```

dcv_val	<i>dcv_val</i>
---------	----------------

Description

Allow to get the end value after an incremental (or decremental loop)

Usage

```
dcv_val(strt_val, cr_val, stop_val = 0)
```

Arguments

strt_val	is the start value
cr_val	is the incremental or decremental value
stop_val	is the value the loop has to stop

Examples

```
print(dcv_val(strt_val=50, cr_val=-5, stop_val=5))

#[1] 5

print(dcv_val(strt_val=47, cr_val=-5, stop_val=5))

#[1] 7

print(dcv_val(strt_val=50, cr_val=5, stop_val=450))

#[1] 450

print(dcv_val(strt_val=53, cr_val=5, stop_val=450))

#[1] 448
```

delta_normal	<i>delta_normal</i>
--------------	---------------------

Description

Returns the cumulative difference between a dataset of values and the normal distribution density formula, see examples

Usage

```
delta_normal(results_v = c(), mean_inpt, sd_inpt)
```

Arguments

`results_v` is the input vector
`mean_inpt` is the mea of the normal distribution
`sd_inpt` is the standard deviation of the normal distribution

Examples

```
x <- rnorm(n = 10000, mean = 15, sd = 1)
print(delta_normal(results_v = x,
                    mean_inpt = 15,
                    sd_inpt = 3))
```

```
[1] 15904.85
```

```
x <- rnorm(n = 10000, mean = 15, sd = 2)
print(delta_normal(results_v = x,
                    mean_inpt = 15,
                    sd_inpt = 3))
```

```
[1] 8050.662
```

```
x <- rnorm(n = 10000, mean = 15, sd = 5)
print(delta_normal(results_v = x,
                    mean_inpt = 15,
                    sd_inpt = 3))
```

```
[1] 16219.87
```

```
x <- rnorm(n = 10000, mean = 15, sd = 4)
print(delta_normal(results_v = x,
                    mean_inpt = 15,
                    sd_inpt = 3))
```

```
[1] 8081.28
```

```
x <- rnorm(n = 10000, mean = 15, sd = 3)
print(delta_normal(results_v = x,
                    mean_inpt = 15,
                    sd_inpt = 3))
```

```
[1] 474.8151
```

delta_unif

delta_unif

Description

Returns the cumulative difference between a known uniform distribution and the input vector that may be a uniform distribution of given min and max, see examples.

Usage

```
delta_unif(inpt_v, min_inpt, max_inpt)
```

Arguments

inpt_v is the input vector that may represent a uniform distribution
 min_inpt is the minimum of your uniform distribution
 max_inpt is the maximum of your uniform distribution

Examples

```
print(delta_unif(inpt_v = runif(n = 5000, min = 12, max = 17), min_inpt = 12, max_inpt =
[1] 170.5542

print(delta_unif(inpt_v = runif(n = 5000, min = 12, max = 17), min_inpt = 122, max_inpt =
[1] 675102.8
```

depth_pairs_findr *depth_pairs_findr*

Description

Takes the pair vector as an input and associate to each pair a level of depth, see examples

Usage

```
depth_pairs_findr(inpt)
```

Arguments

inpt is the pair vector

Examples

```
print(depth_pairs_findr(c(1, 1, 2, 3, 3, 4, 4, 2, 5, 6, 7, 7, 6, 5)))
[1] 1 1 1 2 2 2 2 1 1 2 3 3 2 1
```

diff_datf *diff_datf*

Description

Returns a vector with the coordinates of the cell that are not equal between 2 dataframes (row, column).

Usage

```
diff_datf(datf1, datf2)
```

Arguments

datf1 is an an input dataframe
 datf2 is an an input dataframe

Examples

```
datf1 <- data.frame(c(1:6), c("oui", "oui", "oui", "oui", "oui", "oui"), c(6:1))
datf2 <- data.frame(c(1:7), c("oui", "oui", "oui", "oui", "non", "oui", "zz"))
print(diff_datf(datf1=datf1, datf2=datf2))

#[1] 5 1 5 2
```

```
dynamic_idx_converttr
               dynamic_idx_converttr
```

Description

Allow to convert the indices of vector ('from_v_ids') which are related to the each characters of a vector (from_v_val), to fit the newly established characters of the vector from_v_val, see examples.

Usage

```
dynamic_idx_converttr(from_v_ids, from_v_val)
```

Arguments

from_v_ids is the input vector of indices
 from_v_val is the input vector of elements, or just the total number of characters of the elementsq in the vector

Examples

```
print(dynamic_idx_converttr(from_v_ids = c(1, 5), from_v_val = c("oui", "no", "ouI")))

[1] 1 2

print(dynamic_idx_converttr(from_v_ids = c(1, 6), from_v_val = c("oui", "no", "ouI")))

[1] 1 3
```

edml_normal_gen *edml_normal_gen*

Description

Reimplementation of `rnorm` function. The only difference is that outputed values are already sorted thanks to the algorithm used. You can also choose the most unlikely value to include in the outputed normal distribution. See examples. Warning, the lower `sd_inpt` is, the lower `cur_step` should be.

Usage

```
edml_normal_gen(
  mean_inpt,
  sd_inpt,
  n_inpt,
  offset_proba = 1e-05,
  cur_step = "auto",
  accuracy_factor = 10
)
```

Arguments

`mean_inpt` is the mean of the normal distribution
`sd_inpt` is the standard deviation of the normal distribution
`n_inpt` is the number of values you want to generate
`offset_proba` is the value with the least probability to be included in the normal distribution

Examples

```
x <- edml_normal_gen(mean_inpt = 100,
                      sd_inpt = 15,
                      n_inpt = 15000,
                      offset_proba = 0.00001,
                      cur_step = 0.3,
                      accuracy_factor = 10)

sd(x)

[1] 15.0456

summary(x)

   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
  43.13  89.93  100.43  100.30  110.33  159.53

x <- edml_normal_gen(mean_inpt = 100,
                      sd_inpt = 165,
                      n_inpt = 15000,
                      offset_proba = 0.00001,
                      cur_step = 0.3,
```

```

accuracy_factor = 10)

sd(x)

[1] 164.1441
summary(x)

      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
-444.55  -11.65   99.65   98.81  209.15  635.75

x <- edml_normal_gen(mean_inpt = 100,
                     sd_inpt = 0.45,
                     n_inpt = 15000,
                     offset_proba = 0.00001,
                     cur_step = 0.05,
                     accuracy_factor = 10)

sd(x)

0.4504586

summary(x)

      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
 98.25   99.70  100.00   99.99  100.30  101.55

```

edml_random_val *edml_random_val*

Description

Allow to generate a random number until a maximum length, see examples

Usage

```
edml_random_val(len_until = 5)
```

Arguments

`len_until` is the maximum length that the random number could have

Examples

```

print(edml_random_val(len_until = 5))

[1] 54656

print(edml_random_val(len_until = 8))

[1] 64021015

print(edml_random_val(len_until = 3))

```

```
[1] 45

print(edml_random_val(len_until = 4))

[1] 6146

print(edml_random_val(len_until = 1))

[1] 3
```

```
edml_random_val_spe
      edml_random_val_spe
```

Description

Allow to generate a random number of a pre determined length, see examples.

Usage

```
edml_random_val_spe(len_inpt = 5)
```

Arguments

`len_inpt` i the lenght of the random number that will be generated

Examples

```
print(edml_random_val_spe(len_inpt = 5))

[1] 55272

print(edml_random_val_spe(len_inpt = 8))

[1] 79930782

print(edml_random_val_spe(len_inpt = 3))

[1] 480

print(edml_random_val_spe(len_inpt = 4))

[1] 6865

print(edml_random_val_spe(len_inpt = 1))

[1] 2
```

```
edml_runif_deterministic
      edml_runif_deterministic
```

Description

Produces a deterministic uniform distribution, see examples

Usage

```
edml_runif_deterministic(n_inpt, min_inpt, max_inpt)
```

Arguments

`n_inpt` is the number of wanted values

Examples

```
x <- edml_runif_deterministic(n_inpt = 5000, min_inpt = 10, max_inpt = 15)

sd(x)

[1] 1.44352

sd(runif(n = 5000, min = 10, max = 15))

[1] 1.449532

x <- edml_runif_deterministic(n_inpt = 5000, min_inpt = 10, max_inpt = 115)

sd(x)

[1] 30.31392

sd(runif(n = 5000, min = 10, max = 115))

[1] 30.33717
```

```
edm_arrangr      edm_arranger
```

Description

Arranges data according to the values of a variable, see examples

Usage

```
edm_arrangr(inpt_datf, col_order, top_n = 10, decreasing = TRUE)
```

Arguments

<code>inpt_datf</code>	is the input dataframe
<code>col_order</code>	is the column names or the column number of the variable that will be used to arrange data
<code>top_n</code>	is the top values

Examples

```
print(edm_arrangr(inpt_datf = mtcars, col_order = "wt", top_n = 15, decreasing = FALSE))
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Lotus Europa	30.4	4	95.1	113	3.77	1.513	16.90	1	1	5	2
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Ferrari Dino	19.7	6	145.0	175	3.62	2.770	15.50	0	1	5	6
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Ford Pantera L	15.8	8	351.0	264	4.22	3.170	14.50	0	1	5	4
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2

```
print(edm_arrangr(inpt_datf = mtcars, col_order = "wt", top_n = 10, decreasing = TRUE))
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Lincoln Continental	10.4	8	460.0	215	3.00	5.424	17.82	0	0	3	4
Chrysler Imperial	14.7	8	440.0	230	3.23	5.345	17.42	0	0	3	4
Cadillac Fleetwood	10.4	8	472.0	205	2.93	5.250	17.98	0	0	3	4
Merc 450SE	16.4	8	275.8	180	3.07	4.070	17.40	0	0	3	3
Pontiac Firebird	19.2	8	400.0	175	3.08	3.845	17.05	0	0	3	2
Camaro Z28	13.3	8	350.0	245	3.73	3.840	15.41	0	0	3	4
Merc 450SLC	15.2	8	275.8	180	3.07	3.780	18.00	0	0	3	3
Merc 450SL	17.3	8	275.8	180	3.07	3.730	17.60	0	0	3	3
Duster 360	14.3	8	360.0	245	3.21	3.570	15.84	0	0	3	4
Maserati Bora	15.0	8	301.0	335	3.54	3.570	14.60	0	1	5	8
Dodge Challenger	15.5	8	318.0	150	2.76	3.520	16.87	0	0	3	2

`edm_arrangr2`
`edm_arranger2`

Description

Same as `edm_arrangr` but takes in count power like numbers for the values of the variable used to arrange the data.

Usage

```
edm_arranger2(inpt_datf, col_order, top_n = 10, decreasing = TRUE)
```

Arguments

`inpt_datf` is the input dataframe

`col_order` is the column names or the column number of the variable that will be used to arrange data

`top_n` is the top values

Examples

```
print(edm_arrangr2(inpt_datf = mtcars, col_order = "wt", top_n = 15, decreasing = FALSE))
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Lotus Europa	30.4	4	95.1	113	3.77	1.513	16.90	1	1	5	2
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Ferrari Dino	19.7	6	145.0	175	3.62	2.770	15.50	0	1	5	6
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Ford Pantera L	15.8	8	351.0	264	4.22	3.170	14.50	0	1	5	4
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2

```
print(edm_arrangr2(inpt_datf = mtcars, col_order = "wt", top_n = 10, decreasing = TRUE))
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Lincoln Continental	10.4	8	460.0	215	3.00	5.424	17.82	0	0	3	4
Chrysler Imperial	14.7	8	440.0	230	3.23	5.345	17.42	0	0	3	4
Cadillac Fleetwood	10.4	8	472.0	205	2.93	5.250	17.98	0	0	3	4
Merc 450SE	16.4	8	275.8	180	3.07	4.070	17.40	0	0	3	3
Pontiac Firebird	19.2	8	400.0	175	3.08	3.845	17.05	0	0	3	2
Camaro Z28	13.3	8	350.0	245	3.73	3.840	15.41	0	0	3	4
Merc 450SLC	15.2	8	275.8	180	3.07	3.780	18.00	0	0	3	3
Merc 450SL	17.3	8	275.8	180	3.07	3.730	17.60	0	0	3	3
Duster 360	14.3	8	360.0	245	3.21	3.570	15.84	0	0	3	4
Maserati Bora	15.0	8	301.0	335	3.54	3.570	14.60	0	1	5	8
Dodge Challenger	15.5	8	318.0	150	2.76	3.520	16.87	0	0	3	2

edm_group_by1

edm_group_by1

Description

Performs a group by (different algorithm than `edm_group_by2`), see examples

Usage

```
edm_group_by1(inpt_datf, grp_v = c())
```

Arguments

`inpt_datf` is the input dataframe

`grp_v` is the vector containiong the column names or the column numbers to perform the group by, see examples

Examples

```
datf <- data.frame("col1" = c("A", "B", "B", "A", "C", "B"),
                  "col2" = c("E", "R", "E", "E", "R", "R"),
                  "col3" = c("P", "P", "O", "O", "P", "O"))
```

```
print(datf)
```

	col1	col2	col3
1	A	E	P
2	B	R	P
3	B	E	O
4	A	E	O
5	C	R	P
6	B	R	O

```
print(edm_group_by1(inpt_datf = datf, grp_v = c("col1")))
```

	col1	col2	col3
1	A	E	P
4	A	E	O
2	B	R	P
3	B	E	O
6	B	R	O
5	C	R	P

```
print(edm_group_by1(inpt_datf = datf, grp_v = c("col1", "col2")))
```

	col1	col2	col3
1	A	E	P
4	A	E	O
2	B	R	P
6	B	R	O
3	B	E	O
5	C	R	P

```
print(edm_group_by1(inpt_datf = datf, grp_v = c("col2", "col1", "col3")))
```

	col2	col1	col3
1	E	A	P
4	E	A	O
3	E	B	O
2	R	B	P
6	R	B	O
5	R	C	P

```
print(edm_group_by1(inpt_datf = datf, grp_v = c("col2", "col1", "col3")))
```

	col2	col1	col3
1	E	A	P
4	E	A	O

3	E	B	O
2	R	B	P
6	R	B	O
5	R	C	P

edm_group_by2

*edm_group_by2***Description**

Performs a group by (different algorithm that edm_group_by1), see examples

Usage

```
edm_group_by2(inpt_datf, grp_v)
```

Arguments

`inpt_datf` is the input dataframe

`grp_v` is the vector containiong the column names or the column numbers to perform the group by, see examples

Examples

```
datf <- data.frame("col1" = c("A", "B", "B", "A", "C", "B"),
                  "col2" = c("E", "R", "E", "E", "R", "R"),
                  "col3" = c("P", "P", "O", "O", "P", "O"))
print(datf)

  col1 col2 col3
1    A    E    P
2    B    R    P
3    B    E    O
4    A    E    O
5    C    R    P
6    B    R    O

print(edm_group_by2(inpt_datf = datf, grp_v = c("col1")))

  col1 col2 col3
1    A    E    P
4    A    E    O
2    B    R    P
3    B    E    O
6    B    R    O
5    C    R    P

print(edm_group_by2(inpt_datf = datf, grp_v = c("col1", "col2")))

  col1 col2 col3
1    A    E    P
4    A    E    O
3    B    E    O
```

```

2      B      R      P
6      B      R      O
5      C      R      P

```

```
print(edm_group_by2(inpt_datf = datf, grp_v = c("col2", "col1")))
```

```

      col2 col1 col3
1      E      A      P
4      E      A      O
3      E      B      O
2      R      B      P
6      R      B      O
5      R      C      P

```

edm_pert

edm_pert

Description

Calculates margins and critical path of tasks based on PERT algorith. The first tasks must be at the top of the input dataframe, see examples.

Usage

```
edm_pert(inpt_datf)
```

Arguments

`inpt_datf` is the input dataframe which contains all the tasks, their duration, their finish date at the earliest/latest and their antecedent, so the `inpt_datf` must contain 5 columns see examples

Examples

```

datf <- data.frame("task" = toupper(letters[1:7]),
  "duration" = c(2, 8, 5, 2, 6, 5, 3),
  "antecedent" = c(NA, NA, "A", "B", "B", "E", "A,D"),
  "earliest" = c(2, 8, 19, 10, 14, 19, 19),
  "latest" = c(14, 8, 19, 16, 14, 19, 19))

```

```
print(datf)
```

```

      task duration antecedent earliest latest
1      A          2      <NA>         2     14
2      B          8      <NA>         8      8
3      C          5          A        19     19
4      D          2          B        10     16
5      E          6          B        14     14
6      F          5          E        19     19
7      G          3      A,D        19     19

```

```
print(edm_pert(inpt_datf = datf))
```

```
[[1]]
  rtn_datf free_margin tot_margin
1         A           0          12
2         B           0           0
3         C          12          12
4         D           0           6
5         E           0           0
6         F           0           0
7         G           6           6

[[2]]
[1] "B" "E" "F"
```

```
edm_pivot_longer1  edm_pivot_longer1
```

Description

Performs a pivot longer on dataframe, see examples. The synthax for variables must be value_id-modalitie_var1.modalitie_var2...

Usage

```
edm_pivot_longer1(
  inpt_datf,
  col_vars = c(),
  col_vars_to = c(),
  null_value = c(0),
  nvr_here = "?"
)
```

Arguments

`inpt_datf` is the input dataframe

`col_vars` is a vector containing the column names or column numbers of the variables

`col_vars_to` is a vector containing the varaiaables to which will be assign the modalities, see examples

`individual_col` is the column name or the column number of the individuals

Examples

```
datf <- data.frame("individuals" = c(1, 2, 3),
                   c(1, 2, 3),
                   c(6, 0, 2),
                   c(7, 0, 0),
                   c(0, 0, 0),
                   c(1, 0, 4),
                   c(3, 0, 8),
                   c(9, 0, 0),
```

```

      c(11, 0, 5))

colnames(datf)[2:ncol(datf)] <- c("val1-A.R",
                                "val1-A.T",
                                "val1-B.R",
                                "val1-B.T",
                                "val2-A.R",
                                "val2-A.T",
                                "val2-B.R",
                                "val2-B.T")

datf2 <- data.frame("individuals" = c(1, 2, 3),
                   c(7, 0, 2),
                   c(1, 0, 4),
                   c(9, 0, 8),
                   c(11, 22, 5))
colnames(datf2)[2:ncol(datf2)] <- c(
                                "val1-A",
                                "val1-B",
                                "val2-A",
                                "val2-B"
                                )

print(datf)

  individuals val1-A.R val1-A.T val1-B.R val1-B.T val2-A.R val2-A.T val2-B.R
1           1         1         6         7         0         1         3         9
2           2         2         0         0         0         0         0         0
3           3         3         2         0         0         4         8         0
  val2-B.T
1         11
2          0
3          5

print(edm_pivot_longer1(inpt_datf = datf,
                        col_vars = c(2:9),
                        individual_col = 1,
                        col_vars_to = c("Shape", "Way"),
                        null_value = c(0)))

  individuals Shape Way val1 val2
1           1     A   R     1     1
2           1     A   T     6     3
3           1     B   R     7     9
4           1     B   T     0    11
5           2     A   R     2     0
6           3     A   R     3     4
7           3     A   T     2     8
8           3     B   T     0     5

print(datf2)

  individuals val1-A val1-B val2-A val2-B
1           1         7         1         9        11
2           2         0         0         0        22
3           3         2         4         8         5

```


	individuals	Shape	val1	val2
1	1	A	7	9
2	1	B	1	11
3	2	B	0	22
4	3	A	2	8
5	3	B	4	5

	individual	country	year	twh_cons-biofuel_electricity	
7475	France_1995	France	1995	1.82	
7503	France_2023	France	2023	9.50	
				twh_cons-coal_electricity	twh_cons-gas_electricity
7475				24.18	3.84
7503				2.16	31.43
				twh_cons-hydro_electricity	twh_cons-nuclear_electricity
7475				71.33	377.23
7503				53.19	335.65
				twh_cons-oil_electricity	twh_cons-other_renewable_exc_biofuel_electricity
7475				10.50	0.51
7503				9.71	0.60
				twh_cons-solar_electricity	twh_cons-wind_electricity
7475				0.00	0.00
7503				23.26	48.61

	individual	country	year	type_energie	twh_cons
1	France_1995	France	1995	biofuel_electricity	1.82
2	France_1995	France	1995	coal_electricity	24.18
3	France_1995	France	1995	gas_electricity	3.84
4	France_1995	France	1995	hydro_electricity	71.33
5	France_1995	France	1995	nuclear_electricity	377.23
6	France_1995	France	1995	oil_electricity	10.5
7	France_1995	France	1995	other_renewable_exc_biofuel_electricity	0.51
8	France_2023	France	2023	biofuel_electricity	9.5
9	France_2023	France	2023	coal_electricity	2.16
10	France_2023	France	2023	gas_electricity	31.43
11	France_2023	France	2023	hydro_electricity	53.19
12	France_2023	France	2023	nuclear_electricity	335.65
13	France_2023	France	2023	oil_electricity	9.71
14	France_2023	France	2023	other_renewable_exc_biofuel_electricity	0.6
15	France_2023	France	2023	solar_electricity	23.26
16	France_2023	France	2023	wind_electricity	48.61

edm_pivot_longer2 *edm_pivot_longer2*

Description

Performs a pivot longer on dataframe keeping the null values, see examples. The synthax for variables must be value_id-modalitie_var1.modalitie_var2...

Usage

```
edm_pivot_longer2(inpt_datf, col_vars = c(), col_vars_to = c())
```

Arguments

`inpt_datf` is the input dataframe
`col_vars` is a vector containing the column names or column numbers of the variables
`col_vars_to` is a vector containing the varaibles to which will be assign the modalities, see examples
`individual_col` is the column name or the column number of the individuals

Examples

```
datf <- data.frame("individuals" = c(1, 2, 3),
                  c(1, 2, 3),
                  c(6, 0, 2),
                  c(7, 0, 0),
                  c(0, 0, 0),
                  c(1, 0, 4),
                  c(3, 0, 8),
                  c(9, 0, 0),
                  c(11, 0, 5))

colnames(datf)[2:ncol(datf)] <- c("val1-A.R",
                                "val1-A.T",
                                "val1-B.R",
                                "val1-B.T",
                                "val2-A.R",
                                "val2-A.T",
                                "val2-B.R",
                                "val2-B.T")

datf2 <- data.frame("individuals" = c(1, 2, 3),
                  c(7, 0, 2),
                  c(1, 0, 4),
                  c(9, 0, 8),
                  c(11, 22, 5))
colnames(datf2)[2:ncol(datf2)] <- c(
                                "val1-A",
                                "val1-B",
                                "val2-A",
                                "val2-B")
```

```

    )

print(datf)

  individuals vall-A.R vall-A.T vall-B.R vall-B.T val2-A.R val2-A.T val2-B.R
1             1         1         6         7         0         1         3         9
2             2         2         0         0         0         0         0         0
3             3         3         2         0         0         4         8         0
  val2-B.T
1          11
2           0
3           5

print(edm_pivot_longer2(inpt_datf = datf,
                        col_vars = c(2:9),
                        individual_col = 1,
                        col_vars_to = c("Shape", "Way")))

  individuals Shape Way vall val2
1             1     A   R     1     1
2             1     A   T     6     3
3             1     B   R     7     9
4             1     B   T     0    11
5             2     A   R     2     0
6             2     A   T     0     0
7             2     B   R     0     0
8             2     B   T     0     0
9             3     A   R     3     4
10            3     A   T     2     8
11            3     B   R     0     0
12            3     B   T     0     5

print(datf2)

  individuals vall-A vall-B val2-A val2-B
1             1         7         1         9         11
2             2         0         0         0         22
3             3         2         4         8         5

print(edm_pivot_longer2(inpt_datf = datf2,
                        col_vars = c(2:5),
                        individual_col = 1,
                        col_vars_to = c("Shape")))

  individuals Shape vall val2
1             1     A     7     9
2             1     B     1    11
3             2     A     0     0
4             2     B     0    22
5             3     A     2     8
6             3     B     4     5

print(cur_data)

  individual country year twh_cons-biofuel_electricity

```

```

7475 France_1995 France 1995 1.82
7503 France_2023 France 2023 9.50
      twh_cons-coal_electricity twh_cons-gas_electricity
7475 24.18 3.84
7503 2.16 31.43
      twh_cons-hydro_electricity twh_cons-nuclear_electricity
7475 71.33 377.23
7503 53.19 335.65
      twh_cons-oil_electricity twh_cons-other_renewable_exc_biofuel_electricity
7475 10.50 0.51
7503 9.71 0.60
      twh_cons-solar_electricity twh_cons-wind_electricity
7475 0.00 0.00
7503 23.26 48.61

```

```

print(edm_pivot_longer2(inpt_datf = cur_data,
                        col_vars = c(4:ncol(cur_data)),
                        col_vars_to = "type_energie"))

```

```

      individual country year
1 France_1995 France 1995
2 France_1995 France 1995
3 France_1995 France 1995
4 France_1995 France 1995
5 France_1995 France 1995
6 France_1995 France 1995
7 France_1995 France 1995
8 France_1995 France 1995
9 France_1995 France 1995
10 France_2023 France 2023
11 France_2023 France 2023
12 France_2023 France 2023
13 France_2023 France 2023
14 France_2023 France 2023
15 France_2023 France 2023
16 France_2023 France 2023
17 France_2023 France 2023
18 France_2023 France 2023
      type_energie twh_cons
1 biofuel_electricity 1.82
2 coal_electricity 24.18
3 gas_electricity 3.84
4 hydro_electricity 71.33
5 nuclear_electricity 377.23
6 oil_electricity 10.5
7 other_renewable_exc_biofuel_electricity 0.51
8 solar_electricity 0
9 wind_electricity 0
10 biofuel_electricity 9.5
11 coal_electricity 2.16
12 gas_electricity 31.43
13 hydro_electricity 53.19
14 nuclear_electricity 335.65
15 oil_electricity 9.71
16 other_renewable_exc_biofuel_electricity 0.6
17 solar_electricity 23.26
18 wind_electricity 48.61

```

edm_pivot_series *edm_pivot_series*

Description

Allow to create a new column for the value of the chosen columns at each new value of the column that represents the time. The occurrence of each time stamp has to be equal, see examples (if not consider performing the `time_serie_equalizer` function from the same package)

Usage

```
edm_pivot_series(inpt_datf, time_col, col_v = NULL)
```

Arguments

`inpt_datf` is the input dataframe
`time_col` is the column name or number of the dataframe
`col_v` is a vector containing all the column numbers or names of the variables, if null all the column will be considered as variables apart from the column designated in `time_col`

Examples

```
print(cur_datf)
```

	year	energy_source	twh_cons
1	1995	biofuel_electricity	1.82
2	1995	coal_electricity	24.18
3	1995	gas_electricity	3.84
4	1995	hydro_electricity	71.33
5	1995	nuclear_electricity	377.23
6	1995	oil_electricity	10.50
7	1995	other_renewable_exc_biofuel_electricity	0.51
8	1995	solar_electricity	0.00
9	1995	wind_electricity	0.00
10	2023	biofuel_electricity	9.50
11	2023	coal_electricity	2.16
12	2023	gas_electricity	31.43
13	2023	hydro_electricity	53.19
14	2023	nuclear_electricity	335.65
15	2023	oil_electricity	9.71
16	2023	other_renewable_exc_biofuel_electricity	0.60
17	2023	solar_electricity	23.26
18	2023	wind_electricity	48.61

```
print(edm_pivot_series(inpt_datf = cur_datf, time_col = 1, col_v = c(3)))
```

	energy_source	twh_cons_1995	twh_cons_2023
1	biofuel_electricity	1.82	9.50
2	coal_electricity	24.18	2.16
3	gas_electricity	3.84	31.43

4	hydro_electricity	71.33	53.19
5	nuclear_electricity	377.23	335.65
6	oil_electricity	10.50	9.71
7	other_renewable_exc_biofuel_electricity	0.51	0.60
8	solar_electricity	0.00	23.26
9	wind_electricity	0.00	48.61

```
print(datf)
```

	individual	year	energy_source	tw_h_cons
1	France_1995	1995	biofuel_electricity	1.82
2	France_1995	1995	coal_electricity	24.18
3	France_1995	1995	gas_electricity	3.84
4	France_1995	1995	hydro_electricity	71.33
5	France_1995	1995	nuclear_electricity	377.23
6	France_1995	1995	oil_electricity	10.50
7	France_1995	1995	other_renewable_exc_biofuel_electricity	0.51
8	France_1995	1995	solar_electricity	0.00
9	France_1995	1995	wind_electricity	0.00
10	France_2023	2023	biofuel_electricity	9.50
11	France_2023	2023	coal_electricity	2.16
12	France_2023	2023	gas_electricity	31.43
13	France_2023	2023	hydro_electricity	53.19
14	France_2023	2023	nuclear_electricity	335.65
15	France_2023	2023	oil_electricity	9.71
16	France_2023	2023	other_renewable_exc_biofuel_electricity	0.60
17	France_2023	2023	solar_electricity	23.26
18	France_2023	2023	wind_electricity	48.61

```
print(edm_pivot_series(inpt_datf = cur_datf, time_col = 2, col_v = c(1, 4)))
```

	individual_1995	energy_source	tw_h_cons_1995
1	France_1995	biofuel_electricity	1.82
2	France_1995	coal_electricity	24.18
3	France_1995	gas_electricity	3.84
4	France_1995	hydro_electricity	71.33
5	France_1995	nuclear_electricity	377.23
6	France_1995	oil_electricity	10.50
7	France_1995	other_renewable_exc_biofuel_electricity	0.51
8	France_1995	solar_electricity	0.00
9	France_1995	wind_electricity	0.00

	individual_2023	tw_h_cons_2023
1	France_2023	9.50
2	France_2023	2.16
3	France_2023	31.43
4	France_2023	53.19
5	France_2023	335.65
6	France_2023	9.71
7	France_2023	0.60
8	France_2023	23.26
9	France_2023	48.61

Description

Performs a pivot wider to a dataframe, see examples.

Usage

```
edm_pivot_wider1(inpt_datf, col_vars = c(), col_vals = c(), individual_col)
```

Arguments

`inpt_datf` is the input dataframe

`col_vars` is a vector containig the column names or column numbers of the variables to pivot

`col_vals` is a vector containing the column numbers or column names of the values to pivot

`individual_col` is the column name or column number of the individuals

Examples

```
datf2 <- data.frame("individual" = c(1, 1, 1, 2, 3, 3),
                    "var1" = c("A", "A", "B", "B", "B", "A"),
                    "val1" = c(6, 7, 1, 0, 4, 2),
                    "val2" = c(3, 9, 11, 22, 5, 8))
datf <- data.frame("individual" = c(1, 1, 1, 2, 3, 3),
                   "var1" = c("A", "A", "B", "B", "B", "A"),
                   "var2" = c("R", "T", "T", "R", "T", "R"),
                   "val1" = c(6, 7, 1, 0, 4, 2),
                   "val2" = c(3, 9, 11, 22, 5, 8))
```

```
print(datf)
```

	individual	var1	var2	val1	val2
1	1	A	R	6	3
2	1	A	T	7	9
3	1	B	T	1	11
4	2	B	R	0	22
5	3	B	T	4	5
6	3	A	R	2	8

```
print(datf2)
```

	individual	var1	val1	val2
1	1	A	6	3
2	1	A	7	9
3	1	B	1	11
4	2	B	0	22
5	3	B	4	5
6	3	A	2	8

```
print(edm_pivot_wider1(
  inpt_datf = datf,
  col_vars = c(2, 3),
  col_vals = c(4, 5),
  individual_col = 1)
)
```

```

  individuals vall-A.R vall-A.T vall-B.R vall-B.T val2-A.R val2-A.T val2-B.R
1           1         6         7         0         1         3         9         0
2           2         0         0         0         0         0        22
3           3         2         0         0         4         8         0         0
  val2-B.T
1         11
2          0
3          5

print(edm_pivot_wider1(
  inpt_datf = datf2,
  col_vars = c(2),
  col_vals = c(3, 4),
  individual_col = 1)
)

  individuals vall-A vall-B val2-A val2-B
1           1         7         1         9        11
2           2         0         0         0        22
3           3         2         4         8         5
```

edm_pivot_wider2	<i>edm_pivot_wider2</i>
------------------	-------------------------

Description

Performs a pivot wider to a dataframe with a different alorythm than edm_pivot_wider, see exam-
ples.

Usage

```
edm_pivot_wider2(inpt_datf, col_vars = c(), col_vals = c(), individual_col)
```

Arguments

- inpt_datf is the input dataframe
- col_vars is a vector containig the column names or column numbers of the variables to pivot
- col_vals is a vector containing the column numbers or column names of the values to pivot
- individual_col is the column name or column number of the individuals

Examples

```
datf2 <- data.frame("individual" = c(1, 1, 1, 2, 3, 3),
  "var1" = c("A", "A", "B", "B", "B", "A"),
  "vall" = c(6, 7, 1, 0, 4, 2),
  "val2" = c(3, 9, 11, 22, 5, 8))
datf <- data.frame("individual" = c(1, 1, 1, 2, 3, 3),
  "var1" = c("A", "A", "B", "B", "B", "A"),
  "var2" = c("R", "T", "T", "R", "T", "R"),
```



```

"val1" = c(6, 7, 1, 0, 4, 2),
"val2" = c(3, 9, 11, 22, 5, 8))

print(datf)

  individual var1 var2 val1 val2
1           1   A   R    6    3
2           1   A   T    7    9
3           1   B   T    1   11
4           2   B   R    0   22
5           3   B   T    4    5
6           3   A   R    2    8

print(datf2)

  individual var1 val1 val2
1           1   A    6    3
2           1   A    7    9
3           1   B    1   11
4           2   B    0   22
5           3   B    4    5
6           3   A    2    8

print(edm_pivot_wider2(
  inpt_datf = datf,
  col_vars = c(2, 3),
  col_vals = c(4, 5),
  individual_col = 1)
)

  individuals val1-A.R val1-A.T val1-B.R val1-B.T val2-A.R val2-A.T val2-B.R
1           1         6         7         0         1         3         9         0
2           2         0         0         0         0         0         0        22
3           3         2         0         0         4         8         0         0
  val2-B.T
1          11
2           0
3           5

print(edm_pivot_wider2(
  inpt_datf = datf2,
  col_vars = c(2),
  col_vals = c(3, 4),
  individual_col = 1)
)

  individuals val1-A val1-B val2-A val2-B
1           1         7         1         9        11
2           2         0         0         0        22
3           3         2         4         8         5

```

Description

Takes an input vector with elements that have different occurrence, and output a vector with all these elements with the same number of occurrence, see examples

Usage

```
elements_equalifier(inpt_v, until = 3)
```

Arguments

inpt_v	is the input vector
until	is how many times each elements will be in the output vector

Examples

```
print(elements_equalifier(letters, until = 2))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s"
[20] "t" "u" "v" "w" "x" "y" "z" "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l"
[39] "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z"

print(elements_equalifier(c(letters, letters[-1]), until = 2))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s"
[20] "t" "u" "v" "w" "x" "y" "z" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m"
[39] "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z" "a"
```

equalizer_v

equalizer_v

Description

Takes a vector of character as an input and returns a vector with the elements at the same size. The size can be chosen via depth parameter.

Usage

```
equalizer_v(inpt_v, depth = "max", default_val = "?")
```

Arguments

inpt_v	is the input vector containing all the characters
depth	is the depth parameter, defaults to "max" which means that it is equal to the character number of the element(s) in inpt_v that has the most
default_val	is the default value that will be added to the output characters if those has an inferior length (characters) than the value of depth

Examples

```
print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=2))

#[1] "aa" "zz" "q?"

print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=12))

#[1] "aa?????????" "zzz?????????" "q?????????"
```

extract_normal	<i>extract_normal</i>
----------------	-----------------------

Description

Allow to extract values that fits a normal distribution from any kind of dataset, see examples and parameters

Usage

```
extract_normal(
  inpt_datf,
  mean,
  sd,
  accuracy,
  round_value = 1,
  normalised = FALSE,
  n = NA,
  tries = 3
)
```

Arguments

inpt_datf	is the input dataset as a dataframe, values/modalities are in the first column and frequency (not normalised) is in the second column
mean	is the mean of the target normal distribution
sd	is the standard deviation of the target normal distribution
accuracy	is how much of a difference between the points of the targeted normal distribution and the actual points is tolerated
round_value	is the round value for the normal distribution used under the hood to compare the dataset and extract the best points, defaults to 1
normalised	is if the input frequency is divided by n, if TRUE the parameter n must be filled
n	is the number of points
tries	is how many normal distributions are used under the hood to compare their points to the those in the input dataset, defaults to 3. The higher it is, the higher the number of different points from the input dataset will be in accordance for the normal distribution the function tries to build from the dataset. It does not increase by a lot but can be non-negligible and note that the higher the number of tries is, the higher the execution time of the function will be.

Examples

```

sample_val <- round(rnorm(n = 72000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)
sample_qual <- infinite_char_seq(n = length(sample_freq))
datf_test <- data.frame(sample_qual, sample_freq)
n <- nrow(datf_test)
print(datf_test)

```

	sample_qual	sample_freq
1	a	72
2	b	1155
3	c	1255
4	d	743
5	e	696
6	f	1028
7	g	1160
8	h	1219
9	i	1353
10	j	1336
11	k	1308
12	l	485
13	m	1306
14	n	1429
15	o	623
16	p	1172
17	q	1054
18	r	999
19	s	125
20	t	1461
21	u	1430
22	v	341
23	w	1453
24	x	427
25	y	869
26	z	1395
27	aa	841
28	ab	952
29	ac	246
30	ad	468
31	ae	237
32	af	555
33	ag	1297
34	ah	571
35	ai	349
36	aj	773
37	ak	1086
38	al	1281
39	am	1471
40	an	1236
41	ao	394
42	ap	1433
43	aq	1328
44	ar	976
45	as	640
46	at	308
47	au	698

48	av	864
49	aw	1346
50	ax	1349
51	ay	6
52	az	1071
53	ba	248
54	bb	929
55	bc	925
56	bd	452
57	be	207
58	bf	546
59	bg	62
60	bh	107
61	bi	1184
62	bj	739
63	bk	624
64	bl	850
65	bm	1408
66	bn	620
67	bo	202
68	bp	10
69	bq	700
70	br	397
71	bs	1291
72	bt	178
73	bu	397
74	bv	1089
75	bw	1301
76	bx	328
77	by	1348
78	bz	97
79	ca	1452
80	cb	4
81	cc	100
82	cd	593
83	ce	503
84	cf	164
85	cg	32
86	ch	259
87	ci	1089
88	cj	249
89	ck	165
90	cl	42
91	cm	143
92	cn	467
93	co	347
94	cp	143
95	cq	69
96	cr	18
97	cs	290
98	ct	55
99	cu	141
100	cv	86
101	cw	303
102	cx	88
103	cy	16
104	cz	213

105	da	3
106	db	75
107	dc	32
108	dd	66
109	de	105
110	df	34
111	dg	56
112	dh	17
113	di	22
114	dj	120
115	dk	54
116	dl	9
117	dm	8
118	dn	36
119	do	20
120	dp	26
121	dq	54
122	dr	8
123	ds	10
124	dt	4
125	du	53
126	dv	29
127	dw	1
128	dx	8
129	dy	10
130	dz	4
131	ea	22
132	eb	9
133	ec	17
134	ed	55
135	ee	21
136	ef	6
137	eg	4
138	eh	3
139	ei	7
140	ej	1
141	ek	4
142	el	2
143	em	5
144	en	4
145	eo	1
146	ep	2
147	eq	3
148	er	8
149	es	4
150	et	3
151	eu	3
152	ev	2
153	ew	2
154	ex	2
155	ey	1
156	ez	2
157	fa	2
158	fb	1

```
teste <- extract_normal(inpt_datf = datf_test,
                        mean = 10,
```

```

        sd = 2,
        accuracy = .1,
        round_value = 1,
        normalised = FALSE,
        tries = 5)

print(length(unique(teste[, 1])) / n)

[1] 0.2848101 # so nearly 28.5 % of the different points were in
#accordance with the construction of the target normal distribution

print(teste)

  values      frequency
1      dw 0.0001406866
2      dw 0.0001406866
3      dw 0.0001406866
4      el 0.0002813731
5      el 0.0002813731
6      el 0.0002813731
7      el 0.0002813731
8      da 0.0004220597
9      da 0.0004220597
10     cb 0.0005627462
11     cb 0.0005627462
12     em 0.0007034328
13     ay 0.0008441193
14     ay 0.0008441193
15     ei 0.0009848059
16     ei 0.0009848059
17     ei 0.0009848059
18     dm 0.0011254924
19     bp 0.0014068655
20     cy 0.0022509848
21     cy 0.0022509848
22     cy 0.0022509848
23     dh 0.0023916714
24     dh 0.0023916714
25     cr 0.0025323579
26     ee 0.0029544176
27     di 0.0030951041
28     dp 0.0036578503
29     dp 0.0036578503
30     cg 0.0045019696
31     cg 0.0045019696
32     df 0.0047833427
33     dn 0.0050647158
34     cl 0.0059088351
35     cl 0.0059088351
36     du 0.0074563872
37     du 0.0074563872
38     dg 0.0078784468
39     dg 0.0078784468
40     bg 0.0087225661
41     bg 0.0087225661
42     dd 0.0092853123
43     cq 0.0097073720

```

44	cq	0.0097073720
45	a	0.0101294316
46	cv	0.0120990433
47	cx	0.0123804164
48	cx	0.0123804164
49	bz	0.0136465954
50	cc	0.0140686550
51	bh	0.0150534609
52	bh	0.0150534609
53	dj	0.0168823860
54	s	0.0175858188
55	s	0.0175858188
56	cm	0.0201181767
57	cf	0.0230725943
58	ck	0.0232132808
59	bt	0.0250422060
60	bt	0.0250422060
61	be	0.0291221159
62	be	0.0291221159
63	cz	0.0299662352
64	cz	0.0299662352
65	be	0.0291221159
66	bo	0.0284186832
67	bt	0.0250422060
68	ck	0.0232132808
69	ck	0.0232132808
70	cm	0.0201181767
71	cu	0.0198368036
72	s	0.0175858188
73	dj	0.0168823860
74	bh	0.0150534609
75	bh	0.0150534609
76	de	0.0147720878
77	bz	0.0136465954
78	bz	0.0136465954
79	cx	0.0123804164
80	cv	0.0120990433
81	db	0.0105514913
82	a	0.0101294316
83	cq	0.0097073720
84	dd	0.0092853123
85	dd	0.0092853123
86	bg	0.0087225661
87	bg	0.0087225661
88	dg	0.0078784468
89	dk	0.0075970737
90	du	0.0074563872
91	cl	0.0059088351
92	cl	0.0059088351
93	dn	0.0050647158
94	df	0.0047833427
95	df	0.0047833427
96	cg	0.0045019696
97	dv	0.0040799100
98	dp	0.0036578503
99	di	0.0030951041
100	di	0.0030951041


```

101      ee 0.0029544176
102      cr 0.0025323579
103      dh 0.0023916714
104      cy 0.0022509848
105      cy 0.0022509848
106      cy 0.0022509848
107      cy 0.0022509848
108      dl 0.0012661790
109      dm 0.0011254924
110      ei 0.0009848059
111      ei 0.0009848059
112      ay 0.0008441193
113      ay 0.0008441193
114      em 0.0007034328
115      em 0.0007034328
116      cb 0.0005627462
117      cb 0.0005627462
118      da 0.0004220597
119      da 0.0004220597
120      el 0.0002813731
121      el 0.0002813731
122      el 0.0002813731
123      el 0.0002813731
124      dw 0.0001406866
125      dw 0.0001406866
126      dw 0.0001406866

```

extrt_only_v	<i>extrt_only_v</i>
--------------	---------------------

Description

Returns the elements from a vector "inpt_v" that are in another vector "pttrn_v"

Usage

```
extrt_only_v(inpt_v, pttrn_v)
```

Arguments

inpt_v	is the input vector
pttrn_v	is the vector contining all the elements that can be in inpt_v

Examples

```

print(extrt_only_v(inpt_v=c("oui", "non", "peut", "oo", "ll", "oui", "non", "oui", "oui")
  pttrn_v=c("oui")))

#[1] "oui" "oui" "oui" "oui"

```

fillr

fillr

Description

Allow to fill a vector by the last element n times

Usage

```
fillr(inpt_v, ptrn_fill = "\\\\.\\.\\.\\.\\.\\d")
```

Arguments

inpt_v	is the input vector
ptrn_fill	is the pattern used to detect where the function has to fill the vector by the last element n times. It defaults to "...\\d" where "\\d" is the regex for an int value. So this paramater has to have "\\d" which designates n.

Examples

```
print(fillr(c("a", "b", "...3", "c")))
#[1] "a" "b" "b" "b" "b" "c"
```

fixer_nest_v

fixer_nest_v

Description

Retur the elements of a vector "wrk_v" (1) that corresponds to the pattern of elements in another vector "cur_v" (2) according to another vector "pttrn_v" (3) that contains the patterof elements.

Usage

```
fixer_nest_v(cur_v, pttrn_v, wrk_v)
```

Arguments

cur_v	is the input vector
pttrn_v	is the vector containing all the patterns that may be contained in cur_v
wrk_v	is a vector containing all the indexes of cur_v taken in count in the function

Examples

```
print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"),
  pttrn_v=c("oui", "non", "peut-etre"),
  wrk_v=c(1, 2, 3, 4, 5, 6)))

#[1] 1 2 3 4 5 6

print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"),
  pttrn_v=c("oui", "non"),
  wrk_v=c(1, 2, 3, 4, 5, 6)))

#[1] 1 2 NA 4 5 NA
```

fold_rec

*fold_rec***Description**

Allow to get all the files recursively from a path according to an end and start depth value. If you want to have an other version of this function that uses a more sophisticated algorithm (which can be faster), check file_rec2. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

Usage

```
fold_rec(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax	is the end depth value
xmin	is the start depth value
pathc	is the reference path

fold_rec2

*fold_rec2***Description**

Allow to find the directories and the subdirectories with a specified end and start depth value from a path. This function might be more powerfull than file_rec because it uses a custom algorithm that does not nee to perform a full recursive search before tuning it to only find the directories with a good value of depth. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

Usage

```
fold_rec2(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax	is the depth value
xmin	is the minimum value of depth
pathc	is the reference path, from which depth value is equal to 1

format_date	<i>format_date</i>
-------------	--------------------

Description

Allow to convert xx-month-xxxx date type to xx-xx-xxxx

Usage

```
format_date(f_dialect, sentc, sep_in = "-", sep_out = "-")
```

Arguments

f_dialect	are the months from the language of which the month come
sentc	is the date to convert
sep_in	is the separator of the dat input (default is "-")
sep_out	is the separator of the converted date (default is "-")

Examples

```
print(format_date(f_dialect=c("janvier", "février", "mars", "avril", "mai", "juin",
"juillet", "aout", "septembre", "octobre", "novembre", "décembre"), sentc="11-septembre-2
#[1] "11-09-2023"
```

geo_min	<i>geo_min</i>
---------	----------------

Description

Return a dataframe containing the nearest geographical points (row) according to established geographical points (column).

Usage

```
geo_min(inpt_datf, established_datf)
```

Arguments

inpt_datf	is the input dataframe of the set of geographical points to be classified, its first column is for latitude, the second for the longitude and the third, if exists, is for the altitude. Each point is one row.
established_datf	is the dataframe containing the coordinates of the established geographical points

Examples

```

in_ <- data.frame(c(11, 33, 55), c(113, -143, 167))

in2_ <- data.frame(c(12, 55), c(115, 165))

print(geo_min(inpt_datf=in_, established_datf=in2_))

#           X1           X2
#1    245.266         NA
#2 24200.143         NA
#3           NA 127.7004

in_ <- data.frame(c(51, 23, 55), c(113, -143, 167), c(6, 5, 1))

in2_ <- data.frame(c(12, 55), c(115, 165), c(2, 5))

print(geo_min(inpt_datf=in_, established_datf=in2_))

#           X1           X2
#1           NA 4343.720
#2 26465.63         NA
#3           NA 5825.517

```

get_rec

*get_rec***Description**

Allow to get the value of directorie depth from a path.

Usage

```
get_rec(pathc = ".")
```

Arguments

pathc is the reference path example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

globe

*globe***Description**

Allow to calculate the distances between a set of geographical points and another established geographical point. If the altitude is not filled, so the result returned won't take in count the altitude.

Usage

```
globe(lat_f, long_f, alt_f = NA, lat_n, long_n, alt_n = NA)
```

Arguments

lat_f	is the latitude of the established geographical point
long_f	is the longitude of the established geographical point
alt_f	is the altitude of the established geographical point, defaults to NA
lat_n	is a vector containing the latitude of the set of points
long_n	is a vector containing the longitude of the set of points
alt_n	is a vector containing the altitude of the set of points, defaults to NA

Examples

```
print(globe(lat_f=23, long_f=112, alt_f=NA, lat_n=c(2, 82), long_n=c(165, -55), alt_n=NA))

#[1] 6342.844 7059.080

print(globe(lat_f=23, long_f=112, alt_f=8, lat_n=c(2, 82), long_n=c(165, -55), alt_n=c(8, 10)))

#[1] 6342.844 7059.087
```

glue_grouppr_v	<i>glue_grouppr_v</i>
----------------	-----------------------

Description

Takes an input vector and returns the same vector unlike that certain elements will be glued as an unique element according to those designated in a special vector, see examples.

Usage

```
glue_grouppr_v(inpt_v, group_v = c(), until)
```

Arguments

inpt_v	is the input vector
is	a vector containing all the elements that will be glued in the output vector

Examples

```
print(glue_grouppr_v(inpt_v = c("o", "-", "-", "u", "i", "-", "n",
  "o", "-", "-", "-", "zz", "/", "/"), group_v = c("-", "/")))

[1] "o"  "--" "u"  "i"  "-"  "n"  "o"  "---" "zz" "/"

print(glue_grouppr_v(inpt_v = c("o", "-", "-", "u", "i", "-", "n",
  "o", "-", "-", "-", "-", "zz", "/", "/"), group_v = c("-", "/"), until = 3))

[1] "o"  "--" "u"  "i"  "-"  "n"  "o"  ---  "-"  "zz"  "/"

print(glue_grouppr_v(inpt_v = c("o", "-", "-", "u", "i", "-", "n",
  "o", "-", "-", "-", "-", "zz", "/", "/"), group_v = c("-", "/"), until = 2))

[1] "o"  "--" "u"  "i"  "-"  "n"  "o"  --  --  "zz"  "/"
```

```
grep_all
```

```
grep_all
```

Description

Allow to perform a grep function on multiple input elements

Usage

```
grep_all(inpt_v, pattern_v)
```

Arguments

`inpt_v` is the input vectors to grep elements from
`pattern_v` is a vector containing the patterns to grep

Examples

```
print(grep_all(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "4")))

[1] 15 23 25 4 14 19

print(grep_all(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "^4$")))

[1] 15 23 25 4 19

print(grep_all(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z")))

[1] 15 23 25
```

```
grep_all2
```

```
grep_all2
```

Description

Performs the grep_all function with another algorithm, potentially faster

Usage

```
grep_all2(inpt_v, pattern_v)
```

Arguments

`inpt_v` is the input vectors to grep elements from
`pattern_v` is a vector containing the patterns to grep

Examples

```
print(grep_all2(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "4")))

[1] 15 23 25  4 14 19

print(grep_all2(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "^4$")))

[1] 15 23 25  4 19

print(grep_all2(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z")))

[1] 15 23 25
```

groupr_datf

groupr_datf

Description

Allow to create groups from a dataframe. Indeed, you can create conditions that lead to a flag value for each cell of the input dataframe according to the cell value. This function is based on `see_datf` and `nestr_datf2` functions.

Usage

```
groupr_datf(
  inpt_datf,
  condition_lst,
  val_lst,
  conjunction_lst,
  rtn_val_pos = c()
)
```

Arguments

<code>inpt_datf</code>	is the input dataframe
<code>condition_lst</code>	is a list containing all the condition as a vector for each group
<code>val_lst</code>	is a list containing all the values associated with <code>condition_lst</code> as a vector for each group
<code>conjunction_lst</code>	is a list containing all the conjunctions associated with <code>condition_lst</code> and <code>val_lst</code> as a vector for each group
<code>rtn_val_pos</code>	is a vector containing all the group flag value like this ex: <code>c("flag1", "flag2", "flag3")</code>

Examples

```

interactive()

datf1 <- data.frame(c(1, 2, 1), c(45, 22, 88), c(44, 88, 33))

val_lst <- list(list(c(1), c(1)), list(c(2)), list(c(44, 88)))

condition_lst <- list(c(">", "<"), c("%%"), c("==", "=="))

conjunction_lst <- list(c("|"), c(), c("|"))

rtn_val_pos <- c("+", "++", "+++")

print(groupr_datf(inpt_datf=datf1, val_lst=val_lst, condition_lst=condition_lst,
conjunction_lst=conjunction_lst, rtn_val_pos=rtn_val_pos))

#      X1  X2  X3
#1 <NA>   +  +++
#2   ++  ++  +++
#3 <NA> +++   +

```

gsub_mult

gsub_mult

Description

Performs a gsub operation with n patterns and replacements.

Usage

```
gsub_mult(inpt_v, pattern_v = c(), replacement_v = c())
```

Arguments

`inpt_v` is a vector containing all the elements that contains expressions to be substituted

`pattern_v` is a vector containing all the patterns to be substituted in any elements of `inpt_v`

`replacement_v` is a vector containing the expression that are going to substitute those provided by `pattern_v`

Examples

```

print(gsub_mult(inpt_v = c("X and Y programming languages are great", "More X, more X!"),
  pattern_v = c("X", "Y", "Z"),
  replacement_v = c("C", "R", "GO")))
[1] "C and R programming languages are great"
[2] "More C, more C!"

```

historic_sequence1 *historic_sequence1*

Description

Allow to perform a pivot wider on a sequential dataset (here the type is dataframe), each variable will be duplicated in a column to show the value to this variable at $n - 1$ for each individual, see examples.

Usage

```
historic_sequence1(inpt_datf, bf_ = 1)
```

Arguments

`inpt_datf` is the input dataframe
`bf_` is the number of previous value of the individual it will search for, see examples

Examples

```
set.seed(123)
var1 <- round(runif(n = 14, min = 100, max = 122))
set.seed(123)
var2 <- round(runif(n = 14, min = 14, max = 20))

datf <- data.frame("ids" = c(20, 20, 20, 20, 19, 19, 19, 18, 18, 18, 18,
                             17, 17, 17),
                  "individual" = c("oui", "non", "peut1", "peut2",
                                   "oui", "peut1", "peut2"),
                  "var1" = var1,
                  "var2" = var2)

print(datf)
```

	ids	individual	var1	var2
1	20	oui	106	16
2	20	non	117	19
3	20	peut1	109	16
4	20	peut2	119	19
5	19	oui	121	20
6	19	peut1	101	14
7	19	peut2	112	17
8	18	oui	120	19
9	18	non	112	17
10	18	peut1	110	17
11	18	peut2	121	20
12	17	oui	110	17
13	17	peut1	115	18
14	17	peut2	113	17

```
historic_sequence1(inpt_datf = datf, bf_ = 2)
```

	id_seq	individual	var1-1	var1-2	var2-1	var2-2
1	20	oui	121	120	20	19
2	20	non	NA	112	NA	17

```

3      20      peut1      101      110      14      17
4      20      peut2      112      121      17      20
5      19        oui      120      110      19      17
6      19      peut1      110      115      17      18
7      19      peut2      121      113      20      17

```

```
historic_sequence1(inpt_datf = datf, bf_ = 3)
```

```

  id_seq individual var1-1 var1-2 var1-3 var2-1 var2-2 var2-3
1     20        oui    121    120    110     20     19     17
2     20        non     NA    112     NA     NA     17     NA
3     20      peut1    101    110    115     14     17     18
4     20      peut2    112    121    113     17     20     17

```

historic_sequence2 *historic_sequence2*

Description

Allow to perform a pivot wider on a sequential dataset (here the type is dataframe), each variable will be duplicated in a column to show the value to this variable at $n - 1$ for each individual, see examples.

Usage

```
historic_sequence2(inpt_datf, bf_ = 1)
```

Arguments

`inpt_datf` is the input dataframe
`bf_` is the number of previous value of the individual it will search for, see examples

Examples

```

set.seed(123)
var1 <- round(runif(n = 14, min = 100, max = 122))
set.seed(123)
var2 <- round(runif(n = 14, min = 14, max = 20))

datf <- data.frame("ids" = c(20, 20, 20, 20, 19, 19, 19, 18, 18, 18, 18,
                             17, 17, 17),
                  "individual" = c("oui", "non", "peut1", "peut2",
                                   "oui", "peut1", "peut2"),
                  "var1" = var1,
                  "var2" = var2)

print(datf)

```

```

  ids individual var1 var2
1  20        oui  106  16
2  20        non  117  19
3  20      peut1  109  16
4  20      peut2  119  19
5  19        oui  121  20

```

```

6  19      peut1 101  14
7  19      peut2 112  17
8  18        oui 120  19
9  18        non 112  17
10 18      peut1 110  17
11 18      peut2 121  20
12 17        oui 110  17
13 17      peut1 115  18
14 17      peut2 113  17

```

```
print(historic_sequence2(inpt_datf = datf, bf_ = 2))
```

```

   id_seq individual var1-0 var1-1 var1-2 var2-0 var2-1 var2-2
1      20        oui   106   121   120    16    20    19
2      20        non   117    NA   112    19    NA    17
3      20      peut1   109   101   110    16    14    17
4      20      peut2   119   112   121    19    17    20
5      19        oui   121   120   110    20    19    17
6      19      peut1   101   110   115    14    17    18
7      19      peut2   112   121   113    17    20    17

```

```
print(historic_sequence2(inpt_datf = datf, bf_ = 3))
```

```

   id_seq individual var1-0 var1-1 var1-2 var1-3 var2-0 var2-1 var2-2 var2-3
1      20        oui   106   121   120   110    16    20    19    17
2      20        non   117    NA   112    NA    19    NA    17    NA
3      20      peut1   109   101   110   115    16    14    17    18
4      20      peut2   119   112   121   113    19    17    20    17

```

id_keepr

id_keepr

Description

Allow to get the original indexes after multiple equality comparison according to the original number of row

Usage

```
id_keepr(inpt_datf, col_v = c(), el_v = c(), rstr_l = NA)
```

Arguments

inpt_datf	is the input dataframe
col_v	is the vector containing the column numbers or names to be compared to their respective elements in "el_v"
el_v	is a vector containing the elements that may be contained in their respective column described in "col_v"
rstr_l	is a list containing the vector composed of the indexes of the elements chosen for each comparison. If the length of the list is inferior to the lenght of comparisons, so the last vector of rstr_l will be the same as the last one to fill make rstr_l equal in term of length to col_v and el_v

Examples

```

datf1 <- data.frame(c("oui", "oui", "oui", "non", "oui"),
  c("opui", "op", "op", "zez", "zez"), c(5:1), c(1:5))

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op")))

#[1] 2 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"),
  rstr_l=list(c(1:5), c(3, 2, 2, 2, 3))))

#[1] 2 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"),
  rstr_l=list(c(1:5), c(3))))

#[1] 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5))))

#[1] 2 3

```

incr_fillr

*incr_fillr***Description**

Take a vector uniquely composed by double and sorted ascendingly, a step, another vector of elements whose length is equal to the length of the first vector, and a default value. If an element of the vector is not equal to its predecessor minus a user defined step, so these can be the output according to the parameters (see example):

Usage

```
incr_fillr(inpt_v, wrk_v = NA, default_val = NA, step = 1)
```

Arguments

inpt_v	is the asending double only composed vector
wrk_v	is the other vector (size equal to inpt_v), defaults to NA
default_val	is the default value put when the difference between two following elements of inpt_v is greater than step, defaults to NA
step	is the allowed difference between two elements of inpt_v

Examples

```

print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
  wrk_v=NA,
  default_val="increasing"))

#[1] 1 2 3 4 5 6 7 8 9 10

```

```
print(incr_fillr(inpt_v=c(1, 1, 2, 4, 5, 9),
                 wrk_v=c("ok", "ok", "ok", "ok", "ok"),
                 default_val=NA))

#[1] "ok" "ok" "ok" NA    "ok" "ok" NA    NA    NA

print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
                 wrk_v=NA,
                 default_val="NAN"))

#[1] "1"    "2"    "NAN" "4"    "5"    "NAN" "NAN" "NAN" "9"    "10"
```

`infinite_char_seq` *infinite_char_seq*

Description

Allow to generate an infinite sequence of unique letters

Usage

```
infinite_char_seq(n, base_char = letters)
```

Arguments

`n` is how many sequence of numbers will be generated
`base_char` is the vector containing the elements from which the sequence is generated

Examples

```
print(infinite_char_seq(28))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o"
[16] "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "a" "aa" "ab"
```

`inner_all` *inner_all*

Description

Allow to apply inner join on n dataframes, datatables, tibble

Usage

```
inner_all(..., keep_val = FALSE, id_v)
```

Arguments

... are all the dataframes etc
 keep_val is if you want to keep the id column
 id_v is the common id of all the dataframes etc

Examples

```
datf1 <- data.frame(
  "id1"=c(1:5),
  "var1"=c("oui", "oui", "oui", "non", "non")
)

datf2 <- data.frame(
  "id1"=c(1, 2, 3, 7, 9),
  "var1"=c("oui2", "oui2", "oui2", "non2", "non2")
)

print(inner_all(datf1, datf2, keep_val=FALSE, id_v="id1"))

id1 var1.x var1.y
1 1 oui oui2
2 2 oui oui2
3 3 oui oui2
```

insert_datf

*insert_datf***Description**

Allow to insert dataframe into another dataframe according to coordinates (row, column) from the dataframe that will be inserted

Usage

```
insert_datf(datf_in, datf_ins, ins_loc)
```

Arguments

datf_in is the dataframe that will be inserted
 datf_ins is the dataset to be inserted
 ins_loc is a vector containing two parameters (row, column) of the beginning for the insertion

Examples

```
datf1 <- data.frame(c(1, 4), c(5, 3))

datf2 <- data.frame(c(1, 3, 5, 6), c(1:4), c(5, 4, 5, "ereer"))

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(4, 2)))
```

```
#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1           1      1                5
# 2           3      2                4
# 3           5      3                5
# 4           6      1                5

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(3, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1           1      1                5
# 2           3      2                4
# 3           5      1                5
# 4           6      4                3

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(2, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1           1      1                5
# 2           3      1                5
# 3           5      4                3
# 4           6      4                ereer
```

<code>intersect_all</code>	<i>intersect_all</i>
----------------------------	----------------------

Description

Allows to calculate the intersection between n vectors

Usage

```
intersect_all(...)
```

Arguments

... is all the vector you want to calculate the intersection from

Examples

```
print(intersect_all(c(1:5), c(1, 2, 3, 6), c(1:4)))

[1] 1 2 3
```

intersect_mod	<i>intersect_mod</i>
---------------	----------------------

Description

Returns the mods that have elements in common

Usage

```
intersect_mod(datf, inter_col, mod_col, n_min, descendly_ordered = NA)
```

Arguments

datf	is the input dataframe
inter_col	is the column name or the column number of the values that may be commun between the different mods
mod_col	is the column name or the column number of the mods in the dataframe
n_min	is the minimum elements in common a mod should have to be taken in count
ordered_descendly	in case that the elements in commun are numeric, this option can be enabled by giving a value of TRUE or FALSE see examples

Examples

```
datf <- data.frame("col1"=c("oui", "oui", "oui", "oui", "oui", "oui",  
                           "non", "non", "non", "non", "ee", "ee", "ee"), "col2"=c(1:6, 2:5, 1:3))
```

```
print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=2))
```

```
  col1 col2
2   oui   2
3   oui   3
7   non   2
8   non   3
12  ee    2
13  ee    3
```

```
print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=3))
```

```
  col1 col2
2   oui   2
3   oui   3
4   oui   4
5   oui   5
7   non   2
8   non   3
9   non   4
10  non   5
```

```
print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=5))
```

```
  col1 col2
```

```

1 oui 1
2 oui 2
3 oui 3
4 oui 4
5 oui 5
6 oui 6

```

```

datf <- data.frame("col1"=c("non", "non", "oui", "oui", "oui", "oui",
                           "non", "non", "non", "non", "ee", "ee", "ee"), "col2"=c(1:6, 2:5, 1:6),
                   stringsAsFactors=FALSE)

print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=3))

```

```

      col1 col2
8    non    3
9    non    4
10   non    5
3    oui    3
4    oui    4
5    oui    5

```

intersect_mod2	<i>intersect_mod2</i>
----------------	-----------------------

Description

Returns the mods that have elemnts in common, uses a different algorith than intersect_mod1, see examples

Usage

```
intersect_mod2(inpt_datf, inter_col, mod_col, n_min = 1)
```

Arguments

inpt_datf	is the input dataframe
inter_col	is the column number or name of the elements that may be in common to each mod
mod_col	is the column number or name of the mods
n_min	is the minimum number of elements in common each mod have to have to be outputed in the returned dataframe

Examples

```

datf <- data.frame("country" = c("Germany", "France", "Italy", "France", "Germany", "Italy"),
                  "year" = c(2000, 2000, 2001, 2002, 2003, 2004),
                  "random_value" = c(1, 3, 2, 1, 2, 2))

print(datf)

```

```

      country year random_value
1 Germany 2000             1
2  France 2000             3
3   Italy 2001             2

```

```

4 France 2002          1
5 Germany 2003         2
6 Italy 2004           2

print(intersect_mod2(inpt_datf = datf, inter_col = "year", mod_col = "country"))

country year random_value
1 Germany 2000           1
2 France 2000           3

```

inter_max

inter_max

Description

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: `list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3))`. The function will return the list of lists altered according to the maximum step found in the input list.

Usage

```
inter_max(inpt_l, max_ = -1000, get_lst = TRUE)
```

Arguments

<code>inpt_l</code>	is the input list
<code>max_</code>	is a value you are sure is the minimum step value of all the sub-lists
<code>get_lst</code>	is the parameter that, if set to True, will keep the last values of vectors in the return value if the last step exceeds the end value of the vector.

Examples

```

print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=TRUE))

#[[1]]
#[1] 0 4
#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1.0 2.3

print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=FALSE))

# [[1]]
#[1] 0 4
#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1

```

inter_min

*inter_min***Description**

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)). This function will return the list of vectors with the same steps preserving the begin and end value of each interval. The way the algorithm searches the common step of all the sub-lists is also given by the user as a parameter, see how_to paramaters.

Usage

```
inter_min(
  inpt_l,
  min_ = 1000,
  sensi = 3,
  sensi2 = 3,
  how_to_op = c("divide"),
  how_to_val = c(3)
)
```

Arguments

inpt_l	is the input list containing all the intervals
min_	is a value you are sure is superior to the maximum step value in all the intervals
sensi	is the decimal accuracy of how the difference between each value n to n+1 in an interval is calculated
sensi2	is the decimal accuracy of how the value with the common step is calculated in all the intervals
how_to_op	is a vector containing the operations to perform to the pre-common step value, defaults to only "divide". The operations can be "divide", "subtract", "multiply" or "add". All type of operations can be in this parameter.
how_to_val	is a vector containing the value relatives to the operations in hot_to_op, defaults to 3 output from ex:

Examples

```
print(inter_min(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3))))

# [[1]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
# [20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
# [39] 3.8 3.9 4.0
#
# [[2]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
# [20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
# [39] 3.8 3.9 4.0
#
# [[3]]
```

```
# [1] 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1 2.2 2.3
```

isnt_divisible	<i>isnt_divisible</i>
----------------	-----------------------

Description

Takes a vector as an input and returns all the elements that are not divisible by all choosen numbers from another vector.

Usage

```
isnt_divisible(inpt_v = c(), divisible_v = c())
```

Arguments

inpt_v	is the input vector
divisible_v	is the vector containing all the numbers that will try to divide those contained in inpt_v

Examples

```
print(isnt_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

# [1] 1 3 7 9 11 13 17 19 21 23 27 29 31 33 37 39 41 43 47
# [20] 49 51 53 57 59 61 63 67 69 71 73 77 79 81 83 87 89 91 93
# [39] 97 99 101 103 107 109 111
```

is_divisible	<i>is_divisible</i>
--------------	---------------------

Description

Takes a vector as an input and returns all the elements that are divisible by all choosen numbers from another vector.

Usage

```
is_divisible(inpt_v = c(), divisible_v = c())
```

Arguments

inpt_v	is the input vector
divisible_v	is the vector containing all the numbers that will try to divide those contained in inpt_v

Examples

```
print(is_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

#[1] 20 40 60 80 100
```

join_n_lvl	<i>join_n_lvl</i>
------------	-------------------

Description

Allow to see the progress of the multi-level joins of the different variables modalities. Here, multi-level joins is a type of join that usually needs a concatenation of two or more variables to make a key. But here, there is no need to proceed to a concatenation. See examples.

Usage

```
join_n_lvl(first_datf, scd_datf, join_type = c(), lst_pair = list())
```

Arguments

- first_datf is the first data.frame (table)
- scd_datf is the second data.frame (table)
- join_type is a vector containing all the join type ("left", "inner", "right") for each variable
- lst_pair is a lis of vectors. The vectors refers to a multi-level join. Each vector should have a length of 1. Each vector should have a name. Its name refers to the column name of multi-level variable and its value refers to the column name of the join variable.

Examples

```
datf3 <- data.frame("vil"=c("one", "one", "one", "two", "two", "two"),
                    "charac"=c(1, 2, 2, 1, 2, 2),
                    "rev"=c(1250, 1430, 970, 1630, 2231, 1875),
                    "vil2" = c("one", "one", "one", "two", "two", "two"),
                    "idl2" = c(1:6))
datf4 <- data.frame("vil"=c("one", "one", "one", "two", "two", "three"),
                    "charac"=c(1, 2, 2, 1, 1, 2),
                    "rev"=c(1.250, 1430, 970, 1630, 593, 456),
                    "vil2" = c("one", "one", "one", "two", "two", "two"),
                    "idl2" = c(2, 3, 1, 5, 5, 5))

print(join_n_lvl(first_datf=datf3, scd_datf=datf4, lst_pair=list(c("charac" = "vil"), c("vil2" = "idl2")),
                join_type=c("inner", "left")))

[1] "pair: charac vil"
| | 0%
1
|= | 50%
2
|==| 100%
[1] "pair: vil2 idl2"
```

```
| | 0%
one
|= | 50%
two
|==| 100%

main_id.x vil.x charac.x rev.x vil2.x idl2.x main_id.y vil.y charac.y rev.y
1 1oneone1 one 1 1250 one 1 <NA> <NA> NA NA
2 2oneone2 one 2 1430 one 2 <NA> <NA> NA NA
3 2oneone3 one 2 970 one 3 2oneone3 one 2 1430
4 1twotwo4 two 1 1630 two 4 <NA> <NA> NA NA
vil2.y idl2.y
1 <NA> NA
2 <NA> NA
3 one 3
4 <NA> NA
```

just_anything	<i>just_anything</i>
---------------	----------------------

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_anything(inpt_v, symbol_ = "-", anything_v = c())
```

Arguments

- inpt_v is the input vector
- symbol_ is the chosen symbol to replace numbers

Examples

```
print(just_anything(inpt_v = c("oui222jj644", "oui122jj"),
symbol_ = "-", anything_v = letters))

[1] "oui-jj-" "oui-jj"
```

just_anything2	<i>just_anything2</i>
----------------	-----------------------

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_anything2(inpt_v, symbol_ = "-", anything_v = c())
```

Arguments

inpt_v is the input vector
 symbol_ is the chosen symbol to replace numbers

Examples

```
print(just_anything2(inpt_v = c("oui222jj44", "oui122jj"),
  symbol_ = "-", anything_v = letters))

[1] "oui---jj--" "oui---jj"
```

just_anything3	<i>just_anything3</i>
----------------	-----------------------

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_anything3(inpt_v, anything_v = c())
```

Arguments

inpt_v is the input vector

Examples

```
print(just_anything3(inpt_v = c("oui222jj644", "oui122jj"),
  anything_v = letters))

[1] "oui jj" "oui jj"
```

just_chr	<i>just_chr</i>
----------	-----------------

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_chr(inpt_v, symbol_ = "-")
```

Arguments

inpt_v is the input vector
 symbol_ is the chosen symbol to replace numbers

Examples

```
print(just_chr(inpt_v = c("oui222jj644", "oui122jj"),
  symbol_ = "-"))

[1] "oui-jj-" "oui-jj"
```

just_chr2

just_chr2

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_chr2(inpt_v, symbol_ = "-")
```

Arguments

inpt_v is the input vector
symbol_ is the chosen symbol to replace numbers

Examples

```
print(just_chr2(inpt_v = c("oui222jj44", "oui122jj"),
  symbol_ = "-"))

[1] "oui---jj--" "oui---jj"
```

just_chr3

just_chr3

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_chr3(inpt_v)
```

Arguments

inpt_v is the input vector

Examples

```
print(just_chr3(inpt_v = c("oui222jj644", "oui122jj")))

[1] "oui jj" "oui jj"
```

just_nb

just_nb

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_nb(inpt_v, symbol_ = "-")
```

Arguments

inpt_v is the input vector
symbol_ is the chosen symbol to replace numbers

Examples

```
print(just_nb(inpt_v = c("oui222jj644", "oui122jj"),
  symbol_ = "-"))

[1] "-222-44" "-122-"
```

just_nb2

just_nb2

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_nb2(inpt_v, symbol_ = "-")
```

Arguments

inpt_v is the input vector
symbol_ is the chosen symbol to replace numbers

Examples

```
print(just_nb2(inpt_v = c("oui222jj44", "oui122jj"),
  symbol_ = "-"))

[1] "---222--44" "---122--"
```

just_nb3	<i>just_nb3</i>
----------	-----------------

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_nb3(inpt_v)
```

Arguments

`inpt_v` is the input vector

Examples

```
print(just_nb3(inpt_v = c("oui222jj644", "oui122jj")))
[1] 222644 122
```

just_not_anything	<i>just_not_anything</i>
-------------------	--------------------------

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_not_anything(inpt_v, symbol_ = "-", anything_v = c())
```

Arguments

`inpt_v` is the input vector
`symbol_` is the chosen symbol to replace numbers

Examples

```
print(just_not_anything(inpt_v = c("oui222jj644", "oui122jj"),
  symbol_ = "-", anything_v = letters))
[1] "-222-644" "-122-"
```

```
just_not_anything2 just_not_anything2
```

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_not_anything2(inpt_v, symbol_ = "-", anything_v = c())
```

Arguments

<code>inpt_v</code>	is the input vector
<code>symbol_</code>	is the chosen symbol to replace numbers

Examples

```
print(just_not_anything2(inpt_v = c("oui222jj44", "oui122jj"),  
  symbol_ = "-", anything_v = letters))
```

```
[1] "---222-44" "---122--"
```

```
just_not_anything3 just_not_anything3
```

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_not_anything3(inpt_v, anything_v = c())
```

Arguments

<code>inpt_v</code>	is the input vector
---------------------	---------------------

Examples

```
print(just_not_anything3(inpt_v = c("oui222jj644", "oui122jj"),  
  anything_v = letters))
```

```
[1] "222644" "122"
```

leap_yr	<i>leap_year</i>
---------	------------------

Description

Get if the year is leap

Usage

```
leap_yr(year)
```

Arguments

year is the input year

Examples

```
print(leap_yr(year=2024))

#[1] TRUE
```

left_all	<i>left_all</i>
----------	-----------------

Description

Allow to apply left join on n dataframes, datatables, tibble

Usage

```
left_all(..., keep_val = FALSE, id_v)
```

Arguments

... are all the dataframes etc
 keep_val is if you want to keep the id column
 id_v is the common id of all the dataframes etc

Examples

```
datf1 <- data.frame(
  "id1"=c(1:5),
  "var1"=c("oui", "oui", "oui", "non", "non")
)

datf2 <- data.frame(
  "id1"=c(1, 2, 3, 7, 9),
  "var1"=c("oui2", "oui2", "oui2", "non2", "non2")
)
```

```
print(left_all(datf1, datf2, datf2, datf2, keep_val=FALSE, id_v="id1"))

  id1 var1.x var1.y var1.x.x var1.y.y
1   1    oui  oui2    oui2    oui2
2   2    oui  oui2    oui2    oui2
3   3    oui  oui2    oui2    oui2
4   4   non  <NA>    <NA>    <NA>
5   5   non  <NA>    <NA>    <NA>#'
print(left_all(datf1, datf2, datf2, keep_val=FALSE, id_v="id1"))

  id1 var1.x var1.y var1
1   1    oui  oui2 oui2
2   2    oui  oui2 oui2
3   3    oui  oui2 oui2
4   4   non  <NA> <NA>
5   5   non  <NA> <NA>
```

letter_to_nb	<i>letter_to_nb</i>
--------------	---------------------

Description

Allow to get the number of a spreadsheet based column by the letter ex: AAA = 703

Usage

```
letter_to_nb(letter)
```

Arguments

letter is the letter (name of the column)

Examples

```
print(letter_to_nb("rty"))

#[1] 12713
```

list_files	<i>list_files</i>
------------	-------------------

Description

A list.files() based function addressing the need of listing the files with extension a or or extension b ...

Usage

```
list_files(patternc, pathc = ".")
```

Arguments

patternc is a vector containing all the extensions you want
 pathc is the path, can be a vector of multiple path because list.files() supports it.

lst_flatnr	<i>lst_flatnr</i>
------------	-------------------

Description

Flatten a list to a vector

Usage

```
lst_flatnr(inpt_l)
```

Arguments

inpt_l is the input list

Examples

```
print(lst_flatnr(inpt_l=list(c(1, 2), c(5, 3), c(7, 2, 7))))  

#[1] 1 2 5 3 7 2 7
```

match_by	<i>match_by</i>
----------	-----------------

Description

Allow to match elements by ids, see examples.

Usage

```
match_by(to_match_v = c(), inpt_v = c(), inpt_ids = c())
```

Arguments

to_match_v is the vector containing all the elements to match
 inpt_v is the input vector containong all the elements that could contains the elements to match. Each elements is linked to an element from inpt_ids at any given index, see examples. So inpt_v and inpt_ids must be the same size
 inpt_ids is the vector containing all the ids for the elements in inpt_v. An element is linked to the id x is both are at the same index. So inpt_v and inpt_ids must be the same size

Examples

```
print(match_by(to_match_v = c("a"), inpt_v = c("a", "z", "a", "p", "p", "e", "e", "a"),
             inpt_ids = c(1, 1, 1, 2, 2, 3, 3, 3)))

[1] 1 8

print(match_by(to_match_v = c("a"), inpt_v = c("a", "z", "a", "a", "p", "e", "e", "a"),
             inpt_ids = c(1, 1, 1, 2, 2, 3, 3, 3)))

[1] 1 4 8

print(match_by(to_match_v = c("a", "e"), inpt_v = c("a", "z", "a", "a", "p", "e", "e", "a"),
             inpt_ids = c(1, 1, 1, 2, 2, 3, 3, 3)))

[1] 1 4 8 6
```

match_na_omit	<i>match_na_omit</i>
---------------	----------------------

Description

Performs a match, but remove the NA values in the output if there is one or many, see examples.

Usage

```
match_na_omit(x, table)
```

Arguments

- x is the vector of the patterns to be matched
- table is the vector that may contain the patterns to be matched

Examples

```
match_na_omit(x = c("oui", "non", "2"), table = c("1", "oui", "oui", "ee", "non"))

[1] 2 5
```

multitud	<i>multitud</i>
----------	-----------------

Description

From a list containing vectors allow to generate a vector following this rule: list(c("a", "b"), c("1", "2"), c("A", "Z", "E")) -> c("a1A", "b1A", "a2A", "b2A", "a1Z, ...)

Usage

```
multitud(l, sep_ = "")
```


Arguments

`l` is the list

`sep_` is the separator between elements (default is set to "" as you see in the example)

Examples

```
print(multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep="/")

#[1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
#[8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
#[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
#[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"
```

<code>mutate_vector</code>	<i><code>mutate_vector</code></i>
----------------------------	-----------------------------------

Description

Allow to select elements from a vector according to a uniform distribution (better than `runif`, especially for small vectors). You can choose the seed that the reimplement of the uniform distribution will work with, defaults to 'random_data2.csv', see examples

Usage

```
mutate_vector(
  inpt_v,
  n_inpt,
  nvr_here = "NULL",
  base_seed = "random_data2.csv"
)
```

Arguments

`inpt_v` is the input vector containing the elements to evenly select

`n_inpt` is the number of elements of the output vector

`nvr_here` is a known value that is never in 'inpt_v'

`base_seed` is a csv filename containing the values for the reimplement of the uniform function to work with

Examples

```
library("edml")
library("ggplot2")

test_v <- letters

x <- mutate_vector(inpt_v = test_v,
  n_inpt = 50000,
  nvr_here = "NULL",
  base_seed = "random_data2.csv")
```

```
length(x)

[1] 5000

datf <- occu(x)

datf %>%
  ggplot(mapping = aes(x = var, y = occurrence)) +
  geom_col() +
  theme_minimal()
```

nb2_follow

nb2_follow

Description

Allows to get the number and pattern of potential continuous pattern after an index of a vector, see examples

Usage

```
nb2_follow(inpt_v, inpt_idx, inpt_follow_v = c())
```

Arguments

`inpt_v` is the input vector
`inpt_idx` is the index
`inpt_follow_v` is a vector containing the patterns that are potentially just after `inpt_nb`

Examples

```
print(nb2_follow(inpt_v = c(1:12), inpt_idx = 4, inpt_follow_v = c(5)))

[1] 1 5
# we have 1 times the pattern 5 just after the 4nth index of inpt_v

print(nb2_follow(inpt_v = c(1, "non", "oui", "oui", "oui", "nop", 5), inpt_idx = 2, inpt_follow_v = c(5)))

[1] "3" "oui"

# we have 3 times continuously the pattern 'oui' and 0 times the pattern 5 just after the 2nd index of inpt_v

print(nb2_follow(inpt_v = c(1, "non", "5", "5", "5", "nop", 5), inpt_idx = 2, inpt_follow_v = c(5)))

[1] "3" "5"
```

nb_follow	<i>nb_follow</i>
-----------	------------------

Description

Allow to get the number of certain patterns that may be after an index of a vector continuously, see examples

Usage

```
nb_follow(inpt_v, inpt_idx, inpt_follow_v = c())
```

Arguments

inpt_v	is the input vector
inpt_idx	is the index
inpt_follow_v	is a vector containing all the potential patterns that may follow the element in the vector at the index inpt_idx

Examples

```
print(nb_follow(inpt_v = c(1:13), inpt_idx = 6, inpt_follow_v = c(5:9)))

[1] 3

print(nb_follow(inpt_v = c("ou", "nn", "pp", "zz", "zz", "ee", "pp"), inpt_idx = 2,
  inpt_follow_v = c("pp", "zz")))

[1] 3
```

nb_to_letter	<i>nb_to_letter</i>
--------------	---------------------

Description

Allow to get the letter of a spreadsheet based column by the number ex: 703 = AAA

Usage

```
nb_to_letter(x)
```

Arguments

x	is the number of the column
---	-----------------------------

Examples

```
print(nb_to_letter(5))  
[1] "e"  
print(nb_to_letter(27))  
[1] "aa"  
print(nb_to_letter(51))  
[1] "ay"  
print(nb_to_letter(52))  
[1] "az"  
print(nb_to_letter(53))  
[1] "ba"  
print(nb_to_letter(675))  
[1] "yy"  
print(nb_to_letter(676))  
[1] "yz"  
print(nb_to_letter(677))  
[1] "za"  
print(nb_to_letter(702))  
[1] "zz"  
print(nb_to_letter(703))  
[1] "aaa"  
print(nb_to_letter(18211))  
[1] "zxk"  
print(nb_to_letter(18277))  
[1] "zzy"  
print(nb_to_letter(18278))  
[1] "zzz"  
print(nb_to_letter(18279))  
[1] "aaaa"
```

nestr_datf1	<i>nestr_datf1</i>
-------------	--------------------

Description

Allow to write a value (1a) to a dataframe (1b) to its cells that have the same coordinates (row and column) than the cells whose value is equal to a another special value (2a), from another another dataframe (2b). The value (1a) depends of the cell value coordinates of the third dataframe (3b). If a cell coordinates (1c) of the first dataframe (1b) does not correspond to the coordinates of a good returning cell value (2a) from the dataframe (2b), so this cell (1c) can have its value changed to the same cell coordinates value (3a) of a third dataframe (4b), if (4b) is not set to NA.

Usage

```
nestr_datf1(
  inptf_datf,
  inptt_pos_datf,
  nestr_datf,
  yes_val = TRUE,
  inptt_neg_datf = NA
)
```

Arguments

```
inptf_datf    is the input dataframe (1b)
inptt_pos_datf
               is the dataframe (2b) that corresponds to the (1a) values
nestr_datf    is the dataframe (2b) that has the special value (2a)
yes_val       is the special value (2a)
inptt_neg_datf
               is the dataframe (4b) that has the (3a) values, defaults to NA
```

Examples

```
print(nestr_datf1(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_datf=data.frame(c(44, 44, 33), c(12, 12, 12)),
  nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))

#   c.1..2..1. c.1..5..7.
#1         4         12
#2        44         12
#3         3          2

print(nestr_datf1(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_datf=NA,
  nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))

#   c.1..2..1. c.1..5..7.
```

#1	4	1
#2	2	5
#3	3	2

nestr_datf2	<i>nestr_datf2</i>
-------------	--------------------

Description

Allow to write a special value (1a) in the cells of a dataframe (1b) that correspond (row and column) to those of another dataframe (2b) that return another special value (2a). The cells whose coordinates do not match the coordinates of the dataframe (2b), another special value can be written (3a) if not set to NA.

Usage

```
nestr_datf2(inptf_datf, rtn_pos, rtn_neg = NA, nestr_datf, yes_val = T)
```

Arguments

- inptf_datf is the input dataframe (1b)
- rtn_pos is the special value (1a)
- rtn_neg is the special value (3a)
- nestr_datf is the dataframe (2b)
- yes_val is the special value (2a)

Examples

```
print(nestr_datf2(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)), rtn_pos="yes",
rtn_neg="no", nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=
# c.1..2..1. c.1..5..7.
#1 yes no
#2 no no
#3 yes yes
```

nest_v	<i>nest_v</i>
--------	---------------

Description

Nest two vectors according to the following parameters.

Usage

```
nest_v(f_v, t_v, step = 1, after = 1)
```

Arguments

- f_v is the vector that will welcome the nested vector t_v
- t_v is the imbriuator vector
- step defines after how many elements of f_v the next element of t_v can be put in the output
- after defines after how many elements of f_v, the begining of t_v can be put

Examples

```
print(nest_v(f_v=c(1, 2, 3, 4, 5, 6), t_v=c("oui", "oui2", "oui3", "oui4", "oui5", "oui6"),
step=2, after=2))

#[1] "1" "2" "oui" "3" "4" "oui2" "5" "6" "oui3" "oui4"
```

new_ordered	<i>new_ordered</i>
-------------	--------------------

Description

Returns the indexes of elements contained in "w_v" according to "f_v"

Usage

```
new_ordered(f_v, w_v, nvr_here = NA)
```

Arguments

- f_v is the input vector
- w_v is the vector containing the elements that can be in f_v
- nvr_here is a value you are sure is not present in f_v

Examples

```
print(new_ordered(f_v=c("non", "non", "non", "oui"), w_v=c("oui", "non", "non")))

#[1] 4 1 2
```

normal_dens	<i>normal_dens</i>
-------------	--------------------

Description

Calculates the normal distribution probability, see examples

Usage

```
normal_dens(target_v = c(), mean, sd, step = 0.01)
```

Arguments

target_v	is the input interval, see examples
mean	is the mean of the normal distribution
sd	is the standard deviation of the normal distribution
step	is the step with which the result will be outputed, the smaller the step is, the more accurate the result will be

Examples

```
print(normal_dens(target_v = c(5, 19), mean = 12, sd = 1.5, step = 0.1))

[1] 0.9999974

print(normal_dens(target_v = c(10.5, 13.5), mean = 12, sd = 1.5, step = 0.1))

[1] 0.6986416

print(normal_dens(target_v = c(10.5, 13.5), mean = 12, sd = 1.5, step = 0.01))

[1] 0.6843008
```

normal_offset_prob	<i>normal_offset_prob</i>
--------------------	---------------------------

Description

Returns the probability of the most offset value in the input vector according to the normal distribution, see examples.

Usage

```
normal_offset_prob(inpt_v = c(), mean_inpt, sd_inpt)
```

Arguments

mean_inpt	is the mean of the normal distribution
sd_inpt	is the standard deviations of the normal distribution

Examples

```
print(normal_offset_prob(inpt_v = x,
                        mean_inpt = 15,
                        sd_inpt = 1))

[1] 0.01146424

print(normal_offset_prob(inpt_v = x,
                        mean_inpt = 15,
                        sd_inpt = 2))

[1] 0.08212756
```

normal_offset_val	<i>normal_offset_val</i>
-------------------	--------------------------

Description

normal_offset_val

Usage

```
normal_offset_val(mean_inpt, sd_inpt, proba = 0.01)
```

occu	<i>occu</i>
------	-------------

Description

Allow to see the occurrence of each variable in a vector. Returns a dataframe with, as the first column, the all the unique variable of the vector and , in he second column, their occurrence respectively.

Usage

```
occu(inpt_v)
```

Arguments

inpt_v the input dataframe

Examples

```
print(occu(inpt_v=c("oui", "peut", "peut", "non", "oui")))

#   var occurrence
#1  oui           2
#2  peut          2
#3  non           1
```

old_to_new_idx	<i>old_to_new_idx</i>
----------------	-----------------------

Description

Allow to convert index of elements in a vector `inpt_v` to index of an vector type `1:sum(nchar(inpt_v))`, see examples

Usage

```
old_to_new_idx(inpt_v = c())
```

Arguments

`inpt_v` is the input vector

Examples

```
print(old_to_new_idx(inpt_v = c("oui", "no", "eee")))
[1] 1 1 1 2 2 3 3 3 3
```

or_bool1	<i>or_bool1</i>
----------	-----------------

Description

Returns a boolean vector according to 'or' condition on boolean vector in a dataframe, each column represents a boolean vector, see examples, uses a different algorithm than `or_bool`

Usage

```
or_bool1(inpt_datf)
```

Examples

```
print(or_bool1(inpt_datf = data.frame("bool1" = c(TRUE, FALSE, FALSE, TRUE),
                                       "bool2" = c(TRUE, TRUE, FALSE, TRUE))))
[1] TRUE TRUE FALSE TRUE
```

or_bool2

or_bool2

Description

Returns a boolean vector according to 'or' condition on boolean vector in a dataframe, each column represents a boolean vector, see examples, uses a different algorithm than or_bool1

Usage

```
or_bool2(inpt_datf)
```

Examples

```
print(or_bool2(inpt_datf = data.frame("bool1" = c(TRUE, FALSE, FALSE, TRUE),
                                       "bool2" = c(TRUE, TRUE, FALSE, TRUE)))

[1] TRUE TRUE FALSE TRUE
```

pairs_findr

pairs_findr

Description

Takes a character as input and detect the pairs of pattern, like the parenthesis pairs if the pattern is "(" and then ")"

Usage

```
pairs_findr(inpt, ptrn1 = "(", ptrn2 = ")")
```

Arguments

inpt	is the input character
ptrn1	is the first pattern encountered in the pair
ptrn2	is the second pattern in the pair

Examples

```
print(pairs_findr(inpt="ze+(yu*45/(jk+zz)*(o())p)-(re*(rt+qs)-fg)"))

[[1]]
[1] 4 1 1 3 2 2 3 4 6 5 5 6

[[2]]
[1] 4 11 17 19 21 22 24 25 27 31 37 41
```

pairs_findr_merger *pairs_findr_merger*

Description

Takes two different outputs from pairs_findr and merge them. Can be usefull when the pairs consists in different patterns, for example one output from the pairs_findr function with ptrn1 = "(" and ptrn2 = ")", and a second output from the pairs_findr function with ptrn1 = "" and ptrn2 = "".

Usage

```
pairs_findr_merger(lst1 = list(), lst2 = list())
```

Arguments

lst1 is the first ouput from pairs findr function
 lst2 is the second ouput from pairs findr function

Examples

```
print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 8, 9)),
                        lst2=list(c(1, 1), c(1, 2))))

[[1]]
[1] 1 1 2 3 4 4 3 2

[[2]]
[1] 1 2 3 4 5 7 8 9

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 8, 9)),
                        lst2=list(c(1, 1), c(1, 11))))

[[1]]
[1] 1 2 3 4 4 3 2 1

[[2]]
[1] 1 3 4 5 7 8 9 11

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 8, 10, 11)),
                        lst2=list(c(4, 4), c(6, 7))))

[[1]]
[1] 1 2 3 4 4 3 2 1

[[2]]
[1] 3 4 5 6 7 8 10 11

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 10, 11)),
                        lst2=list(c(4, 4), c(8, 9))))

[[1]]
[1] 1 2 3 3 4 4 2 1

[[2]]
```

```

[1] 3 4 5 7 8 9 10 11

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 10, 11)),
                          lst2=list(c(4, 4), c(18, 19))))

[[1]]
[1] 1 2 3 3 2 1 4 4

[[2]]
[1] 3 4 5 7 10 11 18 19

print(pairs_findr_merger(lst1 = list(c(1, 1, 2, 2, 3, 3), c(1, 25, 26, 32, 33, 38)),
                          lst2 = list(c(1, 1, 2, 2, 3, 3), c(7, 11, 13, 17, 19, 24))))

[[1]]
[1] 1 2 2 3 3 4 4 1 5 5 6 6

[[2]]
[1] 1 7 11 13 17 19 24 25 26 32 33 38

print(pairs_findr_merger(lst1 = list(c(1, 1, 2, 2, 3, 3), c(2, 7, 9, 10, 11, 15)),
                          lst2 = list(c(3, 2, 1, 1, 2, 3, 4, 4), c(1, 17, 18, 22, 23, 29,
[[1]]
[1] 6 5 1 1 2 2 3 3 4 4 5 6 7 7

[[2]]
[1] 1 2 7 9 10 11 15 17 18 22 23 29 35 40

print(pairs_findr_merger(lst1 = list(c(1, 1), c(22, 23)),
                          lst2 = list(c(1, 1, 2, 2), c(3, 21, 27, 32))))

[[1]]
[1] 1 1 2 2 3 3

[[2]]
[1] 3 21 22 23 27 32

```

pairs_insertr

pairs_insertr

Description

Takes a character representing an arbitrary condition (like ReGeX for example) or an information (to a parser for example), vectors containing all the pair of pattern that potentially surrounds condition (flagged_pair_v and corr_v), and a vector containing all the conjunction character, as input and returns the character with all or some of the condition surrounded by the pair characters. See examples. All the pair characters are inserted according to the closest pair they found prioritizing those found next to the condition and on the same depth-level and , if not found, the pair found at the n+1 depth-level.

Usage

```

pairs_insertr(
  inpt,
  algo_used = c(1:3),
  flagged_pair_v = c(")", "]"),
  corr_v = c("(", "["),
  flagged_conj_v = c("&", "|")
)

```

Arguments

<code>inpt</code>	is the input character representing an arbitrary condition, like ReGex for example, or information to a parser for example
<code>algo_used</code>	is a vector containing one or more of the 3 algorithms used. The first algorithm will simply put the pair of parenthesis at the condition surrounded and/or after a character flagged (in <code>flagged_conj_v</code>) as a conjunction. The second algorithm will put parenthesis at the condition that are located after other conditions that are surrounded by a pair. The third algorithm will put a pair at all the condition, it is very powerfull but takes a longer time. See examples and make experience to see which combination of algorithm(s) is the most efficient for your use case.
<code>flagged_pair_v</code>	is a vector containing all the first character of the pairs
<code>corr_v</code>	is a vector containing all the last character of the pairs
<code>flagged_conj_v</code>	is a vector containing all the conjunction character

Examples

```

print(pairs_insertr(inpt = "([one]|two|twob)three(four)", algo_used = c(1)))

[1] "([one]| [two]| [twob])three(four) "

print(pairs_insertr(inpt = "(one|[two]|twob)three(four)", algo_used = c(2)))

[1] "(one|[two]| [twob]) (three) (four) "

print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2)))

[1] "(oneA|[one]| [two]| [twob]) (three) (four) "

print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2, 3)))

[1] "([oneA]| [one]| [two]| [twob]) (three) (four) "

print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(3)))

[1] "([oneA]| [one]| (two) | (twob)) (three) (four) "

print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three((four))", algo_used = c(3)))

[1] "([oneA]| [(one)] | (two) | (twob)) (three) ((four)) "

```

pairs_insertr2	<i>pairs_insertr2</i>
----------------	-----------------------

Description

Takes a character representing an arbitrary condition (like ReGeX for example) or an information (to a parser for example), vectors containing all the pair of pattern that potentially surrounds condition (flagged_pair_v and corr_v), and a vector containing all the conjunction character, as input and returns the character with all or some of the condition surrounded by the pair characters. See examples. All the pair characters are inserted according to the closest pair they found prioritizing those found next to the condition and on the same depth-level and , if not found, the pair found at the n+1 depth-level.

Usage

```
pairs_insertr2(
  inpt,
  algo_used = c(1:3),
  flagged_pair_v = c(")", "["),
  corr_v = c("(", "["),
  flagged_conj_v = c("&", "|"),
  method = c("(", ")")
)
```

Arguments

inpt	is the input character representing an arbitrary condition, like ReGex for example, or information to a parser for example
algo_used	is a vector containing one or more of the 3 algorithms used. The first algorithm will simply put the pair of parenthesis at the condition surrounded and/or after a character flagged (in flagged_conj_v) as a conjunction. The second algorithm will put parenthesis at the condition that are located after other conditions that are surrounded by a pair. The third algorithm will put a pair at all the condition, it is very powerfull but takes a longer time. See examples and make experience to see which combination of algorythm(s) is the most efficient for your use case.
flagged_pair_v	is a vector containing all the first character of the pairs
corr_v	is a vector containing all the last character of the pairs
flagged_conj_v	is a vector containing all the conjunction character
method	is length 2 vector containing as a first index, the first character of the pair inserted, and at the last index, the second and last character of the pair

Examples

```
print(pairs_insertr2(inpt = "([one]|two|twob)three(four)", algo_used = c(1), method = c(
[1] "([one]|(two)|(twob))three(four)"

print(pairs_insertr2(inpt = "([one]|two|twob)three(four)", algo_used = c(1), method = c(
```

```

[1] "([one]|[two]|[twob])three(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2)))

[1] "(oneA|[one]|(two)|(twob))(three)(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2), meth
      flagged_pair_v = c(")", "]", "#"), corr_v = c("(", "[", "-"))

[1] "(oneA|[one]|-two#|-twob#)-three#(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2, 3)))

[1] "((oneA|[one]|(two)|(twob))(three)(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(3), method

[1] "([oneA|[one]|two]|[twob])[three](four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three((four))", algo_used = c(3)))

[1] "((oneA|[one]|(two)|(twob))(three)((four))"

```

paste_datf

paste_datf

Description

Return a vector composed of pasted elements from the input dataframe at the same index.

Usage

```
paste_datf(inpt_datf, sep = "")
```

Arguments

`inpt_datf` is the input dataframe

`sep` is the separator between pasted elements, defaults to ""

Examples

```

print(paste_datf(inpt_datf=data.frame(c(1, 2, 1), c(33, 22, 55))))

[1] "133" "222" "155"

```

paste_datf2	<i>paste_datf2</i>
-------------	--------------------

Description

Return a vector composed of pasted elements from the input dataframe at the same column.

Usage

```
paste_datf2(inpt_datf, sep = "")
```

Arguments

inpt_datf	is the input dataframe
sep	is the separator between pasted elements, defaults to ""

Examples

```
print(paste_datf2(inpt_datf=data.frame(c(1, 2, 1), c(33, 22, 55))))
#[1] "121" "332255"
```

pattern_generator	<i>pattern_generator</i>
-------------------	--------------------------

Description

Allow to create patterns which have a part that is varying randomly each time.

Usage

```
pattern_generator(base_, from_, nb, hmn = 1, after = 1, sep = "")
```

Arguments

base_	is the pattern that will be kept
from_	is the vector from which the elements of the random part will be generated
nb	is the number of random pattern chosen for the varying part
hmn	is how many of varying pattern from the same base will be created
after	is set to 1 by default, it means that the varying part will be after the fixed part, set to 0 if you want the varying part to be before
sep	is the separator between all patterns in the returned value

Examples

```
print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=1, hmn=3))

# [1] "ouier" "ouire" "ouier"

print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=2, hmn=3, after=0, se

# [1] "er-re-o-u-i" "ere-re-o-u-i" "ere-er-o-u-i"
```

pattern_gettr

pattern_gettr

Description

Search for pattern(s) contained in a vector in another vector and return a list containing matched one (first index) and their position (second index) according to these rules: First case: Search for patterns strictly, it means that the searched pattern(s) will be matched only if the patterns contained in the vector that is being explored by the function are present like this c("pattern_searched", "other", ..., "pattern_searched") and not as c("other_thing pattern_searched other_thing", "other", ..., "pattern_searched other_thing") Second case: It is the opposite to the first case, it means that if the pattern is partially present like in the first position and the last, it will be considered like a matched pattern. REGEX can also be used as pattern

Usage

```
pattern_gettr(
  word_,
  vct,
  occ = c(1),
  strict,
  btwn,
  all_in_word = "yes",
  notatall = "###"
)
```

Arguments

word_	is the vector containing the patterns
vct	is the vector being searched for patterns
occ	a vector containing the occurrence of the pattern in word_ to be matched in the vector being searched, if the occurrence is 2 for the nth pattern in word_ and only one occurrence is found in vct so no pattern will be matched, put "forever" to no longer depend on the occurrence for the associated pattern
strict	a vector containing the "strict" condition for each nth vector in word_ ("strict" is the string to activate this option)
btwn	is a vector containing the condition ("yes" to activate this option) meaning that if "yes", all elements between two matched pattern in vct will be returned, so the patterns you enter in word_ have to be in the order you think it will appear in vct

`all_in_word` is a value (default set to "yes", "no" to activate this option) that, if activated, won't authorized a previous matched pattern to be matched again

`notatall` is a string that you are sure is not present in `vct`

Examples

```
print(pattern_gettr(word=c("oui", "non", "erer"), vct=c("oui", "oui", "non", "oui",
  "non", "opp", "opp", "erer", "non", "ok"), occ=c(1, 2, 1),
  btwn=c("no", "yes", "no"), strict=c("no", "no", "ee")))

#[[1]]
#[1] 1 5 8
#
#[[2]]
#[1] "oui" "non" "opp" "opp" "erer"
```

pattern_tuning *pattern_tuning*

Description

Allow to tune a pattern very precisely and output a vector containing its variations `n` times.

Usage

```
pattern_tuning(
  pattn,
  spe_nb,
  spe_l,
  exclude_type,
  hmn = 1,
  rg = c(1, nchar(pattn))
)
```

Arguments

`pattn` is the character that will be tuned

`spe_nb` is the number of new character that will be replaced

`spe_l` is the source vector from which the new characters will replace old ones

`exclude_type` is character that won't be replaced

`hm` is how many output the function will return

`rg` is a vector with two parameters (index of the first letter that will be replaced, index of the last letter that will be replaced) default is set to all the letters from the source pattern

Examples

```
print(pattern_tuning(pattn="oui", spe_nb=2, spe_l=c("e", "r", "T", "O"), exclude_type="o")

#[1] "orT" "oTr" "oOi"
```

power_to_char	<i>power_to_char</i>
---------------	----------------------

Description

Convert a scientific number to a string representing normally the number.

Usage

```
power_to_char(inpt_v = c())
```

Arguments

inpt_v	is the input vector containing scientific number, but also other elements that won't be taken in count
--------	--

Examples

```
print(power_to_char(inpt_v = c(22 * 10000000, 12, 9 * 0.0000002)))
[1] "22000000000" "12"          "0.00000018"
```

pre_to_post_idx	<i>pre_to_post_idx</i>
-----------------	------------------------

Description

Allow to convert indexes from a pre-vector to post-indexes based on a current vector, see examples

Usage

```
pre_to_post_idx(inpt_v = c(), inpt_idx = c(1:length(inppt_v)))
```

Arguments

inpt_v	is the new vector
inpt_idx	is the vector containing the pre-indexes

Examples

```
print(pre_to_post_idx(inpt_v = c("oui", "no", "eee"), inpt_idx = c(1:8)))
[1] 1 1 1 2 2 3 3 3

As if the first vector was c("o", "u", "i", "n", "o", "e", "e", "e")
```

ptrn_switchr	<i>ptrn_switchr</i>
--------------	---------------------

Description

Allow to switch, copy pattern for each element in a vector. Here a pattern is the values that are separated by a same separator. Example: "xx-xxx-xx" or "xx/xx/xxxx". The xx like values can be swiched or copied from whatever index to whatever index. Here, the index is like this 1-2-3 etcetera, it is relative of the separator.

Usage

```
ptrn_switchr(inpt_l, f_idx_l = c(), t_idx_l = c(), sep = "-", default_val = NA)
```

Arguments

inpt_l	is the input vector
f_idx_l	is a vector containing the indexes of the pattern you want to be altered.
t_idx_l	is a vector containing the indexes to which the indexes in f_idx_l are related.
sep	is the separator, defaults to "-"
default_val	is the default value , if not set to NA, of the pattern at the indexes in f_idx_l. If it is not set to NA, you do not need to fill t_idx_l because this is the vector containing the indexes of the patterns that will be set as new values relatively to the indexes in f_idx_l. Defaults to NA.

Examples

```
print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1, 2, 3), t_idx_l=c(3, 2, 1)))

#[1] "11-01-2022" "14-01-2022" "21-01-2022" "01-01-2022"

print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1), default_val="ee"))

#[1] "ee-01-11" "ee-01-14" "ee-01-21" "ee-01-01"
```

ptrn_twkr	<i>ptrn_twkr</i>
-----------	------------------

Description

Allow to modify the pattern length of element in a vector according to arguments. What is here defined as a pattern is something like this xx-xx-xx or xx/xx/xxx... So it is defined by the separator

Usage

```
ptrn_twkr(
  inpt_l,
  depth = "max",
  sep = "-",
  default_val = "0",
  add_sep = TRUE,
  end_ = TRUE
)
```

Arguments

<code>inpt_l</code>	is the input vector
<code>depth</code>	is the number (numeric) of separator it will keep as a result. To keep the number of separator of the element that has the minimum amount of separator do <code>depth="min"</code> and <code>depth="max"</code> (character) for the opposite. This value defaults to "max".
<code>sep</code>	is the separator of the pattern, defaults to "-"
<code>default_val</code>	is the default val that will be placed between the separator, defaults to "00"
<code>add_sep</code>	defaults to TRUE. If set to FALSE, it will remove the separator for the patterns that are included in the interval between the depth amount of separator and the actual number of separator of the element.
<code>end_</code>	is if the default_val will be added at the end or at the beginning of each element that lacks length compared to depth

Examples

```
v <- c("2012-06-22", "2012-06-23", "2022-09-12", "2022")

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE)

#[1] "2012-06-22" "2012-06-23" "2022-09-12" "2022-00-00"

ptrn_twkr(inpt_l=v, depth=1, sep="-", default_val="00", add_sep=TRUE)

#[1] "2012-06" "2012-06" "2022-09" "2022-00"

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE, end_=FALSE)

#[1] "2012-06-22" "2012-06-23" "2022-09-12" "00-00-2022"
```

<code>read_edm_parser</code>	<i>read_edm_parser</i>
------------------------------	------------------------

Description

Allow to read data from edm parsed dataset, see examples

Usage

```
read_edm_parser(inpt, to_find_v = c())
```

Arguments

`inpt` is the input dataset
`to_find_v` is the vector containing the path to find the data, see examples

Examples

```
print(read_edm_parser("(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ee1:4))",
  to_find_v = c("ok", "oui", "rr", "rr2")))

[1] "6"

print(read_edm_parser("(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ee1:4))", t
  to_find_v = c("ok", "oui", "rr", "rr2")))

[1] "56"

print(read_edm_parser("(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ee1:4))", t
  to_find_v = c("ok", "oui", "rr", "rr2")))

[1] "56"
```

rearangr_v

rearangr_v

Description

Rearranges a vector "w_v" according to another vector "inpt_v". inpt_v contains a sequence of number. inpt_v and w_v have the same size and their indexes are related. The output will be a vector containing all the elements of w_v rearranges in descending or ascending order according to inpt_v

Usage

```
rearangr_v(inpt_v, w_v, how = "increasing")
```

Arguments

`inpt_v` is the vector that contains the sequence of number
`w_v` is the vector containing the elements related to inpt_v
`how` is the way the elements of w_v will be outputed according to if inpt_v will be sorted ascendigly or descendigly

Examples

```
print(rearangr_v(inpt_v=c(23, 21, 56), w_v=c("oui", "peut", "non"), how="decreasing"))

#[1] "non" "oui" "peut"
```

```
regex_spe_detect      regex_spe_detect
```

Description

Takes a character as input and returns its regex-friendly character for R.

Usage

```
regex_spe_detect (inpt)
```

Arguments

`inpt` the input character

Examples

```
print(regex_spe_detect("o"))

[1] "o"

print(regex_spe_detect("("))

[1] "\\("

print(regex_spe_detect("tr(o)m"))

[1] "tr\\(o\\)m"

print(regex_spe_detect(inpt="fggfg[fggf]fgfg(vg?fgfgf.gf)"))

[1] "fggfg\\[fggf\\]fgfg\\(vg\\?fgfgf\\.gf\\)"

print(regex_spe_detect(inpt = "---"))

[1] "\\-\\-\\-"
```

```
regroupr              regroupr
```

Description

Allow to sort data like "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to what you want. For example it can be to "c(X1/Y1/21, X1/Y1/Z2, ...)"

Usage

```
regroupr (
  inpt_v,
  sep_ = "-",
  order = c(1:length(unlist(strsplit(x = inpt_v[1], split = sep_)))),
  l_order = NA
)
```


Arguments

<code>inpt_v</code>	is the input vector containing all the data you want to sort in a specific way. All the sub-elements should be separated by a unique separator such as "-" or "/"
<code>sep_</code>	is the unique separator separating the sub-elements in each elements of <code>inpt_v</code>
<code>order</code>	is a vector describing the way the elements should be sorted. For example if you want this dataset "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to be sorted by the last element you should have <code>order=c(3:1)</code> , for example, and it should returns something like this c(X1/Y1/Z1, X2/Y1/Z1, X1/Y2/Z1, ...) assuming you have only two values for X.
<code>l_order</code>	is a list containing the vectors of values you want to order first for each sub-elements

Examples

```
vec <- multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")

print(vec)

# [1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
# [8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
#[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
#[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"

print(regroupr(inpt_v=vec, sep_="/"))

# [1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
# [7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
#[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/1/18/18"
#[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23" "b/2/24/24"

vec <- vec[-2]

print(regroupr(inpt_v=vec, sep_="/"))

# [1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
# [7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
#[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/2/18/18"
#[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23"

print(regroupr(inpt_v=vec, sep_="/", order=c(4:1)))

#[1] "1/1/A/Q" "2/2/A/Q" "3/3/A/Q" "4/4/A/Q" "5/5/Z/Q" "6/6/Z/Q"
# [7] "7/7/Z/Q" "8/8/Z/Q" "9/9/E/Q" "10/10/E/Q" "11/11/E/Q" "12/12/E/Q"
#[13] "13/13/A/F" "14/14/A/F" "15/15/A/F" "16/16/A/F" "17/17/Z/F" "18/18/Z/F"
#[19] "19/19/Z/F" "20/20/Z/F" "21/21/E/F" "22/22/E/F" "23/23/E/F" "24/24/E/F"
```

rm_na_rows

rm_na_rows

Description

Allow to remove certain rows that contains NA, see examples.

Usage

```
rm_na_rows(inpt_datf, flagged_vals = c())
```

Arguments

`inpt_datf` is the input dataframe

`flagged_vals` is a vector containing the characters that will drop any rows that contains it

Examples

```
datf <- data.frame(c(1, 2, NA, 4), c(1:4))
print(datf)
```

```
  c.1..2..NA..4. c.1.4.
1             1      1
2             2      2
3            NA      3
4             4      4
```

```
print(rm_na_rows(inpt_datf = datf))
```

```
  c.1..2..NA..4. c.1.4.
1             1      1
2             2      2
4             4      4
```

 rm_rows

rm_rows

Description

Allow to remove certain rows that contains certains characters, see examples.

Usage

```
rm_rows(inpt_datf, flagged_vals = c())
```

Arguments

`inpt_datf` is the input dataframe

`flagged_vals` is a vector containing the characters that will drop any rows that contains it

Examples

```
datf <- data.frame(c(1, 2, NA, 4), c(1:4))
print(datf)
```

```
  c.1..2..NA..4. c.1.4.
1             1      1
2             2      2
3            NA      3
4             4      4
```

```
print(rm_rows(inpt_datf = datf, flagged_vals = c(1, 4)))

  c.1..2..NA..4. c.1.4.
2             2      2
3             NA      3
```

row_to_col	<i>row_to_col</i>
------------	-------------------

Description

Allow to reverse a dataframe (rows become cols and cols become rows)

Usage

```
row_to_col(inpt_datf)
```

Arguments

`inpt_datf` is the inout dataframe

Examples

```
datf_test <- data.frame(c(1, 11), c(2, 10), c(3, 9), c(4, 8))

print(datf_test)

  c.1..11. c.2..10. c.3..9. c.4..8.
1         1         2         3         4
2        11        10         9         8

print(row_to_col(inpt_datf = datf_test))

  1  2
1 1 11
2 2 10
3 3  9
4 4  8
```

r_print	<i>r_print</i>
---------	----------------

Description

Allow to print vector elements in one row.

Usage

```
r_print(inpt_v, sep_ = "and", begn = "This is", end = ", voila!")
```

Arguments

- inpt_v is the input vector
- sep_ is the separator between each elements
- begn is the character put at the beginning of the print
- end is the character put at the end of the print

Examples

```
print(r_print(inpt_v=c(1:33)))

#[1] "This is  1 and 2 and 3 and 4 and 5 and 6 and 7 and 8 and 9 and 10 and 11 and 12 and
#and 14 and 15 and 16 and 17 and 18 and 19 and 20 and 21 and 22 and 23 and 24 and 25 and
#and 27 and 28 and 29 and 30 and 31 and 32 and 33 and , voila!"
```

save_untl	<i>save_untl</i>
-----------	------------------

Description

Get the elements in each vector from a list that are located before certain values

Usage

```
save_untl(inpt_l = list(), val_to_stop_v = c())
```

Arguments

- inpt_l is the input list containing all the vectors
- val_to_stop_v is a vector containing the values that marks the end of the vectors returned in the returned list, see the examples

Examples

```
print(save_untl(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3, 4)))

#[[1]]
#[1] 1 2
#
#[[2]]
#[1] 1 1
#
#[[3]]
#[1] 1 2

print(save_untl(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3)))

#[[1]]
#[1] 1 2
#
#[[2]]
```

```
#[1] 1 1
#
#[[3]]
#[1] 1 2 4
```

see_datf

see_datf

Description

Allow to return a dataframe with special value cells (ex: TRUE) where the condition entered are respected and another special value cell (ex: FALSE) where these are not

Usage

```
see_datf(
  datf,
  condition_l,
  val_l,
  conjunction_l = c(),
  rt_val = TRUE,
  f_val = FALSE
)
```

Arguments

<code>datf</code>	is the input dataframe
<code>condition_l</code>	is the vector of the possible conditions ("==", ">", "<", "!=", "%%", "reg", "not_reg", "sup_nchar", "inf_nchar", "nchar") (equal to some elements in a vector, greater than, lower than, not equal to, is divisible by, the regex condition returns TRUE, the regex condition returns FALSE, the length of the elements is strictly superior to X, the length of the element is strictly inferior to X, the length of the element is equal to one element in a vector), you can put the same condition n times.
<code>val_l</code>	is the list of vectors containing the values or vector of values related to <code>condition_l</code> (so the vector of values has to be placed in the same order)
<code>conjunction_l</code>	contains the and or conjunctions, so if the length of <code>condition_l</code> is equal to 3, there will be 2 conjunctions. If the length of <code>conjunction_l</code> is inferior to the length of <code>condition_l</code> minus 1, <code>conjunction_l</code> will match its goal length value with its last argument as the last arguments. For example, <code>c("&", "l", "&")</code> with a goal length value of 5 -> <code>c("&", "l", "&", "&", "&")</code>
<code>rt_val</code>	is a special value cell returned when the conditions are respected
<code>f_val</code>	is a special value cell returned when the conditions are not respected

Details

This function will return an error if number only comparative conditions are given in addition to having character values in the input dataframe.

Examples

```

datf1 <- data.frame(c(1, 2, 4), c("a", "a", "zu"))

print(see_datf(datf=datf1, condition_l=c("nchar"), val_l=list(c(1))))

#      X1      X2
#1 TRUE  TRUE
#2 TRUE  TRUE
#3 TRUE FALSE

print(see_datf(datf=datf1, condition_l=c("=="), val_l=list(c("a", 1))))

#      X1      X2
#1 TRUE  TRUE
#2 FALSE TRUE
#3 FALSE FALSE

print(see_datf(datf=datf1, condition_l=c("nchar"), val_l=list(c(1, 2))))

#      X1      X2
#1 TRUE TRUE
#2 TRUE TRUE
#3 TRUE TRUE

print(see_datf(datf=datf1, condition_l=c("not_reg"), val_l=list("[a-z]")))

#      X1      X2
#1 TRUE FALSE
#2 TRUE FALSE
#3 TRUE FALSE

```

see_diff

see_diff

Description

Output the opposite of intersect(a, b). Already seen at: <https://stackoverflow.com/questions/19797954/function-to-find-symmetric-difference-opposite-of-intersection-in-r>

Usage

```
see_diff(vec1 = c(), vec2 = c())
```

Arguments

vec1	is the first vector
vec2	is the second vector

Examples

```
print(see_diff(c(1:7), c(4:12)))

[1] 1 2 3 8 9 10 11 12
```

see_diff_all	<i>see_diff_all</i>
--------------	---------------------

Description

Allow to perform the opposite of intersect function to n vectors.

Usage

```
see_diff_all(...)
```

Arguments

... are all the input vectors

Examples

```
vec1 <- c(3:6)
vec2 <- c(1:8)
vec3 <- c(12:16)

print(see_diff_all(vec1, vec2))

[1] 1 2 7 8

print(see_diff_all(vec1, vec2, vec3))

[1] 3 4 5 6 1 2 7 8 12 13 14 15 16
```

see_diff_detailed	<i>see_diff_detailed</i>
-------------------	--------------------------

Description

Behaves exactly like the see_diff function but is written more explicitly, see examples

Usage

```
see_diff_detailed(vec1 = c(), vec2 = c())
```

Arguments

vec1	is one of the input vector
vec2	is the other input vector

Examples

```
print(see_diff_detailed(c(1:6), c(3:9)))

[1] 1 2 7 8 9
```

see_file

see_file

Description

Allow to get the filename or its extension

Usage

```
see_file(string_, index_ext = 1, ext = TRUE)
```

Arguments

string_	is the input string
index_ext	is the occurrence of the dot that separates the filename and its extension
ext	is a boolean that if set to TRUE, will return the file extension and if set to FALSE, will return filename

Examples

```
print(see_file(string_="file.abc.xyz"))

#[1] ".abc.xyz"

print(see_file(string_="file.abc.xyz", ext=FALSE))

#[1] "file"

print(see_file(string_="file.abc.xyz", index_ext=2))

#[1] ".xyz"
```

see_idx

see_idx

Description

Returns a boolean vector to see if a set of elements contained in v1 is also contained in another vector (v2)

Usage

```
see_idx(v1, v2)
```


Arguments

v1 is the first vector
v2 is the second vector

Examples

```
print(see_idx(v1=c("oui", "non", "peut", "oo"), v2=c("oui", "peut", "oui")))

#[1]  TRUE FALSE  TRUE  FALSE
```

see_inside	<i>see_inside</i>
------------	-------------------

Description

Return a list containing all the column of the files in the current directory with a chosen file extension and its associated file and sheet if xlsx. For example if i have 2 files "out.csv" with 2 columns and "out.xlsx" with 1 column for its first sheet and 2 for its second one, the return will look like this: c(column_1, column_2, column_3, column_4, column_5, unique_separator, "1-2-out.csv", "3-3-sheet_1-out.xlsx", 4-5-sheet_2-out.xlsx)

Usage

```
see_inside(
  pattern_,
  path_ = ".",
  sep_ = c(", "),
  unique_sep = "#####",
  rec = FALSE
)
```

Arguments

pattern_ is a vector containin the file extension of the spreadsheets ("xlsx", "csv"...)

path_ is the path where are located the files

sep_ is a vector containing the separator for each csv type file in order following the operating system file order, if the vector does not match the number of the csv files found, it will assume the separator for the rest of the files is the same as the last csv file found. It means that if you know the separator is the same for all the csv type files, you just have to put the separator once in the vector.

unique_sep is a pattern that you know will never be in your input files

rec is a boolean allows to get files recursively if set to TRUE, defaults to TRUE If x is the return value, to see all the files name, position of the columns and possible sheet name associated with, do the following:

see_in_grep	<i>see_in_grep</i>
-------------	--------------------

Description

Allow to get the indices of the elements of a vector that contains certyain patterns. The type of the output may change in function of the input vectors, see examples

Usage

```
see_in_grep(from_v = c(), in_v = c())
```

Arguments

from_v	is the vector that may contains elements that contains the same patterns that those in in_v, see examples
in_v	is a vector that contains the patterns to find

Examples

```
print(see_in_grep(from_v = c("oui", "non", "peut"),
                  in_v = c("ou", "eu", "plm")))

      ou      eu      plm
      1      3      -1

print(see_in_grep(from_v = c("oui", "non", "peut", "oui"),
                  in_v = c("ou", "eu", "plm")))

$ou
[1] 1 4

$eu
[1] 3

$plm
[1] -1
```

see_in_l	<i>see_in_l</i>
----------	-----------------

Description

Allow to get the patterns that are present in the elements of a vector, see examples

Usage

```
see_in_l(from_v = c(), in_v = c())
```

Arguments

`from_v` is the vector that may contains elements that contains the same patterns that those in `in_v`, see examples

`in_v` is a vector that contains the patterns to find

Examples

```
print(see_in_l(from_v = c("oui", "non", "peut"),
  in_v = c("ou", "pe", "plm")))

   ou   pe  plm
TRUE TRUE FALSE
```

see_mode

see_mode

Description

Allow to get the mode of a vector, see examples.

Usage

```
see_mode(inpt_v = c())
```

Arguments

`inpt_v` is the input vector

Examples

```
print(see_mode(inpt_v = c(1, 1, 2, 2, 2, 3, 1, 2)))

[1] 2

print(see_mode(inpt_v = c(1, 1, 2, 2, 2, 3, 1)))

[1] 1
```

selected_char

selected_char

Description

Allow to generate a char based on a combinaison on characters from a vector and a number

Usage

```
selected_char(n, base_char = letters)
```

Arguments

`n` is how many sequence of numbers will be generated
`base_char` is the vector containing the elements from which the character is generated

Examples

```
print(selected_char(1222))

[1] "zta"
```

```
sequence_na_mean1    sequence_na_mean1
```

Description

In a dataframe generated by the function `historic_sequence1`, convert all NA to the mean of the values at the same variable for the individual at the id where the NA occurs, see examples (only accepts numeric variables)

Usage

```
sequence_na_mean1(inpt_datf, bf_)
```

Arguments

`inpt_datf` is the input dataframe

Examples

```
set.seed(123)
var1 <- round(runif(n = 14, min = 100, max = 122))
set.seed(123)
var2 <- round(runif(n = 14, min = 14, max = 20))

datf <- data.frame("ids" = c(20, 20, 20, 20, 19, 19, 19, 18, 18, 18, 18,
17, 17, 17),
"individual" = c("oui", "non", "peut1", "peut2",
"oui", "peut1", "peut2"),
"var1" = var1,
"var2" = var2)
datf <- historic_sequence1(inpt_datf = datf, bf_ = 2)
datf[3, 4] <- NA
datf[6, 4] <- NA
datf[1, 3] <- NA
print(datf)
```

	id_seq	individual	var1-1	var1-2	var2-1	var2-2
1	20	oui	NA	120	20	19
2	20	non	NA	112	NA	17
3	20	peut1	101	NA	14	17
4	20	peut2	112	121	17	20
5	19	oui	120	110	19	17

```

6      19      peut1      110      NA      17      18
7      19      peut2      121      113      20      17

print(sequence_na_mean1(inpt_datf = datf, bf_ = 2))

  id_seq individual var1-1 var1-2 var2-1 var2-2
1      20         oui    115  120.0     20    19
2      20         non    112  112.0     17    17
3      20      peut1    101  105.5     14    17
4      20      peut2    112  121.0     17    20
5      19         oui    120  110.0     19    17
6      19      peut1    110  105.5     17    18
7      19      peut2    121  113.0     20    17

```

```
sequence_na_mean2  sequence_na_mean2
```

Description

In a dataframe generated by the function `historic_sequence1`, convert all NA to the mean of the values at the same variable for the individual at the id where the NA occurs, see examples (only accepts numeric variables)

Usage

```
sequence_na_mean2(inpt_datf, bf_)
```

Arguments

`inpt_datf` is the input dataframe

`bf_` is how at how many n -1 we look for the value of the variables for the individual at time index n

Examples

```

set.seed(123)
var1 <- round(runif(n = 14, min = 100, max = 122))
set.seed(123)
var2 <- round(runif(n = 14, min = 14, max = 20))

datf <- data.frame("ids" = c(20, 20, 20, 20, 19, 19, 19, 18, 18, 18, 18,
17, 17, 17, 17),
"individual" = c("oui", "non", "peut1", "peut2",
"oui", "peut1", "peut2"),
"var1" = var1,
"var2" = var2)
datf <- historic_sequence2(inpt_datf = datf, bf_ = 2)
datf[3, 4] <- NA
datf[6, 4] <- NA
datf[1, 3] <- NA
print(datf)

```

```

  id_seq individual var1-0 var1-1 var1-2 var2-0 var2-1 var2-2

```

1	20	oui	NA	121	120	16	NA	19
2	20	non	117	NA	112	19	NA	17
3	20	peut1	109	NA	110	16	14	17
4	20	peut2	119	112	121	19	17	20
5	19	oui	121	120	110	20	19	17
6	19	peut1	101	NA	115	14	17	18
7	19	peut2	112	121	113	17	20	17

```
print(sequence_na_mean2(inpt_datf = datf, bf_ = 2))
```

	id_seq	individual	var1-0	var1-1	var1-2	var2-0	var2-1	var2-2
1	20	oui	117	121.0000	120	16	18	19
2	20	non	117	114.5000	112	19	18	17
3	20	peut1	109	108.3333	110	16	14	17
4	20	peut2	119	112.0000	121	19	17	20
5	19	oui	121	120.0000	110	20	19	17
6	19	peut1	101	108.3333	115	14	17	18
7	19	peut2	112	121.0000	113	17	20	17

sequence_na_med1	<i>sequence_na_med1</i>
------------------	-------------------------

Description

In a dataframe generated by the function `historic_sequence1`, convert all NA to the median of the values at the same variable for the individual at the id where the NA occurs, see examples (only accepts numeric variables)

Usage

```
sequence_na_med1(inpt_datf, bf_)
```

Arguments

<code>inpt_datf</code>	is the input dataframe
<code>bf_</code>	is how at how many n - 1 we look for the value of the variables for the individual at time index n

Examples

```
set.seed(123)
var1 <- round(runif(n = 14, min = 100, max = 122))
set.seed(123)
var2 <- round(runif(n = 14, min = 14, max = 20))

datf <- data.frame("ids" = c(20, 20, 20, 20, 19, 19, 19, 18, 18, 18, 18,
17, 17, 17),
"individual" = c("oui", "non", "peut1", "peut2",
"oui", "peut1", "peut2"),
"var1" = var1,
"var2" = var2)
datf <- historic_sequence1(inpt_datf = datf, bf_ = 2)
datf[3, 4] <- NA
```

```

datf[6, 4] <- NA
datf[1, 3] <- NA
print(datf)

  id_seq individual var1-1 var1-2 var2-1 var2-2
1     20         oui     NA    120     20     19
2     20         non     NA    112     NA     17
3     20      peut1    101     NA     14     17
4     20      peut2    112    121     17     20
5     19         oui    120    110     19     17
6     19      peut1    110     NA     17     18
7     19      peut2    121    113     20     17

print(sequence_na_med1(inpt_datf = datf, bf_ = 2))

  id_seq individual var1-1 var1-2 var2-1 var2-2
1     20         oui    115  120.0     20     19
2     20         non    112  112.0     17     17
3     20      peut1    101  105.5     14     17
4     20      peut2    112  121.0     17     20
5     19         oui    120  110.0     19     17
6     19      peut1    110  105.5     17     18
7     19      peut2    121  113.0     20     17

```

sequence_na_med2	<i>sequence_na_med2</i>
------------------	-------------------------

Description

In a dataframe generated by the function `historic_sequence2`, convert all NA to the median of the values at the same variable for the individual at the id where the NA occurs, see examples (only accepts numeric variables)

Usage

```
sequence_na_med2(inpt_datf, bf_)
```

Arguments

<code>inpt_datf</code>	is the input dataframe
<code>bf_</code>	is how at how many n -1 we look for the value of the variables for the individual at time index n

Examples

```

set.seed(123)
var1 <- round(runif(n = 14, min = 100, max = 122))
set.seed(123)
var2 <- round(runif(n = 14, min = 14, max = 20))
datf <- data.frame("ids" = c(20, 20, 20, 20, 19, 19, 19, 18, 18, 18, 18,
17, 17, 17),
"individual" = c("oui", "non", "peut1", "peut2",
"oui", "peut1", "peut2"),

```

```
"var1" = var1,
"var2" = var2)
datf <- historic_sequence2(inpt_datf = datf, bf_ = 2)
datf[3, 4] <- NA
datf[6, 4] <- NA
datf[1, 3] <- NA
print(datf)
```

	id_seq	individual	var1-0	var1-1	var1-2	var2-0	var2-1	var2-2
1	20	oui	NA	121	120	16	20	19
2	20	non	117	NA	112	19	NA	17
3	20	peut1	109	NA	110	16	14	17
4	20	peut2	119	112	121	19	17	20
5	19	oui	121	120	110	20	19	17
6	19	peut1	101	NA	115	14	17	18
7	19	peut2	112	121	113	17	20	17

```
print(sequence_na_med2(inpt_datf = datf, bf_ = 2))
```

	id_seq	individual	var1-0	var1-1	var1-2	var2-0	var2-1	var2-2
1	20	oui	120	121.0	120	16	20	19
2	20	non	117	114.5	112	19	18	17
3	20	peut1	109	109.0	110	16	14	17
4	20	peut2	119	112.0	121	19	17	20
5	19	oui	121	120.0	110	20	19	17
6	19	peut1	101	109.0	115	14	17	18
7	19	peut2	112	121.0	113	17	20	17

sort_date

sort_date

Description

Allow to sort any vector containing a date, from any kind of format (my, hdmy, ymd ...), see examples.

Usage

```
sort_date(inpt_v, frmt, sep_ = "-", ascending = FALSE, give = "value")
```

Arguments

inpt_v	is the input vector containing all the dates
frmt	is the format of the dates, (any combinaison of letters "s" for second, "n", for minute, "h" for hour, "d" for day, "m" for month and "y" for year)
sep_	is the separator used for the dates
ascending	is the used to sort the dates
give	takes only two values "index" or "value", if give == "index", the function will output the index of sorted dates from inpt_v, if give == "value", the function will output the value, it means directly the sorted dates in inpt_v, see examples

Examples

```
print(sort_date(inpt_v = c("01-11-2025", "08-08-1922", "12-04-1966")
, frmt = "dmy", sep_ = "-", ascending = TRUE, give = "value"))

[1] "08-08-1922" "12-04-1966" "01-11-2025"

print(sort_date(inpt_v = c("01-11-2025", "08-08-1922", "12-04-1966")
, frmt = "dmy", sep_ = "-", ascending = FALSE, give = "value"))

[1] "01-11-2025" "12-04-1966" "08-08-1922"

print(sort_date(inpt_v = c("01-11-2025", "08-08-1922", "12-04-1966")
, frmt = "dmy", sep_ = "-", ascending = TRUE, give = "index"))

[1] 2 3 1

print(sort_date(inpt_v = c("22-01-11-2025", "11-12-04-1966", "12-12-04-1966")
, frmt = "hdmy", sep_ = "-", ascending = FALSE, give = "value"))

[1] "22-01-11-2025" "12-12-04-1966" "11-12-04-1966"

print(sort_date(inpt_v = c("03-22-01-11-2025", "56-11-12-04-1966", "23-12-12-04-1966")
, frmt = "nhdmy", sep_ = "-", ascending = FALSE, give = "value"))

[1] "03-22-01-11-2025" "23-12-12-04-1966" "56-11-12-04-1966"
```

sort_normal_qual	<i>sort_normal_qual</i>
------------------	-------------------------

Description

Sort qualitative modalities that have their frequency normally distributed from an unordered dataset, see examples. This function uses an another algorithym than choose_normal_qual2 which may be faster.

Usage

```
sort_normal_qual(inpt_datf)
```

Arguments

`inpt_datf` is the input dataframe, containing the values in the first column and their frequency in the second

Examples

```
sample_val <- round(rnorm(n = 2000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)
sample_qual <- infinite_char_seq(n = length(sample_freq))
datf_test <- data.frame(sample_qual, sample_freq)
datf_test[, 2] <- datf_test[, 2] / sum(datf_test[, 2]) # optional
```

```
print(datf_test)
```

```

    sample_qual sample_freq
1             a 0.208695652
2             b 0.234782609
3             c 0.321739130
4             d 0.339130435
5             e 0.330434783
6             f 0.069565217
7             g 0.234782609
8             h 0.400000000
9             i 0.347826087
10            j 0.043478261
11            k 0.278260870
12            l 0.286956522
13            m 0.243478261
14            n 0.147826087
15            o 0.234782609
16            p 0.252173913
17            q 0.417391304
18            r 0.095652174
19            s 0.313043478
20            t 0.008695652
21            u 0.130434783
22            v 0.391304348
23            w 0.113043478
24            x 0.295652174
25            y 0.243478261
26            z 0.382608696
27           aa 0.008695652
28           ab 0.347826087
29           ac 0.330434783
30           ad 0.321739130
31           ae 0.347826087
32           af 0.321739130
33           ag 0.173913043
34           ah 0.278260870
35           ai 0.278260870
36           aj 0.347826087
37           ak 0.026086957
38           al 0.295652174
39           am 0.226086957
40           an 0.295652174
41           ao 0.234782609
42           ap 0.113043478
43           aq 0.234782609
44           ar 0.173913043
45           as 0.017391304
46           at 0.252173913
47           au 0.078260870
48           av 0.086956522
49           aw 0.278260870
50           ax 0.086956522
51           ay 0.200000000
52           az 0.295652174
53           ba 0.052173913
54           bb 0.165217391

```

55	bc	0.408695652
56	bd	0.269565217
57	be	0.104347826
58	bf	0.391304348
59	bg	0.104347826
60	bh	0.043478261
61	bi	0.200000000
62	bj	0.095652174
63	bk	0.191304348
64	bl	0.008695652
65	bm	0.165217391
66	bn	0.226086957
67	bo	0.086956522
68	bp	0.017391304
69	bq	0.121739130
70	br	0.234782609
71	bs	0.121739130
72	bt	0.078260870
73	bu	0.173913043
74	bv	0.104347826
75	bw	0.208695652
76	bx	0.017391304
77	by	0.243478261
78	bz	0.034782609
79	ca	0.017391304
80	cb	0.008695652
81	cc	0.173913043
82	cd	0.147826087
83	ce	0.060869565
84	cf	0.017391304
85	cg	0.060869565
86	ch	0.008695652
87	ci	0.208695652
88	cj	0.043478261
89	ck	0.052173913
90	cl	0.017391304
91	cm	0.017391304
92	cn	0.095652174
93	co	0.113043478
94	cp	0.017391304
95	cq	0.017391304
96	cr	0.026086957
97	cs	0.034782609
98	ct	0.017391304
99	cu	0.026086957
100	cv	0.026086957
101	cw	0.026086957
102	cx	0.017391304
103	cy	0.043478261
104	cz	0.008695652
105	da	0.034782609
106	db	0.017391304
107	dc	0.060869565
108	dd	0.008695652
109	de	0.008695652
110	df	0.017391304
111	dg	0.008695652

```

112          dh 0.008695652
113          di 0.017391304
114          dj 0.008695652
115          dk 0.008695652

```

```
print(sort_normal_qual(inpt_datf = datf_test))
```

```

0.00869565217391304 0.00869565217391304 0.00869565217391304 0.00869565217391304
      "aa"          "cb"          "cz"          "de"
0.00869565217391304 0.00869565217391304 0.0173913043478261 0.0173913043478261
      "dh"          "dk"          "bp"          "ca"
0.0173913043478261 0.0173913043478261 0.0173913043478261 0.0173913043478261
      "cl"          "cp"          "ct"          "db"
0.0173913043478261 0.0260869565217391 0.0260869565217391 0.0347826086956522
      "di"          "cr"          "cv"          "bz"
0.0347826086956522 0.0434782608695652 0.0434782608695652 0.0521739130434783
      "da"          "bh"          "cy"          "ck"
0.0608695652173913 0.0695652173913043 0.0782608695652174 0.0869565217391304
      "cg"          "f"          "bt"          "ax"
0.0956521739130435 0.0956521739130435 0.104347826086957 0.11304347826087
      "r"          "cn"          "bg"          "w"
0.11304347826087 0.121739130434783 0.147826086956522 0.165217391304348
      "co"          "bs"          "n"          "bb"
0.173913043478261 0.173913043478261 0.191304347826087 0.2
      "ag"          "bu"          "bk"          "bi"
0.208695652173913 0.226086956521739 0.234782608695652 0.234782608695652
      "bw"          "am"          "b"          "o"
0.234782608695652 0.243478260869565 0.243478260869565 0.252173913043478
      "aq"          "m"          "by"          "at"
0.278260869565217 0.278260869565217 0.28695652173913 0.295652173913043
      "k"          "ai"          "l"          "al"
0.295652173913043 0.321739130434783 0.321739130434783 0.330434782608696
      "az"          "c"          "af"          "ac"
0.347826086956522 0.347826086956522 0.382608695652174 0.391304347826087
      "i"          "ae"          "z"          "bf"
0.408695652173913 0.417391304347826 0.4 0.391304347826087
      "bc"          "q"          "h"          "v"
0.347826086956522 0.347826086956522 0.339130434782609 0.330434782608696
      "aj"          "ab"          "d"          "e"
0.321739130434783 0.31304347826087 0.295652173913043 0.295652173913043
      "ad"          "s"          "an"          "x"
0.278260869565217 0.278260869565217 0.269565217391304 0.252173913043478
      "aw"          "ah"          "bd"          "p"
0.243478260869565 0.234782608695652 0.234782608695652 0.234782608695652
      "y"          "br"          "ao"          "g"
0.226086956521739 0.208695652173913 0.208695652173913 0.2
      "bn"          "ci"          "a"          "ay"
0.173913043478261 0.173913043478261 0.165217391304348 0.147826086956522
      "cc"          "ar"          "bm"          "cd"
0.130434782608696 0.121739130434783 0.11304347826087 0.104347826086957
      "u"          "bq"          "ap"          "bv"
0.104347826086957 0.0956521739130435 0.0869565217391304 0.0869565217391304
      "be"          "bj"          "bo"          "av"
0.0782608695652174 0.0608695652173913 0.0608695652173913 0.0521739130434783
      "au"          "dc"          "ce"          "ba"
0.0434782608695652 0.0434782608695652 0.0347826086956522 0.0260869565217391
      "cj"          "j"          "cs"          "cw"

```

```

0.0260869565217391 0.0260869565217391 0.0173913043478261 0.0173913043478261
      "cu"          "ak"          "df"          "cx"
0.0173913043478261 0.0173913043478261 0.0173913043478261 0.0173913043478261
      "cq"          "cm"          "cf"          "bx"
0.0173913043478261 0.00869565217391304 0.00869565217391304 0.00869565217391304
      "as"          "dj"          "dg"          "dd"
0.00869565217391304 0.00869565217391304 0.00869565217391304
      "ch"          "bl"          "t"

```

```
sort_normal_qual2  sort_normal_qual2
```

Description

Sort qualitative modalities that have their frequency normally distributed from an unordered dataset, see examples. This function uses an another algorithm than choose_normal_qual which may be faster.

Usage

```
sort_normal_qual2(inpt_datf)
```

Arguments

`inpt_datf` is the input dataframe, containing the values in the first column and their frequency in the second

Examples

```

sample_val <- round(rnorm(n = 2000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)
sample_qual <- infinite_char_seq(n = length(sample_freq))
datf_test <- data.frame(sample_qual, sample_freq)
datf_test[, 2] <- datf_test[, 2] / sum(datf_test[, 2])

print(datf_test)

```

```

      sample_qual sample_freq
1              a 0.208695652
2              b 0.234782609
3              c 0.321739130
4              d 0.339130435
5              e 0.330434783
6              f 0.069565217
7              g 0.234782609
8              h 0.400000000
9              i 0.347826087
10             j 0.043478261
11             k 0.278260870
12             l 0.286956522
13             m 0.243478261
14             n 0.147826087
15             o 0.234782609

```

16	p	0.252173913
17	q	0.417391304
18	r	0.095652174
19	s	0.313043478
20	t	0.008695652
21	u	0.130434783
22	v	0.391304348
23	w	0.113043478
24	x	0.295652174
25	y	0.243478261
26	z	0.382608696
27	aa	0.008695652
28	ab	0.347826087
29	ac	0.330434783
30	ad	0.321739130
31	ae	0.347826087
32	af	0.321739130
33	ag	0.173913043
34	ah	0.278260870
35	ai	0.278260870
36	aj	0.347826087
37	ak	0.026086957
38	al	0.295652174
39	am	0.226086957
40	an	0.295652174
41	ao	0.234782609
42	ap	0.113043478
43	aq	0.234782609
44	ar	0.173913043
45	as	0.017391304
46	at	0.252173913
47	au	0.078260870
48	av	0.086956522
49	aw	0.278260870
50	ax	0.086956522
51	ay	0.200000000
52	az	0.295652174
53	ba	0.052173913
54	bb	0.165217391
55	bc	0.408695652
56	bd	0.269565217
57	be	0.104347826
58	bf	0.391304348
59	bg	0.104347826
60	bh	0.043478261
61	bi	0.200000000
62	bj	0.095652174
63	bk	0.191304348
64	bl	0.008695652
65	bm	0.165217391
66	bn	0.226086957
67	bo	0.086956522
68	bp	0.017391304
69	bq	0.121739130
70	br	0.234782609
71	bs	0.121739130
72	bt	0.078260870

```

73      bu 0.173913043
74      bv 0.104347826
75      bw 0.208695652
76      bx 0.017391304
77      by 0.243478261
78      bz 0.034782609
79      ca 0.017391304
80      cb 0.008695652
81      cc 0.173913043
82      cd 0.147826087
83      ce 0.060869565
84      cf 0.017391304
85      cg 0.060869565
86      ch 0.008695652
87      ci 0.208695652
88      cj 0.043478261
89      ck 0.052173913
90      cl 0.017391304
91      cm 0.017391304
92      cn 0.095652174
93      co 0.113043478
94      cp 0.017391304
95      cq 0.017391304
96      cr 0.026086957
97      cs 0.034782609
98      ct 0.017391304
99      cu 0.026086957
100     cv 0.026086957
101     cw 0.026086957
102     cx 0.017391304
103     cy 0.043478261
104     cz 0.008695652
105     da 0.034782609
106     db 0.017391304
107     dc 0.060869565
108     dd 0.008695652
109     de 0.008695652
110     df 0.017391304
111     dg 0.008695652
112     dh 0.008695652
113     di 0.017391304
114     dj 0.008695652
115     dk 0.008695652

```

```
print(sort_normal_qual2(inpt_datf = datf_test))
```

```

0.00869565217391304 0.00869565217391304 0.00869565217391304 0.00869565217391304
      "aa"          "cb"          "cz"          "de"
0.00869565217391304 0.00869565217391304 0.0173913043478261 0.0173913043478261
      "dh"          "dk"          "bp"          "ca"
0.0173913043478261 0.0173913043478261 0.0173913043478261 0.0173913043478261
      "cl"          "cp"          "ct"          "db"
0.0173913043478261 0.0260869565217391 0.0260869565217391 0.0347826086956522
      "di"          "cr"          "cv"          "bz"
0.0347826086956522 0.0434782608695652 0.0434782608695652 0.0521739130434783
      "da"          "bh"          "cy"          "ck"
0.0608695652173913 0.0695652173913043 0.0782608695652174 0.0869565217391304

```

"cg"	"f"	"bt"	"ax"
0.0956521739130435	0.0956521739130435	0.104347826086957	0.11304347826087
"r"	"cn"	"bg"	"w"
0.11304347826087	0.121739130434783	0.147826086956522	0.165217391304348
"co"	"bs"	"n"	"bb"
0.173913043478261	0.173913043478261	0.191304347826087	0.2
"ag"	"bu"	"bk"	"bi"
0.208695652173913	0.226086956521739	0.234782608695652	0.234782608695652
"bw"	"am"	"b"	"o"
0.234782608695652	0.243478260869565	0.243478260869565	0.252173913043478
"aq"	"m"	"by"	"at"
0.278260869565217	0.278260869565217	0.28695652173913	0.295652173913043
"k"	"ai"	"l"	"al"
0.295652173913043	0.321739130434783	0.321739130434783	0.330434782608696
"az"	"c"	"af"	"ac"
0.347826086956522	0.347826086956522	0.382608695652174	0.391304347826087
"i"	"ae"	"z"	"bf"
0.408695652173913	0.417391304347826	0.4	0.391304347826087
"bc"	"q"	"h"	"v"
0.347826086956522	0.347826086956522	0.339130434782609	0.330434782608696
"aj"	"ab"	"d"	"e"
0.321739130434783	0.31304347826087	0.295652173913043	0.295652173913043
"ad"	"s"	"an"	"x"
0.278260869565217	0.278260869565217	0.269565217391304	0.252173913043478
"aw"	"ah"	"bd"	"p"
0.243478260869565	0.234782608695652	0.234782608695652	0.234782608695652
"y"	"br"	"ao"	"g"
0.226086956521739	0.208695652173913	0.208695652173913	0.2
"bn"	"ci"	"a"	"ay"
0.173913043478261	0.173913043478261	0.165217391304348	0.147826086956522
"cc"	"ar"	"bm"	"cd"
0.130434782608696	0.121739130434783	0.11304347826087	0.104347826086957
"u"	"bq"	"ap"	"bv"
0.104347826086957	0.0956521739130435	0.0869565217391304	0.0869565217391304
"be"	"bj"	"bo"	"av"
0.0782608695652174	0.0608695652173913	0.0608695652173913	0.0521739130434783
"au"	"dc"	"ce"	"ba"
0.0434782608695652	0.0434782608695652	0.0347826086956522	0.0260869565217391
"cj"	"j"	"cs"	"cw"
0.0260869565217391	0.0260869565217391	0.0173913043478261	0.0173913043478261
"cu"	"ak"	"df"	"cx"
0.0173913043478261	0.0173913043478261	0.0173913043478261	0.0173913043478261
"cq"	"cm"	"cf"	"bx"
0.0173913043478261	0.00869565217391304	0.00869565217391304	0.00869565217391304
"as"	"dj"	"dg"	"dd"
0.00869565217391304	0.00869565217391304	0.00869565217391304	
"ch"	"bl"	"t"	

split_by_step

split_by_step

Description

Allow to split a string or a vector of strings by a step, see examples.

Usage

```
split_by_step(inpt_v, by)
```

Arguments

`inpt_v` is the input character or vector of characters
`by` is the step

Examples

```
print(split_by_step(inpt_v = c("o", "u", "i", "n", "o", "o", "u", "i", "o", "Z"), by = 2)

[1] "ou" "in" "oo" "ui" "oZ"

print(split_by_step(inpt_v = c("o", "u", "i", "n", "o", "o", "u", "i", "o", "Z"), by = 3)

[1] "oui" "noo" "uio" "Z"

print(split_by_step(inpt_v = c("o", "u", "i", "n", "o", "o", "u", "i", "o", "Z"), by = 4)

[1] "ouin" "ooui" "oZ"

print(split_by_step(inpt_v = 'ouinoouioz', by = 4))

[1] "ouin" "ooui" "oZ"
```

str_remove_untl	<i>str_remove_untl</i>
-----------------	------------------------

Description

Allow to remove pattern within elements from a vector precisely according to their occurrence.

Usage

```
str_remove_untl(
  inpt_v,
  ptrn_rm_v = c(),
  until = list(c(1)),
  nvr_following_ptrn = "NA"
)
```

Arguments

`inpt_v` is the input vector
`ptrn_rm_v` is a vector containing the patterns to remove
`until` is a list containing the occurrence(s) of each pattern to remove in the elements.
`nvr_following_ptrn` is a sequel of characters that you are sure is not present in any of the elements in `inpt_v`

Examples

```
vec <- c("45/56-/98mm", "45/56-/98mm", "45/56-/98-mm//")

print(str_remove_until(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1))))

#[1] "4556/98mm"      "4556/98mm"      "4556/98mm//"

print(str_remove_until(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1:2))))

#[1] "455698mm"       "455698mm"       "455698mm//"

print(str_remove_until(inpt_v=vec[1], ptrn_rm_v=c("-", "/"), until=c("max")))

#[1] "455698mm" "455698mm" "455698mm"
```

sub_mult

sub_mult

Description

Performs a sub operation with n patterns and replacements.

Usage

```
sub_mult(inpt_v, pattern_v = c(), replacement_v = c())
```

Arguments

`inpt_v` is a vector containing all the elements that contains expressions to be substituted

`pattern_v` is a vector containing all the patterns to be substituted in any elements of `inpt_v`

`replacement_v` is a vector containing the expression that are going to substitute those provided by `pattern_v`

Examples

```
print(sub_mult(inpt_v = c("X and Y programming languages are great", "More X, more X!"),
  pattern_v = c("X", "Y", "Z"),
  replacement_v = c("C", "R", "GO"))

[1] "C and R programming languages are great"
[2] "More C, more X!"
```

successive_diff	<i>successive_diff</i>
-----------------	------------------------

Description

Allow to see the difference between the successive elements of a numeric vector

Usage

```
successive_diff(inp_v)
```

Arguments

`inp_v` is the input numeric vector

Examples

```
print(successive_diff(c(1:10)))
[1] 1 1 1 1 1

print(successive_diff(c(1:11, 13, 19)))
[1] 1 1 1 1 1 2 6
```

sum_group1	<i>sum_group1</i>
------------	-------------------

Description

Allow to aggregate variables according to groups, do not visually group the individual unlike `sum_group2`, see examples

Usage

```
sum_group1(inp_datf, col_grp = c(), col_to_add = c())
```

Arguments

`inp_datf` is the input dataframe
`col_grp` is a vector containing the column names or the column numbers of the groups
`col_to_add` is a vector containing the column names or the column numbers of the variables to aggregate

Examples

```

set.seed(123)
datf <- data.frame("country" = c("France", "Germany", "France", "Italy", "Italy", "France"),
  "year" = c(2012, 2012, 2013, 2011, 2012, 2011),
  "comp_arm" = c("higher", "lower", "higher", "higher", "lower", "lower"),
  "pop" = runif(n = 6, min = 65000000, max = 69000000),
  "random_var" = round(x = runif(n = 6, min = 16, max = 78), digits = 0))

datf

  country year comp_arm      pop random_var
1  France 2012   higher 66150310         49
2 Germany 2012    lower 68153221         71
3  France 2013   higher 66635908         50
4   Italy 2011   higher 68532070         44
5   Italy 2012    lower 68761869         75
6  France 2011    lower 65182226         44

print(sum_group1(inpt_datf = datf, col_grp = c("country", "year"), col_to_add = c("random_var", "pop")))

  country year comp_arm      pop random_var
1  France 2012   higher 66150310         49
2 Germany 2012    lower 68153221         71
3  France 2013   higher 66635908         50
4   Italy 2011   higher 68532070         44
5   Italy 2012    lower 68761869         75
6  France 2011    lower 65182226         44

print(sum_group1(inpt_datf = datf, col_grp = c("year"), col_to_add = c("random_var", "pop")))

  country year comp_arm      pop random_var
1  France 2012   higher 203065400        195
2 Germany 2012    lower 203065400        195
3  France 2013   higher  66635908         50
4   Italy 2011   higher 133714296         88
5   Italy 2012    lower 203065400        195
6  France 2011    lower 133714296         88

print(sum_group1(inpt_datf = datf, col_grp = c("country"), col_to_add = c("random_var", "pop")))

  country year comp_arm      pop random_var
1  France 2012   higher 197968444        143
2 Germany 2012    lower  68153221         71
3  France 2013   higher 197968444        143
4   Italy 2011   higher 137293939        119
5   Italy 2012    lower 137293939        119
6  France 2011    lower 197968444        143

set.seed(123)
pop_v <- runif(n = 6, min = 65000000, max = 69000000)
pop_v[c(1, 3)] <- NA
set.seed(123)
datf <- data.frame("country" = c("France", "Germany", "France", "Italy", "Italy", "France"),
  "year" = c(2012, 2012, 2013, 2011, 2012, 2011),
  "comp_arm" = c("higher", "lower", "higher", "higher", "lower", "lower"),
  "pop" = pop_v,
  "random_var" = round(x = runif(n = 6, min = 16, max = 78), digits = 0))

```

```
datf
```

	country	year	comp_arm	pop	random_var
1	France	2012	higher	NA	34
2	Germany	2012	lower	68153221	65
3	France	2013	higher	NA	41
4	Italy	2011	higher	68532070	71
5	Italy	2012	lower	68761869	74
6	France	2011	lower	65182226	19

```
print(sum_group1(inpt_datf = datf, col_grp = c("year"), col_to_add = c("random_var", "pop"))
```

	country	year	comp_arm	pop	random_var
1	France	2012	higher	136915090	173
2	Germany	2012	lower	136915090	173
3	France	2013	higher	NA	41
4	Italy	2011	higher	133714296	90
5	Italy	2012	lower	136915090	173
6	France	2011	lower	133714296	90

sum_group2

sum_group2

Description

Allow to aggregate variables according to groups, see examples

Usage

```
sum_group2(inpt_datf, col_grp = c(), col_to_add = c())
```

Arguments

`inpt_datf` is the input dataframe

`col_grp` is a vector containing the column names or the column numbers of the groups

`col_to_add` is a vector containing the column names or the column numbers of the variables to aggregate

Examples

```
set.seed(123)
datf <- data.frame("country" = c("France", "Germany", "France", "Italy", "Italy", "France"),
  "year" = c(2012, 2012, 2013, 2011, 2012, 2011),
  "comp_arm" = c("higher", "lower", "higher", "higher", "lower", "lower"),
  "pop" = runif(n = 6, min = 65000000, max = 69000000),
  "random_var" = round(x = runif(n = 6, min = 16, max = 78), digits = 0))
datf
```

	country	year	comp_arm	pop	random_var
1	France	2012	higher	66150310	49
2	Germany	2012	lower	68153221	71
3	France	2013	higher	66635908	50

```

4   Italy 2011   higher 68532070      44
5   Italy 2012   lower 68761869      75
6   France 2011   lower 65182226      44

```

```
print(sum_group2(inpt_datf = datf, col_grp = c("country"), col_to_add = c("random_var", "pop"))
```

```

  country year comp_arm      pop random_var
1  France 2012   higher 197968444      143
3  France 2013   higher 197968444      143
6  France 2011   lower 197968444      143
2 Germany 2012   lower  68153221       71
4   Italy 2011   higher 137293939     119
5   Italy 2012   lower 137293939     119

```

```
print(sum_group2(inpt_datf = datf, col_grp = c("year"), col_to_add = c("random_var", "pop"))
```

```

  country year comp_arm      pop random_var
1  France 2012   higher 203065400     195
2 Germany 2012   lower 203065400     195
5   Italy 2012   lower 203065400     195
3  France 2013   higher  66635908       50
4   Italy 2011   higher 133714296       88
6  France 2011   lower 133714296       88

```

```
print(sum_group2(inpt_datf = datf, col_grp = c("country", "year"), col_to_add = c("random_var", "pop"))
```

```

  country year comp_arm      pop random_var
1  France 2012   higher 66150310       49
2 Germany 2012   lower 68153221       71
3  France 2013   higher 66635908       50
4   Italy 2011   higher 68532070       44
5   Italy 2012   lower 68761869       75
6  France 2011   lower 65182226       44

```

```
set.seed(123)
```

```
pop_v <- runif(n = 6, min = 65000000, max = 690000000)
```

```
pop_v[c(1, 3)] <- NA
```

```
set.seed(123)
```

```

datf <- data.frame("country" = c("France", "Germany", "France", "Italy", "Italy", "France"),
                  "year" = c(2012, 2012, 2013, 2011, 2012, 2011),
                  "comp_arm" = c("higher", "lower", "higher", "higher", "lower", "lower"),
                  "pop" = pop_v,
                  "random_var" = round(x = runif(n = 6, min = 16, max = 78), digits = 0))

```

```
datf
```

```

  country year comp_arm      pop random_var
1  France 2012   higher      NA       34
2 Germany 2012   lower 68153221       65
3  France 2013   higher      NA       41
4   Italy 2011   higher 68532070       71
5   Italy 2012   lower 68761869       74
6  France 2011   lower 65182226       19

```

```
print(sum_group2(inpt_datf = datf, col_grp = c("year"), col_to_add = c("random_var", "pop"))
```

```

  country year comp_arm      pop random_var
1  France 2012   higher 136915090     173
2 Germany 2012   lower 136915090     173

```

5	Italy	2012	lower	136915090	173
3	France	2013	higher	NA	41
4	Italy	2011	higher	133714296	90
6	France	2011	lower	133714296	90

swipr

swipr

Description

Returns an ordered dataframes according to the elements order given. The input datafram has two columns, one with the ids which can be bonded to multiple elements in the other column.

Usage

```
swipr(inpt_datf, how_to = c(), id_w = 2, id_ids = 1)
```

Arguments

<code>inpt_datf</code>	is the input dataframe
<code>how_to</code>	is a vector containing the elements in the order wanted
<code>id_w</code>	is the column number or the column name of the elements
<code>id_ids</code>	is the column number or the column name of the ids

Examples

```
datf <- data.frame("col1"=c("Af", "Al", "Al", "Al", "Arg", "Arg", "Arg", "Arm", "Arm", "A",
                             "col2"=c("B", "B", "G", "S", "B", "S", "G", "B", "G", "B"))

print(swipr(inpt_datf=datf, how_to=c("G", "S", "B")))
```

	col1	col2
1	Af	B
2	Al	G
3	Al	S
4	Al	B
5	Arg	G
6	Arg	S
7	Arg	B
8	Arm	G
9	Arm	B
10	Al	B

test_order	<i>test_order</i>
------------	-------------------

Description

Allow to get if two vectors have their commun elements in the same order, see examples

Usage

```
test_order(inpt_v_from, inpt_v_test)
```

Arguments

is	the vector we want to test if its commun element with inpt_v_from are in the same order
----	---

Examples

```
print(test_order(inpt_v_from = c(1:8), inpt_v_test = c(1, 4)))

[1] TRUE

print(test_order(inpt_v_from = c(1:8), inpt_v_test = c(1, 4, 2)))

[1] FALSE
```

time_serie_equalizer	<i>time_serie_equalizer</i>
----------------------	-----------------------------

Description

Allow ewualize the occurence of each elements in all the timestamps, see examples

Usage

```
time_serie_equalizer(
  inpt_datf,
  time_col,
  null_value = 0,
  individual_col,
  var_col = c()
)
```


Arguments

`inpt_datf` is the input dataframe
`time_col` is the column number or name of the time values
`null_value` is the default value of the variable of the elements that will be added
`individual_col` is the column name or number of the individuals
`var_col` is a vector containing the column names or numbers if the variables that will equal the `null_value` for the individual at the new time values

Examples

```
print(datf)
```

	individual	country	year	energy_source	twh_cons
1	A	France	1995	biofuel_electricity	1.82
2	A	France	1996	coal_electricity	24.18
3	A	France	1997	gas_electricity	3.84
4	A	France	1998	hydro_electricity	71.33
5	A	France	1999	nuclear_electricity	377.23
6	A	France	2000	oil_electricity	10.50
7	A	France	2001	other_renewable_exc_biofuel_electricity	0.51
10	B	France	1995	biofuel_electricity	9.50
11	B	France	1996	coal_electricity	2.16
12	B	France	1997	gas_electricity	31.43
13	B	France	1998	hydro_electricity	53.19
14	B	France	1999	nuclear_electricity	335.65
15	B	France	2000	oil_electricity	9.71
16	B	France	2001	other_renewable_exc_biofuel_electricity	0.60
17	B	France	2002	solar_electricity	23.26
18	B	France	2003	wind_electricity	48.61

```
print(time_serie_equalizer(inpt_datf = datf,
                           time_col = "year",
                           null_value = 0,
                           individual_col = 1,
                           var_col = "twh_cons"))
```

	individual	country	year	energy_source	twh_cons
1	A	France	1995	biofuel_electricity	1.82
2	A	France	1996	coal_electricity	24.18
3	A	France	1997	gas_electricity	3.84
4	A	France	1998	hydro_electricity	71.33
5	A	France	1999	nuclear_electricity	377.23
6	A	France	2000	oil_electricity	10.50
7	A	France	2001	other_renewable_exc_biofuel_electricity	0.51
8	B	France	1995	biofuel_electricity	9.50
9	B	France	1996	coal_electricity	2.16
10	B	France	1997	gas_electricity	31.43
11	B	France	1998	hydro_electricity	53.19
12	B	France	1999	nuclear_electricity	335.65
13	B	France	2000	oil_electricity	9.71
14	B	France	2001	other_renewable_exc_biofuel_electricity	0.60
15	B	France	2002	solar_electricity	23.26
16	B	France	2003	wind_electricity	48.61
17	A	France	2002	biofuel_electricity	0.00

18	A	France 2003	biofuel_electricity	0.00
----	---	-------------	---------------------	------

to_unique	<i>to_unique</i>
-----------	------------------

Description

Allow to transform a vector containing elements that have more than 1 occurrence to a vector with only unique elements.

Usage

```
to_unique(inpt_v, distinct_type = "suffix", distinct_val = "number", sep = "-")
```

Arguments

`inpt_v` is the input vectors

`distinct_type` takes two values: suffix or prefix

`distinct_val` takes two values: number (unique sequence of number to differentiate each value) or letter (unique sequence of letters to differentiate each value)

Examples

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "suffix",
  distinct_val = "number",
  sep = "-"))
```

```
[1] "a-1" "a-2" "e"   "a-3" "i-1" "i-2"
```

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "suffix",
  distinct_val = "letter",
  sep = "-"))
```

```
[1] "a-a" "a-b" "e"   "a-c" "i-a" "i-b"
```

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "prefix",
  distinct_val = "number",
  sep = "/"))
```

```
[1] "1/a" "2/a" "e"   "3/a" "1/i" "2/i"
```

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "prefix",
  distinct_val = "letter",
  sep = "_"))
```

```
[1] "a_a" "b_a" "e"   "c_a" "a_i" "b_i"
```

union_all

union_all

Description

Allow to perform a union function to n vectors.

Usage

```
union_all(...)
```

Arguments

... are all the input vectors

Examples

```
print(union_all(c(1, 2), c(3, 4), c(1:8)))
[1] 1 2 3 4 5 6 7 8

print(union_all(c(1, 2), c(3, 4), c(7:8)))
[1] 1 2 3 4 7 8
```

union_keep

union_keep

Description

Performs a union operation keeping the number of elements of all input vectors, see examples

Usage

```
union_keep(...)
```

Arguments

... are all the input vectors

Examples

```
print(union_keep(c("a", "ee", "ee"), c("p", "p", "a", "i"), c("a", "a", "z")))
[1] "a" "ee" "ee" "p" "p" "i" "z"

print(union_keep(c("a", "ee", "ee"), c("p", "p", "a", "i")))
[1] "a" "ee" "ee" "p" "p" "i"
```

unique_datf	<i>unique_datf</i>
-------------	--------------------

Description

Returns the input dataframe with the unique columns or rows.

Usage

```
unique_datf(inpt_datf, col = FALSE)
```

Arguments

- inpt_datf is the input dataframe
- col is a parameter that specifies if the dataframe returned should have unique columns or rows, defaults to F, so the dataframe returned by default has unique rows

Examples

```
datf1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"))

print(datf1)

  c.1..2..1..3. c..a....z....a....p.. c.1..2..1..3..1
1              1                      a              1
2              2                      z              2
3              1                      a              1
4              3                      p              3

print(unique_datf(inpt_datf=datf1))

#   c.1..2..1..3. c..a....z....a....p..
#1              1                      a
#2              2                      z
#4              3                      p

datf1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"), c(1, 2, 1, 3))

print(datf1)

  c.1..2..1..3. c..a....z....a....p..
1              1                      a
2              2                      z
3              1                      a
4              3                      p

print(unique_datf(inpt_datf=datf1, col=TRUE))

#   cur_v cur_v
#1      1     a
#2      2     z
#3      1     a
#4      3     p
```

```
unique_ltr_from_v  unique_ltr_from_v
```

Description

Returns the unique characters contained in all the elements from an input vector "inpt_v"

Usage

```
unique_ltr_from_v(inpt_v, keep_v = c("?", "!", ":", "&", ",", ".", letters))
```

Arguments

`inpt_v` is the input vector containing all the elements
`keep_v` is the vector containing all the characters that the elements in `inpt_v` may contain

Examples

```
print(unique_ltr_from_v(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "a  

#[1] "b" "o" "n" "j" "u" "r" "l" "p" "e" "c" "a" "v" "i"
```

```
unique_pos  unique_pos
```

Description

Allow to find the first index of the unique values from a vector.

Usage

```
unique_pos(vec)
```

Arguments

`vec` is the input vector

Examples

```
print(unique_pos(vec=c(3, 4, 3, 5, 6)))  
#[1] 1 2 4 5
```

<code>unique_total</code>	<i>unique_total</i>
---------------------------	---------------------

Description

Returns a vector with the total amount of occurrences for each element in the input vector. The occurrences of each element follow the same order as the unique function does, see examples

Usage

```
unique_total(inpt_v = c())
```

Arguments

`inpt_v` is the input vector containing all the elements

Examples

```
print(unique_total(inpt_v = c(1:12, 1)))

[1] 2 1 1 1 1 1 1 1 1 1 1 1

print(unique_total(inpt_v = c(1:12, 1, 11, 11)))

[1] 2 1 1 1 1 1 1 1 1 1 3 1

vec <- c(1:12, 1, 11, 11)
names(vec) <- c(1:15)
print(unique_total(inpt_v = vec))

 1  2  3  4  5  6  7  8  9 10 11 12
2  1  1  1  1  1  1  1  1  1  3  1
```

<code>until_stnl</code>	<i>until_stnl</i>
-------------------------	-------------------

Description

Maxes a vector to a chosen length. ex: if i want my vector c(1, 2) to be 5 of length this function will return me: c(1, 2, 1, 2, 1)

Usage

```
until_stnl(vec1, goal)
```

Arguments

`vec1` is the input vector
`goal` is the length to reach

Examples

```
print(until_stnl(vec1=c(1, 3, 2), goal=56))

# [1] 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3
#[39] 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3
```

val_replacer	<i>val_replacer</i>
--------------	---------------------

Description

Allow to replace value from dataframe to another one.

Usage

```
val_replacer(datf, val_replaced, val_replacor = TRUE)
```

Arguments

`datf` is the input dataframe
`val_replaced` is a vector of the value(s) to be replaced
`val_replacor` is the value that will replace `val_replaced`

Examples

```
print(val_replacer(datf=data.frame(c(1, "oo4", TRUE, FALSE), c(TRUE, FALSE, TRUE, TRUE)),
  val_replaced=c(TRUE), val_replacor="NA"))

# c.1...oo4...T..F. c.T..F..T..T.
#1                1                NA
#2                oo4                FALSE
#3                NA                NA
#4                FALSE                NA
```

vector_replacor	<i>vector_replacor</i>
-----------------	------------------------

Description

Allow to replace certain values in a vector.

Usage

```
vector_replacor(inpt_v = c(), sus_val = c(), rpl_val = c(), grep_ = FALSE)
```

Arguments

- inpt_v is the input vector
- sus_val is a vector containing all the values that will be replaced
- rpl_val is a vector containing the value of the elements to be replaced (sus_val), so sus_val and rpl_val should be the same size
- grep_ is if the elements in sus_val should be equal to the elements to replace in inpt_v or if they just should found in the elements

Examples

```
print(vector_replacor(inpt_v=c(1:15), sus_val=c(3, 6, 8, 12),
  rpl_val=c("oui", "non", "e", "a")))

# [1] "1" "2" "oui" "4" "5" "non" "7" "e" "9" "10" "11" "a"
#[13] "13" "14" "15"

print(vector_replacor(inpt_v=c("non", "zez", "pp a ftf", "fdatfd", "assistance",
  "ert", "repas", "repos"),
  sus_val=c("pp", "as", "re"), rpl_val=c("oui", "non", "zz"), grep_=TRUE))

#[1] "non" "zez" "oui" "fdatfd" "non" "ert" "non" "zz"
```

vec_in_datf	<i>vec_in_datf</i>
-------------	--------------------

Description

Allow to get if a vector is in a dataframe. Returns the row and column of the vector in the dataframe if the vector is contained in the dataframe.

Usage

```
vec_in_datf(
  inpt_datf,
  inpt_vec = c(),
  coeff = 0,
  stop_untl = 1,
  conventional = FALSE
)
```

Arguments

- inpt_datf is the input dataframe
- inpt_vec is the vector that may be in the input dataframe
- coeff is the "slope coefficient" of inpt_vec
- stop_untl is the maximum number of the input vector the function returns, if in the dataframe
- conventional is if a positive slope coefficient means that the vector goes upward or downward

Examples

```

datf1 <- data.frame(c(1:5), c(5:1), c("a", "z", "z", "z", "a"))

print(datf1)

#   c.1.5. c.5.1. c..a....z....z....z....a..
#1      1      5                      a
#2      2      4                      z
#3      3      3                      z
#4      4      2                      z
#5      5      1                      a

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 4, "z"), coeff=1))

#NULL

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=1))

#[1] 5 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(3, "z"), coeff=1))

#[1] 3 2

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(4, "z"), coeff=-1))

#[1] 2 2

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(2, 3, "z"), coeff=-1))

#[1] 2 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=-1, conventional=TRUE))

#[1] 5 1

datf1[4, 2] <- 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(1, "z"), coeff=-1, conventional=TRUE, stop_

#[1] 4 2 5 2

```

vlookup_datf

vlookup_datf

Description

Allow to perform a vlookup on a dataframe

Usage

```
vlookup_datf(datf, v_id, col_id = 1, included_col_id = "yes")
```

Arguments

- datf is the input dataframe
- v_id is a vector containing the ids
- col_id is the column that contains the ids (default is equal to 1)
- included_col_id is if the result should return the col_id (default set to yes)

Examples

```
datf1 <- data.frame(c("az1", "az3", "az4", "az2"), c(1:4), c(4:1))

print(vlookup_datf(datf=datf1, v_id=c("az1", "az2", "az3", "az4")))
```

#	c..az1....az3....az4....az2..	c.1.4.	c.4.1.
#2	az1	1	4
#4	az2	4	1
#21	az3	2	3
#3	az4	3	2

wider_datf	<i>wider_datf</i>
------------	-------------------

Description

Takes a dataframe as an input and the column to split according to a separator.

Usage

```
wider_datf(inpt_datf, col_to_splt = c(), sep_ = "-")
```

Arguments

- inpt_datf is the input dataframe
- col_to_splt is a vector containing the number or the colnames of the columns to split according to a separator
- sep_ is the separator of the elements to split to new columns in the input dataframe

Examples

```
datf1 <- data.frame(c(1:5), c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"), c(5:1))

datf2 <- data.frame("col1"=c(1:5), "col2"=c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"))

print(wider_datf(inpt_datf=datf1, col_to_splt=c(2), sep_="-"))
```

#	pre_datf	X.o.	X.y.
#o-y	1	"o"	"y" 5
#hj-yy	2	"hj"	"yy" 4
#er-y	3	"er"	"y" 3
#k-ll	4	"k"	"ll" 2

```
#ooo-mm 5      "ooo" "mm" 1

print(wider_datf(inpt_datf=datf2, col_to_splt=c("col2"), sep="-"))

#      pre_datf X.o.  X.y.
#o-y   1      "o"   "y"
#hj-yy 2      "hj"  "yy"
#er-y   3      "er"  "y"
#k-ll   4      "k"   "ll"
#ooo-mm 5      "ooo" "mm"
```

```
wide_to_narrow_idx wide_to_narrow_idx
```

Description

Allow to convert the indices of vector ('from_v_ids') which are related to each characters of a vector, to fit the newly established maximum character of the vector, see examples.

Usage

```
wide_to_narrow_idx(from_v_val = c(), from_v_ids = c(), val = 1)
```

Arguments

from_v_val	is the input vector of elements, or just the total number of characters of the elementsq in the vector
from_v_ids	is the input vector of indices
val	is the value - 1 from which the number of character of an element is too high, so the indices in 'from_v_ids' will be modified

Examples

```
print(wide_to_narrow_idx(from_v_val = c("oui", "no", "oui"), from_v_ids = c(4, 6, 9), val = 5))
[1] 2 4 5

print(wide_to_narrow_idx(from_v_val = c("oui", "no", "oui"), from_v_ids = c(4, 6, 9), val = 3))
[1] 2 2 3

print(wide_to_narrow_idx(from_v_val = c("oui", "no", "oui"), from_v_ids = c(4, 6, 9), val = 9))
[1] 4 6 9
```

write_edm_parser	<i>write_edm_parser</i>
------------------	-------------------------

Description

Allow to write data to edm parsed dataset, see examples

Usage

```
write_edm_parser(inpt, to_write_v, write_data)
```

Arguments

`inpt` is the input dataset
`to_write_v` is the vector containing the path to write the data, see examples

Examples

```
print(write_edm_parser("(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ee1:4))",
  to_write_v = c("ok", "ee"), write_data = c("ii", "olm")))

[1] "(ok(ee:56)(ii:olm))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ee1:4))"

print(write_edm_parser("(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ee1:4))",
  to_write_v = c("ok", "oui"), write_data = c("ii", "olm")))

[1] "(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(ii:olm)(oui(bb(rr2:1)))(ee1:4))"

print(write_edm_parser("(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ee1:4))",
  to_write_v = c("ok", "oui", "oui"), write_data = c("ii", "olm")))

[1] "(ok(ee:56))(ok(oui(rr((rr2:6)(rr:5))))(oui(bb(rr2:1)))(ii:olm)(ee1:4))"

print(write_edm_parser("",
  to_write_v = c(), write_data = c("ii", "olm")))

[1] "(ii:olm)"
```

Index

all_concat, 5
all_stat, 6
and_bool1, 7
and_bool2, 7
any_join_datf, 8
appndr, 10
arroundr_mean, 11
arroundr_min, 11

better_match, 12
better_split, 13
better_split_any, 13
better_sub, 14
better_sub_mult, 15
better_unique, 16
bind_cols, 17
bind_rows, 18

can_be_num, 18
closer_ptrn, 19
closer_ptrn_adv, 21
clusterizer_v, 23
col_converter, 26
col_to_row, 27
colins_datf, 25
converter_date, 27
converter_format, 28
cost_and_taxes, 29
cumulated_rows, 30
cumulated_rows_na, 31
cut_v, 32
cutr_v, 31

data_gen, 33
data_meshup, 35
date_addr, 36
date_converter_reverse, 37
datf_appendr, 38
datf_appendr2, 38
datf_insertr, 39
datf_row_appendr, 40
datf_row_appendr2, 40
dcr_untl, 41
dcr_val, 42

delta_normal, 42
delta_unif, 43
depth_pairs_findr, 44
diff_datf, 44
dynamic_idx_converter, 45

edml_normal_gen, 46
edml_random_val, 47
edml_random_val_spe, 48
edml_runif_deterministic, 49
edm_arrangr, 49
edm_arrangr2, 50
edm_group_by1, 51
edm_group_by2, 53
edm_pert, 54
edm_pivot_longer1, 55
edm_pivot_longer2, 58
edm_pivot_series, 61
edm_pivot_wider1, 62
edm_pivot_wider2, 64
elements_equalifier, 65
equalizer_v, 66
extract_normal, 67
extrt_only_v, 73

fillr, 74
fixer_nest_v, 74
fold_rec, 75
fold_rec2, 75
format_date, 76

geo_min, 76
get_rec, 77
globe, 77
glue_groupr_v, 78
grep_all, 79
grep_all2, 79
groupr_datf, 80
gsub_mult, 81

historic_sequence1, 82
historic_sequence2, 83

id_keepr, 84
incr_fillr, 85

- infinite_char_seq, 86
- inner_all, 86
- insert_datf, 87
- inter_max, 91
- inter_min, 92
- intersect_all, 88
- intersect_mod, 89
- intersect_mod2, 90
- is_divisible, 93
- isnt_divisible, 93
- join_n_lvl, 94
- just_anything, 95
- just_anything2, 95
- just_anything3, 96
- just_chr, 96
- just_chr2, 97
- just_chr3, 97
- just_nb, 98
- just_nb2, 98
- just_nb3, 99
- just_not_anything, 99
- just_not_anything2, 100
- just_not_anything3, 100
- leap_yr, 101
- left_all, 101
- letter_to_nb, 102
- list_files, 102
- lst_flatnr, 103
- match_by, 103
- match_na_omit, 104
- multitud, 104
- mutate_vector, 105
- nb2_follow, 106
- nb_follow, 107
- nb_to_letter, 107
- nest_v, 110
- nestr_datf1, 109
- nestr_datf2, 110
- new_ordered, 111
- normal_dens, 112
- normal_offset_prob, 112
- normal_offset_val, 113
- occu, 113
- old_to_new_idx, 114
- or_bool1, 114
- or_bool2, 115
- pairs_findr, 115
- pairs_findr_merger, 116
- pairs_insertr, 117
- pairs_insertr2, 119
- paste_datf, 120
- paste_datf2, 121
- pattern_generator, 121
- pattern_gettr, 122
- pattern_tuning, 123
- power_to_char, 124
- pre_to_post_idx, 124
- ptrn_switchr, 125
- ptrn_twkr, 125
- r_print, 131
- read_edm_parser, 126
- rearangr_v, 127
- regex_spe_detect, 128
- regroupr, 128
- rm_na_rows, 129
- rm_rows, 130
- row_to_col, 131
- save_until, 132
- see_datf, 133
- see_diff, 134
- see_diff_all, 135
- see_diff_detailed, 135
- see_file, 136
- see_idx, 136
- see_in_grep, 138
- see_in_l, 138
- see_inside, 137
- see_mode, 139
- selected_char, 139
- sequence_na_mean1, 140
- sequence_na_mean2, 141
- sequence_na_med1, 142
- sequence_na_med2, 143
- sort_date, 144
- sort_normal_qual, 145
- sort_normal_qual2, 149
- split_by_step, 152
- str_remove_until, 153
- sub_mult, 154
- successive_diff, 155
- sum_group1, 155
- sum_group2, 157
- swipr, 159
- test_order, 160
- time_serie_equalizer, 160
- to_unique, 162
- union_all, 163

union_keep, [163](#)
unique_datf, [164](#)
unique_ltr_from_v, [165](#)
unique_pos, [165](#)
unique_total, [166](#)
until_stnl, [166](#)

val_replacer, [167](#)
vec_in_datf, [168](#)
vector_replacor, [167](#)
vlookup_datf, [169](#)

wide_to_narrow_idx, [171](#)
wider_datf, [170](#)
write_edm_parser, [172](#)