

Package ‘edm1’

March 20, 2024

Title Simplify complex data manipulation

Version 0.0.0.9000

Description Simplify complex data manipulation.

License use_gpl3_license() or friends to pick a
license

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports stringr,
stringi,
openxlsx

R topics documented:

all_stat	3
any_join_df	4
appndr	6
better_match	7
can_be_num	7
closer_ptrn	8
closer_ptrn_adv	10
clusterizer_v	11
colins_df	14
converter_date	15
converter_format	16
cost_and_taxes	16
cut_v	17
data_gen	18
data_meshup	20
date_addr	21
date_converter_reverse	22
dcr_untl	23
dcr_val	24
diff_xlsx	24
equalizer_v	25
extrt_only_v	26
fillr	26

fixer_nest_v	27
fold_rec	27
fold_rec2	28
format_date	28
geo_min	29
get_rec	30
globe	30
groupr_df	31
id_keepr	32
incr_fillr	33
insert_df	34
inter_max	35
inter_min	36
isnt_divisible	37
is_divisible	37
leap_yr	38
letter_to_nb	38
list_files	39
lst_flatnr	39
multitud	40
nb_to_letter	40
nestr_df1	41
nestr_df2	42
nest_v	42
new_ordered	43
non_unique	43
occu	44
paste_df	45
pattern_generator	45
pattern_gettr	46
pattern_tuning	47
ptrn_switchr	48
ptrn_twkr	48
rearrngr_v	49
regroupr	50
save_untl	51
see_df	52
see_file	53
see_idx	54
see_inside	55
str_remove_untl	55
unique_df	56
unique_ltr_from_v	57
unique_pos	57
until_stnl	58
val_replacer	58
vector_replacor	59
vec_in_df	59
vlookup_df	60
wider_df	61

all_stat	<i>all_stat</i>
----------	-----------------

Description

Allow to see all the main statistics indicators (mean, median, variance, standard deviation, sum, max, min, quantile) of variables in a dataframe by the modality of a variable in a column of the input datarame. In addition to that, you can get the occurrence of other qualitative variables by your chosen qualitative variable, you have just to precise it in the vector "stat_var" where all the statistics indicators are given with "occu-var_you_want/".

Usage

```
all_stat(inpt_v, var_add = c(), stat_var = c(), inpt_df)
```

Arguments

inpt_v	is the modalities of the variables
var_add	is the variables you want to get the stats from
stat_var	is the stats indicators you want
inpt_df	is the input dataframe

Examples

```
df <- data.frame("mod"=c("first", "seco", "seco", "first", "first", "third", "first"),
  "var1"=c(11, 22, 21, 22, 22, 11, 9),
  "var2"=c("d", "d", "z", "z", "z", "d", "z"),
  "var3"=c(45, 44, 43, 46, 45, 45, 42),
  "var4"=c("A", "A", "A", "A", "B", "C", "C"))
```

```
print(all_stat(inpt_v=c("first", "seco"), var_add = c("var1", "var2", "var3", "var4"),
  stat_var=c("sum", "mean", "median", "sd", "occu-var2/", "occu-var4/", "variance", "quantile-0.75"),
  inpt_df=df))
```

	modal_v	var_vector	occu	sum	mean	med	standard_devaition	variance
1	first							
2		var1		64	16	16.5	6.97614984548545	48.6666666666667
3		var2-d	1					
4		var2-z	3					
5		var3		178	44.5	45	1.73205080756888	3
6		var4-A	2					
7		var4-B	1					
8		var4-C	1					
9	seco							
10		var1		43	21.5	21.5	0.707106781186548	0.5
11		var2-d	1					
12		var2-z	1					
13		var3		87	43.5	43.5	0.707106781186548	0.5
14		var4-A	2					
15		var4-B	0					
16		var4-C	0					
1	quantile-0.75							

```

2          22
3
4
5          45.25
6
7
8
9
10         21.75
11
12
13         43.75
14
15
16

```

any_join_df	<i>any_join_df</i>
-------------	--------------------

Description

Allow to perform SQL joints with more features

Usage

```

any_join_df(
  inpt_df_l,
  join_type = "inner",
  join_spe = NA,
  id_v = c(),
  excl_col = c(),
  rtn_col = c(),
  d_val = NA
)

```

Arguments

inpt_df_l	is a list containing all the dataframe
join_type	is the joint type. Defaults to inner but can be changed to a vector containing all the dataframes you want to take their ids to don external joints.
join_spe	can be equal to a vector to do an external joints on all the dataframes. In this case, join_type should not be equal to "inner"
id_v	is a vector containing all the ids name of the dataframes. The ids names can be changed to number of their columns taking in count their position in inpt_df_l. It means that if my id is in the third column of the second dataframe and the first dataframe have 5 columns, the column number of the ids is $5 + 3 = 8$
excl_col	is a vector containing the column names to exclude, if this vector is filled so "rtn_col" should not be filled. You can also put the column number in the manner indicated for "id_v". Defaults to c()


```
8  a11 <NA> <NA> <NA> <NA> 1 a oui 11 9 a oui
9  z12 <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA>
10 a8 <NA> <NA> <NA> <NA> 4 a oui 8 4 a oui
second_ids
1 13
2 12
3 <NA>
4 <NA>
5 <NA>
6 <NA>
7 <NA>
8 11
9 <NA>
10 8

print(any_join_df(inpt_df_l=list(df1, df2, df3), join_type=c(1), id_v=c("ids"),
excl_col=c(), rtn_col=c()))

ids val ids last second_ids val ids bool second_ids val ids last
1 e 1 e oui 13 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
2 a 1 a oui 11 3 a TRUE 13 1 a oui
3 z 2 z non 12 7 z FALSE 12 2 z non
4 a 4 a oui 8 4 a FALSE 34 9 a oui
second_ids
1 <NA>
2 13
3 12
4 11
```

appndr	<i>appndr</i>
--------	---------------

Description

Append to a vector "inpt_v" a special value "val" n times "mmn". The appending begins at "strt" index.

Usage

```
appndr(inpt_v, val = NA, hmn, strt = "max")
```

Arguments

- inpt_v is the input vector
- val is the special value
- hmn is the number of special value element added
- strt is the index from which appending begins, defaults to max which means the end of "inpt_v"

Examples

```
print(appndr(inpt_v=c(1:3), val="oui", hmn=5))

[1] "1"  "2"  "3"  "oui" "oui" "oui" "oui" "oui"

print(appndr(inpt_v=c(1:3), val="oui", hmn=5, strt=1))

[1] "1"  "oui" "oui" "oui" "oui" "oui" "2"  "3"
```

better_match	<i>better_match</i>
--------------	---------------------

Description

Allow to get the nth element matched in a vector

Usage

```
better_match(inpt_v = c(), ptrn, until = 1, nvr_here = NA)
```

Arguments

inpt_v	is the input vector
ptrn	is the pattern to be matched
until	is the maximum number of matched pattern outputed
nvr_here	is a value you are sure is not present in inpt_v

Examples

```
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=1))

[1] 3

print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=5))

[1] 3 13 16
```

can_be_num	<i>can_be_num</i>
------------	-------------------

Description

Return TRUE if a variable can be converted to a number and FALSE if not (supports float)

Usage

```
can_be_num(x)
```

Arguments

`x` is the input value

Examples

```
print(can_be_num("34.677"))
[1] TRUE
print(can_be_num("34"))
[1] TRUE
print(can_be_num("3rt4"))
[1] FALSE
print(can_be_num(34))
[1] TRUE
```

`closer_ptrn`

closer_ptrn

Description

Take a vector of patterns as input and output each chosen word with their closest patterns from chosen patterns.

Usage

```
closer_ptrn(
  inpt_v,
  base_v = c("?", letters),
  excl_v = c(),
  rtn_v = c(),
  sub_excl_v = c(),
  sub_rtn_v = c()
)
```

Arguments

<code>inpt_v</code>	is the input vector containing all the patterns
<code>base_v</code>	must contain all the characters that the patterns are susceptible to contain, defaults to <code>c("?", letters)</code> . "?" is necessary because it is internally the default value added to each element that does not have a sufficient length compared to the longest pattern in <code>inpt_v</code> . If set to NA, the function will find by itself the elements to be filled with but it may take an extra time
<code>excl_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to exclude for comparing them to others patterns. If this parameter is filled, so <code>"rtn_v"</code> must be empty.
<code>rtn_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to keep for comparing them to others patterns. If this parameter is filled, so <code>"rtn_v"</code> must be empty.
<code>sub_excl_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to exclude for using them to compare to another pattern. If this parameter is filled, so <code>"sub_rtn_v"</code> must be empty.
<code>sub_rtn_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to retain for using them to compare to another pattern. If this parameter is filled, so <code>"sub_excl_v"</code> must be empty.

Examples

```

print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir")

[[1]]
[1] "bonjour"

[[2]]
[1] "lpoerc" "nonnour" "bonnour" "nonjour" "aurevoir"

[[3]]
[1] 1 1 2 7 8

[[4]]
[1] "lpoerc"

[[5]]
[1] "bonjour" "nonnour" "bonnour" "nonjour" "aurevoir"

[[6]]
[1] 7 7 7 7 7

[[7]]
[1] "nonnour"

[[8]]
[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"

[[9]]
[1] 1 1 2 7 8

[[10]]
[1] "bonnour"

[[11]]
[1] "bonjour" "lpoerc" "nonnour" "nonjour" "aurevoir"

[[12]]
[1] 1 1 2 7 8

[[13]]
[1] "nonjour"

[[14]]
[1] "bonjour" "lpoerc" "nonnour" "bonnour" "aurevoir"

[[15]]
[1] 1 1 2 7 8

[[16]]
[1] "aurevoir"

[[17]]
[1] "bonjour" "lpoerc" "nonnour" "bonnour" "nonjour"

[[18]]
[1] 7 8 8 8 8

```

```

print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir",
                           sub_excl_v=c("nonnour")))

[1] 3 5
[[1]]
[1] "bonjour"

[[2]]
[1] "lpoerc" "bonnour" "nonjour" "aurevoir"

[[3]]
[1] 1 1 7 8

[[4]]
[1] "lpoerc"

[[5]]
[1] "bonjour" "bonnour" "nonjour" "aurevoir"

[[6]]
[1] 7 7 7 7

[[7]]
[1] "bonnour"

[[8]]
[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"

[[9]]
[1] 0 1 2 7 8

[[10]]
[1] "aurevoir"

[[11]]
[1] "bonjour" "lpoerc" "nonjour" "aurevoir"

[[12]]
[1] 0 7 8 8

```

closer_ptrn_adv	<i>closer_ptrn_adv</i>
-----------------	------------------------

Description

Allow to find how patterns are far or near between each other relatively to a vector containing characters at each index ("base_v"). The function gets the sum of the indexes of each pattern letter relatively to the characters in base_v. So each pattern can be compared.

Usage

```

closer_ptrn_adv(
  inpt_v,
  res = "raw_stat",

```

```

    default_val = "?",
    base_v = c(default_val, letters),
    c_word = NA
  )

```

Arguments

<code>inpt_v</code>	is the input vector containing all the patterns to be analyzed
<code>res</code>	is a parameter controlling the result. If set to "raw_stat", each word in <code>inpt_v</code> will come with its score (indexes of its letters relatively to <code>base_v</code>). If set to something else, so "c_word" parameter must be filled.
<code>default_val</code>	is the value that will be added to all patterns that do not equal the length of the longest pattern in <code>inpt_v</code> . Those get this value added to make all patterns equal in length so they can be compared, defaults to "?"
<code>base_v</code>	is the vector from which all pattern get its result (letters indexes for each pattern relatively to <code>base_v</code>), defaults to <code>c("default_val", letters)</code> . "default_val" is another parameter and letters is all the western alphabetic letters in a vector
<code>c_word</code>	is a pattern from which the nearest to the farrest pattern in <code>inpt_v</code> will be compared

Examples

```

print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois", "bonjour"))

[[1]]
[1] 1 5 15 17 38 65

[[2]]
[1] "bonjour" "bonnour" "aurevoir" "nonnour" "mois" "fin"

print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois")))

[[1]]
[1] 117 107 119 37 64

[[2]]
[1] "aurevoir" "bonnour" "nonnour" "fin" "mois"

```

clusterizer_v

clusterizer_v

Description

Allow to output clusters of elements. Takes as input a vector "inpt_v" containing a sequence of number. Can also take another vector "w_v" that has the same size of `inpt_v` because its elements are related to it. The way the clusters are made is related to an accuracy value which is "c_val". It means that if the difference between the values associated to 2 elements is superior to `c_val`, these two elements are in distinct clusters. The second element of the outputted list is the begin and end value of each cluster.

Usage

```
clusterizer_v(inpt_v, w_v = NA, c_val)
```

Arguments

<code>inpt_v</code>	is the vector containing the sequence of number
<code>w_v</code>	is the vector containing the elements related to <code>inpt_v</code> , defaults to NA
<code>c_val</code>	is the accuracy of the clusterization

Examples

```
print(clusterizer_v(inpt_v=sample.int(20, 26, replace=T), w_v=NA, c_val=0.9))

[[1]]
[[1]][[1]]
[1] 1

[[1]][[2]]
[1] 2

[[1]][[3]]
[1] 3

[[1]][[4]]
[1] 4

[[1]][[5]]
[1] 5 5

[[1]][[6]]
[1] 6 6 6 6

[[1]][[7]]
[1] 7 7 7

[[1]][[8]]
[1] 8 8 8

[[1]][[9]]
[1] 9

[[1]][[10]]
[1] 10

[[1]][[11]]
[1] 12

[[1]][[12]]
[1] 13 13 13

[[1]][[13]]
[1] 18 18 18

[[1]][[14]]
[1] 20
```

```

[[2]]
[1] "1" "1" "-" "2" "2" "-" "3" "3" "-" "4" "4" "-" "5" "5" "-"
[16] "6" "6" "-" "7" "7" "-" "8" "8" "-" "9" "9" "-" "10" "10" "-"
[31] "12" "12" "-" "13" "13" "-" "18" "18" "-" "20" "20"

print(clusterizer_v(inpt_v=sample.int(40, 26, replace=T), w_v=letters, c_val=0.29))

[[1]]
[[1]][[1]]
[1] "a"

[[1]][[2]]
[1] "b"

[[1]][[3]]
[1] "c" "d"

[[1]][[4]]
[1] "e" "f"

[[1]][[5]]
[1] "g" "h" "i" "j"

[[1]][[6]]
[1] "k"

[[1]][[7]]
[1] "l"

[[1]][[8]]
[1] "m" "n"

[[1]][[9]]
[1] "o"

[[1]][[10]]
[1] "p"

[[1]][[11]]
[1] "q" "r"

[[1]][[12]]
[1] "s" "t" "u"

[[1]][[13]]
[1] "v"

[[1]][[14]]
[1] "w"

[[1]][[15]]
[1] "x"

[[1]][[16]]
[1] "y"

```

```
[[1]][[17]]
[1] "z"
```

```
[[2]]
[1] "13" "13" "-" "14" "14" "-" "15" "15" "-" "16" "16" "-" "17" "17" "-"
[16] "19" "19" "-" "21" "21" "-" "22" "22" "-" "23" "23" "-" "25" "25" "-"
[31] "27" "27" "-" "29" "29" "-" "30" "30" "-" "31" "31" "-" "34" "34" "-"
[46] "35" "35" "-" "37" "37"
```

colins_df

colins_df

Description

Allow to insert vectors into a dataframe.

Usage

```
colins_df(inpt_df, target_col = list(), target_pos = list())
```

Arguments

`inpt_df` is the dataframe where vectors will be inserted
`target_col` is a list containing all the vectors to be inserted
`target_pos` is a list containing the vectors made of the columns names or numbers where the associated vectors from `target_col` will be inserted after

Examples

```
df1 <- data.frame("frst_col"=c(1:5), "scd_col"=c(5:1))
```

```
print(colins_df(inpt_df=df1, target_col=list(c("oui", "oui", "oui", "non", "non"), c("u", "z", "z", "z", "u")),
  target_pos=list(c("frst_col", "scd_col"), c("scd_col"))))
```

```
  frst_col cur_col scd_col cur_col.1 cur_col
1         1     oui         5      oui         u
2         2     oui         4      oui         z
3         3     oui         3      oui         z
4         4     non         2      non         z
5         5     non         1      non         u
```

```
print(colins_df(inpt_df=df1, target_col=list(c("oui", "oui", "oui", "non", "non"), c("u", "z", "z", "z", "u")),
  target_pos=list(c(1, 2), c("frst_col"))))
```

```
  frst_col cur_col scd_col cur_col cur_col
1         1     oui         5         u     oui
2         2     oui         4         z     oui
3         3     oui         3         z     oui
4         4     non         2         z     non
5         5     non         1         u     non
```

converter_date	<i>converter_date</i>
----------------	-----------------------

Description

Allow to convert any date like second/minute/hour/day/month/year to either second, minute...year. The input date should not necessarily have all its time units (second, minute...) but all the time units according to a format. Example: "snhdmy" is for second, hour, minute, day, month, year. And "mdy" is for month, day, year.

Usage

```
converter_date(inpt_date, convert_to, frmt = "snhdmy", sep_ = "-")
```

Arguments

- inpt_date is the input date
- convert_to is the time unit the input date will be converted ("s", "n", "h", "d", "m", "y")
- frmt is the format of the input date
- sep_n is the separator of the input date. For example this input date "12-07-2012" has "-" as a separator

Examples

```
print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="m"))
[1] 24299.15

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="y"))
[1] 2024.929

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="s"))
[1] 63900626400

print(converter_date(inpt_date="63900626400", sep_="-", frmt="s", convert_to="y"))
[1] 2024.929

print(converter_date(inpt_date="2024", sep_="-", frmt="y", convert_to="s"))
[1] 63873964800
```

converter_format	<i>converter_format</i>
------------------	-------------------------

Description

Allow to convert a format to another

Usage

```
converter_format(inpt_val, sep_ = "-", inpt_frmt, frmt, default_val = "00")
```

Arguments

inpt_val	is the input value that is linked to the format
sep_	is the separator of the value in inpt_val
inpt_frmt	is the format of the input value
frmt	is the format you want to convert to
default_val	is the default value given to the units that are not present in the input format

Examples

```
print(converter_format(inpt_val="23-12-05-1567", sep_="-",
                      inpt_frmt="shmy", frmt="snhdmy", default_val="00"))

[1] "23-00-12-00-05-1567"

print(converter_format(inpt_val="23-12-05-1567", sep_="-",
                      inpt_frmt="shmy", frmt="Pnhdmy", default_val="00"))

[1] "00-00-12-00-05-1567"
```

cost_and_taxes	<i>cost_and_taxes</i>
----------------	-----------------------

Description

Allow to calculate basic variables related to cost and taxes from a bunch of products (elements) So put every variable you know in the following order:

Usage

```
cost_and_taxes(
  qte = NA,
  pu = NA,
  prix_ht = NA,
  tva = NA,
  prix_ttc = NA,
  prix_tva = NA,
```



```

    pu_ttc = NA,
    adjust = NA,
    prix_d_ht = NA,
    prix_d_ttc = NA,
    pu_d = NA,
    pu_d_ttc = NA
  )

```

Arguments

qte	is the quantity of elements
pu	is the price of a single elements without taxes
prix_ht	is the duty-free price of the whole set of elements
tva	is the percentage of all taxes
prix_ttc	is the price of all the elements with taxes
prix_tva	is the cost of all the taxes
pu_ttc	is the price of a single element taxes included
adjust	is the discount percentage
prix_d_ht	is the free-duty price of an element after discount
prix_d_ttc	is the price with taxes of an element after discount
pu_d	is the price of a single element after discount and without taxes
pu_d_ttc	is the free-duty price of a single element after discount the function return a vector with the previous variables in the same order those that could not be calculated will be represented with NA value

Examples

```

print(cost_and_taxes(pu=45, prix_ttc=21, qte=3423))

[1] 3.423000e+03 4.500000e+01 4.500000e+01 -9.998637e-01 2.100000e+01
[6] -1.540140e+05 4.500000e+01 NA NA NA
[11] NA NA

```

cut_v	<i>v_to_df</i>
-------	----------------

Description

Allow to convert a vector to a dataframe according to a separator.

Usage

```
cut_v(inpt_v, sep_ = "")
```

Arguments

inpt_v	is the input vector
sep_	is the separator of the elements in inpt_v, defaults to ""

Examples

```
print(cut_v(inpt_v=c("oui", "non", "oui", "non")))

      X.o. X.u. X.i.
oui  "o"  "u"  "i"
non  "n"  "o"  "n"
oui  "o"  "u"  "i"
non  "n"  "o"  "n"

print(cut_v(inpt_v=c("ou-i", "n-on", "ou-i", "n-on"), sep_="-"))

      X.ou. X.i.
ou-i  "ou"  "i"
n-on  "n"   "on"
ou-i  "ou"  "i"
n-on  "n"   "on"
```

data_gen

*data_gen***Description**

Allo to generate in a csv all kind of data you can imagine according to what you provide

Usage

```
data_gen(
  type_ = c("number", "mixed", "string"),
  strt_l = c(0, 0, 10),
  nb_r = c(50, 10, 40),
  output = NA,
  properties = c("1-5", "1-5", "1-5"),
  type_distri = c("random", "random", "random"),
  str_source = c("a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m",
    "o", "p", "q", "r", "s", "t", "u", "w", "x", "y", "z"),
  round_l = c(0, 0, 0),
  sep_ = ",",
)
```

Arguments

type_	is a vector. Its arguments designates a column, a column can be made of numbers ("number"), string ("string") or both ("mixed")
strt_l	is a vector containing for each column the row from which the data will begin to be generated
nb_r	is a vector containing for each column, the number of row full from generated data
output	is the name of the output csv file, defaults to NA so no csv will be outputted by default

properties	is linked to type_distri because it is the parameters ("min_val-max_val") for "random type", ("u-x") for the poisson distribution, ("u-d") for gaussian distribution
type_distri	is a vector which, for each column, associate a type of distribution ("random", "poisson", "gaussian"), it means that not only the number but also the length of the string will be randomly generated according to these distribution laws
str_source	is the source (vector) from which the character creating random string are (default set to the occidental alphabet)
round_l	is a vector which, for each column containing number, associate a round value, if the type of the value is numeric
sep_	is the separator used to write data in the csv

Value

new generated data in addition to saving it in the output

Examples

```
print(data_gen())
```

	X1	X2	X3
1	4	2	<NA>
2	2	4	<NA>
3	5	2	<NA>
4	2	abcd	<NA>
5	4	abcd	<NA>
6	2	4	<NA>
7	2	abc	<NA>
8	4	abc	<NA>
9	4	3	<NA>
10	4	abc	abcd
11	5	<NA>	abc
12	4	<NA>	abc
13	1	<NA>	ab
14	1	<NA>	abcde
15	2	<NA>	abc
16	4	<NA>	a
17	1	<NA>	abcd
18	4	<NA>	ab
19	2	<NA>	abcd
20	3	<NA>	ab
21	3	<NA>	abcd
22	2	<NA>	a
23	4	<NA>	abc
24	1	<NA>	abcd
25	4	<NA>	abc
26	4	<NA>	ab
27	2	<NA>	abc
28	5	<NA>	ab
29	3	<NA>	abc
30	5	<NA>	abcd
31	2	<NA>	abc
32	2	<NA>	abc
33	1	<NA>	ab
34	5	<NA>	a

```

35  4 <NA>    ab
36  1 <NA>    ab
37  1 <NA> abcde
38  5 <NA>    abc
39  4 <NA>    ab
40  5 <NA> abcde
41  2 <NA>    ab
42  3 <NA>    ab
43  2 <NA>    ab
44  4 <NA> abcd
45  5 <NA> abcd
46  3 <NA> abcd
47  2 <NA> abcd
48  3 <NA> abcd
49  3 <NA> abcd
50  4 <NA>    a

```

```
print(data_gen(strt_l=c(0, 0, 0), nb_r=c(5, 5, 5)))
```

```

  X1    X2  X3
1  2     a  abc
2  3 abcde  ab
3  4 abcde  a
4  1     3  abc
5  3     a abcd

```

data_mesup

data_mesup

Description

Allow to automatically arrange 1 dimensional data according to vector and parameters

Usage

```

data_mesup(
  data,
  cols = NA,
  file_ = NA,
  sep_ = ";",
  organisation = c(2, 1, 0),
  unic_sep1 = "_",
  unic_sep2 = "-"
)

```

Arguments

data	is the data provided (vector) each column is separated by a unic separator and each dataset from the same column is separated by another unic separator (ex: <code>c("", c("d", "-", "e", "-", "f"), "", c("a", "a1", "-", "b", "-", "c", "c1"), "-")</code>)
cols	are the colnames of the data generated in a csv
file_	is the file to which the data will be outputed, defaults to NA which means that the funcio will return the dataframe generated and won't write it to a csv file

sep_ is the separator of the csv outputed

organisation is the way variables include themselves, for instance ,resuming precedent example, if organisation=c(1, 0) so the data output will be: d, a d, a1 e, c f, c f, c1

unic_sep1 is the unic separator between variables (default is "_")

unic_sep2 is the unic separator between datasets (default is "-")

Examples

```
print(data_meshup(data=c("_", c("-", "d", "-", "e", "-", "f"), "_", c("-", "a", "a1", "-"),
  X1 X2
1 d a
2 d a1
3 e B
4 e r
5 e uy
6 f c
7 f c1
```

date_addr	<i>date_addr</i>
-----------	------------------

Description

Allow to add or subtract two dates that have the same time unit or not

Usage

```
date_addr(
  date1,
  date2,
  add = F,
  frmt1,
  frmt2 = frmt1,
  sep_ = "-",
  convert_to = "dmy"
)
```

Arguments

date1 is the date from which the second date will be added or subtracted

date2 is the date that will be added or will subtract date1

add equals to FALSE if you want date1 - date2 and TRUE if you want date1 + date2

frmt1 is the format of date1 (snhdmy) (second, minute, hour, day, monthn year)

frmt2 is the format of date2 (snhdmy)

sep_ is the separator of date1 and date2

convert_to is the format of the outputed date

Examples

```

print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",
               convert_to="dmy"))

[1] "18-2-0"

print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",
               convert_to="dmy", add=T))

[1] "3-3-0"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="dmy", add=T))

[1] "27-3-2024"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="dmy", add=F))

[1] "23-1-2024"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="n", add=F))

[1] "1064596320"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="s", add=F))

[1] "63875779200"

```

```

date_converter_reverse
      date_converter_reverse

```

Description

Allow to convert single date value like 2025.36 year to a date like second/minutehour/day/month/year (snhdmy)

Usage

```
date_converter_reverse(inpt_date, convert_to = "dmy", frmt = "y", sep_ = "-")
```

Arguments

inpt_date	is the input date
convert_to	is the date format the input date will be converted
frmt	is the time unit of the input date
sep_	is the separator of the outputed date

Examples

```
print(date_converter_reverse(inpt_date="2024.929", convert_to="hmy", frmt="y", sep="-"))

[1] "110-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dmy", frmt="y", sep="-"))

[1] "4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="hdmy", frmt="y", sep="-"))

[1] "14-4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dhym", frmt="y", sep="-"))

[1] "4-14-2024-11"
```

dcr_untl

dcr_untl

Description

Allow to get the final value of a incremental or decremental loop.

Usage

```
dcr_untl(strt_val, cr_val, stop_val = 0)
```

Arguments

strt_val	is the start value
cr_val	is the incremental (or decremental value)
stop_val	is the value where the loop has to stop

Examples

```
print(dcr_untl(strt_val=50, cr_val=-5, stop_val=5))

[1] 9

print(dcr_untl(strt_val=50, cr_val=5, stop_val=450))

[1] 80
```

dcr_val	<i>dcr_val</i>
---------	----------------

Description

Allow to get the end value after an incremental (or decremental loop)

Usage

```
dcr_val(strt_val, cr_val, stop_val = 0)
```

Arguments

strt_val	is the start value
cr_val	is the incremental or decremental value
stop_val	is the value the loop has to stop

Examples

```
print(dcr_val(strt_val=50, cr_val=-5, stop_val=5))
[1] 5

print(dcr_val(strt_val=47, cr_val=-5, stop_val=5))
[1] 7

print(dcr_val(strt_val=50, cr_val=5, stop_val=450))
[1] 450

print(dcr_val(strt_val=53, cr_val=5, stop_val=450))
[1] 448
```

diff_xlsx	<i>diff_xlsx</i>
-----------	------------------

Description

Allow to see the difference between two datasets and output it into an xlsx file. If the dimensions of the new datasets are bigger than the old one, only the matching cells will be compared, if the dimensions of the new one are lower than the old one, there will be an error.

Usage

```
diff_xlsx(
  file_,
  sht,
  v_old_begin,
  v_old_end,
  v_new_begin,
  v_new_end,
  df2 = NA,
  overwrite = T,
  color_ = "red",
  pattern = "",
  output = "out.xlsx",
  new_val = T,
  pattern_only = T
)
```

Arguments

<code>file_</code>	is the file where the data is
<code>sht</code>	is the sheet where the data is
<code>v_old_begin</code>	is a vector containing the coordinates (row, column) where the data to be compared starts
<code>v_old_end</code>	is the same but for its end
<code>v_new_begin</code>	is the coordinates where the comparator data starts
<code>v_new_end</code>	is the same but for its end If the dimensions of the new datasets are bigger than the old one, only the matching cells will be compared, if the dimensions of the new one are lower than the old one, there will be an error.
<code>df2</code>	is optional, if the comparator dataset is directly a dataframe
<code>overwrite</code>	allow to overwrite differences is (set to T by default)
<code>color_</code>	is the color the differences will be outputed
<code>pattern</code>	is the pattern that will be added to the differences if overwritten is set to TRUE
<code>output</code>	is the name of the outputed xlsx (can be set to NA if no output)
<code>new_val</code>	if overwrite is TRUE, then the differences will be overwritten by the comparator data
<code>pattern_only</code>	will cover differences by pattern if overwritten is set to TRUE

equalizer_v

equalizer_v

Description

Takes a vector of character as an input and returns a vector with the elements at the same size. The size can be chosen via depth parameter.

Usage

```
equalizer_v(inpt_v, depth = "max", default_val = "?")
```

Arguments

<code>inpt_v</code>	is the input vector containing all the characters
<code>depth</code>	is the depth parameter, defaults to "max" which means that it is equal to the character number of the element(s) in <code>inpt_v</code> that has the most
<code>default_val</code>	is the default value that will be added to the output characters if those has an inferior length (characters) than the value of <code>depth</code>

Examples

```
print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=2))
[1] "aa" "zz" "q?"

print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=12))
[1] "aa?????????" "zzz?????????" "q?????????"
```

<code>extrt_only_v</code>	<i>extrt_only_v</i>
---------------------------	---------------------

Description

return the elements from a vector "inpt_v" that are in another vector "pttrn_v"

Usage

```
extrt_only_v(inpt_v, pttrn_v)
```

Arguments

<code>inpt_v</code>	is the input vector
<code>pttrn_v</code>	is the vector contining all the elements that can be in <code>inpt_v</code>

Examples

```
print(extrt_only_v(inpt_v=c("oui", "non", "peut", "oo", "ll", "oui", "non", "oui", "oui"))
[1] "oui" "oui" "oui" "oui"
```

<code>fillr</code>	<i>fillr</i>
--------------------	--------------

Description

Allow to fill a vector by the last element n times

Usage

```
fillr(inpt_v, ptrn_fill = "...\\d")
```

Arguments

`inpt_v` is the input vector

`ptrn_fill` is the pattern used to detect where the function has to fill the vector by the last element `n` times. It defaults to "...\\d" where "\\d" is the regex for an int value. So this paramater has to have "\\d" which designates `n`.

Examples

```
print(fillr(c("a", "b", "...3", "c")))
```

```
[1] "a" "b" "b" "b" "b" "c"
```

<code>fixer_nest_v</code>	<i>fixer_nest_v</i>
---------------------------	---------------------

Description

Retur the elements of a vector "`wrk_v`" (1) that corresponds to the pattern of elements in another vector "`cur_v`" (2) according to another vector "`pttrn_v`" (3) that contains the patterof eleemnts.

Usage

```
fixer_nest_v(cur_v, pttrn_v, wrk_v)
```

Examples

```
print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"), pttrn_v=c(1, 2, 3, 4, 5, 6), wrk_v=c(1, 2, 3, 4, 5, 6)))
```

```
[1] 1 2 3 4 5 6
```

```
print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"), pttrn_v=c(1, 2, 3, 4, 5, 6), wrk_v=c(1, 2, 3, 4, 5, 6)))
```

```
[1] 1 2 NA 4 5 NA
```

<code>fold_rec</code>	<i>fold_rec</i>
-----------------------	-----------------

Description

Allow to get all the files recursively from a path according to an end and start depth value. If you want to have an other version of this function that uses a more sophisticated algorythm (which can be faster), check `file_rec2`. Depth example: if i have `dir/dir2/dir3`, `dir/dir2b/dir3b`, i have a depth equal to 3

Usage

```
fold_rec(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax	is the end depth value
xmin	is the start depth value
pathc	is the reference path

fold_rec2	<i>fold_rec2</i>
-----------	------------------

Description

Allow to find the directories and the subdirectories with a specified end and start depth value from a path. This function might be more powerfull than file_rec because it uses a custom algorythm that does not nee to perform a full recursive search before tuning it to only find the directories with a good value of depth. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

Usage

```
fold_rec2(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax	is the depth value
xmin	is the minimum value of depth
pathc	is the reference path, from which depth value is equal to 1

format_date	<i>format_date</i>
-------------	--------------------

Description

Allow to convert xx-month-xxxx date type to xx-xx-xxxx

Usage

```
format_date(f_dialect, sentc, sep_in = "-", sep_out = "-")
```

Arguments

f_dialect	are the months from the language of which the month come
sentc	is the date to convert
sep_in	is the separator of the dat input (default is "-")
sep_out	is the separator of the converted date (default is "-")

Examples

```
print(format_date(f_dialect=c("janvier", "février", "mars", "avril", "mai", "juin",
                              "juillet", "aout", "septembre", "octobre", "novembre", "décembre"),
            sentc="11-09-2023", sep_in="-", sep_out="-")
[1] "11-09-2023"
```

geo_min	<i>geo_min</i>
---------	----------------

Description

Return a dataframe containing the nearest geographical points (row) according to established geographical points (column).

Usage

```
geo_min(inpt_df, established_df)
```

Arguments

`inpt_df` is the input dataframe of the set of geographical points to be classified, its first column is for latitude, the second for the longitude and the third, if exists, is for the altitude. Each point is one row.

`established_df` is the dataframe containing the coordinates of the established geographical points

Examples

```
in_ <- data.frame(c(11, 33, 55), c(113, -143, 167))

in2_ <- data.frame(c(12, 55), c(115, 165))

print(geo_min(inpt_df=in_, established_df=in2_))

      X1      X2
1  245.266    NA
2 24200.143    NA
3      NA 127.7004

in_ <- data.frame(c(51, 23, 55), c(113, -143, 167), c(6, 5, 1))

in2_ <- data.frame(c(12, 55), c(115, 165), c(2, 5))

print(geo_min(inpt_df=in_, established_df=in2_))

      X1      X2
1      NA 4343.720
2 26465.63      NA
3      NA 5825.517
```

get_rec

get_rec

Description

Allow to get the value of directorie depth from a path.

Usage

```
get_rec(pathc = ".")
```

Arguments

pathc is the reference path example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

globe

globe

Description

Allow to calculate the distances between a set of geographical points and another established geographical point. If the altitude is not filled, so the result returned won't take in count the altitude.

Usage

```
globe(lat_f, long_f, alt_f = NA, lat_n, long_n, alt_n = NA)
```

Arguments

lat_f is the latitude of the established geographical point
long_f is the longitude of the established geographical point
alt_f is the altitude of the established geographical point, defaults to NA
lat_n is a vector containing the latitude of the set of points
long_n is a vector containing the longitude of the set of points
alt_n is a vector containing the altitude of the set of points, defaults to NA

Examples

```
print(globe(lat_f=23, long_f=112, alt_f=NA, lat_n=c(2, 82), long_n=c(165, -55), alt_n=NA))
[1] 6342.844 7059.080

print(globe(lat_f=23, long_f=112, alt_f=8, lat_n=c(2, 82), long_n=c(165, -55), alt_n=c(8, 8)))
[1] 6342.844 7059.087
```

groupr_df

*groupr_df***Description**

Allow to create groups from a dataframe. Indeed, you can create conditions that lead to a flag value for each cell of the input dataframe according to the cell value. This function is based on `see_df` and `nestr_df2` functions.

Usage

```
groupr_df(inpt_df, condition_lst, val_lst, conjunction_lst, rtn_val_pos = c())
```

Arguments

`inpt_df` is the input dataframe

`condition_lst` is a list containing all the condition as a vector for each group

`val_lst` is a list containing all the values associated with `condition_lst` as a vector for each group

`conjunction_lst` is a list containing all the conjunctions associated with `condition_lst` and `val_lst` as a vector for each group

`rtn_val_pos` is a vector containing all the group flag value like this ex: `c("flag1", "flag2", "flag3")`

Examples

```
interactive()

df1 <- data.frame(c(1, 2, 1), c(45, 22, 88), c(44, 88, 33))

val_lst <- list(list(c(1), c(1)), list(c(2)), list(c(44, 88)))

condition_lst <- list(c(">", "<"), c("%%", "==" , "=="))

conjunction_lst <- list(c("|"), c(), c("|"))

rtn_val_pos <- c("+", "++", "+++")

print(groupr_df(inpt_df=df1, val_lst=val_lst, condition_lst=condition_lst,
conjunction_lst=conjunction_lst, rtn_val_pos=rtn_val_pos))
```

```

      X1  X2  X3
1 <NA>   + +++
2    ++  ++ +++
3 <NA> +++  +

```

id_keepr	<i>id_keepr_df</i>
----------	--------------------

Description

Allow to get the original indexes after multiple equality comparison according to the original number of row

Usage

```
id_keepr(inpt_df, col_v = c(), el_v = c(), rstr_l = NA)
```

Arguments

inpt_df	is the input dataframe
col_v	is the vector containing the column numbers or names to be compared to their respective elements in "el_v"
el_v	is a vector containing the elements that may be contained in their respective column described in "col_v"
rstr_l	is a list containing the vector composed of the indexes of the elements chosen for each comparison. If the length of the list is inferior to the lenght of comparisons, so the last vector of rstr_l will be the same as the last one to fill make rstr_l equal in term of length to col_v and el_v

Examples

```
df1 <- data.frame(c("oui", "oui", "oui", "non", "oui"), c("opui", "op", "op", "zez", "zez"))
print(id_keepr(inpt_df=df1, col_v=c(1, 2), el_v=c("oui", "op")))
[1] 2 3
print(id_keepr(inpt_df=df1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5), c(3, 4))))
[1] 2 3
print(id_keepr(inpt_df=df1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5), c(3))))
[1] 3
print(id_keepr(inpt_df=df1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5))))
[1] 2 3
```

incr_fillr	<i>incr_fillr</i>
------------	-------------------

Description

Take a vector uniquely composed by double and sorted ascendingly, a step, another vector of elements whose length is equal to the length of the first vector, and a default value. If an element of the vector is not equal to its predecessor minus a user defined step, so these can be the output according to the parameters (see example):

Usage

```
incr_fillr(inpt_v, wrk_v = NA, default_val = NA, step = 1)
```

Arguments

inpt_v	is the asending double only composed vector
wrk_v	is the other vector (size equal to inpt_v), defaults to NA
default_val	is the default value put when the difference between two following elements of inpt_v is greater than step, defaults to NA
step	is the allowed difference between two elements of inpt_v

Examples

```
print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
                 wrk_v=NA,
                 default_val="increasing"))

[1] 1 2 3 4 5 6 7 8 9 10

print(incr_fillr(inpt_v=c(1, 1, 2, 4, 5, 9),
                 wrk_v=c("ok", "ok", "ok", "ok", "ok"),
                 default_val=NA))

[1] "ok" "ok" "ok" NA    "ok" "ok" NA    NA    NA

print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
                 wrk_v=NA,
                 default_val="NAN"))

[1] "1"  "2"  "NAN" "4"  "5"  "NAN" "NAN" "NAN" "9"  "10"
```

insert_df	<i>insert_df</i>
-----------	------------------

Description

Allow to insert dataframe into another dataframe according to coordinates (row, column) from the dataframe that will be inserted

Usage

```
insert_df(df_in, df_ins, ins_loc)
```

Arguments

df_in	is the dataframe that will be inserted
df_ins	is the dataset to be inserted
ins_loc	is a vector containg two parameters (row, column) of the begining for the insertion

Examples

```
df1 <- data.frame(c(1, 4), c(5, 3))

df2 <- data.frame(c(1, 3, 5, 6), c(1:4), c(5, 4, 5, "ereer"))

print(insert_df(df_in=df2, df_ins=df1, ins_loc=c(4, 2)))

  c.1..3..5..6. c.1.4. c.5..4..5...ereer..
1             1      1                    5
2             3      2                    4
3             5      3                    5
4             6      1                    5

print(insert_df(df_in=df2, df_ins=df1, ins_loc=c(3, 2)))

  c.1..3..5..6. c.1.4. c.5..4..5...ereer..
1             1      1                    5
2             3      2                    4
3             5      1                    5
4             6      4                    3

print(insert_df(df_in=df2, df_ins=df1, ins_loc=c(2, 2)))

  c.1..3..5..6. c.1.4. c.5..4..5...ereer..
1             1      1                    5
2             3      1                    5
3             5      4                    3
4             6      4                ereer
```

inter_max	<i>inter_max</i>
-----------	------------------

Description

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)) The function will return the list of lists altered according to the maximum step found in the input list.

Usage

```
inter_max(inpt_l, max_ = -1000, get_lst = T)
```

Arguments

inpt_l	is the input list
max_	is a value you are sure is the minimum step value of all the sub-lists
get_lst	is the parameter that, if set to True, will keep the last values of vectors in the return value if the last step exceeds the end value of the vector.

Examples

```
print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=T))

[[1]]
[1] 0 4

[[2]]
[1] 0 4

[[3]]
[1] 1.0 2.3

print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=F))

[[1]]
[1] 0 4

[[2]]
[1] 0 4

[[3]]
[1] 1
```

inter_min

*inter_min***Description**

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)) This function will return the list of vectors with the same steps preserving the begin and end value of each interval. The way the algorithm searches the common step of all the sub-lists is also given by the user as a parameter, see how_to paramaters.

Usage

```
inter_min(
  inpt_l,
  min_ = 1000,
  sensi = 3,
  sensi2 = 3,
  how_to_op = c("divide"),
  how_to_val = c(3)
)
```

Arguments

inpt_l	is the input list containing all the intervals
min_	is a value you are sure is superior to the maximum step value in all the intervals
sensi	is the decimal accuracy of how the difference between each value n to n+1 in an interval is calculated
sensi2	is the decimal accuracy of how the value with the common step is calculated in all the intervals
how_to_op	is a vector containing the operations to perform to the pre-common step value, defaults to only "divide". The operations can be "divide", "subtract", "multiply" or "add". All type of operations can be in this parameter.
how_to_val	is a vector containing the value relatives to the operations in hot_to_op, defaults to 3 output from ex:

Examples

```
print(inter_min(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3))))

[[1]]
[1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
[20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
[39] 3.8 3.9 4.0

[[2]]
[1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
[20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
[39] 3.8 3.9 4.0

[[3]]
```

```
[1] 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1 2.2 2.3
```

isnt_divisible	<i>isnt_divisible</i>
----------------	-----------------------

Description

Takes a vector as an input and returns all the elements that are not divisible by all choosen numbers from another vector.

Usage

```
isnt_divisible(inpt_v = c(), divisible_v = c())
```

Arguments

inpt_v	is the input vector
divisible_v	is the vector containing all the numbers that will try to divide those contained in inpt_v

Examples

```
print(isnt_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

[1] 1 3 7 9 11 13 17 19 21 23 27 29 31 33 37 39 41 43 47
[20] 49 51 53 57 59 61 63 67 69 71 73 77 79 81 83 87 89 91 93
[39] 97 99 101 103 107 109 111
```

is_divisible	<i>is_divisible</i>
--------------	---------------------

Description

Takes a vector as an input and returns all the elements that are divisible by all choosen numbers from another vector.

Usage

```
is_divisible(inpt_v = c(), divisible_v = c())
```

Arguments

inpt_v	is the input vector
divisible_v	is the vector containing all the numbers that will try to divide those contained in inpt_v

Examples

```
print(is_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

[1] 20 40 60 80 100
```

leap_yr	bsx_year
---------	----------

Description

Get if the year is leap

Usage

```
leap_yr(year)
```

Arguments

year is the input year

Examples

```
print(leap_yr(year=2024))

[1] TRUE
```

letter_to_nb	letter_to_nb
--------------	--------------

Description

Allow to get the number of a spreadsheet based column by the letter ex: AAA = 703

Usage

```
letter_to_nb(letter)
```

Arguments

letter is the letter (name of the column)

Examples

```
print(letter_to_nb("rty"))

[1] 12713
```

list_files	<i>list_files</i>
------------	-------------------

Description

A list.files() based function addressing the need of listing the files with extension a or or extension b ...

Usage

```
list_files(patternc, pathc = ".")
```

Arguments

patternc	is a vector containing all the extensions you want
pathc	is the path, can be a vector of multiple path because list.files() supports it.

lst_flatnr	<i>lst_flatnr</i>
------------	-------------------

Description

Flatten a list to a vector

Usage

```
lst_flatnr(inpt_l)
```

Arguments

lst_flatnr	is the input list
------------	-------------------

Examples

```
print(lst_flatnr(inpt_l=list(c(1, 2), c(5, 3), c(7, 2, 7))))
[1] 1 2 5 3 7 2 7
```

multitud

multitud

Description

From a list containing vectors allow to generate a vector following this rule: `list(c("a", "b"), c("1", "2"), c("A", "Z", "E"))` -> `c("a1A", "b1A", "a2A", "b2A", "a1Z, ...)`

Usage

```
multitud(l, sep_ = "")
```

Arguments

`l` is the list

`sep_` is the separator between elements (default is set to "" as you see in the example)

Examples

```
print(multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")

[1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
[8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"
```

nb_to_letter

nb_to_letter

Description

Allow to get the letter of a spreadsheet based column by the number ex: 703 = AAA

Usage

```
nb_to_letter(x)
```

Arguments

`x` is the number of the column

Examples

```
print(nb_to_letter(12713))

[1] "rty"
```

nestr_dfl	<i>nestr_dfl</i>
-----------	------------------

Description

Allow to write a value (1a) to a dataframe (1b) to its cells that have the same coordinates (row and column) than the cells whose value is equal to a another special value (2a), from another another dataframe (2b). The value (1a) depends of the cell value coordinates of the third dataframe (3b). If a cell coordinates (1c) of the first dataframe (1b) does not correspond to the coordinates of a good returning cell value (2a) from the dataframe (2b), so this cell (1c) can have its value changed to the same cell coordinates value (3a) of a third dataframe (4b), if (4b) is not set to NA.

Usage

```
nestr_dfl(inptf_df, inptt_pos_df, nestr_df, yes_val = T, inptt_neg_df = NA)
```

Arguments

inptf_df is the input dataframe (1b)
 inptt_pos_df is the dataframe (2b) that corresponds to the (1a) values
 nestr_df is the dataframe (2b) that has the special value (2a)
 yes_val is the special value (2a)
 inptt_neg_df is the dataframe (4b) that has the (3a) values, defaults to NA

Examples

```
print(nestr_dfl(inptf_df=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_df=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_df=data.frame(c(44, 44, 33), c(12, 12, 12)),
  nestr_df=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))
```

```
  c.1..2..1. c.1..5..7.
1         4        12
2        44        12
3         3         2
```

```
print(nestr_dfl(inptf_df=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_df=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_df=NA,
  nestr_df=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))
```

```
  c.1..2..1. c.1..5..7.
1         4         1
2         2         5
3         3         2
```

nestr_df2	nestr_df2
-----------	-----------

Description

Allow to write a special value (1a) in the cells of a dataframe (1b) that correspond (row and column) to those of another dataframe (2b) that return another special value (2a). The cells whose coordinates do not match the coordinates of the dataframe (2b), another special value can be written (3a) if not set to NA.

Usage

```
nestr_df2(inptf_df, rtn_pos, rtn_neg = NA, nestr_df, yes_val = T)
```

Arguments

- inptf_df is the input dataframe (1b)
- rtn_pos is the special value (1a)
- rtn_neg is the special value (3a)
- nestr_df is the dataframe (2b)
- yes_val is the special value (2a)

Examples

```
print(nestr_df2(inptf_df=data.frame(c(1, 2, 1), c(1, 5, 7)), rtn_pos="yes",
rtn_neg="no", nestr_df=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=T)

c.1..2..1. c.1..5..7.
1      yes      no
2      no       no
3      yes      yes
```

nest_v	nest_v
--------	--------

Description

Nest two vectors according to the following parameters.

Usage

```
nest_v(f_v, t_v, step = 1, after = 1)
```

Arguments

- f_v is the vector that will welcome the nested vector t_v
- t_v is the imbricator vector
- step defines after how many elements of f_v the next element of t_v can be put in the output
- after defines after how many elements of f_v, the begining of t_v can be put

Examples

```
print(nest_v(f_v=c(1, 2, 3, 4, 5, 6), t_v=c("oui", "oui2", "oui3", "oui4", "oui5", "oui6")
[1] "1"    "2"    "oui"  "3"    "4"    "oui2" "5"    "6"    "oui3" "oui4"
```

new_ordered	<i>new_ordered</i>
-------------	--------------------

Description

Returns the indexes of elements contained in "w_v" according to "f_v"

Usage

```
new_ordered(f_v, w_v, nvr_here = NA)
```

Arguments

f_v	is the input vector
w_v	is the vector containing the elements that can be in f_v
nvr_here	is a value you are sure is not present in f_v

Examples

```
print(fittr_v(f_v=c("non", "non", "non", "oui"), w_v=c("oui", "non", "non")))
[1] 4 1 2
```

non_unique	<i>non_unique</i>
------------	-------------------

Description

Returns the element that are not unique from the input vector

Usage

```
non_unique(inpt_v, occu = ">-1-")
```

Arguments

inpt_v	is the input vector containing the elements
occu	is a parameter that specifies the occurrence of the elements that must be returned, defaults to ">-1-" it means that the function will return all the elements that are present more than one time in inpt_v. The syntax is the following "comparaison_type-actual_value-". The comparaison type may be "==" or ">". Occu can also be a vector containing all the occurrence that must have the elements to be returned.

Examples

```
print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non")))
[1] "oui" "non"

print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=="=="))
[1] "oui"

print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu==">-2"))
[1] "non"

print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=c(1,
[1] "non"      "peut"    "peut1"
```

occu	<i>occu</i>
------	-------------

Description

Allow to see the occurrence of each variable in a vector. Returns a dataframe with, as the first column, the all the unique variable of the vector and , in he second column, their occurrence respectively.

Usage

```
occu(inpt_v)
```

Arguments

`inpt_v` the input dataframe

Examples

```
print(occu(inpt_v=c("oui", "peut", "peut", "non", "oui")))

var occurrence
1 oui 2
2 peut 2
3 non 1
```

paste_df	<i>paste_df</i>
----------	-----------------

Description

Return a vector composed of pasted elements from the input dataframe at the same index.

Usage

```
paste_df(inpt_df, sep = "")
```

Arguments

inpt_df	is the input dataframe
sep	is the separator between pasted elements, defaults to ""

Examples

```
print(paste_df(inpt_df=data.frame(c(1, 2, 1), c(33, 22, 55))))
[1] "133" "222" "155"
```

pattern_generator	<i>pattern_generator</i>
-------------------	--------------------------

Description

Allow to create patterns which have a part that is varying randomly each time.

Usage

```
pattern_generator(base_, from_, nb, hmn = 1, after = 1, sep = "")
```

Arguments

base_	is the pattern that will be kept
from_	is the vector from which the elements of the random part will be generated
nb	is the number of random pattern chosen for the varying part
hmn	is how many of varying pattern from the same base will be created
after	is set to 1 by default, it means that the varying part will be after the fixed part, set to 0 if you want the varying part to be before
sep	is the separator between all patterns in the returned value

Examples

```
print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=1, hmn=3))

[1] "ouier" "ouire" "ouier"

print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=2, hmn=3, after=0, se

[1] "er-re-o-u-i" "ere-re-o-u-i" "ere-er-o-u-i"
```

pattern_gettr

pattern_gettr

Description

Search for pattern(s) contained in a vector in another vector and return a list containing matched one (first index) and their position (second index) according to these rules: First case: Search for patterns strictly, it means that the searched pattern(s) will be matched only if the patterns contained in the vector that is being explored by the function are present like this c("pattern_searched", "other", ..., "pattern_searched") and not as c("other_thing pattern_searched other_thing", "other", ..., "pattern_searched other_thing") Second case: It is the opposite to the first case, it means that if the pattern is partially present like in the first position and the last, it will be considered like a matched pattern. REGEX can also be used as pattern

Usage

```
pattern_gettr(
  word_,
  vct,
  occ = c(1),
  strict,
  btwn,
  all_in_word = "yes",
  notatall = "###"
)
```

Arguments

word_	is the vector containing the patterns
vct	is the vector being searched for patterns
occ	a vector containing the occurrence of the pattern in word_ to be matched in the vector being searched, if the occurrence is 2 for the nth pattern in word_ and only one occurrence is found in vct so no pattern will be matched, put "forever" to no longer depend on the occurrence for the associated pattern
strict	a vector containing the "strict" condition for each nth vector in word_ ("strict" is the string to activate this option)
btwn	is a vector containing the condition ("yes" to activate this option) meaning that if "yes", all elements between two matched pattern in vct will be returned, so the patterns you enter in word_ have to be in the order you think it will appear in vct

<code>all_in_word</code>	is a value (default set to "yes", "no" to activate this option) that, if activated, won't authorized a previous matched pattern to be matched again
<code>notatall</code>	is a string that you are sure is not present in <code>vct</code>

Examples

```
print(pattern_gettr(word=c("oui", "non", "erer"), vct=c("oui", "oui", "non", "oui", "non"))
[[1]]
[1] 1 5 8

[[2]]
[1] "oui"  "non"  "opp"  "opp"  "erer"
```

pattern_tuning	<i>pattern_tuning</i>
----------------	-----------------------

Description

Allow to tune a pattern very precisely and output a vector containing its variations n times.

Usage

```
pattern_tuning(  
  patrn,  
  spe_nb,  
  spe_l,  
  exclude_type,  
  hmn = 1,  
  rg = c(1, nchar(patrnr))  
)
```

Arguments

<code>patrn</code>	is the character that will be tuned
<code>spe_nb</code>	is the number of new character that will be replaced
<code>spe_l</code>	is the source vector from which the new characters will replace old ones
<code>exclude_type</code>	is character that won't be replaced
<code>hmn</code>	is how many output the function will return
<code>rg</code>	is a vector with two parameters (index of the first letter that will be replaced, index of the last letter that will be replaced) default is set to all the letters from the source pattern

Examples

```
print(pattern_tuning(patrn="oui", spe_nb=2, spe_l=c("e", "r", "T", "O"), exclude_type="o"))
```

```
[1] "orT" "oTr" "oOi"
```

ptrn_switchr	<i>ptrn_switchr</i>
--------------	---------------------

Description

Allow to switch, copy pattern for each element in a vector. Here a pattern is the values that are separated by a same separator. Example: "xx-xxx-xx" or "xx/xx/xxxx". The xx like values can be swiched or copied from whatever index to whatever index. Here, the index is like this 1-2-3 etcetera, it is relative of the separator.

Usage

```
ptrn_switchr(inpt_l, f_idx_l = c(), t_idx_l = c(), sep = "-", default_val = NA)
```

Arguments

inpt_l	is the input vector
f_idx_l	is a vector containing the indexes of the pattern you want to be altered.
t_idx_l	is a vector containing the indexes to which the indexes in f_idx_l are related.
sep	is the separator, defaults to "-"
default_val	is the default value , if not set to NA, of the pattern at the indexes in f_idx_l. If it is not set to NA, you do not need to fill t_idx_l because this is the vector containing the indexes of the patterns that will be set as new values relatively to the indexes in f_idx_l. Defaults to NA.

Examples

```
print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1, 2, 3), t_idx_l=c(3, 2, 1)))

[1] "11-01-2022" "14-01-2022" "21-01-2022" "01-01-2022"

print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1), default_val="ee"))

[1] "ee-01-11" "ee-01-14" "ee-01-21" "ee-01-01"
```

ptrn_twkr	<i>ptrn_twkr</i>
-----------	------------------

Description

Allow to modify the pattern length of element in a vector according to arguments. What is here defined as a pattern is something like this xx-xx-xx or xx/xx/xxx... So it is defined by the separator

Usage

```
ptrn_twkr(
  inpt_l,
  depth = "max",
  sep = "-",
  default_val = "0",
  add_sep = T,
  end_ = T
)
```

Arguments

<code>inpt_l</code>	is the input vector
<code>depth</code>	is the number (numeric) of separator it will keep as a result. To keep the number of separator of the element that has the minimum amount of separator do <code>depth="min"</code> and <code>depth="max"</code> (character) for the opposite. This value defaults to "max".
<code>sep</code>	is the separator of the pattern, defaults to "-"
<code>default_val</code>	is the default val that will be placed between the separator, defaults to "00"
<code>add_sep</code>	defaults to TRUE. If set to FALSE, it will remove the separator for the patterns that are included in the interval between the depth amount of separator and the actual number of separator of the element.
<code>end_</code>	is if the default_val will be added at the end or at the beginning of each element that lacks length compared to depth

Examples

```
v <- c("2012-06-22", "2012-06-23", "2022-09-12", "2022")

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE)

[1] "2012-06-22" "2012-06-23" "2022-09-12" "2022-00-00"

ptrn_twkr(inpt_l=v, depth=1, sep="-", default_val="00", add_sep=TRUE)

[1] "2012-06" "2012-06" "2022-09" "2022-00"

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE, end_=F)

[1] "2012-06-22" "2012-06-23" "2022-09-12" "00-00-2022"
```

rearangr_v

rearangr_v

Description

Rearranges a vector "w_v" according to another vector "inpt_v". inpt_v contains a sequence of number. inpt_v and w_v have the same size and their indexes are related. The output will be a vector containing all the elements of w_v rearranges in descending or ascending order according to inpt_v

Usage

```
rearangr_v(inpt_v, w_v, how = "increasing")
```

Arguments

<code>inpt_v</code>	is the vector that contains the sequence of number
<code>w_v</code>	is the vector containing the elements related to <code>inpt_v</code>
<code>how</code>	is the way the elements of <code>w_v</code> will be outputed according to if <code>inpt_v</code> will be sorted ascendigly or descendigly

Examples

```
print(rearangr_v(inpt_v=c(23, 21, 56), w_v=c("oui", "peut", "non"), how="decreasing"))
[1] "non" "oui" "peut"
```

<code>regroupr</code>	<i>regroupr</i>
-----------------------	-----------------

Description

Allow to sort data like "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to what you want. For example it can be to "c(X1/Y1/Z1, X1/Y1/Z2, ...)"

Usage

```
regroupr(
  inpt_v,
  sep_ = "-",
  order = c(1:length(unlist(strsplit(x = inpt_v[1], split = sep_)))),
  l_order = NA
)
```

Arguments

<code>inpt_v</code>	is the input vector containing all the data you want to sort in a specific way. All the sub-elements should be separated by a unique separator such as "-" or "/"
<code>sep_</code>	is the unique separator separating the sub-elements in each elements of <code>inpt_v</code>
<code>order</code>	is a vector describing the way the elements should be sorted. For example if you want this dataset "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to be sorted by the last element you should have <code>order=c(3:1)</code> , for example, and it should returns something like this "c(X1/Y1/Z1, X2/Y1/Z1, X1/Y2/Z1, ...)" assuming you have only two values for X.
<code>l_order</code>	is a list containing the vectors of values you want to order first for each sub-elements

Examples

```
vec <- multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")

print(vec)

[1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
[8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"

print(regroupr(inpt_v=vec, sep_="/"))

[1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
[7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/1/18/18"
[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23" "b/2/24/24"

vec <- vec[-2]

print(regroupr(inpt_v=vec, sep_="/"))

[1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
[7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/2/18/18"
[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23"

print(regroupr(inpt_v=vec, sep_="/", order=c(4:1)))

[1] "1/1/A/Q" "2/2/A/Q" "3/3/A/Q" "4/4/A/Q" "5/5/Z/Q" "6/6/Z/Q"
[7] "7/7/Z/Q" "8/8/Z/Q" "9/9/E/Q" "10/10/E/Q" "11/11/E/Q" "12/12/E/Q"
[13] "13/13/A/F" "14/14/A/F" "15/15/A/F" "16/16/A/F" "17/17/Z/F" "18/18/Z/F"
[19] "19/19/Z/F" "20/20/Z/F" "21/21/E/F" "22/22/E/F" "23/23/E/F" "24/24/E/F"
```

save_untl

save_untl

Description

Get the elements in each vector from a list that are located before certain values

Usage

```
save_untl(inpt_l = list(), val_to_stop_v = c())
```

Arguments

`inpt_l` is the input list containing all the vectors

`val_to_stop` is a vector containing the values that marks the end of the vectors returned in the returned list, see the examples

Examples

```
print(save_until(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3, 4))

[[1]]
[1] 1 2

[[2]]
[1] 1 1

[[3]]
[1] 1 2

print(save_until(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3)))

[[1]]
[1] 1 2

[[2]]
[1] 1 1

[[3]]
[1] 1 2 4
```

see_df

see_df

Description

Allow to return a dataframe with special value cells (ex: TRUE) where the condition entered are respected and another special value cell (ex: FALSE) where these are not

Usage

```
see_df(df, condition_l, val_l, conjunction_l = c(), rt_val = T, f_val = F)
```

Arguments

df	is the input dataframe
condition_l	is the vector of the possible conditions ("==", ">", "<", "!=", "%%", "reg", "not_reg", "sup_nchar", "inf_nchar", "nchar") (equal to some elements in a vector, greater than, lower than, not equal to, is divisible by, the regex condition returns TRUE, the regex condition returns FALSE, the length of the elements is strictly superior to X, the length of the element is strictly inferior to X, the length of the element is equal to one element in a vector), you can put the same condition n times.
val_l	is the list of vectors containing the values or vector of values related to condition_l (so the vector of values has to be placed in the same order)
conjunction_l	contains the and or conjunctions, so if the length of condition_l is equal to 3, there will be 2 conjunctions. If the length of conjunction_l is inferior to the length of condition_l minus 1, conjunction_l will match its goal length value with its last argument as the last arguments. For example, c("&", "I", "&") with a goal length value of 5 -> c("&", "I", "&", "&", "&")

rt_val is a special value cell returned when the conditions are respected
 f_val is a special value cell returned when the conditions are not respected

Details

This function will return an error if number only comparative conditions are given in addition to having character values in the input dataframe.

Examples

```
df1 <- data.frame(c(1, 2, 4), c("a", "a", "zu"))

print(see_df(df=df1, condition_l=c("nchar"), val_l=list(c(1))))

      X1    X2
1 TRUE  TRUE
2 TRUE  TRUE
3 TRUE FALSE

print(see_df(df=df1, condition_l=c("=="), val_l=list(c("a", 1))))

      X1    X2
1 TRUE  TRUE
2 FALSE TRUE
3 FALSE FALSE

print(see_df(df=df1, condition_l=c("nchar"), val_l=list(c(1, 2))))

      X1    X2
1 TRUE  TRUE
2 TRUE  TRUE
3 TRUE  TRUE

print(see_df(df=df1, condition_l=c("not_reg"), val_l=list("[a-z]")))

      X1    X2
1 TRUE FALSE
2 TRUE FALSE
3 TRUE FALSE
```

 see_file

see_file

Description

Allow to get the filename or its extension

Usage

```
see_file(string_, index_ext = 1, ext = T)
```

Arguments

string_	is the input string
index_ext	is the occurrence of the dot that separates the filename and its extension
ext	is a boolean that if set to TRUE, will return the file extension and if set to FALSE, will return filename

Examples

```
print(see_file(string_="file.abc.xyz"))

[1] ".abc.xyz"

print(see_file(string_="file.abc.xyz", ext=F))

[1] "file"

print(see_file(string_="file.abc.xyz", index_ext=2))

[1] ".xyz"
```

see_idx

see_idx

Description

Returns a boolean vector to see if a set of elements contained in v1 is also contained in another vector (v2)

Usage

```
see_idx(v1, v2, exclude_val = "#####")
```

Arguments

v1	is the first vector
v2	is the second vector

Examples

```
print(see_idx(v1=c("oui", "non", "peut", "oo"), v2=c("oui", "peut", "oui")))

[1] TRUE FALSE TRUE FALSE
```

see_inside

see_inside

Description

Return a list containing all the column of the files in the current directory with a chosen file extension and its associated file and sheet if `xlsx`. For example if i have 2 files "out.csv" with 2 columns and "out.xlsx" with 1 column for its first sheet and 2 for its second one, the return will look like this: `c(column_1, column_2, column_3, column_4, column_5, unique_separator, "1-2-out.csv", "3-3-sheet_1-out.xlsx", 4-5-sheet_2-out.xlsx)`

Usage

```
see_inside(pattern_, path_ = ".", sep_ = c(", "), unique_sep = "#####", rec = F)
```

Arguments

<code>pattern_</code>	is a vector containin the file extension of the spreadsheets ("xlsx", "csv"...)
<code>path_</code>	is the path where are located the files
<code>sep_</code>	is a vector containing the separator for each csv type file in order following the operating system file order, if the vector does not match the number of the csv files found, it will assume the separator for the rest of the files is the same as the last csv file found. It means that if you know the separator is the same for all the csv type files, you just have to put the separator once in the vector.
<code>unique_sep</code>	is a pattern that you know will never be in your input files
<code>rec</code>	is a boolean allows to get files recursively if set to TRUE, defaults to TRUE If <code>x</code> is the return value, to see all the files name, position of the columns and possible sheet name associanted with, do the following: Examples: <code>print(x[(grep(unique_sep, x)+1):length(x)])</code> #If you just want to see the columns do the following: <code>print(x[1:(grep(unique_sep, x) - 1)])</code>

str_remove_until

str_remove_until

Description

Allow to remove pattern within elements from a vector precisely according to their occurrence.

Usage

```
str_remove_until(
  inpt_v,
  ptrn_rm_v = c(),
  until = list(c(1)),
  nvr_following_ptrn = "NA"
)
```

Arguments

- inpt_v is the input vector
- ptrn_rm_v is a vector containing the patterns to remove
- until is a list containing the occurrence(s) of each pattern to remove in the elements.
- nvr_following_ptrn is a sequel of characters that you are sure is not present in any of the elements in inpt_v

Examples

```
vec <- c("45/56-/98mm", "45/56-/98mm", "45/56-/98-mm/")

print(str_remove_until(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1))))

[1] "4556/98mm" "4556/98mm" "4556/98mm/"

print(str_remove_until(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1:2))))

[1] "455698mm" "455698mm" "455698mm/"

print(str_remove_until(inpt_v=vec[1], ptrn_rm_v=c("-", "/"), until=c("max")))

[1] "455698mm" "455698mm" "455698mm"
```

unique_df	<i>unique_df</i>
-----------	------------------

Description

Returns the input dataframe with the unique columns or rows.

Usage

```
unique_df(inpt_df, col = F)
```

Arguments

- inpt_df is the input dataframe
- col is a parameter that specifies if the dataframe returned should have unique columns or rows, defaults to F, so the dataframe returned by default has unique rows

Examples

```
df1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"))

print(unique_df(inpt_df=df1))

c.1..2..1..3. c..a....z....a....p..
1             1             a
2             2             z
4             3             p
```



```
df1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"), c(1, 2, 1, 3))

print(unique_df(inpt_df=df1, col=T))
```

```
  cur_v cur_v
1     1     a
2     2     z
3     1     a
4     3     p
```

unique_ltr_from_v	<i>unique_ltr_from_v</i>
-------------------	--------------------------

Description

Returns the unique characters contained in all the elements from an input vector "inpt_v"

Usage

```
unique_ltr_from_v(inpt_v, keep_v = c("?", "!", ":", "&", ",", ".", letters))
```

Arguments

inpt_v	is the input vector containing all the elements
keep_v	is the vector containing all the characters that the elements in inpt_v may contain

Examples

```
print(unique_ltr_from_v(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "a
[1] "b" "o" "n" "j" "u" "r" "l" "p" "e" "c" "a" "v" "i"
```

unique_pos	<i>unique_pos</i>
------------	-------------------

Description

Allow to find indexes of the unique values from a vector.

Usage

```
unique_pos(vec)
```

Arguments

vec	is the input vector
-----	---------------------

Examples

```
print(unique_pos(c(3, 4, 3, 5, 6)))
[1] 1 2 4 5
```

until_stnl	<i>until_stnl</i>
------------	-------------------

Description

Maxes a vector to a chosen length ex: if i want my vector c(1, 2) to be 5 of length this function will return me: c(1, 2, 1, 2, 1)

Usage

```
until_stnl(vec1, goal)
```

Arguments

- vec1 is the input vector
- goal is the length to reach

Examples

```
print(until_stnl(vec1=c(1, 3, 2), goal=56))  
  
[1] 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3  
[39] 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3
```

val_replacer	<i>val_replacer</i>
--------------	---------------------

Description

Allow to replace value from dataframe to another one.

Usage

```
val_replacer(df, val_replaced, val_replacor = T, df_rpt = NA)
```

Arguments

- df is the input dataframe
- val_replaced is a vector of the value(s) to be replaced
- val_replacor is the value that will replace val_replaced

Examples

```
print(val_replacer(df=data.frame(c(1, "oo4", T, F), c(T, F, T, T)), val_replaced=c(T), va  
  
c.1...oo4...T..F. c.T..F..T..T.  
1 1 NA  
2 oo4 FALSE  
3 NA NA  
4 FALSE NA
```

vector_replacor	<i>vector_replacor</i>
-----------------	------------------------

Description

Allow to replace certain values in a vector.

Usage

```
vector_replacor(inpt_v = c(), sus_val = c(), rpl_val = c(), grep_ = F)
```

Arguments

inpt_v	is the input vector
sus_val	is a vector containing all the values that will be replaced
rpl_val	is a vector containing the value of the elements to be replaced (sus_val), so sus_val and rpl_val should be the same size
grep_	is if the elements in sus_val should be equal to the elements to replace in inpt_v or if they just should found in the elements

Examples

```
print(vector_replacor(inpt_v=c(1:15), sus_val=c(3, 6, 8, 12), rpl_val=c("oui", "non", "e")

[1] "1"   "2"   "oui" "4"   "5"   "non" "7"   "e"   "9"   "10"  "11"  "a"
[13] "13"  "14"  "15"
```

```
print(vector_replacor(inpt_v=c("non", "zez", "pp a ftf", "fdfd", "assistance", "ert", "re

[1] "non" "zez" "oui" "fdfd" "non" "ert" "non" "zz"
```

vec_in_df	<i>vec_in_df</i>
-----------	------------------

Description

Allow to get if a vector is in a dataframe. Returns the row and column of the vector in the dataframe if the vector is contained in the dataframe.

Usage

```
vec_in_df(inpt_df, inpt_vec = c(), coeff = 0, stop_untl = 1, conventional = F)
```

Arguments

inpt_df	is the input dataframe
inpt_vec	is the vector that may be in the input dataframe
coeff	is the "slope coefficient" of inpt_vec
stop_untl	is the maximum number of the input vector the function returns, if in the dataframe
conventinal	is if a positive slope coefficient means that the vector goes upward or downward

Examples

```
df1 <- data.frame(c(1:5), c(5:1), c("a", "z", "z", "z", "a"))

print(df1)

  c.1.5. c.5.1. c..a....z....z....z....a..
1      1      5                               a
2      2      4                               z
3      3      3                               z
4      4      2                               z
5      5      1                               a

print(vec_in_df(inpt_df=df1, inpt_vec=c(5, 4, "z"), coeff=1))

NULL

print(vec_in_df(inpt_df=df1, inpt_vec=c(5, 2, "z"), coeff=1))

[1] 5 1

print(vec_in_df(inpt_df=df1, inpt_vec=c(3, "z"), coeff=1))

[1] 3 2

print(vec_in_df(inpt_df=df1, inpt_vec=c(4, "z"), coeff=-1))

[1] 2 2

print(vec_in_df(inpt_df=df1, inpt_vec=c(2, 3, "z"), coeff=-1))

[1] 2 1

print(vec_in_df(inpt_df=df1, inpt_vec=c(5, 2, "z"), coeff=-1, conventional=T))

[1] 5 1

df1[4, 2] <- 1

print(vec_in_df(inpt_df=df1, inpt_vec=c(1, "z"), coeff=-1, conventional=T, stop_untl=4))

[1] 4 2 5 2
```

vlookup_df	<i>vlookup_df</i>
------------	-------------------

Description

Allow to perform a vlookup on a dataframe

Usage

```
vlookup_df(df, v_id, col_id = 1, included_col_id = "yes")
```

Arguments

df is the input dataframe

v_id is a vector containing the ids

col_id is the column that contains the ids (default is equal to 1)

included_col_id is if the result should return the col_id (default set to yes)

Examples

```
df1 <- data.frame(c("az1", "az3", "az4", "az2"), c(1:4), c(4:1))

print(vlookup_df(df=df1, v_id=c("az1", "az2", "az3", "az4")))
```

	c..az1....az3....az4....az2..	c.1.4.	c.4.1.
2	az1	1	4
4	az2	4	1
21	az3	2	3
3	az4	3	2

wider_df

*wider_df***Description**

Takes a dataframe as an input and the column to split according to a separator.

Usage

```
wider_df(inpt_df, col_to_splt = c(), sep_ = "-")
```

Arguments

inpt_df is the input dataframe

col_to_splt is a vector containing the number or the colnames of the columns to split according to a separator

sep_ is the separator of the elements to split to new columns in the input dataframe

Examples

```
df1 <- data.frame(c(1:5), c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"), c(5:1))

df2 <- data.frame(c(1:5), c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"))

print(wider_df(inpt_df=df1, col_to_splt=c(2), sep_="-"))
```

	pre_df	X.o.	X.y.
o-y	1	"o"	"y" 5
hj-yy	2	"hj"	"yy" 4
er-y	3	"er"	"y" 3
k-ll	4	"k"	"ll" 2
ooo-mm	5	"ooo"	"mm" 1

```
print(wider_df(inpt_df=df2, col_to_splt=c(2), sep="-"))
```

```
pre_df X.o. X.y.  
o-y    1    "o"  "y"  
hj-yy  2    "hj" "yy"  
er-y   3    "er"  "y"  
k-ll   4    "k"   "ll"  
ooo-mm 5    "ooo" "mm"
```

Index

1:(grep(unique_sep, x) - 1), 55
1, 55
all_stat, 3
any_join_df, 4
appndr, 6
better_match, 7
can_be_num, 7
closer_ptrn, 8
closer_ptrn_adv, 10
clusterizer_v, 11
colins_df, 14
converter_date, 15
converter_format, 16
cost_and_taxes, 16
cut_v, 17
data_gen, 18
data_meshup, 20
date_addr, 21
date_converter_reverse, 22
dcr_untl, 23
dcr_val, 24
diff_xlsx, 24
equalizer_v, 25
extrt_only_v, 26
fillr, 26
fixer_nest_v, 27
fold_rec, 27
fold_rec2, 28
format_date, 28
geo_min, 29
get_rec, 30
globe, 30
groupr_df, 31
id_keepr, 32
incr_fillr, 33
insert_df, 34
inter_max, 35
inter_min, 36
is_divisible, 37
isnt_divisible, 37
leap_yr, 38
letter_to_nb, 38
list_files, 39
lst_flatnr, 39
multitud, 40
nb_to_letter, 40
nest_v, 42
nestr_df1, 41
nestr_df2, 42
new_ordered, 43
non_unique, 43
occu, 44
paste_df, 45
pattern_generator, 45
pattern_gettr, 46
pattern_tuning, 47
ptrn_switchr, 48
ptrn_twkr, 48
rearangr_v, 49
regroupr, 50
save_untl, 51
see_df, 52
see_file, 53
see_idx, 54
see_inside, 55
str_remove_untl, 55
unique_df, 56
unique_ltr_from_v, 57
unique_pos, 57
until_stnl, 58
val_replacer, 58
vec_in_df, 59

`vector_replacor`, [59](#)

`vlookup_df`, [60](#)

`wider_df`, [61](#)