

Package ‘edm1’

March 24, 2024

Title Simplify complex data manipulation

Version 0.0.0.9000

Description Simplify complex data manipulation.

License GPL (==3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports stringr,
stringi,
openxlsx

R topics documented:

all_stat	3
any_join_datf	4
appndr	6
better_match	7
can_be_num	7
closer_ptrn	8
closer_ptrn_adv	10
clusterizer_v	12
colins_datf	14
converter_date	15
converter_format	16
cost_and_taxes	17
cut_v	18
data_gen	18
data_meshup	20
date_addr	21
date_converter_reverse	23
dcr_untl	23
dcr_val	24
equalizer_v	25
extrt_only_v	25
fillr	26
fixer_nest_v	26
fold_rec	27

fold_rec2	27
format_date	28
geo_min	28
get_rec	29
globe	29
groupr_datf	30
id_keepr	31
incr_fillr	32
insert_datf	33
inter_max	34
inter_min	35
isnt_divisible	36
is_divisible	36
leap_yr	37
letter_to_nb	37
list_files	38
lst_flatnr	38
multitud	39
nb_to_letter	39
nestr_datf1	40
nestr_datf2	41
nest_v	41
new_ordered	42
non_unique	43
occu	43
paste_datf	44
pattern_generator	44
pattern_gettr	45
pattern_tuning	46
ptrn_switchr	47
ptrn_twkr	48
rearangr_v	49
regroupr	50
save_untl	51
see_datf	52
see_file	53
see_idx	54
see_inside	54
str_remove_untl	55
unique_datf	56
unique_ltr_from_v	57
unique_pos	57
until_stnl	58
val_replacer	58
vector_replacor	59
vec_in_datf	59
vlookup_datf	61
wider_datf	61

all_stat	<i>all_stat</i>
----------	-----------------

Description

Allow to see all the main statistics indicators (mean, median, variance, standard deviation, sum, max, min, quantile) of variables in a dataframe by the modality of a variable in a column of the input datarame. In addition to that, you can get the occurrence of other qualitative variables by your chosen qualitative variable, you have just to precise it in the vector "stat_var" where all the statistics indicators are given with "occu-var_you_want/".

Usage

```
all_stat(inpt_v, var_add = c(), stat_var = c(), inpt_datf)
```

Arguments

inpt_v is the modalities of the variables
var_add is the variables you want to get the stats from
stat_var is the stats indicators you want
inpt_datf is the input dataframe

Examples

```
datf <- data.frame("mod"=c("first", "seco", "seco", "first", "first", "third", "first"),
  "var1"=c(11, 22, 21, 22, 22, 11, 9),
  "var2"=c("d", "d", "z", "z", "z", "d", "z"),
  "var3"=c(45, 44, 43, 46, 45, 45, 42),
  "var4"=c("A", "A", "A", "A", "B", "C", "C"))

print(all_stat(inpt_v=c("first", "seco"), var_add = c("var1", "var2", "var3", "var4"),
  stat_var=c("sum", "mean", "median", "sd", "occu-var2/", "occu-var4/", "variance", "quantile-0.75"),
  inpt_datf=datf))

#   modal_v var_vector occu sum mean  med standard_devaition      variance
#1      first
#2          var1      64   16 16.5   6.97614984548545 48.6666666666667
#3          var2-d      1
#4          var2-z      3
#5          var3     178 44.5   45   1.73205080756888      3
#6          var4-A      2
#7          var4-B      1
#8          var4-C      1
#9      seco
#10         var1     43 21.5 21.5   0.707106781186548      0.5
#11         var2-d      1
#12         var2-z      1
#13         var3     87 43.5 43.5   0.707106781186548      0.5
#14         var4-A      2
#15         var4-B      0
#16         var4-C      0
#   quantile-0.75
#1
```

```
#2          22
#3
#4
#5          45.25
#6
#7
#8
#9
#10         21.75
#11
#12
#13         43.75
#14
#15
#16
```

any_join_datf	<i>any_join_datf</i>
---------------	----------------------

Description

Allow to perform SQL joints with more features

Usage

```
any_join_datf(
  inpt_datf_l,
  join_type = "inner",
  join_spe = NA,
  id_v = c(),
  excl_col = c(),
  rtn_col = c(),
  d_val = NA
)
```

Arguments

<code>inpt_datf_l</code>	is a list containing all the dataframe
<code>join_type</code>	is the joint type. Defaults to inner but can be changed to a vector containing all the dataframes you want to take their ids to don external joints.
<code>join_spe</code>	can be equal to a vector to do an external joints on all the dataframes. In this case, <code>join_type</code> should not be equal to "inner"
<code>id_v</code>	is a vector containing all the ids name of the dataframes. The ids names can be changed to number of their columns taking in count their position in <code>inpt_datf_l</code> . It means that if my id is in the third column of the second dataframe and the first dataframe have 5 columns, the column number of the ids is $5 + 3 = 8$
<code>excl_col</code>	is a vector containing the column names to exclude, if this vector is filled so "rtn_col" should not be filled. You can also put the column number in the manner indicated for "id_v". Defaults to <code>c()</code>

`rtn_col` is a vector containing the column names to retain, if this vector is filled so "`excl_col`" should not be filled. You can also put the column number in the manner indicated for "`id_v`". Defaults to `c()`

`d_val` is the default val when here is no match

Examples

```
datf1 <- data.frame("val"=c(1, 1, 2, 4), "ids"=c("e", "a", "z", "a"),
  "last"=c("oui", "oui", "non", "oui"),
  "second_ids"=c(13, 11, 12, 8), "third_col"=c(4:1))
```

```
datf2 <- data.frame("val"=c(3, 7, 2, 4, 1, 2), "ids"=c("a", "z", "z", "a", "a", "a"),
  "bool"=c(TRUE, FALSE, FALSE, FALSE, TRUE, TRUE),
  "second_ids"=c(13, 12, 8, 34, 22, 12))
```

```
datf3 <- data.frame("val"=c(1, 9, 2, 4), "ids"=c("a", "a", "z", "a"),
  "last"=c("oui", "oui", "non", "oui"),
  "second_ids"=c(13, 11, 12, 8))
```

```
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type="inner",
  id_v=c("ids", "second_ids"),
  excl_col=c(), rtn_col=c()))
```

```
# ids val ids last second_ids val ids bool second_ids val ids last second_ids
#3 z12 2 z non 12 7 z FALSE 12 2 z non 12
```

```
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type="inner", id_v=c("ids",
  excl_col=c(), rtn_col=c()))
```

```
# ids val ids last second_ids val ids bool second_ids val ids last second_ids
#2 a 1 a oui 11 3 a TRUE 13 1 a oui 13
#3 z 2 z non 12 7 z FALSE 12 2 z non 12
#4 a 4 a oui 8 4 a FALSE 34 9 a oui 11
```

```
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type=c(1), id_v=c("ids"),
  excl_col=c(), rtn_col=c()))
```

```
# ids val ids last second_ids val ids bool second_ids val ids last
#1 e 1 e oui 13 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#2 a 1 a oui 11 3 a TRUE 13 1 a oui
#3 z 2 z non 12 7 z FALSE 12 2 z non
#4 a 4 a oui 8 4 a FALSE 34 9 a oui
# second_ids
#1 <NA>
#2 13
#3 12
#4 11
```

```
print(any_join_datf(inpt_datf_l=list(datf2, datf1, datf3), join_type=c(1, 3), id_v=c("ids",
  excl_col=c(), rtn_col=c()))
```

```
# ids val ids bool second_ids val ids last second_ids val ids last
#1 a13 3 a TRUE 13 <NA> <NA> <NA> <NA> 1 a oui
#2 z12 7 z FALSE 12 2 z non 12 2 z non
#3 z8 2 z FALSE 8 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#4 a34 4 a FALSE 34 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#5 a22 1 a TRUE 22 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
```

```
#6 a12      2      a TRUE          12 <NA> <NA> <NA>          <NA> <NA> <NA> <NA>
#7 a13 <NA> <NA> <NA>          <NA> <NA> <NA> <NA>          <NA> <NA> <NA> <NA>
#8 a11 <NA> <NA> <NA>          <NA>      1      a oui          11      9      a oui
#9 z12 <NA> <NA> <NA>          <NA> <NA> <NA> <NA>          <NA> <NA> <NA> <NA>
#10 a8 <NA> <NA> <NA>          <NA>      4      a oui          8      4      a oui
# second_ids
#1      13
#2      12
#3      <NA>
#4      <NA>
#5      <NA>
#6      <NA>
#7      <NA>
#8      11
#9      <NA>
#10     8

print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type=c(1), id_v=c("ids"),
                    excl_col=c(), rtn_col=c()))

#ids val ids last second_ids val ids bool second_ids val ids last
#1 e 1 e oui 13 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#2 a 1 a oui 11 3 a TRUE 13 1 a oui
#3 z 2 z non 12 7 z FALSE 12 2 z non
#4 a 4 a oui 8 4 a FALSE 34 9 a oui
# second_ids
#1 <NA>
#2 13
#3 12
#4 11
```

appndr	<i>appndr</i>
--------	---------------

Description

Append to a vector "inpt_v" a special value "val" n times "mmn". The appending begins at "strt" index.

Usage

```
appndr(inpt_v, val = NA, hmn, strt = "max")
```

Arguments

- inpt_v is the input vector
- val is the special value
- hmn is the number of special value element added
- strt is the index from which appending begins, defaults to max which means the end of "inpt_v"

Examples

```
print(appndr(inpt_v=c(1:3), val="oui", hmn=5))

#[1] "1"    "2"    "3"    "oui" "oui" "oui" "oui" "oui"

print(appndr(inpt_v=c(1:3), val="oui", hmn=5, strt=1))

#[1] "1"    "oui" "oui" "oui" "oui" "oui" "2"    "3"
```

better_match	<i>better_match</i>
--------------	---------------------

Description

Allow to get the nth element matched in a vector

Usage

```
better_match(inpt_v = c(), ptrn, until = 1, nvr_here = NA)
```

Arguments

inpt_v	is the input vector
ptrn	is the pattern to be matched
until	is the maximum number of matched pattern outputed
nvr_here	is a value you are sure is not present in inpt_v

Examples

```
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=1))

#[1] 3

print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=5))

#[1] 3 13 16
```

can_be_num	<i>can_be_num</i>
------------	-------------------

Description

Return TRUE if a variable can be converted to a number and FALSE if not (supports float)

Usage

```
can_be_num(x)
```

Arguments

`x` is the input value

Examples

```
print(can_be_num("34.677"))

#[1] TRUE

print(can_be_num("34"))

#[1] TRUE

print(can_be_num("3rt4"))

#[1] FALSE

print(can_be_num(34))

#[1] TRUE
```

`closer_ptrn`

closer_ptrn

Description

Take a vector of patterns as input and output each chosen word with their closest patterns from chosen patterns.

Usage

```
closer_ptrn(
  inpt_v,
  base_v = c("?", letters),
  excl_v = c(),
  rtn_v = c(),
  sub_excl_v = c(),
  sub_rtn_v = c()
)
```

Arguments

`inpt_v` is the input vector containing all the patterns

`base_v` must contain all the characters that the patterns are susceptible to contain, defaults to `c("?", letters)`. "?" is necessary because it is internally the default value added to each element that does not have a sufficient length compared to the longest pattern in `inpt_v`. If set to NA, the function will find by itself the elements to be filled with but it may take an extra time

`excl_v` is the vector containing all the patterns from `inpt_v` to exclude for comparing them to others patterns. If this parameter is filled, so `"rtn_v"` must be empty.

`rtn_v` is the vector containing all the patterns from `inpt_v` to keep for comparing them to others patterns. If this parameter is filled, so `"rtn_v"` must be empty.

`sub_excl_v` is the vector containing all the patterns from `inpt_v` to exclude for using them to compare to another pattern. If this parameter is filled, so `"sub_rtn_v"` must be empty.

`sub_rtn_v` is the vector containing all the patterns from `inpt_v` to retain for using them to compare to another pattern. If this parameter is filled, so `"sub_excl_v"` must be empty.

Examples

```
print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir")

#[[1]]
#[1] "bonjour"
#
#[[2]]
#[1] "lpoerc"      "nonnour"      "bonnour"      "nonjour"      "aurevoir"
#
#[[3]]
#[1] 1 1 2 7 8
#
#[[4]]
#[1] "lpoerc"
#
#[[5]]
#[1] "bonjour"      "nonnour"      "bonnour"      "nonjour"      "aurevoir"
#
#[[6]]
#[1] 7 7 7 7 7
#
#[[7]]
#[1] "nonnour"
#
#[[8]]
#[1] "bonjour"      "lpoerc"      "bonnour"      "nonjour"      "aurevoir"
#
#[[9]]
#[1] 1 1 2 7 8
#
#[[10]]
#[1] "bonnour"
#
#[[11]]
#[1] "bonjour"      "lpoerc"      "nonnour"      "nonjour"      "aurevoir"
#
#[[12]]
#[1] 1 1 2 7 8
#
#[[13]]
#[1] "nonjour"
#
#[[14]]
#[1] "bonjour"      "lpoerc"      "nonnour"      "bonnour"      "aurevoir"
#
#[[15]]
```

```

#[1] 1 1 2 7 8
#
#[[16]]
#[1] "aurevoir"
#
#[[17]]
#[1] "bonjour" "lpoerc" "nonnour" "bonnour" "nonjour"
#
#[[18]]
#[1] 7 8 8 8 8

print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir",
                           sub_excl_v=c("nonnour"))))

#[1] 3 5
#[[1]]
#[1] "bonjour"
#
#[[2]]
#[1] "lpoerc" "bonnour" "nonjour" "aurevoir"
#
#[[3]]
#[1] 1 1 7 8
#
#[[4]]
#[1] "lpoerc"
#
#[[5]]
#[1] "bonjour" "bonnour" "nonjour" "aurevoir"
#
#[[6]]
#[1] 7 7 7 7
#
#[[7]]
#[1] "bonnour"
#
#[[8]]
#[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"
#
#[[9]]
#[1] 0 1 2 7 8
#
#[[10]]
#[1] "aurevoir"
#
#[[11]]
#[1] "bonjour" "lpoerc" "nonjour" "aurevoir"
#
#[[12]]
#[1] 0 7 8 8

```

Description

Allow to find how patterns are far or near between each other relatively to a vector containing characters at each index ("base_v"). The function gets the sum of the indexes of each pattern letter relatively to the characters in base_v. So each pattern can be compared.

Usage

```
closer_ptrn_adv(
  inpt_v,
  res = "raw_stat",
  default_val = "?",
  base_v = c(default_val, letters),
  c_word = NA
)
```

Arguments

inpt_v	is the input vector containing all the patterns to be analyzed
res	is a parameter controlling the result. If set to "raw_stat", each word in inpt_v will come with its score (indexes of its letters relatively to base_v). If set to something else, so "c_word" parameter must be filled.
default_val	is the value that will be added to all patterns that do not equal the length of the longest pattern in inpt_v. Those get this value added to make all patterns equal in length so they can be compared, defaults to "?"
base_v	is the vector from which all pattern get its result (letters indexes for each pattern relatively to base_v), defaults to c("default_val", letters). "default_val" is another parameter and letters is all the western alphabetic letters in a vector
c_word	is a pattern from which the nearest to the farthest pattern in inpt_v will be compared

Examples

```
print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois", "bonjour")

#[[1]]
#[1] 1 5 15 17 38 65
#
#[[2]]
#[1] "bonjour" "bonnour" "aurevoir" "nonnour" "mois" "fin"

print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois")))

#[[1]]
#[1] 117 107 119 37 64
#
#[[2]]
#[1] "aurevoir" "bonnour" "nonnour" "fin" "mois"
```

clusterizer_v	<i>clusterizer_v</i>
---------------	----------------------

Description

Allow to output clusters of elements. Takes as input a vector "inpt_v" containing a sequence of number. Can also take another vector "w_v" that has the same size of inpt_v because its elements are related to it. The way the clusters are made is related to an accuracy value which is "c_val". It means that if the difference between the values associated to 2 elements is superior to c_val, these two elements are in distinct clusters. The second element of the outputed list is the begin and end value of each cluster.

Usage

```
clusterizer_v(inpt_v, w_v = NA, c_val)
```

Arguments

inpt_v	is the vector containing the sequence of number
w_v	is the vector containing the elements related to inpt_v, defaults to NA
c_val	is the accuracy of the clusterization

Examples

```
print(clusterizer_v(inpt_v=sample.int(20, 26, replace=TRUE), w_v=NA, c_val=0.9))

# [[1]]
# [[1]] [[1]]
# [1] 1
#
# [[1]] [[2]]
# [1] 2
#
# [[1]] [[3]]
# [1] 3
#
# [[1]] [[4]]
# [1] 4
#
# [[1]] [[5]]
# [1] 5 5
#
# [[1]] [[6]]
# [1] 6 6 6 6
#
# [[1]] [[7]]
# [1] 7 7 7
#
# [[1]] [[8]]
# [1] 8 8 8
#
# [[1]] [[9]]
# [1] 9
```

```

#
#[[1]][[10]]
#[1] 10
#
#[[1]][[11]]
#[1] 12
#
#[[1]][[12]]
#[1] 13 13 13
#
#[[1]][[13]]
#[1] 18 18 18
#
#[[1]][[14]]
#[1] 20
#
#
#[[2]]
# [1] "1" "1" "-" "2" "2" "-" "3" "3" "-" "4" "4" "-" "5" "5" "-"
#[16] "6" "6" "-" "7" "7" "-" "8" "8" "-" "9" "9" "-" "10" "10" "-"
#[31] "12" "12" "-" "13" "13" "-" "18" "18" "-" "20" "20"

print(clusterizer_v(inpt_v=sample.int(40, 26, replace=TRUE), w_v=letters, c_val=0.29))

#[[1]]
#[[1]][[1]]
#[1] "a"
#
#[[1]][[2]]
#[1] "b"
#
#[[1]][[3]]
#[1] "c" "d"
#
#[[1]][[4]]
#[1] "e" "f"
#
#[[1]][[5]]
#[1] "g" "h" "i" "j"
#
#[[1]][[6]]
#[1] "k"
#
#[[1]][[7]]
#[1] "l"
#
#[[1]][[8]]
#[1] "m" "n"
#
#[[1]][[9]]
#[1] "o"
#
#[[1]][[10]]
#[1] "p"
#
#[[1]][[11]]
#[1] "q" "r"

```

```

#
#[[1]][[12]]
#[1] "s" "t" "u"
#
#[[1]][[13]]
#[1] "v"
#
#[[1]][[14]]
#[1] "w"
#
#[[1]][[15]]
#[1] "x"
#
#[[1]][[16]]
#[1] "y"
#
#[[1]][[17]]
#[1] "z"
#
#
#[[2]]
# [1] "13" "13" "-" "14" "14" "-" "15" "15" "-" "16" "16" "-" "17" "17" "-"
#[16] "19" "19" "-" "21" "21" "-" "22" "22" "-" "23" "23" "-" "25" "25" "-"
#[31] "27" "27" "-" "29" "29" "-" "30" "30" "-" "31" "31" "-" "34" "34" "-"
#[46] "35" "35" "-" "37" "37"

```

colins_datf

colins_datf

Description

Allow to insert vectors into a dataframe.

Usage

```
colins_datf(inpt_datf, target_col = list(), target_pos = list())
```

Arguments

inpt_datf	is the dataframe where vectors will be inserted
target_col	is a list containing all the vectors to be inserted
target_pos	is a list containing the vectors made of the columns names or numbers where the associated vectors from target_col will be inserted after

Examples

```

datf1 <- data.frame("frst_col"=c(1:5), "scd_col"=c(5:1))

print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
  target_pos=list(c("frst_col", "scd_col"), c("scd_col"))))

# frst_col cur_col scd_col cur_col.1 cur_col

```

```
#1      1      oui      5      oui      u
#2      2      oui      4      oui      z
#3      3      oui      3      oui      z
#4      4      non      2      non      z
#5      5      non      1      non      u

print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
target_pos=list(c(1, 2), c("first_col"))))

#  first_col cur_col scd_col cur_col cur_col
#1      1      oui      5      u      oui
#2      2      oui      4      z      oui
#3      3      oui      3      z      oui
#4      4      non      2      z      non
#5      5      non      1      u      non
```

converter_date	converter_date
----------------	----------------

Description

Allow to convert any date like second/minute/hour/day/month/year to either second, minute...year. The input date should not necessarily have all its time units (second, minute...) but all the time units according to a format. Example: "snhdmy" is for second, hour, minute, day, month, year. And "mdy" is for month, day, year.

Usage

```
converter_date(inpt_date, convert_to, frmt = "snhdmy", sep_ = "-")
```

Arguments

- inpt_date is the input date
- convert_to is the time unit the input date will be converted ("s", "n", "h", "d", "m", "y")
- frmt is the format of the input date
- sep_ is the separator of the input date. For example this input date "12-07-2012" has "-" as a separator

Examples

```
print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="m"))

#[1] 24299.15

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="y"))

#[1] 2024.929

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="s"))

#[1] 63900626400
```

```
print(converter_date(inpt_date="63900626400", sep="-", frmt="s", convert_to="y"))
#[1] 2024.929

print(converter_date(inpt_date="2024", sep="-", frmt="y", convert_to="s"))
#[1] 63873964800
```

```
converter_format      converter_format
```

Description

Allow to convert a format to another

Usage

```
converter_format(inpt_val, sep_ = "-", inpt_frmt, frmt, default_val = "00")
```

Arguments

<code>inpt_val</code>	is the input value that is linked to the format
<code>sep_</code>	is the separator of the value in <code>inpt_val</code>
<code>inpt_frmt</code>	is the format of the input value
<code>frmt</code>	is the format you want to convert to
<code>default_val</code>	is the default value given to the units that are not present in the input format

Examples

```
print(converter_format(inpt_val="23-12-05-1567", sep="-",
                       inpt_frmt="shmy", frmt="snhdmy", default_val="00"))
#[1] "23-00-12-00-05-1567"

print(converter_format(inpt_val="23-12-05-1567", sep="-",
                       inpt_frmt="shmy", frmt="Pnhdmy", default_val="00"))
#[1] "00-00-12-00-05-1567"
```

cost_and_taxes	<i>cost_and_taxes</i>
----------------	-----------------------

Description

Allow to calculate basic variables related to cost and taxes from a bunch of products (elements). So put every variable you know in the following order:

Usage

```
cost_and_taxes (
  qte = NA,
  pu = NA,
  prix_ht = NA,
  tva = NA,
  prix_ttc = NA,
  prix_tva = NA,
  pu_ttc = NA,
  adjust = NA,
  prix_d_ht = NA,
  prix_d_ttc = NA,
  pu_d = NA,
  pu_d_ttc = NA
)
```

Arguments

qte	is the quantity of elements
pu	is the price of a single elements without taxes
prix_ht	is the duty-free price of the whole set of elements
tva	is the percentage of all taxes
prix_ttc	is the price of all the elements with taxes
prix_tva	is the cost of all the taxes
pu_ttc	is the price of a single element taxes included
adjust	is the discount percentage
prix_d_ht	is the free-duty price of an element after discount
prix_d_ttc	is the price with taxes of an element after discount
pu_d	is the price of a single element after discount and without taxes
pu_d_ttc	is the free-duty price of a single element after discount

Examples

```
print(cost_and_taxes(pu=45, prix_ttc=21, qte=3423))

#[1] 3.423000e+03 4.500000e+01 4.500000e+01 -9.998637e-01 2.100000e+01
#[6] -1.540140e+05 4.500000e+01 NA NA NA
#[11] NA NA
```

cut_v	<i>v_to_datf</i>
-------	------------------

Description

Allow to convert a vector to a dataframe according to a separator.

Usage

```
cut_v(inpt_v, sep_ = "")
```

Arguments

inpt_v	is the input vector
sep_	is the separator of the elements in inpt_v, defaults to ""

Examples

```
print(cut_v(inpt_v=c("oui", "non", "oui", "non")))

#      X.o. X.u. X.i.
#oui  "o"  "u"  "i"
#non  "n"  "o"  "n"
#oui  "o"  "u"  "i"
#non  "n"  "o"  "n"

print(cut_v(inpt_v=c("ou-i", "n-on", "ou-i", "n-on"), sep_="-"))

#      X.ou. X.i.
#ou-i  "ou"  "i"
#n-on  "n"   "on"
#ou-i  "ou"  "i"
#n-on  "n"   "on"
```

data_gen	<i>data_gen</i>
----------	-----------------

Description

Allo to generate in a csv all kind of data you can imagine according to what you provide

Usage

```
data_gen(
  type_ = c("number", "mixed", "string"),
  strt_l = c(0, 0, 10),
  nb_r = c(50, 10, 40),
  output = NA,
  properties = c("1-5", "1-5", "1-5"),
  type_distri = c("random", "random", "random"),
```

```

    str_source = c("a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m",
                  "o", "p", "q", "r", "s", "t", "u", "w", "x", "y", "z"),
    round_l = c(0, 0, 0),
    sep_ = ",",
  )

```

Arguments

type_	is a vector. Its arguments designates a column, a column can be made of numbers ("number"), string ("string") or both ("mixed")
strt_l	is a vector containing for each column the row from which the data will begin to be generated
nb_r	is a vector containing for each column, the number of row full from generated data
output	is the name of the output csv file, defaults to NA so no csv will be outputted by default
properties	is linked to type_distri because it is the parameters ("min_val-max_val") for "random type", ("u-x") for the poisson distribution, ("u-d") for gaussian distribution
type_distri	is a vector which, for each column, associate a type of distribution ("random", "poisson", "gaussian"), it means that non only the number but also the length of the string will be randomly generated according to these distribution laws
str_source	is the source (vector) from which the character creating random string are (default set to the occidental alphabet)
round_l	is a vector which, for each column containing number, associate a round value, if the type of the value is numeric
sep_	is the separator used to write data in the csv

Value

new generated data in addition to saving it in the output

Examples

```

print(data_gen())

#   X1   X2   X3
#1   4    2 <NA>
#2   2    4 <NA>
#3   5    2 <NA>
#4   2 abcd <NA>
#5   4 abcd <NA>
#6   2    4 <NA>
#7   2  abc <NA>
#8   4  abc <NA>
#9   4    3 <NA>
#10  4  abc abcd
#11  5 <NA>  abc
#12  4 <NA>  abc
#13  1 <NA>   ab
#14  1 <NA> abcde
#15  2 <NA>  abc

```

```

#16 4 <NA>      a
#17 1 <NA>    abcd
#18 4 <NA>      ab
#19 2 <NA>    abcd
#20 3 <NA>      ab
#21 3 <NA>    abcd
#22 2 <NA>      a
#23 4 <NA>     abc
#24 1 <NA>    abcd
#25 4 <NA>     abc
#26 4 <NA>      ab
#27 2 <NA>     abc
#28 5 <NA>      ab
#29 3 <NA>     abc
#30 5 <NA>    abcd
#31 2 <NA>     abc
#32 2 <NA>     abc
#33 1 <NA>      ab
#34 5 <NA>      a
#35 4 <NA>      ab
#36 1 <NA>      ab
#37 1 <NA> abcde
#38 5 <NA>     abc
#39 4 <NA>      ab
#40 5 <NA> abcde
#41 2 <NA>      ab
#42 3 <NA>      ab
#43 2 <NA>      ab
#44 4 <NA>    abcd
#45 5 <NA>    abcd
#46 3 <NA>    abcd
#47 2 <NA>    abcd
#48 3 <NA>    abcd
#49 3 <NA>    abcd
#50 4 <NA>      a

print(data_gen(strt_l=c(0, 0, 0), nb_r=c(5, 5, 5)))

#  X1    X2    X3
#1  2      a  abc
#2  3 abcde   ab
#3  4 abcde    a
#4  1      3  abc
#5  3      a abcd

```

data_mesgup

data_mesgup

Description

Allow to automatically arrange 1 dimensional data according to vector and parameters

Usage

```
data_mesgup (
```

```

data,
cols = NA,
file_ = NA,
sep_ = ";",
organisation = c(2, 1, 0),
unic_sep1 = "_",
unic_sep2 = "-"
)

```

Arguments

data	is the data provided (vector) each column is separated by a unic separator and each dataset from the same column is separated by another unic separator (ex: <code>c("", c("d", "-", "e", "-", "f"), "", c("a", "a1", "-", "b", "-", "c", "c1"), "_")</code>)
cols	are the colnames of the data generated in a csv
file_	is the file to which the data will be outputed, defaults to NA which means that the functio will return the dataframe generated and won't write it to a csv file
sep_	is the separator of the csv outputed
organisation	is the way variables include themselves, for instance ,resuming precedent example, if organisation=c(1, 0) so the data output will be: d, a d, a1 e, c f, c f, c1
unic_sep1	is the unic separator between variables (default is "_")
unic_sep2	is the unic separator between datasets (default is "-")

Examples

```

print(data_meshup(data=c("_", c("-", "d", "-", "e", "-", "f"), "_", c("-", "a", "a1", "-"),
#   X1 X2
#1   d  a
#2   d a1
#3   e  B
#4   e  r
#5   e uy
#6   f  c
#7   f c1

```

date_addr

date_addr

Description

Allow to add or subtract two dates that have the same time unit or not

Usage

```

date_addr (
    date1,
    date2,
    add = FALSE,
    frmt1,
    frmt2 = frmt1,
    sep_ = "-",
    convert_to = "dmy"
)

```

Arguments

date1	is the date from which the second date will be added or subtracted
date2	is the date that will be added or will subtract date1
add	equals to FALSE if you want date1 - date2 and TRUE if you want date1 + date2
frmt1	is the format of date1 (snhdmy) (second, minute, hour, day, monthn year)
frmt2	is the format of date2 (snhdmy)
sep_	is the separator of date1 and date2
convert_to	is the format of the outputed date

Examples

```

print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",
               convert_to="dmy"))

#[1] "18-2-0"

print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",
               convert_to="dmy", add=TRUE))

#[1] "3-3-0"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="dmy", add=TRUE))

#[1] "27-3-2024"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="dmy", add=FALSE))

#[1] "23-1-2024"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="n", add=FALSE))

#[1] "1064596320"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="s", add=FALSE))

#[1] "63875779200"

```

date_converter_reverse	<i>date_converter_reverse</i>
------------------------	-------------------------------

Description

Allow to convert single date value like 2025.36 year to a date like second/minutehour/day/month/year (snhdmy)

Usage

```
date_converter_reverse(inpt_date, convert_to = "dmy", frmt = "y", sep_ = "-")
```

Arguments

- inpt_date is the input date
- convert_to is the date format the input date will be converted
- frmt is the time unit of the input date
- sep_ is the separator of the outputed date

Examples

```
print(date_converter_reverse(inpt_date="2024.929", convert_to="hmy", frmt="y", sep_="-"))
#[1] "110-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dmy", frmt="y", sep_="-"))
#[1] "4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="hdmy", frmt="y", sep_="-"))
#[1] "14-4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dhym", frmt="y", sep_="-"))
#[1] "4-14-2024-11"
```

dcr_untl	<i>dcr_untl</i>
----------	-----------------

Description

Allow to get the final value of a incremental or decremental loop.

Usage

```
dcr_untl(strt_val, cr_val, stop_val = 0)
```

Arguments

<code>strt_val</code>	is the start value
<code>cr_val</code>	is the incremental (or decremental value)
<code>stop_val</code>	is the value where the loop has to stop

Examples

```
print(dcr_until(strt_val=50, cr_val=-5, stop_val=5))

#[1] 9

print(dcr_until(strt_val=50, cr_val=5, stop_val=450))

#[1] 80
```

<code>dcr_val</code>	<i>dcr_val</i>
----------------------	----------------

Description

Allow to get the end value after an incremental (or decremental loop)

Usage

```
dcr_val(strt_val, cr_val, stop_val = 0)
```

Arguments

<code>strt_val</code>	is the start value
<code>cr_val</code>	is the incremental or decremental value
<code>stop_val</code>	is the value the loop has to stop

Examples

```
print(dcr_val(strt_val=50, cr_val=-5, stop_val=5))

#[1] 5

print(dcr_val(strt_val=47, cr_val=-5, stop_val=5))

#[1] 7

print(dcr_val(strt_val=50, cr_val=5, stop_val=450))

#[1] 450

print(dcr_val(strt_val=53, cr_val=5, stop_val=450))

#[1] 448
```

equalizer_v	<i>equalizer_v</i>
-------------	--------------------

Description

Takes a vector of character as an input and returns a vector with the elements at the same size. The size can be chosen via depth parameter.

Usage

```
equalizer_v(inpt_v, depth = "max", default_val = "?")
```

Arguments

inpt_v	is the input vector containing all the characters
depth	is the depth parameter, defaults to "max" which means that it is equal to the character number of the element(s) in inpt_v that has the most
default_val	is the default value that will be added to the output characters if those has an inferior length (characters) than the value of depth

Examples

```
print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=2))

#[1] "aa" "zz" "q?"

print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=12))

#[1] "aa???????????" "zzz???????????" "q?????????????"
```

extrt_only_v	<i>extrt_only_v</i>
--------------	---------------------

Description

Returns the elements from a vector "inpt_v" that are in another vector "pttrn_v"

Usage

```
extrt_only_v(inpt_v, pttrn_v)
```

Arguments

inpt_v	is the input vector
pttrn_v	is the vector contining all the elements that can be in inpt_v

Examples

```
print(extrt_only_v(inpt_v=c("oui", "non", "peut", "oo", "ll", "oui", "non", "oui", "oui"))

#[1] "oui" "oui" "oui" "oui"
```

fillr

fillr

Description

Allow to fill a vector by the last element n times

Usage

```
fillr(inpt_v, ptrn_fill = "...\\d")
```

Arguments

inpt_v	is the input vector
ptrn_fill	is the pattern used to detect where the function has to fill the vector by the last element n times. It defaults to "...\\d" where "\\d" is the regex for an int value. So this paramater has to have "\\d" which designates n.

Examples

```
print(fillr(c("a", "b", "...3", "c")))

#[1] "a" "b" "b" "b" "b" "c"
```

fixer_nest_v

fixer_nest_v

Description

Retur the elements of a vector "wrk_v" (1) that corresponds to the pattern of elements in another vector "cur_v" (2) according to another vector "pttrn_v" (3) that contains the patterof elements.

Usage

```
fixer_nest_v(cur_v, pttrn_v, wrk_v)
```

Arguments

cur_v	is the input vector
pttrn_v	is the vector containing all the patterns that may be contained in cur_v
wrk_v	is a vector containing all the indexes of cur_v taken in count in the function

Examples

```
print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"), pttrn_v=
      wrk_v=c(1, 2, 3, 4, 5, 6)))

#[1] 1 2 3 4 5 6

print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"), pttrn_v=
      wrk_v=c(1, 2, 3, 4, 5, 6)))

#[1] 1 2 NA 4 5 NA
```

fold_rec

*fold_rec***Description**

Allow to get all the files recursively from a path according to an end and start depth value. If you want to have an other version of this function that uses a more sophisticated algorithm (which can be faster), check file_rec2. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

Usage

```
fold_rec(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax	is the end depth value
xmin	is the start depth value
pathc	is the reference path

fold_rec2

*fold_rec2***Description**

Allow to find the directories and the subdirectories with a specified end and start depth value from a path. This function might be more powerfull than file_rec because it uses a custom algorythm that does not nee to perform a full recursive search before tuning it to only find the directories with a good value of depth. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

Usage

```
fold_rec2(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax	is the depth value
xmin	is the minimum value of depth
pathc	is the reference path, from which depth value is equal to 1

format_date	<i>format_date</i>
-------------	--------------------

Description

Allow to convert xx-month-xxxx date type to xx-xx-xxxx

Usage

```
format_date(f_dialect, sentc, sep_in = "-", sep_out = "-")
```

Arguments

- f_dialect are the months from the language of which the month come
- sentc is the date to convert
- sep_in is the separator of the dat input (default is "-")
- sep_out is the separator of the converted date (default is "-")

Examples

```
print(format_date(f_dialect=c("janvier", "février", "mars", "avril", "mai", "juin",  
                             "juillet", "aout", "septembre", "octobre", "novembre", "décembre"),  
      "11-09-2023")  
#[1] "11-09-2023"
```

geo_min	<i>geo_min</i>
---------	----------------

Description

Return a dataframe containing the nearest geographical points (row) according to established geographical points (column).

Usage

```
geo_min(inpt_datf, established_datf)
```

Arguments

- inpt_datf is the input dataframe of the set of geographical points to be classified, its firts column is for latitude, the second for the longitude and the third, if exists, is for the altitude. Each point is one row.
- established_datf is the dataframe containing the coordiantes of the established geographical points

Examples

```

in_ <- data.frame(c(11, 33, 55), c(113, -143, 167))

in2_ <- data.frame(c(12, 55), c(115, 165))

print(geo_min(inpt_datf=in_, established_datf=in2_))

#           X1           X2
#1    245.266         NA
#2 24200.143         NA
#3           NA 127.7004

in_ <- data.frame(c(51, 23, 55), c(113, -143, 167), c(6, 5, 1))

in2_ <- data.frame(c(12, 55), c(115, 165), c(2, 5))

print(geo_min(inpt_datf=in_, established_datf=in2_))

#           X1           X2
#1           NA 4343.720
#2 26465.63         NA
#3           NA 5825.517

```

get_rec

*get_rec***Description**

Allow to get the value of directorie depth from a path.

Usage

```
get_rec(pathc = ".")
```

Arguments

pathc is the reference path example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

globe

*globe***Description**

Allow to calculate the distances between a set of geographical points and another established geographical point. If the altitude is not filled, so the result returned won't take in count the altitude.

Usage

```
globe(lat_f, long_f, alt_f = NA, lat_n, long_n, alt_n = NA)
```

Arguments

lat_f	is the latitude of the established geographical point
long_f	is the longitude of the established geographical point
alt_f	is the altitude of the established geographical point, defaults to NA
lat_n	is a vector containing the latitude of the set of points
long_n	is a vector containing the longitude of the set of points
alt_n	is a vector containing the altitude of the set of points, defaults to NA

Examples

```
print(globe(lat_f=23, long_f=112, alt_f=NA, lat_n=c(2, 82), long_n=c(165, -55), alt_n=NA))

#[1] 6342.844 7059.080

print(globe(lat_f=23, long_f=112, alt_f=8, lat_n=c(2, 82), long_n=c(165, -55), alt_n=c(8, 8)))

#[1] 6342.844 7059.087
```

groupr_datf	<i>groupr_datf</i>
-------------	--------------------

Description

Allow to create groups from a dataframe. Indeed, you can create conditions that lead to a flag value for each cell of the input dataframe according to the cell value. This function is based on `see_datf` and `nestr_datf2` functions.

Usage

```
groupr_datf(
  inpt_datf,
  condition_lst,
  val_lst,
  conjunction_lst,
  rtn_val_pos = c()
)
```

Arguments

inpt_datf	is the input dataframe
condition_lst	is a list containing all the condition as a vector for each group
val_lst	is a list containing all the values associated with condition_lst as a vector for each group
conjunction_lst	is a list containing all the conjunctions associated with condition_lst and val_lst as a vector for each group
rtn_val_pos	is a vector containing all the group flag value like this ex: c("flag1", "flag2", "flag3")

Examples

```

interactive()

datf1 <- data.frame(c(1, 2, 1), c(45, 22, 88), c(44, 88, 33))

val_lst <- list(list(c(1), c(1)), list(c(2)), list(c(44, 88)))

condition_lst <- list(c(">", "<"), c("%%", c("==", "=="))

conjunction_lst <- list(c("|"), c(), c("|"))

rtn_val_pos <- c("+", "++", "+++")

print(groupr_datf(inpt_datf=datf1, val_lst=val_lst, condition_lst=condition_lst,
conjunction_lst=conjunction_lst, rtn_val_pos=rtn_val_pos))

#      X1  X2  X3
#1 <NA>   +  +++
#2   ++  ++  +++
#3 <NA> +++   +

```

*id_keepr**id_keepr_datf*

Description

Allow to get the original indexes after multiple equality comparison according to the original number of row

Usage

```
id_keepr(inpt_datf, col_v = c(), el_v = c(), rstr_l = NA)
```

Arguments

<code>inpt_datf</code>	is the input dataframe
<code>col_v</code>	is the vector containing the column numbers or names to be compared to their respective elements in "el_v"
<code>el_v</code>	is a vector containing the elements that may be contained in their respective column described in "col_v"
<code>rstr_l</code>	is a list containing the vector composed of the indexes of the elements chosen for each comparison. If the length of the list is inferior to the lenght of comparisons, so the last vector of rstr_l will be the same as the last one to fill make rstr_l equal in term of length to col_v and el_v

Examples

```

datf1 <- data.frame(c("oui", "oui", "oui", "non", "oui"), c("opui", "op", "op", "zez", "z
print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op")))

```

```

#[1] 2 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5), c(1:5)))

#[1] 2 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5), c(1:5)))

#[1] 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5)))

#[1] 2 3

```

incr_fillr

incr_fillr

Description

Take a vector uniquely composed by double and sorted ascendingly, a step, another vector of elements whose length is equal to the length of the first vector, and a default value. If an element of the vector is not equal to its predecessor minus a user defined step, so these can be the output according to the parameters (see example):

Usage

```
incr_fillr(inpt_v, wrk_v = NA, default_val = NA, step = 1)
```

Arguments

inpt_v	is the asending double only composed vector
wrk_v	is the other vector (size equal to inpt_v), defaults to NA
default_val	is the default value put when the difference between two following elements of inpt_v is greater than step, defaults to NA
step	is the allowed difference between two elements of inpt_v

Examples

```

print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
                 wrk_v=NA,
                 default_val="increasing"))

#[1] 1 2 3 4 5 6 7 8 9 10

print(incr_fillr(inpt_v=c(1, 1, 2, 4, 5, 9),
                 wrk_v=c("ok", "ok", "ok", "ok", "ok"),
                 default_val=NA))

#[1] "ok" "ok" "ok" NA "ok" "ok" NA NA

print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
                 wrk_v=NA,

```



```

                                default_val="NAN"))
# [1] "1"    "2"    "NAN" "4"    "5"    "NAN" "NAN" "NAN" "9"    "10"

```

insert_datf	<i>edml insert_datf</i>
-------------	-------------------------

Description

Allow to insert dataframe into another dataframe according to coordinates (row, column) from the dataframe that will be inserted

Usage

```
insert_datf(datf_in, datf_ins, ins_loc)
```

Arguments

datf_in	is the dataframe that will be inserted
datf_ins	is the dataset to be inserted
ins_loc	is a vector containing two parameters (row, column) of the beginning for the insertion

Examples

```

datf1 <- data.frame(c(1, 4), c(5, 3))

datf2 <- data.frame(c(1, 3, 5, 6), c(1:4), c(5, 4, 5, "ereer"))

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(4, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1              1      1                   5
# 2              3      2                   4
# 3              5      3                   5
# 4              6      1                   5

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(3, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1              1      1                   5
# 2              3      2                   4
# 3              5      1                   5
# 4              6      4                   3

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(2, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1              1      1                   5
# 2              3      1                   5
# 3              5      4                   3
# 4              6      4                   ereer

```

inter_max

inter_max

Description

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)). The function will return the list of lists altered according to the maximum step found in the input list.

Usage

```
inter_max(inpt_l, max_ = -1000, get_lst = TRUE)
```

Arguments

inpt_l	is the input list
max_	is a value you are sure is the minimum step value of all the sub-lists
get_lst	is the parameter that, if set to True, will keep the last values of vectors in the return value if the last step exceeds the end value of the vector.

Examples

```
print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=TRUE))

#[[1]]
#[1] 0 4
#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1.0 2.3

print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=FALSE))

# [[1]]
#[1] 0 4
#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1
```

inter_min

*inter_min***Description**

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)). This function will return the list of vectors with the same steps preserving the begin and end value of each interval. The way the algorithm searches the common step of all the sub-lists is also given by the user as a parameter, see `how_to` paramaters.

Usage

```
inter_min(
  inpt_l,
  min_ = 1000,
  sensi = 3,
  sensi2 = 3,
  how_to_op = c("divide"),
  how_to_val = c(3)
)
```

Arguments

<code>inpt_l</code>	is the input list containing all the intervals
<code>min_</code>	is a value you are sure is superior to the maximum step value in all the intervals
<code>sensi</code>	is the decimal accuracy of how the difference between each value n to $n+1$ in an interval is calculated
<code>sensi2</code>	is the decimal accuracy of how the value with the common step is calculated in all the intervals
<code>how_to_op</code>	is a vector containing the operations to perform to the pre-common step value, defaults to only "divide". The operations can be "divide", "substract", "multiply" or "add". All type of operations can be in this parameter.
<code>how_to_val</code>	is a vector containing the value relatives to the operations in <code>hot_to_op</code> , defaults to 3 output from ex:

Examples

```
print(inter_min(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3))))

# [[1]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
# [20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
# [39] 3.8 3.9 4.0
#
# [[2]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
# [20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
# [39] 3.8 3.9 4.0
#
# [[3]]
```

```
# [1] 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1 2.2 2.3
```

isnt_divisible	<i>isnt_divisible</i>
----------------	-----------------------

Description

Takes a vector as an input and returns all the elements that are not divisible by all choosen numbers from another vector.

Usage

```
isnt_divisible(inpt_v = c(), divisible_v = c())
```

Arguments

inpt_v	is the input vector
divisible_v	is the vector containing all the numbers that will try to divide those contained in inpt_v

Examples

```
print(isnt_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

# [1] 1 3 7 9 11 13 17 19 21 23 27 29 31 33 37 39 41 43 47
# [20] 49 51 53 57 59 61 63 67 69 71 73 77 79 81 83 87 89 91 93
# [39] 97 99 101 103 107 109 111
```

is_divisible	<i>is_divisible</i>
--------------	---------------------

Description

Takes a vector as an input and returns all the elements that are divisible by all choosen numbers from another vector.

Usage

```
is_divisible(inpt_v = c(), divisible_v = c())
```

Arguments

inpt_v	is the input vector
divisible_v	is the vector containing all the numbers that will try to divide those contained in inpt_v

Examples

```
print(is_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

#[1] 20 40 60 80 100
```

leap_yr

bsx_year

Description

Get if the year is leap

Usage

```
leap_yr(year)
```

Arguments

year is the input year

Examples

```
print(leap_yr(year=2024))

#[1] TRUE
```

letter_to_nb

letter_to_nb

Description

Allow to get the number of a spreadsheet based column by the letter ex: AAA = 703

Usage

```
letter_to_nb(letter)
```

Arguments

letter is the letter (name of the column)

Examples

```
print(letter_to_nb("rty"))

#[1] 12713
```

list_files	<i>list_files</i>
------------	-------------------

Description

A list.files() based function addressing the need of listing the files with extension a or or extension b ...

Usage

```
list_files(patternc, pathc = ".")
```

Arguments

patternc	is a vector containing all the extensions you want
pathc	is the path, can be a vector of multiple path because list.files() supports it.

lst_flatnr	<i>lst_flatnr</i>
------------	-------------------

Description

Flatten a list to a vector

Usage

```
lst_flatnr(inpt_l)
```

Arguments

inpt_l	is the input list
--------	-------------------

Examples

```
print(lst_flatnr(inpt_l=list(c(1, 2), c(5, 3), c(7, 2, 7))))
#[1] 1 2 5 3 7 2 7
```

multitud	<i>multitud</i>
----------	-----------------

Description

From a list containing vectors allow to generate a vector following this rule: `list(c("a", "b"), c("1", "2"), c("A", "Z", "E")) -> c("a1A", "b1A", "a2A", "b2A", a1Z, ...)`

Usage

```
multitud(l, sep_ = "")
```

Arguments

<code>l</code>	is the list
<code>sep_</code>	is the separator between elements (default is set to "" as you see in the example)

Examples

```
print(multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")

#[1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
#[8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
#[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
#[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"
```

<code>nb_to_letter</code>	<i>nb_to_letter</i>
---------------------------	---------------------

Description

Allow to get the letter of a spreadsheet based column by the number ex: 703 = AAA

Usage

```
nb_to_letter(x)
```

Arguments

<code>x</code>	is the number of the column
----------------	-----------------------------

Examples

```
print(nb_to_letter(12713))

#[1] "rty"
```

nestr_datf1	<i>nestr_datf1</i>
-------------	--------------------

Description

Allow to write a value (1a) to a dataframe (1b) to its cells that have the same coordinates (row and column) than the cells whose value is equal to a another special value (2a), from another another dataframe (2b). The value (1a) depends of the cell value coordinates of the third dataframe (3b). If a cell coordinates (1c) of the first dataframe (1b) does not correspond to the coordinates of a good returning cell value (2a) from the dataframe (2b), so this cell (1c) can have its value changed to the same cell coordinates value (3a) of a third dataframe (4b), if (4b) is not set to NA.

Usage

```
nestr_datf1(
  inptf_datf,
  inptt_pos_datf,
  nestr_datf,
  yes_val = TRUE,
  inptt_neg_datf = NA
)
```

Arguments

`inptf_datf` is the input dataframe (1b)
`inptt_pos_datf` is the dataframe (2b) that corresponds to the (1a) values
`nestr_datf` is the dataframe (2b) that has the special value (2a)
`yes_val` is the special value (2a)
`inptt_neg_datf` is the dataframe (4b) that has the (3a) values, defaults to NA

Examples

```
print(nestr_datf1(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_datf=data.frame(c(44, 44, 33), c(12, 12, 12)),
  nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))

# c.1..2..1. c.1..5..7.
#1          4          12
#2          44          12
#3           3           2

print(nestr_datf1(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_datf=NA,
  nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))

# c.1..2..1. c.1..5..7.
#1          4          1
#2          2          5
```


#3	3	2
----	---	---

nestr_datf2	<i>nestr_datf2</i>
-------------	--------------------

Description

Allow to write a special value (1a) in the cells of a dataframe (1b) that correspond (row and column) to those of another dataframe (2b) that return another special value (2a). The cells whose coordinates do not match the coordinates of the dataframe (2b), another special value can be written (3a) if not set to NA.

Usage

```
nestr_datf2(inptf_datf, rtn_pos, rtn_neg = NA, nestr_datf, yes_val = T)
```

Arguments

inptf_datf	is the input dataframe (1b)
rtn_pos	is the special value (1a)
rtn_neg	is the special value (3a)
nestr_datf	is the dataframe (2b)
yes_val	is the special value (2a)

Examples

```
print(nestr_datf2(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)), rtn_pos="yes",
  rtn_neg="no", nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=
  # c.1..2..1. c.1..5..7.
  #1          yes          no
  #2          no           no
  #3          yes          yes
```

nest_v	<i>nest_v</i>
--------	---------------

Description

Nest two vectors according to the following parameters.

Usage

```
nest_v(f_v, t_v, step = 1, after = 1)
```

Arguments

<code>f_v</code>	is the vector that will welcome the nested vector <code>t_v</code>
<code>t_v</code>	is the imbriuator vector
<code>step</code>	defines after how many elements of <code>f_v</code> the next element of <code>t_v</code> can be put in the output
<code>after</code>	defines after how many elements of <code>f_v</code> , the beginning of <code>t_v</code> can be put

Examples

```
print(nest_v(f_v=c(1, 2, 3, 4, 5, 6), t_v=c("oui", "oui2", "oui3", "oui4", "oui5", "oui6"))
# [1] "1"      "2"      "oui"    "3"      "4"      "oui2"   "5"      "6"      "oui3"   "oui4"
```

<code>new_ordered</code>	<i>new_ordered</i>
--------------------------	--------------------

Description

Returns the indexes of elements contained in "w_v" according to "f_v"

Usage

```
new_ordered(f_v, w_v, nvr_here = NA)
```

Arguments

<code>f_v</code>	is the input vector
<code>w_v</code>	is the vector containing the elements that can be in <code>f_v</code>
<code>nvr_here</code>	is a value you are sure is not present in <code>f_v</code>

Examples

```
print(new_ordered(f_v=c("non", "non", "non", "oui"), w_v=c("oui", "non", "non")))
# [1] 4 1 2
```

non_unique	<i>non_unique</i>
------------	-------------------

Description

Returns the element that are not unique from the input vector

Usage

```
non_unique(inpt_v, occu = ">-1-")
```

Arguments

inpt_v	is the input vector containing the elements
occu	is a parameter that specifies the occurrence of the elements that must be returned, defaults to ">-1-" it means that the function will return all the elements that are present more than one time in inpt_v. The syntax is the following "comparaison_type-actual_value-". The comparaison type may be "==" or ">". Occu can also be a vector containing all the occurrence that must have the elements to be returned.

Examples

```
print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non")))
#[1] "oui" "non"

print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=="==2-"))
#[1] "oui"

print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=">-2-"))
#[1] "non"

print(non_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=c(1, 2)))
#[1] "non" "peut" "peut1"
```

occu	<i>occu</i>
------	-------------

Description

Allow to see the occurrence of each variable in a vector. Returns a dataframe with, as the first column, the all the unique variable of the vector and , in he second column, their occurrence respectively.

Usage

```
occu(inpt_v)
```

Arguments

`inpt_v` the input dataframe

Examples

```
print(occu(inpt_v=c("oui", "peut", "peut", "non", "oui")))

#   var occurrence
#1  oui           2
#2  peut          2
#3  non           1
```

<code>paste_datf</code>	<i><code>paste_datf</code></i>
-------------------------	--------------------------------

Description

Return a vector composed of pasted elements from the input dataframe at the same index.

Usage

```
paste_datf(inpt_datf, sep = "")
```

Arguments

`inpt_datf` is the input dataframe
`sep` is the separator between pasted elements, defaults to ""

Examples

```
print(paste_datf(inpt_datf=data.frame(c(1, 2, 1), c(33, 22, 55))))

#[1] "133" "222" "155"
```

<code>pattern_generator</code>	<i><code>pattern_generator</code></i>
--------------------------------	---------------------------------------

Description

Allow to create patterns which have a part that is varying randomly each time.

Usage

```
pattern_generator(base_, from_, nb, hmn = 1, after = 1, sep = "")
```

Arguments

base_	is the pattern that will be kept
from_	is the vector from which the elements of the random part will be generated
nb	is the number of random pattern chosen for the varying part
hmn	is how many of varying pattern from the same base will be created
after	is set to 1 by default, it means that the varying part will be after the fixed part, set to 0 if you want the varying part to be before
sep	is the separator between all patterns in the returned value

Examples

```
print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=1, hmn=3))

# [1] "ouier" "ouire" "ouier"

print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=2, hmn=3, after=0, se

# [1] "er-re-o-u-i" "ere-re-o-u-i" "ere-er-o-u-i"
```

pattern_gettr

pattern_gettr

Description

Search for pattern(s) contained in a vector in another vector and return a list containing matched one (first index) and their position (second index) according to these rules: First case: Search for patterns strictly, it means that the searched pattern(s) will be matched only if the patterns contained in the vector that is being explored by the function are present like this `c("pattern_searched", "other", ..., "pattern_searched")` and not as `c("other_thing pattern_searched other_thing", "other", ..., "pattern_searched other_thing")` Second case: It is the opposite to the first case, it means that if the pattern is partially present like in the first position and the last, it will be considered like a matched pattern. REGEX can also be used as pattern

Usage

```
pattern_gettr(
  word_,
  vct,
  occ = c(1),
  strict,
  btwn,
  all_in_word = "yes",
  notatall = "###"
)
```

Arguments

<code>word_</code>	is the vector containing the patterns
<code>vct</code>	is the vector being searched for patterns
<code>occ</code>	a vector containing the occurrence of the pattern in <code>word_</code> to be matched in the vector being searched, if the occurrence is 2 for the <i>n</i> th pattern in <code>word_</code> and only one occurrence is found in <code>vct</code> so no pattern will be matched, put "forever" to no longer depend on the occurrence for the associated pattern
<code>strict</code>	a vector containing the "strict" condition for each <i>n</i> th vector in <code>word_</code> ("strict" is the string to activate this option)
<code>btwn</code>	is a vector containing the condition ("yes" to activate this option) meaning that if "yes", all elements between two matched pattern in <code>vct</code> will be returned, so the patterns you enter in <code>word_</code> have to be in the order you think it will appear in <code>vct</code>
<code>all_in_word</code>	is a value (default set to "yes", "no" to activate this option) that, if activated, won't authorize a previous matched pattern to be matched again
<code>notatall</code>	is a string that you are sure is not present in <code>vct</code>

Examples

```
print(pattern_gettr(word=c("oui", "non", "erer"), vct=c("oui", "oui", "non", "oui", "non"),
# [[1]]
# [1] 1 5 8
#
# [[2]]
# [1] "oui" "non" "opp" "opp" "erer"
```

pattern_tuning	<i>pattern_tuning</i>
----------------	-----------------------

Description

Allow to tune a pattern very precisely and output a vector containing its variations *n* times.

Usage

```
pattern_tuning(
  patrn,
  spe_nb,
  spe_l,
  exclude_type,
  hmn = 1,
  rg = c(1, nchar(patrnr))
)
```

Arguments

<code>patrn</code>	is the character that will be tuned
<code>spe_nb</code>	is the number of new character that will be replaced
<code>spe_l</code>	is the source vector from which the new characters will replace old ones
<code>exclude_type</code>	is character that won't be replaced
<code>hmn</code>	is how many output the function will return
<code>rg</code>	is a vector with two parameters (index of the first letter that will be replaced, index of the last letter that will be replaced) default is set to all the letters from the source pattern

Examples

```
print(pattern_tuning(patrn="oui", spe_nb=2, spe_l=c("e", "r", "T", "O"), exclude_type="c")
# [1] "orT" "oTr" "oOi"
```

ptrn_switchr

*ptrn_switchr***Description**

Allow to switch, copy pattern for each element in a vector. Here a pattern is the values that are separated by a same separator. Example: "xx-xxx-xx" or "xx/xx/xxxx". The xx like values can be swiched or copied from whatever index to whatever index. Here, the index is like this 1-2-3 etcetera, it is relative of the separator.

Usage

```
ptrn_switchr(inpt_l, f_idx_l = c(), t_idx_l = c(), sep = "-", default_val = NA)
```

Arguments

<code>inpt_l</code>	is the input vector
<code>f_idx_l</code>	is a vector containing the indexes of the pattern you want to be altered.
<code>t_idx_l</code>	is a vector containing the indexes to which the indexes in <code>f_idx_l</code> are related.
<code>sep</code>	is the separator, defaults to "-"
<code>default_val</code>	is the default value , if not set to NA, of the pattern at the indexes in <code>f_idx_l</code> . If it is not set to NA, you do not need to fill <code>t_idx_l</code> because this is the vector containing the indexes of the patterns that will be set as new values relatively to the indexes in <code>f_idx_l</code> . Defaults to NA.

Examples

```
print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1, 2, 3), t_idx_l=c(3, 2, 1)))

#[1] "11-01-2022" "14-01-2022" "21-01-2022" "01-01-2022"

print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1), default_val="ee"))

#[1] "ee-01-11" "ee-01-14" "ee-01-21" "ee-01-01"
```

ptrn_twkr

*ptrn_twkr***Description**

Allow to modify the pattern length of element in a vector according to arguments. What is here defined as a pattern is something like this xx-xx-xx or xx/xx/xxx... So it is defined by the separator

Usage

```
ptrn_twkr(
  inpt_l,
  depth = "max",
  sep = "-",
  default_val = "0",
  add_sep = TRUE,
  end_ = TRUE
)
```

Arguments

inpt_l	is the input vector
depth	is the number (numeric) of separator it will keep as a result. To keep the number of separator of the element that has the minimum amount of separator do depth="min" and depth="max" (character) for the opposite. This value defaults to "max".
sep	is the separator of the pattern, defaults to "-"
default_val	is the default val that will be placed between the separator, defaults to "00"
add_sep	defaults to TRUE. If set to FALSE, it will remove the separator for the patterns that are included in the interval between the depth amount of separator and the actual number of separator of the element.
end_	is if the default_val will be added at the end or at the beginning of each element that lacks length compared to depth

Examples

```
v <- c("2012-06-22", "2012-06-23", "2022-09-12", "2022")

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE)

#[1] "2012-06-22" "2012-06-23" "2022-09-12" "2022-00-00"

ptrn_twkr(inpt_l=v, depth=1, sep="-", default_val="00", add_sep=TRUE)

#[1] "2012-06" "2012-06" "2022-09" "2022-00"

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE, end_=FALSE)

#[1] "2012-06-22" "2012-06-23" "2022-09-12" "00-00-2022"
```

rearangr_v

rearangr_v

Description

Rearranges a vector "w_v" according to another vector "inpt_v". inpt_v contains a sequence of number. inpt_v and w_v have the same size and their indexes are related. The output will be a vector containing all the elements of w_v rearranges in descending or asending order according to inpt_v

Usage

```
rearangr_v(inpt_v, w_v, how = "increasing")
```

Arguments

inpt_v	is the vector that contains the sequence of number
w_v	is the vector containing the elements related to inpt_v
how	is the way the elements of w_v will be outputed according to if inpt_v will be sorted ascendigly or descendingly

Examples

```
print(rearangr_v(inpt_v=c(23, 21, 56), w_v=c("oui", "peut", "non"), how="decreasing"))

#[1] "non" "oui" "peut"
```

regroupr	<i>regroupr</i>
----------	-----------------

Description

Allow to sort data like "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to what you want. For example it can be to "c(X1/Y1/Z1, X1/Y1/Z2, ...)"

Usage

```
regroupr(
  inpt_v,
  sep_ = "-",
  order = c(1:length(unlist(strsplit(x = inpt_v[1], split = sep_)))),
  l_order = NA
)
```

Arguments

<code>inpt_v</code>	is the input vector containing all the data you want to sort in a specific way. All the sub-elements should be separated by a unique separator such as "-" or "/"
<code>sep_</code>	is the unique separator separating the sub-elements in each elements of <code>inpt_v</code>
<code>order</code>	is a vector describing the way the elements should be sorted. For example if you want this dataset "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to be sorted by the last element you should have <code>order=c(3:1)</code> , for example, and it should returns something like this <code>c(X1/Y1/Z1, X2/Y1/Z1, X1/Y2/Z1, ...)</code> assuming you have only two values for X.
<code>l_order</code>	is a list containing the vectors of values you want to order first for each sub-elements

Examples

```
vec <- multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")

print(vec)

# [1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
# [8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
# [15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
# [22] "b/1/E/F" "a/2/E/F" "b/2/E/F"

print(regroupr(inpt_v=vec, sep_="/"))

# [1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
# [7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
# [13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/1/18/18"
# [19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23" "b/2/24/24"

vec <- vec[-2]

print(regroupr(inpt_v=vec, sep_="/"))
```

```
# [1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
# [7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
#[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/2/18/18"
#[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23"

print(regrouppr(inpt_v=vec, sep="/", order=c(4:1)))

#[1] "1/1/A/Q" "2/2/A/Q" "3/3/A/Q" "4/4/A/Q" "5/5/Z/Q" "6/6/Z/Q"
# [7] "7/7/Z/Q" "8/8/Z/Q" "9/9/E/Q" "10/10/E/Q" "11/11/E/Q" "12/12/E/Q"
#[13] "13/13/A/F" "14/14/A/F" "15/15/A/F" "16/16/A/F" "17/17/Z/F" "18/18/Z/F"
#[19] "19/19/Z/F" "20/20/Z/F" "21/21/E/F" "22/22/E/F" "23/23/E/F" "24/24/E/F"
```

save_until

save_until

Description

Get the elements in each vector from a list that are located before certain values

Usage

```
save_until(inpt_l = list(), val_to_stop_v = c())
```

Arguments

`inpt_l` is the input list containing all the vectors

`val_to_stop_v` is a vector containing the values that marks the end of the vectors returned in the returned list, see the examples

Examples

```
print(save_until(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3, 4))

#[[1]]
#[1] 1 2
#
#[[2]]
#[1] 1 1
#
#[[3]]
#[1] 1 2

print(save_until(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3))

#[[1]]
#[1] 1 2
#
#[[2]]
#[1] 1 1
#
#[[3]]
#[1] 1 2 4
```

see_datf

see_datf

Description

Allow to return a dataframe with special value cells (ex: TRUE) where the condition entered are respected and another special value cell (ex: FALSE) where these are not

Usage

```
see_datf(
  datf,
  condition_l,
  val_l,
  conjunction_l = c(),
  rt_val = TRUE,
  f_val = FALSE
)
```

Arguments

<code>datf</code>	is the input dataframe
<code>condition_l</code>	is the vector of the possible conditions (" <code>==</code> ", " <code>></code> ", " <code><</code> ", " <code>!=</code> ", " <code>%%</code> ", " <code>reg</code> ", " <code>not_reg</code> ", " <code>sup_nchar</code> ", " <code>inf_nchar</code> ", " <code>nchar</code> ") (equal to some elements in a vector, greater than, lower than, not equal to, is divisible by, the regex condition returns TRUE, the regex condition returns FALSE, the length of the elements is strictly superior to X, the length of the element is strictly inferior to X, the length of the element is equal to one element in a vector), you can put the same condition n times.
<code>val_l</code>	is the list of vectors containing the values or vector of values related to <code>condition_l</code> (so the vector of values has to be placed in the same order)
<code>conjunction_l</code>	contains the and or conjunctions, so if the length of <code>condition_l</code> is equal to 3, there will be 2 conjunctions. If the length of <code>conjunction_l</code> is inferior to the length of <code>condition_l</code> minus 1, <code>conjunction_l</code> will match its goal length value with its last argument as the last arguments. For example, <code>c("&", "l", "&")</code> with a goal length value of 5 -> <code>c("&", "l", "&", "&", "&")</code>
<code>rt_val</code>	is a special value cell returned when the conditions are respected
<code>f_val</code>	is a special value cell returned when the conditions are not respected

Details

This function will return an error if number only comparative conditions are given in addition to having character values in the input dataframe.

Examples

```
datf1 <- data.frame(c(1, 2, 4), c("a", "a", "zu"))

print(see_datf(datf=datf1, condition_l=c("nchar"), val_l=list(c(1))))
```

```

#      X1      X2
#1 TRUE  TRUE
#2 TRUE  TRUE
#3 TRUE FALSE

print(see_datf(datf=datf1, condition_l=c("=="), val_l=list(c("a", 1))))

#      X1      X2
#1 TRUE  TRUE
#2 FALSE TRUE
#3 FALSE FALSE

print(see_datf(datf=datf1, condition_l=c("nchar"), val_l=list(c(1, 2))))

#      X1      X2
#1 TRUE TRUE
#2 TRUE TRUE
#3 TRUE TRUE

print(see_datf(datf=datf1, condition_l=c("not_reg"), val_l=list("[a-z]")))

#      X1      X2
#1 TRUE FALSE
#2 TRUE FALSE
#3 TRUE FALSE

```

see_file

see_file

Description

Allow to get the filename or its extension

Usage

```
see_file(string_, index_ext = 1, ext = TRUE)
```

Arguments

string_	is the input string
index_ext	is the occurrence of the dot that separates the filename and its extension
ext	is a boolean that if set to TRUE, will return the file extension and if set to FALSE, will return filename

Examples

```

print(see_file(string_="file.abc.xyz"))

#[1] ".abc.xyz"

```

```
print(see_file(string_="file.abc.xyz", ext=FALSE))

#[1] "file"

print(see_file(string_="file.abc.xyz", index_ext=2))

#[1] ".xyz"
```

see_idx

see_idx

Description

Returns a boolean vector to see if a set of elements contained in v1 is also contained in another vector (v2)

Usage

```
see_idx(v1, v2)
```

Arguments

v1	is the first vector
v2	is the second vector

Examples

```
print(see_idx(v1=c("oui", "non", "peut", "oo"), v2=c("oui", "peut", "oui")))

#[1] TRUE FALSE TRUE FALSE
```

see_inside

see_inside

Description

Return a list containing all the column of the files in the current directory with a chosen file extension and its associated file and sheet if xlsx. For example if i have 2 files "out.csv" with 2 columns and "out.xlsx" with 1 column for its first sheet and 2 for its second one, the return will look like this: c(column_1, column_2, column_3, column_4, column_5, unique_separator, "1-2-out.csv", "3-3-sheet_1-out.xlsx", 4-5-sheet_2-out.xlsx)

Usage

```
see_inside(
  pattern_,
  path_ = ".",
  sep_ = c(", "),
  unique_sep = "#####",
  rec = FALSE
)
```

Arguments

pattern_	is a vector containin the file extension of the spreadsheets ("xlsx", "csv"...)
path_	is the path where are located the files
sep_	is a vector containing the separator for each csv type file in order following the operating system file order, if the vector does not match the number of the csv files found, it will assume the separator for the rest of the files is the same as the last csv file found. It means that if you know the separator is the same for all the csv type files, you just have to put the separator once in the vector.
unique_sep	is a pattern that you know will never be in your input files
rec	is a boolean allows to get files recursively if set to TRUE, defaults to TRUE If x is the return value, to see all the files name, position of the columns and possible sheet name associanted with, do the following:

str_remove_untl	<i>str_remove_untl</i>
-----------------	------------------------

Description

Allow to remove pattern within elements from a vector precisely according to their occurrence.

Usage

```
str_remove_untl(
  inpt_v,
  ptrn_rm_v = c(),
  untl = list(c(1)),
  nvr_following_ptrn = "NA"
)
```

Arguments

inpt_v	is the input vector
ptrn_rm_v	is a vector containing the patterns to remove
until	is a list containing the occurrence(s) of each pattern to remove in the elements.
nvr_following_ptrn	is a sequel of characters that you are sure is not present in any of the elements in inpt_v

Examples

```
vec <- c("45/56-/98mm", "45/56-/98mm", "45/56-/98-mm//")

print(str_remove_untl(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1))))

#[1] "4556/98mm" "4556/98mm" "4556/98mm//"
```

```
print(str_remove_untl(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1:2))))

#[1] "455698mm" "455698mm" "455698mm//"
```

```
print(str_remove_until(inpt_v=vec[1], ptrn_rm_v=c("-", "/"), until=c("max")))
```

```
#[1] "455698mm" "455698mm" "455698mm"
```

unique_datf	<i>unique_datf</i>
-------------	--------------------

Description

Returns the input dataframe with the unique columns or rows.

Usage

```
unique_datf(inpt_datf, col = FALSE)
```

Arguments

inpt_datf	is the input dataframe
col	is a parameter that specifies if the dataframe returned should have unique columns or rows, defaults to F, so the dataframe returned by default has unique rows

Examples

```
datf1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"))
```

```
print(unique_datf(inpt_datf=datf1))
```

```
#   c.1..2..1..3. c..a.....z....a....p..
#1           1           a
#2           2           z
#4           3           p
```

```
datf1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"), c(1, 2, 1, 3))
```

```
print(unique_datf(inpt_datf=datf1, col=TRUE))
```

```
#   cur_v cur_v
#1     1     a
#2     2     z
#3     1     a
#4     3     p
```

```
unique_ltr_from_v  unique_ltr_from_v
```

Description

Returns the unique characters contained in all the elements from an input vector "inpt_v"

Usage

```
unique_ltr_from_v(inpt_v, keep_v = c("?", "!", ":", "&", ",", ".", letters))
```

Arguments

`inpt_v` is the input vector containing all the elements
`keep_v` is the vector containing all the characters that the elements in `inpt_v` may contain

Examples

```
print(unique_ltr_from_v(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "a  

#[1] "b" "o" "n" "j" "u" "r" "l" "p" "e" "c" "a" "v" "i"
```

```
unique_pos  unique_pos
```

Description

Allow to find the first index of the unique values from a vector.

Usage

```
unique_pos(vec)
```

Arguments

`vec` is the input vector

Examples

```
print(unique_pos(vec=c(3, 4, 3, 5, 6)))  

#[1] 1 2 4 5
```

until_stnl	<i>until_stnl</i>
------------	-------------------

Description

Maxes a vector to a chosen length. ex: if i want my vector c(1, 2) to be 5 of length this function will return me: c(1, 2, 1, 2, 1)

Usage

```
until_stnl(vec1, goal)
```

Arguments

vec1	is the input vector
goal	is the length to reach

Examples

```
print(until_stnl(vec1=c(1, 3, 2), goal=56))

# [1] 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3
#[39] 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3
```

val_replacer	<i>val_replacer</i>
--------------	---------------------

Description

Allow to replace value from dataframe to another one.

Usage

```
val_replacer(datf, val_replaced, val_replacor = TRUE)
```

Arguments

datf	is the input dataframe
val_replaced	is a vector of the value(s) to be replaced
val_replacor	is the value that will replace val_replaced

Examples

```
print(val_replacer(datf=data.frame(c(1, "oo4", TRUE, FALSE), c(TRUE, FALSE, TRUE, TRUE)),

# c.1...oo4...T..F. c.T..F..T..T.
#1                1                NA
#2                oo4                FALSE
#3                NA                NA
#4                FALSE                NA
```

vector_replacor	<i>vector_replacor</i>
-----------------	------------------------

Description

Allow to replace certain values in a vector.

Usage

```
vector_replacor(inpt_v = c(), sus_val = c(), rpl_val = c(), grep_ = FALSE)
```

Arguments

inpt_v	is the input vector
sus_val	is a vector containing all the values that will be replaced
rpl_val	is a vector containing the value of the elements to be replaced (sus_val), so sus_val and rpl_val should be the same size
grep_	is if the elements in sus_val should be equal to the elements to replace in inpt_v or if they just should found in the elements

Examples

```
print(vector_replacor(inpt_v=c(1:15), sus_val=c(3, 6, 8, 12), rpl_val=c("oui", "non", "e")
# [1] "1" "2" "oui" "4" "5" "non" "7" "e" "9" "10" "11" "a"
#[13] "13" "14" "15"

print(vector_replacor(inpt_v=c("non", "zez", "pp a ftf", "fdatfd", "assistance", "ert", "
#[1] "non" "zez" "oui" "fdatfd" "non" "ert" "non" "zz"
```

vec_in_datf	<i>vec_in_datf</i>
-------------	--------------------

Description

Allow to get if a vector is in a dataframe. Returns the row and column of the vector in the dataframe if the vector is contained in the dataframe.

Usage

```
vec_in_datf(
  inpt_datf,
  inpt_vec = c(),
  coeff = 0,
  stop_untl = 1,
  conventional = FALSE
)
```

Arguments

`inpt_datf` is the input dataframe
`inpt_vec` is the vector that may be in the input dataframe
`coeff` is the "slope coefficient" of `inpt_vec`
`stop_until` is the maximum number of the input vector the function returns, if in the dataframe
`conventional` is if a positive slope coefficient means that the vector goes upward or downward

Examples

```

datf1 <- data.frame(c(1:5), c(5:1), c("a", "z", "z", "z", "a"))

print(datf1)

#  c.1.5. c.5.1. c..a....z....z....z....a..
#1      1      5                                a
#2      2      4                                z
#3      3      3                                z
#4      4      2                                z
#5      5      1                                a

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 4, "z"), coeff=1))

#NULL

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=1))

#[1] 5 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(3, "z"), coeff=1))

#[1] 3 2

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(4, "z"), coeff=-1))

#[1] 2 2

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(2, 3, "z"), coeff=-1))

#[1] 2 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=-1, conventional=TRUE))

#[1] 5 1

datf1[4, 2] <- 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(1, "z"), coeff=-1, conventional=TRUE, stop_
#[1] 4 2 5 2

```

vlookup_datf	<i>vlookup_datf</i>
--------------	---------------------

Description

Allow to perform a vlookup on a dataframe

Usage

```
vlookup_datf(datf, v_id, col_id = 1, included_col_id = "yes")
```

Arguments

datf	is the input dataframe
v_id	is a vector containing the ids
col_id	is the column that contains the ids (default is equal to 1)
included_col_id	is if the result should return the col_id (default set to yes)

Examples

```
datf1 <- data.frame(c("az1", "az3", "az4", "az2"), c(1:4), c(4:1))

print(vlookup_datf(datf=datf1, v_id=c("az1", "az2", "az3", "az4")))

#   c..az1....az3....az4....az2.. c.1.4. c.4.1.
#2                                az1      1      4
#4                                az2      4      1
#21                               az3      2      3
#3                                az4      3      2
```

wider_datf	<i>wider_datf</i>
------------	-------------------

Description

Takes a dataframe as an input and the column to split according to a separator.

Usage

```
wider_datf(inpt_datf, col_to_splt = c(), sep_ = "-")
```

Arguments

inpt_datf	is the input dataframe
col_to_splt	is a vector containing the number or the colnames of the columns to split according to a separator
sep_	is the separator of the elements to split to new columns in the input dataframe

Examples

```

datf1 <- data.frame(c(1:5), c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"), c(5:1))

datf2 <- data.frame("col1"=c(1:5), "col2"=c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"))

print(wider_datf(inpt_datf=datf1, col_to_splt=c(2), sep="-"))

#      pre_datf X.o.  X.y.
#o-y      1      "o"   "y"   5
#hj-yy     2      "hj"  "yy"  4
#er-y      3      "er"   "y"   3
#k-ll      4      "k"   "ll"  2
#ooo-mm    5      "ooo" "mm"  1

print(wider_datf(inpt_datf=datf2, col_to_splt=c("col2"), sep="-"))

#      pre_datf X.o.  X.y.
#o-y      1      "o"   "y"
#hj-yy     2      "hj"  "yy"
#er-y      3      "er"   "y"
#k-ll      4      "k"   "ll"
#ooo-mm    5      "ooo" "mm"

```

Index

all_stat, [3](#)
any_join_datf, [4](#)
appndr, [6](#)

better_match, [7](#)

can_be_num, [7](#)
closer_ptrn, [8](#)
closer_ptrn_adv, [10](#)
clusterizer_v, [12](#)
colins_datf, [14](#)
converter_date, [15](#)
converter_format, [16](#)
cost_and_taxes, [17](#)
cut_v, [18](#)

data_gen, [18](#)
data_meshup, [20](#)
date_addr, [21](#)
date_converter_reverse, [23](#)
dcr_untl, [23](#)
dcr_val, [24](#)

equalizer_v, [25](#)
extrt_only_v, [25](#)

fillr, [26](#)
fixer_nest_v, [26](#)
fold_rec, [27](#)
fold_rec2, [27](#)
format_date, [28](#)

geo_min, [28](#)
get_rec, [29](#)
globe, [29](#)
groupr_datf, [30](#)

id_keepr, [31](#)
incr_fillr, [32](#)
insert_datf, [33](#)
inter_max, [34](#)
inter_min, [35](#)
is_divisible, [36](#)
isnt_divisible, [36](#)

leap_yr, [37](#)
letter_to_nb, [37](#)
list_files, [38](#)
lst_flatnr, [38](#)

multitud, [39](#)

nb_to_letter, [39](#)
nest_v, [41](#)
nestr_datf1, [40](#)
nestr_datf2, [41](#)
new_ordered, [42](#)
non_unique, [43](#)

occu, [43](#)

paste_datf, [44](#)
pattern_generator, [44](#)
pattern_gettr, [45](#)
pattern_tuning, [46](#)
ptrn_switchr, [47](#)
ptrn_twkr, [48](#)

rearangr_v, [49](#)
regroupr, [50](#)

save_untl, [51](#)
see_datf, [52](#)
see_file, [53](#)
see_idx, [54](#)
see_inside, [54](#)
str_remove_untl, [55](#)

unique_datf, [56](#)
unique_ltr_from_v, [57](#)
unique_pos, [57](#)
until_stnl, [58](#)

val_replacer, [58](#)
vec_in_datf, [59](#)
vector_replacor, [59](#)
vlookup_datf, [61](#)

wider_datf, [61](#)