Package 'edm1'

July 17, 2024

Title Simplify Complex Data Manipulation

 better_unique
 12

 can_be_num
 13

 closer_ptrn
 13

 closer_ptrn_adv
 16

 clusterizer_v
 17

 colins_datf
 19

 col_to_row
 20

 converter_date
 21

 converter_format
 22

 cost_and_taxes
 22

 cumulated_rows
 23

 cumulated_rows_na
 24

 cutr_v
 25

2 Contents

cut_v	25
lata_gen	26
lata_meshup	28
date_addr	29
date_converter_reverse	30
dcr_untl	31
der val	32
lepth_pairs_findr	32
liff_datf	33
lynamic_idx_convertr	33
elements equalifier	34
equalizer_v	35
extract_normal	35
extrt_only_v	41
_ • -	42
illr	
ixer_nest_v	43
fold_rec	43
fold_rec2	44
Format_date	44
geo_min	45
get_rec	46
globe	46
glue_groupr_v	47
grep_all	47
grep_all2	48
groupr_datf	49
gsub_mult	50
now_normal	50
 now_unif	53
d_keepr	
ncr_fillr	55
nfinite_char_seq	
nner all	
nsert_datf	57
ntersect_all	58
	58
ntersect_mod	
nter_max	60
nter_min	61
snt_divisible	62
s_divisible	62
oin_n_lvl	63
ust_chr	64
ust_chr2	65
ust_nb	65
ust_nb2	66
eap_yr	66
eft_all	67
etter_to_nb	68
ist files	68
st flatnr	69
match by	69
militud	70

Contents 3

b2_follow	71
b_follow	71
b_to_letter	72
estr_datf1	73
estr_datf2	74
est_v	75
ew_ordered	76
ormal dens	76
	77
ld_to_new_idx	77
	78
airs findr merger	78
airs_insertr	80
airs_insertr2	81
aste_datf	83
attern_generator	83
attern_gettr	84
attern_tuning	85
ower_to_char	86
re to post idx	86
<u> </u>	87
trn_switchr	
trn_twkr	87
ead_edm_parser	88
earangr_v	89
gex_spe_detect	90
egroupr	90
ow_to_col	91
_print	92
ave_untl	93
ee_datf	93
ee_diff	95
ee_diff_all	95
ee_file	96
ee_idx	97
ee_inside	97
ee_mode	98
elected_char	99
ort_date	99
ort_normal_qual	100
ort_normal_qual2	104
blit by step	107
r remove untl	108
ıb mult	
ccessive diff	
wipr	
est order	
o_unique	
nion all	
nion_keep	
nique_datf	
nique_ltr_from_v	
nique_nu_rrom_v	
mque pus	113

4 all_stat

```
      unique_total
      116

      until_stnl
      116

      val_replacer
      117

      vector_replacor
      117

      vec_in_datf
      118

      vlookup_datf
      119

      wider_datf
      120

      wide_to_narrow_idx
      121

      write_edm_parser
      122

      Index
      123
```

all stat all stat

Description

Allow to see all the main statistics indicators (mean, median, variance, standard deviation, sum, max, min, quantile) of variables in a dataframe by the modality of a variable in a column of the input datarame. In addition to that, you can get the occurrence of other qualitative variables by your chosen qualitative variable, you have just to precise it in the vector "stat_var" where all the statistics indicators are given with "occu-var_you_want/".

Usage

```
all_stat(inpt_v, var_add = c(), stat_var = c(), inpt_datf)
```

Arguments

inpt_v is the modalities of the variables
var_add is the variables you want to get the stats from
stat_var is the stats indicators you want
inpt_datf is the input dataframe

```
datf <- data.frame("mod"=c("first", "seco", "seco", "first", "first", "third", "first"),
                "var1"=c(11, 22, 21, 22, 22, 11, 9),
                                       "z", "z", "d",
               "var2"=c("d", "d", "z",
               "var3"=c(45, 44, 43, 46, 45, 45, 42),
              "var4"=c("A", "A", "A", "A", "B", "C",
                                                     "C"))
print(all_stat(inpt_v=c("first", "seco"), var_add = c("var1", "var2", "var3", "var4"),
 stat_var=c("sum", "mean", "median", "sd", "occu-var2/", "occu-var4/", "variance",
"quantile-0.75/"),
inpt_datf=datf))
#
    modal_v var_vector occu sum mean med standard_devaition
                                                                      variance
#1
     first
#2
                                  16 16.5
                                             6.97614984548545 48.6666666666667
                  var1
#3
                var2-d
                        1
#4
                var2-z
#5
                  var3
                            178 44.5
                                       45
                                            1.73205080756888
                                                                              3
```

any_join_datf 5

```
#6
                var4-A
#7
                var4-B
                          1
#8
                var4-C
                          1
#9
      seco
                             43 21.5 21.5 0.707106781186548
                                                                           0.5
#10
                 var1
                       1
#11
               var2-d
#12
                var2-z
                        1
                 var3
                             87 43.5 43.5 0.707106781186548
                                                                           0.5
#13
                       2
#14
                var4-A
#15
                var4-B
                        0
#16
                var4-C
   quantile-0.75
#1
#2
               22
#3
#4
#5
           45.25
#6
#7
#8
#9
#10
           21.75
#11
#12
           43.75
#13
#14
#15
#16
```

any_join_datf

any_join_datf

Description

Allow to perform SQL joints with more features

Usage

```
any_join_datf(
  inpt_datf_l,
  join_type = "inner",
  join_spe = NA,
  id_v = c(),
  excl_col = c(),
  rtn_col = c(),
  d_val = NA
)
```

Arguments

```
inpt_datf_l is a list containing all the dataframe
```

join_type is the joint type. Defaults to inner but can be changed to a vector containing all the dataframes you want to take their ids to don external joints.

6 any_join_datf

can be equal to a vector to do an external joints on all the dataframes. In this join spe case, join type should not be equal to "inner" id_v is a vector containing all the ids name of the dataframes. The ids names can be changed to number of their columns taking in count their position in inpt_datf_l. It means that if my id is in the third column of the second dataframe and the first dataframe have 5 columns, the column number of the ids is 5 + 3 = 8is a vector containing the column names to exclude, if this vector is filled so excl col "rtn_col" should not be filled. You can also put the column number in the manner indicated for "id_v". Defaults to c() is a vector containing the column names to retain, if this vector is filled so rtn_col "excl col" should not be filled. You can also put the column number in the manner indicated for "id v". Defaults to c() is the default val when here is no match d_val

Examples

#

#2

#3

13

12

```
datf1 \leftarrow data.frame("val"=c(1, 1, 2, 4), "ids"=c("e", "a", "z", "a"),
"last"=c("oui", "oui", "non", "oui"),
"second_ids"=c(13, 11, 12, 8), "third_col"=c(4:1))
"bool"=c(TRUE, FALSE, FALSE, FALSE, TRUE, TRUE),
"second_ids"=c(13, 12, 8, 34, 22, 12))
datf3 \leftarrow data.frame("val"=c(1, 9, 2, 4), "ids"=c("a", "a", "z", "a"),
"last"=c("oui", "oui", "non", "oui"),
"second_ids"=c(13, 11, 12, 8))
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type="inner",
id_v=c("ids", "second_ids"),
               excl_col=c(), rtn_col=c()))
# ids val ids last second_ids val ids bool second_ids val ids last second_ids
#3 z12
      2 z non
                        12 7 z FALSE
                                               12 2 z non
                                                                    12
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type="inner", id_v=c("ids
excl_col=c(), rtn_col=c()))
#
  ids val ids last second_ids val ids bool second_ids val ids last second_ids
#2
      1 a oui
                     11 3 a TRUE
                                             13 1 a oui
                                                                  1.3
  а
#3
    z
        2
           z non
                         12
                             7
                                 z FALSE
                                                12
                                                    2
                                                        Z
                                                          non
                                                                     12
#4
    а
           a oui
                             4
                                 a FALSE
                                                34
                                                    9
                                                        а
                                                          oui
                                                                     11
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type=c(1), id_v=c("ids"),
               excl_col=c(), rtn_col=c()))
  ids val ids last second_ids val ids bool second_ids val ids last
                         13 <NA> <NA>
#1
    е
       1
          e oui
                                     <NA>
                                              <NA> <NA> <NA> <NA>
                                 a TRUE
#2
                         11
                             3
                                                 13
    а
       1
           а
              oui
                                                      1
                                                           a oui
       2 z non
                              7
#3
   Z
                        12
                                  z FALSE
                                                 12
                                                       2
                                                           z non
#4
                         8
                            4
                                  a FALSE
                                                 34
                                                       9
       4
          a oui
                                                           a oui
   а
# second_ids
#1
        <NA>
```

appndr 7

```
#4
         11
print(any_join_datf(inpt_datf_l=list(datf2, datf1, datf3), join_type=c(1, 3),
              id_v=c("ids", "second_ids"),
              excl_col=c(), rtn_col=c()))
   ids val ids bool second_ids val ids last second_ids val ids last
#1 a13
       3 a TRUE 13 <NA> <NA> <NA>
                                                   1 a oui
        7 z FALSE
                         12
                                              12 2 z non
#2
  z12
                             2 z non
                          8 <NA> <NA> <NA>
                                             <NA> <NA> <NA> <NA>
#3
   z8
        2 z FALSE
                         34 <NA> <NA> <NA>
#4 a34
        4 a FALSE
                                             <NA> <NA> <NA> <NA>
#5 a22
        1 a TRUE
                         22 <NA> <NA> <NA>
                                             <NA> <NA> <NA> <NA>
#6 a12
        2 a TRUE
                         12 <NA> <NA> <NA>
                                             <NA> <NA> <NA> <NA>
#7 a13 <NA> <NA> <NA>
                       <NA> <NA> <NA> <NA>
                                             <NA> <NA> <NA> <NA>
                       <NA> 1 a oui
#8 all <NA> <NA> <NA>
                                               11 9 a oui
#9 z12 <NA> <NA> <NA>
                       <NA> <NA> <NA> <NA>
                                             <NA> <NA> <NA> <NA>
#10 a8 <NA> <NA> <NA>
                                              8 4 a oui
                        <NA> 4 a oui
   second_ids
#
#1
         13
#2
         12
#3
        <NA>
#4
        <NA>
#5
        <NA>
#6
        <NA>
#7
        <NA>
         11
#8
#9
        <NA>
#10
         8
print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type=c(1), id_v=c("ids"),
             excl_col=c(), rtn_col=c()))
#ids val ids last second_ids val ids bool second_ids val ids last
                  13 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#1 e 1 e oui
#2
      1 a oui
                      11 3 a TRUE
                                            13 1 a oui
                      12 7 z FALSE
#3 z 2 z non
                                            12 2 z non
                      8 4 a FALSE
                                                9 a oui
                                             34
#4
      4 a oui
# second_ids
#1
       <NA>
#2
        13
         12
#3
#4
         11
```

appndr appndr

Description

Append to a vector "inpt_v" a special value "val" n times "mmn". The appending begins at "strt" index.

Usage

```
appndr(inpt_v, val = NA, hmn, strt = "max")
```

8 better_match

Arguments

inpt_v is the input vector

val is the special value

hmn is the number of special value element added

strt is the index from which appending begins, defaults to max which means the end of "inpt_v"

Examples

```
print(appndr(inpt_v=c(1:3), val="oui", hmn=5))
#[1] "1"    "2"    "3"    "oui" "oui" "oui" "oui" "oui"
print(appndr(inpt_v=c(1:3), val="oui", hmn=5, strt=1))
#[1] "1"    "oui" "oui" "oui" "oui" "oui" "2"    "3"
```

better_match

better_match

Description

Allow to get the nth element matched in a vector

Usage

```
better_match(inpt_v = c(), ptrn, untl = 1, nvr_here = NA)
```

Arguments

inpt_v is the input vector
ptrn is the pattern to be matched
untl is the maximum number of matched pattern outputed
nvr_here is a value you are sure is not present in inpt_v

```
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, untl=1))
#[1] 3
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, untl=5))
#[1] 3 13 16
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=c(3, 4), untl=5))
[1] 3 13 16 4 14
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=c(3, 4), untl=c(1, 5)))
```

better_split 9

```
[1] 3 4 14
```

```
better_split better_split
```

Description

Allows to split a string by multiple split, returns a vector and not a list.

Usage

```
better_split(inpt, split_v = c())
```

Arguments

```
inpt is the input character
split_v is the vector containing the splits
```

Examples

```
print(better_split(inpt = "o-u_i", split_v = c("-")))
[1] "o" "u_i"
print(better_split(inpt = "o-u_i", split_v = c("-", "_")))
[1] "o" "u" "i"
```

```
better_split_any better_split_any
```

Description

Allows to split a string by multiple split regardless of their length, returns a vector and not a list. Contrary to better_split, this functions keep the delimiters in the output.

Usage

```
better_split_any(inpt, split_v = c())
```

Arguments

```
inpt is the input character
split_v is the vector containing the splits
```

10 better_sub

Examples

```
print(better_split_any(inpt = "o-u_i", split_v = c("-")))
[1] "o" "-" "u_i"
print(better_split_any(inpt = "o-u_i", split_v = c("-", "_")))
[1] "o" "-" "u" "_" "i"
[1] "--"
                "/"
          " 0 "
                                   "m"
                                                "m"
                                                       "/"
[10] "_"
                "-opo-" "/"
                                          "-u"
          "_"
                             "m"
                                   "/"
                                                       "i-"
[19] "_"
          "__"
print(better_split_any(inpt = "(ok(ee:56))(ok2(oui)(ee:4))", split_v = c("(", ")", ":")))
        "ok" "("
[1] "("
                 "ee" ":"
                           "56" ")"
                                     ")" "(" "ok2" "(" "oui"
        "("
             "ee" ":"
                       "4"
                            ")"
                                ")"
 [13] ")"
```

better_sub

better_sub

Description

Allow to perform a sub operation to a given number of matched patterns, see examples

Usage

```
better_sub(inpt_v = c(), pattern, replacement, untl_v = c())
```

Arguments

inpt_v is a vector containing all the elements that contains expressions to be substituted
pattern is the expression that will be substituted
replacement is the expression that will substituate pattern
untl_v is a vector containing, for each element of inpt_v, the number of pattern that will be substituted

better_sub_mult 11

better_sub_mult

better_sub_mult

Description

Allow to perform a sub_mult operation to a given number of matched patterns, see examples

Usage

```
better_sub_mult(
  inpt_v = c(),
  pattern_v = c(),
  replacement_v = c(),
  untl_v = c()
```

Arguments

inpt_v is a vector containing all the elements that contains expressions to be substituted
pattern_v is a vector containing all the patterns to be substituted in any elements of inpt_v
replacement_v
 is a vector containing the expression that are going to substituate those provided
 by pattern_v

untl_v is a vector containing, for each element of inpt_v, the number of pattern that will
be substituted

12 better_unique

better_unique

better_unique

Description

Returns the element that are not unique from the input vector

Usage

```
better_unique(inpt_v, occu = ">-1-")
```

Arguments

inpt_v

is the input vector containing the elements

occu

is a parameter that specifies the occurence of the elements that must be returned, defaults to ">-1-" it means that the function will return all the elements that are present more than one time in inpt_v. The synthax is the following "comparaison_type-actual_value-". The comparaison type may be "==" or ">" or "<". Occu can also be a vector containing all the occurence that must have the elements to be returned.

```
print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non")))
#[1] "oui" "non"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu="=
#[1] "oui"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=">
#[1] "non"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=c("oui", "oui", "non", "peut", "peut1", "non")
```

can_be_num 13

```
print(better_unique(inpt_v = c("a", "b", "c", "c"), occu = "==-1-"))
[1] "a" "b"
print(better_unique(inpt_v = c("a", "b", "c", "c"), occu = "<-2-"))
[1] "a" "b"</pre>
```

can_be_num

can_be_num

Description

Return TRUE if a variable can be converted to a number and FALSE if not (supports float)

Usage

```
can_be_num(x)
```

Arguments

Х

is the input value

Examples

```
print(can_be_num("34.677"))
#[1] TRUE
print(can_be_num("34"))
#[1] TRUE
print(can_be_num("3rt4"))
#[1] FALSE
print(can_be_num(34))
#[1] TRUE
```

closer_ptrn

closer_ptrn

Description

Take a vector of patterns as input and output each chosen word with their closest patterns from chosen patterns.

14 closer_ptrn

Usage

```
closer_ptrn(
  inpt_v,
  base_v = c("?", letters),
  excl_v = c(),
  rtn_v = c(),
  sub_excl_v = c(),
  sub_rtn_v = c()
)
```

Arguments

inpt_v	is the input vector containing all the patterns
base_v	must contain all the characters that the patterns are succeptible to contain, defaults to c("?", letters). "?" is necessary because it is internaly the default value added to each element that does not have a sufficient length compared to the longest pattern in inpt_v. If set to NA, the function will find by itself the elements to be filled with but it may takes an extra time
excl_v	is the vector containing all the patterns from inpt_v to exclude for comparing them to others patterns. If this parameter is filled, so "rtn_v" must be empty.
rtn_v	is the vector containing all the patterns from inpt_v to keep for comparing them to others patterns. If this parameter is filled, so "rtn_v" must be empty.
sub_excl_v	is the vector containing all the patterns from inpt_v to exclude for using them to compare to another pattern. If this parameter is filled, so "sub_rtn_v" must be empty.
sub_rtn_v	is the vector containing all the patterns from inpt_v to retain for using them to compare to another pattern. If this parameter is filled, so "sub_excl_v" must be empty.

```
print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir"
# [[1]]
#[1] "bonjour"
# 
# [[2]]
#[1] "lpoerc" "nonnour" "bonnour" "aurevoir"
# 
# [[3]]
# [1] 1 1 2 7 8
# 
# [[4]]
# [1] "lpoerc"
# 
# [[5]]
# [1] "bonjour" "nonnour" "bonnour" "aurevoir"
# 
# [[6]]
# [1] 7 7 7 7 7
# 
# # [[7]]
# [1] "nonnour"
```

closer_ptrn 15

```
#[[8]]
#[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"
#[[9]]
#[1] 1 1 2 7 8
#[[10]]
#[1] "bonnour"
#[[11]]
#[1] "bonjour" "lpoerc" "nonnour" "nonjour" "aurevoir"
#[[12]]
#[1] 1 1 2 7 8
#[[13]]
#[1] "nonjour"
#[[14]]
#[1] "bonjour" "lpoerc" "nonnour" "bonnour" "aurevoir"
#[[15]]
#[1] 1 1 2 7 8
#[[16]]
#[1] "aurevoir"
#[[17]]
#[1] "bonjour" "lpoerc" "nonnour" "bonnour" "nonjour"
#[[18]]
#[1] 7 8 8 8 8
print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoi
excl_v=c("nonnour", "nonjour"),
                sub_excl_v=c("nonnour")))
#[1] 3 5
#[[1]]
#[1] "bonjour"
#[[2]]
#[1] "lpoerc" "bonnour" "nonjour" "aurevoir"
#[[3]]
#[1] 1 1 7 8
#[[4]]
#[1] "lpoerc"
#[[5]]
#[1] "bonjour" "bonnour" "nonjour" "aurevoir"
#[[6]]
#[1] 7 7 7 7
```

16 closer_ptrn_adv

```
#[[7]]
#[1] "bonnour"
#
#[[8]]
#[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"
#
#[[9]]
#[1] 0 1 2 7 8
#
#[[10]]
#[1] "aurevoir"
#
#[[11]]
#[1] "bonjour" "lpoerc" "nonjour" "aurevoir"
#
#[[12]]
#[1] 0 7 8 8
```

closer_ptrn_adv

closer_ptrn_adv

Description

Allow to find how patterns are far or near between each other relatively to a vector containing characters at each index ("base_v"). The function gets the sum of the indexes of each pattern letter relatively to the characters in base_v. So each pattern can be compared.

Usage

```
closer_ptrn_adv(
  inpt_v,
  res = "raw_stat",
  default_val = "?",
  base_v = c(default_val, letters),
  c_word = NA
)
```

Arguments

inpt_v	is the input vector containing all the patterns to be analyzed
res	is a parameter controling the result. If set to "raw_stat", each word in inpt_v will come with its score (indexes of its letters relatively to base_v). If set to something else, so "c_word" parameter must be filled.
default_val	is the value that will be added to all patterns that do not equal the length of the longest pattern in inpt_v. Those get this value added to make all patterns equal in length so they can be compared, defaults to "?"
base_v	is the vector from which all pattern get its result (letters indexes for each pattern relatively to base_v), defaults to c("default_val", letters). "default_val" is another parameter and letters is all the western alphabetic letters in a vector
c_word	is a pattern from which the nearest to the farest pattern in inpt_v will be compared

clusterizer_v 17

Examples

```
clusterizer_v clusterizer_v
```

Description

Allow to output clusters of elements. Takes as input a vector "inpt_v" containing a sequence of number. Can also take another vector "w_v" that has the same size of inpt_v because its elements are related to it. The way the clusters are made is related to an accuracy value which is "c_val". It means that if the difference between the values associated to 2 elements is superior to c_val, these two elements are in distinct clusters. The second element of the outputed list is the begin and end value of each cluster.

Usage

```
clusterizer_v(inpt_v, w_v = NA, c_val)
```

Arguments

inpt_v is the vector containing the sequence of number
w_v is the vector containing the elements related to inpt_v, defaults to NA
c_val is the accuracy of the clusterization

```
print(clusterizer_v(inpt_v=sample.int(20, 26, replace=TRUE), w_v=NA, c_val=0.9))
# [[1]]
# [[1]][[1]]
# [1] 1
# # [[1]][[2]]
# [1] 2
```

18 clusterizer_v

```
#[[1]][[3]]
#[1] 3
#[[1]][[4]]
#[1] 4
#[[1]][[5]]
#[1] 5 5
#[[1]][[6]]
#[1] 6 6 6 6
#[[1]][[7]]
#[1] 7 7 7
#[[1]][[8]]
#[1] 8 8 8
#[[1]][[9]]
#[1] 9
#[[1]][[10]]
#[1] 10
#[[1]][[11]]
#[1] 12
#[[1]][[12]]
#[1] 13 13 13
#[[1]][[13]]
#[1] 18 18 18
#[[1]][[14]]
#[1] 20
#
#[[2]]
# [1] "1" "1" "-" "2" "2" "-" "3" "3" "-" "4" "4" "-" "5" "5" "-" #[16] "6" "6" "-" "7" "7" "-" "8" "8" "-" "9" "9" "-" "10" "10" "-"
#[31] "12" "12" "-" "13" "13" "-" "18" "18" "-"
                                                        "20" "20"
print(clusterizer_v(inpt_v=sample.int(40, 26, replace=TRUE), w_v=letters, c_val=0.29))
#[[1]]
#[[1]][[1]]
#[1] "a"
#[[1]][[2]]
#[1] "b"
#[[1]][[3]]
#[1] "c" "d"
#[[1]][[4]]
#[1] "e" "f"
#
```

colins_datf

```
#[[1]][[5]]
#[1] "g" "h" "i" "j"
#[[1]][[6]]
#[1] "k"
#[[1]][[7]]
#[1] "1"
#[[1]][[8]]
#[1] "m" "n"
#[[1]][[9]]
#[1] "o"
#[[1]][[10]]
#[1] "p"
#[[1]][[11]]
#[1] "q" "r"
#[[1]][[12]]
#[1] "s" "t" "u"
#[[1]][[13]]
#[1] "v"
#[[1]][[14]]
#[1] "w"
#[[1]][[15]]
#[1] "x"
#[[1]][[16]]
#[1] "y"
#[[1]][[17]]
#[1] "z"
#[[2]]
# [1] "13" "13" "-" "14" "14" "-" "15" "15" "-" "16" "16" "-" "17" "17" "-" # [16] "19" "19" "-" "21" "21" "-" "22" "22" "-" "23" "23" "-" "25" "25" "-" # [31] "27" "27" "-" "29" "29" "-" "30" "30" "-" "31" "31" "-" "34" "34" "-" # [46] "35" "35" "-" "37" "37"
```

colins_datf

colins_datf

Description

Allow to insert vectors into a dataframe.

20 col_to_row

Usage

```
colins_datf(inpt_datf, target_col = list(), target_pos = list())
```

Arguments

is the dataframe where vectors will be inserted inpt_datf target_col is a list containing all the vectors to be inserted is a list containing the vectors made of the columns names or numbers where target_pos the associated vectors from target_col will be inserted after

Examples

```
datf1 <- data.frame("frst_col"=c(1:5), "scd_col"=c(5:1))</pre>
print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
           c("u", "z", "z", "z", "u")),
              target_pos=list(c("frst_col", "scd_col"), c("scd_col"))))
  frst_col cur_col scd_col cur_col.1 cur_col
#1
        1
              oui 5 oui
                      4
#2
         2
              oui
                              oui
#3
        3
                      3
                              oui
              oui
                                       Z
#4
        4
                      2
                              non
              non
#5
        5
                      1
              non
                              non
print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
            c("u", "z", "z", "z", "u")),
              target_pos=list(c(1, 2), c("frst_col"))))
# frst_col cur_col scd_col cur_col cur_col
       1 oui 5 u
#1
        2
                      4
                      4 3 z 2 2 1 u
#2
            oui
                                    oui
#3
        3 oui
                                    oui
```

non

non

```
col_to_row
                      col_to_row
```

Description

#4

#5

Allow to reverse a dataframe (cols become rows and rows become cols)

Usage

```
col_to_row(inpt_datf)
```

Arguments

```
is the inout dataframe
inpt_datf
```

4 non

non

5

converter_date 21

Examples

```
datf_test <- data.frame(c(1:11), c(11:1))
print(col_to_row(inpt_datf = datf_test))

X1 X2 X3 X4 X5 X6 X7 X8 X9 X10 X11
1 1 2 3 4 5 6 7 8 9 10 11
2 11 10 9 8 7 6 5 4 3 2 1</pre>
```

converter_date

converter_date

Description

Allow to convert any date like second/minute/hour/day/month/year to either second, minute...year. The input date should not necessarily have all its time units (second, minute...) but all the time units according to a format. Example: "snhdmy" is for second, hour, minute, day, month, year. And "mdy" is for month, day, year.

Usage

```
converter_date(inpt_date, convert_to, frmt = "snhdmy", sep_ = "-")
```

Arguments

```
inpt_date is the input date
convert_to is the time unit the input date will be converted ("s", "n", "h", "d", "m", "y")
frmt is the format of the input date
sep_ is the separator of the input date. For example this input date "12-07-2012" has
"-" as a separator
```

```
print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="m"))
#[1] 24299.15
print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="y"))
#[1] 2024.929
print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="s"))
#[1] 63900626400
print(converter_date(inpt_date="63900626400", sep_="-", frmt="s", convert_to="y"))
#[1] 2024.929
print(converter_date(inpt_date="2024", sep_="-", frmt="y", convert_to="s"))
#[1] 63873964800
```

22 cost_and_taxes

```
converter_format converter_format
```

Description

Allow to convert a format to another

Usage

```
converter_format(inpt_val, sep_ = "-", inpt_frmt, frmt, default_val = "00")
```

Arguments

```
    inpt_val is the input value that is linked to the format
    sep_ is the separator of the value in inpt_val
    inpt_frmt is the format of the input value
    frmt is the format you want to convert to
    default_val is the default value given to the units that are not present in the input format
```

Examples

```
cost_and_taxes cost_and_taxes
```

Description

Allow to calculate basic variables related to cost and taxes from a bunch of products (elements). So put every variable you know in the following order:

Usage

```
cost_and_taxes(
  qte = NA,
  pu = NA,
  prix_ht = NA,
  tva = NA,
  prix_ttc = NA,
  prix_tva = NA,
```

cumulated_rows 23

```
pu_ttc = NA,
adjust = NA,
prix_d_ht = NA,
prix_d_ttc = NA,
pu_d = NA,
pu_d_ttc = NA
```

Arguments

is the quantity of elements qte is the price of a single elements without taxes рu is the duty-free price of the whole set of elements prix_ht tva is the percentage of all taxes is the price of all the elements with taxes prix_ttc is the cost of all the taxes prix_tva is the price of a single element taxes included pu_ttc is the discount percentage adjust prix_d_ht is the free-duty price of an element after discount is the price with taxes of an element after discount prix_d_ttc pu_d is the price of a single element after discount and without taxes is the free-duty price of a single element after discount pu_d_ttc

Examples

```
print(cost_and_taxes(pu=45, prix_ttc=2111, qte=23))
# [1] 23.000000 45.000000 1.039614 2111.000000 1076.000000
# [7] 45.000000 NA NA NA NA NA
```

cumulated_rows cumulated_rows

Description

Output a vector of size that equals to the rows number of the input dataframe, with TRUE value at the indices corresponding to the row where at least a cell of any column is equal to one of the values inputed in $values\ v$

Usage

```
cumulated_rows(inpt_datf, values_v = c())
```

Arguments

 $\verb"inpt_datf" is the input data.frame"$

values_v is a vector containing all the values that a cell has to equal to return a TRUE

value in the output vector at the index corresponding to the row of the cell

24 cumulated_rows_na

Examples

```
datf\_teste <- data.frame(c(1:10), c(10:1))
print(datf_teste)
  c.1.10. c.10.1.
        1
              10
2
        2
3
        3
                8
4
        4
                7
5
        5
6
        6
7
        7
                4
8
       8
                3
9
        9
                2
10
       10
                1
print(cumulated_rows(inpt_datf = datf_teste, values_v = c(2, 3)))
     FALSE TRUE TRUE
[1]
                      FALSE FALSE FALSE TRUE TRUE
                                                              FALSE
```

Description

Output a vector of size that equals to the rows number of the input dataframe, with TRUE value at the indices corresponding to the row where at least a cell of any column is equal to NA.

Usage

```
cumulated_rows_na(inpt_datf)
```

Arguments

```
inpt_datf is the input data.frame
```

```
datf_teste <- data.frame(c(1, 2, 3, 4, 5, NA, 7), c(10, 9, 8, NA, 7, 6, NA))
print(datf_teste)
  c.1..2..3..4..5..NA..7. c.10..9..8..NA..7..6..NA.
2
                        2
                                                    9
3
                                                    8
                        3
4
                        4
                                                   NA
5
                        5
                                                    7
6
                       NA
                                                    6
                                                   NA
print(cumulated_rows_na(inpt_datf = datf_teste))
```

cutr_v 25

```
[1] FALSE FALSE TRUE FALSE TRUE TRUE
```

```
cutr_v cutr_v
```

Description

Allow to reduce all the elements in a vector to a defined size of nchar

Usage

```
cutr_v(inpt_v, untl = "min")
```

Arguments

```
inpt_v is the input vector
unt1 is the maximum size of nchar authorized by an element, defaults to "min", it
means the shortest element in the list
```

Examples

```
test_v <- c("oui", "nonon", "ez", "aa", "a", "dsfsdsds")
print(cutr_v(inpt_v=test_v, untl="min"))
#[1] "o" "n" "e" "a" "a" "d"
print(cutr_v(inpt_v=test_v, untl=3))
#[1] "oui" "non" "ez" "aa" "a" "dsf"</pre>
```

```
cut_v cut_v
```

Description

Allow to convert a vector to a dataframe according to a separator.

Usage

```
cut_v(inpt_v, sep_ = "")
```

Arguments

```
inpt_v is the input vector
sep_ is the separator of the elements in inpt_v, defaults to ""
```

26 data_gen

Examples

data_gen

data_gen

Description

Allo to generate in a csv all kind of data you can imagine according to what you provide

Usage

Arguments

type_	is a vector. Its arguments designates a column, a column can be made of numbers ("number"), string ("string") or both ("mixed")
strt_l	is a vector containing for each column the row from which the data will begin to be generated
nb_r	is a vector containing for each column, the number of row full from generated data
output	is the name of the output csv file, defaults to NA so no csv will be outputed by default

data_gen 27

properties	is linked to type_distri because it is the parameters ("min_val-max_val") for "random type", ("u-x") for the poisson distribution, ("u-d") for gaussian distribution
type_distri	is a vector which, for each column, associate a type of distribution ("random", "poisson", "gaussian"), it meas that non only the number but also the length of the string will be randomly generated according to these distribution laws
str_source	is the source (vector) from which the character creating random string are (default set to the occidental alphabet)
round_l	is a vector which, for each column containing number, associate a round value, if the type of the value is numeric
sep_	is the separator used to write data in the csv

Value

new generated data in addition to saving it in the output

```
print(data_gen())
# X1
      X2
            ХЗ
  4 2
#1
           <NA>
   2
#2
           <NA>
   5 2
#3
           <NA>
   2 abcd <NA>
#4
  4 abcd
#5
           <NA>
#6
   2 4 <NA>
   2 abc <NA>
#7
#8 4 abc <NA>
#9 4 3 <NA>
#10 4 abc abcd
#11 5 <NA>
           abc
#12 4 <NA>
           abc
#13 1 <NA>
            ab
#14 1 <NA> abcde
#15 2 <NA> abc
#16 4 <NA>
            а
#17 1 <NA> abcd
#18 4 <NA>
           ab
#19 2 <NA> abcd
           ab
#20 3 <NA>
   3 <NA> abcd
#21
#22 2 <NA>
            a
#23
    4 <NA>
            abc
#24 1 <NA>
           abcd
#25 4 <NA>
           abc
#26 4 <NA>
            ab
#27 2 <NA>
            abc
#28 5 <NA>
            ab
#29 3 <NA>
            abc
#30 5 <NA> abcd
#31 2 <NA>
           abc
#32 2 <NA>
            abc
#33 1 <NA>
           ab
#34 5 <NA>
```

28 data_meshup

```
ab
ab
#35 4 <NA>
#36 1 <NA>
#37 1 <NA> abcde
#38 5 <NA> abc
#39 4 <NA>
#40 5 <NA> abcde
#41 2 <NA> ab
#42 3 <NA> ab
#43 2 <NA> ab
#44 4 <NA> abcd
#45 5 <NA> abcd
#46 3 <NA> abcd
#47 2 <NA> abcd
#48 3 <NA> abcd
#49 3 <NA> abcd
#50 4 <NA>
print(data_gen(strt_l=c(0, 0, 0), nb_r=c(5, 5, 5)))
     X2
# X1
            Х3
#1
   2
       a abc
#2
   3 abcde ab
#3
   4 abcde
#4 1 3 abcd
#5 3 a abcd
```

data_meshup

data_meshup

Description

Allow to automatically arrange 1 dimensional data according to vector and parameters

Usage

```
data_meshup(
  data,
  cols = NA,
  file_ = NA,
  sep_ = ";",
  organisation = c(2, 1, 0),
  unic_sep1 = "_",
  unic_sep2 = "-"
)
```

Arguments

data	is the data provided (vector) each column is separated by a unic separator and each dataset from the same column is separated by another unic separator (ex: c("", c("d", "-", "e", "-", "f"), "", c("a", "a1", "-", "b", "-", "c", "c1"), "_")
cols	are the colnames of the data generated in a csv
file_	is the file to which the data will be outputed, defaults to NA which means that the functio will return the dataframe generated and won't write it to a csv file

date_addr 29

```
sep_ is the separator of the csv outputed
organisation is the way variables include themselves, for instance ,resuming precedent ex-
ample, if organisation=c(1, 0) so the data output will be: d, a d, a1 e, c f, c f,
c1
unic_sep1 is the unic separator between variables (default is "_")
unic_sep2 is the unic separator between datasets (default is "-")
```

Examples

date_addr

 $date_addr$

Description

Allow to add or substract two dates that have the same time unit or not

Usage

```
date_addr(
  date1,
  date2,
  add = FALSE,
  frmt1,
  frmt2 = frmt1,
  sep_ = "-",
  convert_to = "dmy"
)
```

Arguments

date1	is the date from which the second date will be added or substracted
date2	is the date that will be added or will substract date1
add	equals to FALSE if you want date 1 - date 2 and TRUE if you want date 1 + date 2
frmt1	is the format of date1 (snhdmy) (second, minute, hour, day, monthn year)
frmt2	is the format of date2 (snhdmy)
sep_	is the separator of date1 and date2
convert_to	is the format of the outputed date

Examples

```
print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",
                convert_to="dmy"))
#[1] "18-2-0"
print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",
                convert_to="dmy", add=TRUE))
#[1] "3-3-0"
print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
                convert_to="dmy", add=TRUE))
#[1] "27-3-2024"
print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
                convert_to="dmy", add=FALSE))
#[1] "23-1-2024"
print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
                 convert_to="n", add=FALSE))
#[1] "1064596320"
print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
                 convert_to="s", add=FALSE))
#[1] "63875779200"
```

Description

date_converter_reverse

Allow to convert single date value like 2025.36 year to a date like second/minutehour/day/month/year (snhdmy)

Usage

```
date_converter_reverse(inpt_date, convert_to = "dmy", frmt = "y", sep_ = "-")
```

Arguments

date_converter_reverse

dcr_untl 31

Examples

```
print(date_converter_reverse(inpt_date="2024.929", convert_to="hmy", frmt="y", sep_="-"))
#[1] "110-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dmy", frmt="y", sep_="-"))
#[1] "4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="hdmy", frmt="y", sep_="-")
#[1] "14-4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dhym", frmt="y", sep_="-")
#[1] "4-14-2024-11"
```

dcr_untl

dcr_untl

Description

Allow to get the final value of a incremental or decremental loop.

Usage

```
dcr_untl(strt_val, cr_val, stop_val = 0)
```

Arguments

```
strt_val is the start value
cr_val is the incremental (or decremental value)
stop_val is the value where the loop has to stop
```

```
print(dcr_untl(strt_val=50, cr_val=-5, stop_val=5))
#[1] 9
print(dcr_untl(strt_val=50, cr_val=5, stop_val=450))
#[1] 80
```

32 depth_pairs_findr

dcr_val

dcr_val

Description

Allow to get the end value after an incremental (or decremental loop)

Usage

```
dcr_val(strt_val, cr_val, stop_val = 0)
```

Arguments

```
strt_val is the start value
cr_val is the incremental or decremental value
stop_val is the value the loop has to stop
```

Examples

```
print(dcr_val(strt_val=50, cr_val=-5, stop_val=5))
#[1] 5
print(dcr_val(strt_val=47, cr_val=-5, stop_val=5))
#[1] 7
print(dcr_val(strt_val=50, cr_val=5, stop_val=450))
#[1] 450
print(dcr_val(strt_val=53, cr_val=5, stop_val=450))
#[1] 448
```

```
{\tt depth\_pairs\_findr} \quad \textit{depth\_pairs\_findr}
```

Description

Takes the pair vector as an input and associate to each pair a level of depth, see examples

Usage

```
depth_pairs_findr(inpt)
```

Arguments

inpt is the pair vector

diff_datf 33

Examples

```
print(depth_pairs_findr(c(1, 1, 2, 3, 3, 4, 4, 2, 5, 6, 7, 7, 6, 5)))
[1] 1 1 1 2 2 2 2 1 1 2 3 3 2 1
```

diff_datf

diff_datf

Description

Returns a vector with the coordinates of the cell that are not equal between 2 dataframes (row, column).

Usage

```
diff_datf(datf1, datf2)
```

Arguments

```
datf1 is an an input dataframe datf2 is an an input dataframe
```

Examples

```
datf1 <- data.frame(c(1:6), c("oui", "oui", "oui", "oui", "oui", "oui", c(6:1))
datf2 <- data.frame(c(1:7), c("oui", "oui", "oui", "oui", "non", "oui", "zz"))
print(diff_datf(datf1=datf1, datf2=datf2))
#[1] 5 1 5 2</pre>
```

Description

Allow to convert the indices of vector ('from_v_ids') which are related to the each characters of a vector (from_v_val), to fit the newly established characters of the vector from_v_val, see examples.

Usage

```
dynamic_idx_convertr(from_v_ids, from_v_val)
```

34 elements_equalifier

Arguments

```
from_v_ids is the input vector of indices
from_v_val is the input vector of elements, or just the total number of characters of the elementsq in the vector
```

Examples

```
print(dynamic_idx_convertr(from_v_ids = c(1, 5), from_v_val = c("oui", "no", "ouI")))
[1] 1 2
print(dynamic_idx_convertr(from_v_ids = c(1, 6), from_v_val = c("oui", "no", "ouI")))
[1] 1 3
```

```
elements_equalifier

elements_equalifier
```

Description

Takes an input vector with elements that have different occurence, and output a vector with all these elements with the same number of occurence, see examples

Usage

```
elements_equalifier(inpt_v, untl = 3)
```

Arguments

```
inpt_v is the input vector
unt1 is how many times each elements will be in the output vector
```

```
print(elements_equalifier(letters, untl = 2))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" [20] "t" "u" "v" "w" "x" "y" "z" "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" [39] "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z"

print(elements_equalifier(c(letters, letters[-1]), untl = 2))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" [20] "t" "u" "v" "w" "x" "y" "z" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" [39] "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z" "a"
```

equalizer_v 35

```
equalizer_v equalizer_v
```

Description

Takes a vector of character as an input and returns a vector with the elements at the same size. The size can be chosen via depth parameter.

Usage

```
equalizer_v(inpt_v, depth = "max", default_val = "?")
```

Arguments

inpt_v is the input vector containing all the characters
depth is the depth parameter, defaults to "max" which means that it is equal to the character number of the element(s) in inpt_v that has the most
default_val is the default value that will be added to the output characters if those has an inferior length (characters) than the value of depth

Examples

```
print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=2))
#[1] "aa" "zz" "q?"
print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=12))
#[1] "aa?????????" "zzz???????" "q?????????"
```

extract_normal extract_normal

Description

Allow to extract values that fits a normal distribution from any kind of dataset, see examples and parameters

Usage

```
extract_normal(
  inpt_datf,
  mean,
  sd,
  accuracy,
  round_value = 1,
  normalised = FALSE,
  n = NA,
  tries = 3
)
```

36 extract_normal

Arguments

inpt_datf is the input dataset as a dataframe, values/modalities are in the first column and frequency (not normalised) is in the second column is the mean of the target normal distribution mean sd is the standard deviation of the target normal distribution is how much of a difference beetween the points of the targeted normal distribuaccuracy tion and the actual points is tolerated is the round value for the normal distribution used under the hood to compare round_value the dataset and extract the best points, defaults to 1 is if the input frequency is divided by n, if TRUE the parameter n must be filled normalised n is the number of points is how many normal distributions are used under the hood to compare their tries points to the those in the input dataset, defaults to 3. The higher it is, the higher the number of different points from the input dataset will be in accordance for the normal distribution the function tries to build from the dataset. It does not increase by a lot but can be non-negligible and note that the higher the number of tries is, the higher the execution time of the function will be.

```
sample\_val \leftarrow round(rnorm(n = 72000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)</pre>
sample_qual <- infinite_char_seq(n = length(sample_freq))</pre>
datf_test <- data.frame(sample_qual, sample_freq)</pre>
n <- nrow(datf_test)</pre>
print(datf_test)
   sample_qual sample_freq
1
               а
2
               b
                          1155
3
                          1255
               С
4
               d
                          743
5
                е
                           696
               f
6
                          1028
7
                g
                          1160
8
                          1219
               h
9
               i
                          1353
10
                          1336
                j
11
               k
                          1308
12
               1
                           485
13
                          1306
               m
14
                          1429
                n
15
                           623
                0
16
                          1172
               р
17
                q
                          1054
                           999
18
               r
                           125
19
               S
2.0
                          1461
               t
21
                          1430
               u
22
               V
                           341
23
               W
                          1453
24
               Х
                           427
25
               У
                           869
```

2.6		1005
26	Z	1395
27	aa	841
28 29	ab	952 246
30	ac ad	468
31	ae	237
32	af	555
33	ag	1297
34	ah	571
35	ai	349
36	aj	773
37	ak	1086
38	al	1281
39	am	1471
40	an	1236
41	ao	394
42	ap	1433
43	aq	1328
44	ar	976
45	as	640
46	at	308
47	au	698
48	av	864
49 50	aw	1346 1349
51	ax	1349
52	ay az	1071
53	ba	248
54	bb	929
55	bc	925
56	bd	452
57	be	207
58	bf	546
59	bg	62
60	bh	107
61	bi	1184
62	bj	739
63	bk	624
64	bl	850
65	bm	1408
66	bn	620
67	bo	202
68	bp	10
69 70	bq	700
70	br bs	397 1291
72	bt	178
73	bu	397
74	bv	1089
75	bw	1301
76	bx	328
77	by	1348
78	bz	97
79	ca	1452
80	cb	4
81	CC	100
82	cd	593

83	ce	503
84	cf	164
85		32
	cg	
86	ch	259
87	ci	1089
88	сj	249
89	ck	165
90	cl	42
91	cm	143
92	cn	467
93	co	347
94		
	cp	143
95	cq	69
96	cr	18
97	CS	290
98	ct	55
99	cu	141
100	CV	86
101	CW	303
102	CX	88
103		16
	сУ	
104	CZ	213
105	da	3
106	db	75
107	dc	32
108	dd	66
109	de	105
110	df	34
111	dg	56
112	dh	17
113	di	22
114	dj	120
115	dk	54
116	dl	9
117	dm	8
118	dn	36
119	do	20
120	dp	26
121	dq	54
122	dr	8
123	ds	10
124	dt	4
125	du	53
126	dv	29
127	dw	1
128	dx	8
129	dy	10
130	dz	4
131	ea	22
132	eb	9
133	ec	17
134	ed	55
135	ee	21
136	ef	6
137	eg	4
138	eh	3
139	ei	7

```
140
          еj
141
           ek
                       2
142
           el
143
           em
144
           en
                       4
145
                       1
           eo
146
          ер
                       2
          eq
                       3
147
          er
148
149
                       4
          es
150
                       3
          et
                       3
151
          eu
                       2
152
          ev
                       2
153
          ew
                       2
154
          ex
155
                       1
          ey
156
                       2
          ez
157
          fa
                       2
158
           fb
teste <- extract_normal(inpt_datf = datf_test,</pre>
                   mean = 10,
                   sd = 2,
                   accuracy = .1,
                   round_value = 1,
                   normalised = FALSE,
                   tries = 5)
print(length(unique(teste[, 1])) / n)
[1] 0.2848101 # so nearly 28.5 % of the different points were in
 #accordance with the construction of the target normal distribution
print(teste)
  values frequency
    dw 0.0001406866
1
       dw 0.0001406866
2
       dw 0.0001406866
3
4
      el 0.0002813731
5
       el 0.0002813731
6
       el 0.0002813731
7
       el 0.0002813731
8
       da 0.0004220597
9
       da 0.0004220597
10
       cb 0.0005627462
11
       cb 0.0005627462
12
       em 0.0007034328
      ay 0.0008441193
13
      ay 0.0008441193
14
15
      ei 0.0009848059
```

16

17

18

19

20 21 ei 0.0009848059

ei 0.0009848059

dm 0.0011254924

bp 0.0014068655 cy 0.0022509848

cy 0.0022509848

```
22
        cy 0.0022509848
23
        dh 0.0023916714
24
        dh 0.0023916714
25
        cr 0.0025323579
26
        ee 0.0029544176
27
        di 0.0030951041
28
        dp 0.0036578503
        dp 0.0036578503
29
        cg 0.0045019696
30
31
        cq 0.0045019696
32
        df 0.0047833427
33
        dn 0.0050647158
34
        cl 0.0059088351
35
        cl 0.0059088351
        du 0.0074563872
36
37
        du 0.0074563872
38
        dg 0.0078784468
39
        dg 0.0078784468
40
        bg 0.0087225661
41
        bg 0.0087225661
42
        dd 0.0092853123
43
        cq 0.0097073720
44
        cq 0.0097073720
45
        a 0.0101294316
46
        cv 0.0120990433
        cx 0.0123804164
47
48
        cx 0.0123804164
49
        bz 0.0136465954
50
        cc 0.0140686550
        bh 0.0150534609
51
        bh 0.0150534609
52
53
        dj 0.0168823860
54
        s 0.0175858188
55
        s 0.0175858188
56
        cm 0.0201181767
57
        cf 0.0230725943
58
        ck 0.0232132808
59
        bt 0.0250422060
60
        bt 0.0250422060
61
        be 0.0291221159
62
        be 0.0291221159
63
        cz 0.0299662352
64
        cz 0.0299662352
65
        be 0.0291221159
66
        bo 0.0284186832
67
        bt 0.0250422060
68
        ck 0.0232132808
69
        ck 0.0232132808
70
        cm 0.0201181767
71
        cu 0.0198368036
72
        s 0.0175858188
73
        di 0.0168823860
74
        bh 0.0150534609
75
        bh 0.0150534609
76
        de 0.0147720878
77
       bz 0.0136465954
78
        bz 0.0136465954
```

extrt_only_v 41

```
79
       cx 0.0123804164
80
       cv 0.0120990433
81
       db 0.0105514913
82
       a 0.0101294316
83
       cq 0.0097073720
84
       dd 0.0092853123
85
       dd 0.0092853123
86
       bq 0.0087225661
87
       bq 0.0087225661
88
       da 0.0078784468
89
       dk 0.0075970737
90
       du 0.0074563872
91
       cl 0.0059088351
92
       cl 0.0059088351
93
       dn 0.0050647158
94
       df 0.0047833427
95
       df 0.0047833427
       cg 0.0045019696
96
97
       dv 0.0040799100
       dp 0.0036578503
98
99
       di 0.0030951041
100
       di 0.0030951041
101
       ee 0.0029544176
102
       cr 0.0025323579
       dh 0.0023916714
103
       cy 0.0022509848
104
       cy 0.0022509848
105
       cy 0.0022509848
106
107
       cy 0.0022509848
       dl 0.0012661790
108
       dm 0.0011254924
109
110
       ei 0.0009848059
111
       ei 0.0009848059
112
       ay 0.0008441193
113
      ay 0.0008441193
114
      em 0.0007034328
       em 0.0007034328
115
116
       cb 0.0005627462
       cb 0.0005627462
117
118
       da 0.0004220597
119
       da 0.0004220597
120
       el 0.0002813731
121
       el 0.0002813731
122
       el 0.0002813731
123
       el 0.0002813731
124
       dw 0.0001406866
125
       dw 0.0001406866
126
       dw 0.0001406866
```

```
extrt_only_v extrt_only_v
```

Description

Returns the elements from a vector "inpt_v" that are in another vector "pttrn_v"

fillr

Usage

```
extrt_only_v(inpt_v, pttrn_v)
```

Arguments

```
inpt_v is the input vector
pttrn_v is the vector contining all the elements that can be in inpt_v
```

Examples

```
print(extrt_only_v(inpt_v=c("oui", "non", "peut", "oo", "ll", "oui", "non", "oui", "oui")
    pttrn_v=c("oui")))
#[1] "oui" "oui" "oui" "oui"
```

fillr fillr

Description

Allow to fill a vector by the last element n times

Usage

```
fillr(inpt_v, ptrn_fill = "\\.\\.\\d")
```

Arguments

inpt_v is the input vector

 $\verb|ptrn_fill| is the pattern used to detect where the function has to fill the vector by the last$

element n times. It defaults to "...\d" where "\d" is the regex for an int value. So

this paramater has to have " \d " which designates n.

```
print(fillr(c("a", "b", "...3", "c")))
#[1] "a" "b" "b" "b" "c"
```

fixer_nest_v 43

```
fixer_nest_v fixer_nest_v
```

Description

Retur the elements of a vector "wrk_v" (1) that corresponds to the pattern of elements in another vector "cur_v" (2) according to another vector "pttrn_v" (3) that contains the patter felements.

Usage

```
fixer_nest_v(cur_v, pttrn_v, wrk_v)
```

Arguments

```
cur_v is the input vector

pttrn_v is the vector containing all the patterns that may be contained in cur_v

wrk_v is a vector containing all the indexes of cur_v taken in count in the function
```

Examples

fold_rec fold_rec

Description

Allow to get all the files recursively from a path according to an end and start depth value. If you want to have an other version of this function that uses a more sophisticated algorythm (which can be faster), check file_rec2. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

Usage

```
fold_rec(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax	is the end depth value
xmin	is the start depth value
pathc	is the reference path

44 format_date

Description

Allow to find the directories and the subdirectories with a specified end and start depth value from a path. This function might be more powerfull than file_rec because it uses a custom algorythm that does not nee to perform a full recursive search before tuning it to only find the directories with a good value of depth. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

Usage

```
fold_rec2(xmax, xmin = 1, pathc = ".")
```

Arguments

xmax is the depth value

xmin is the minimum value of depth

pathc is the reference path, from which depth value is equal to 1

Description

Allow to convert xx-month-xxxx date type to xx-xx-xxxx

Usage

```
format_date(f_dialect, sentc, sep_in = "-", sep_out = "-")
```

Arguments

f_dialect are the months from the language of which the month come

sentc is the date to convert

sep_in is the separator of the dat input (default is "-")
sep_out is the separator of the converted date (default is "-")

```
print(format_date(f_dialect=c("janvier", "février", "mars", "avril", "mai", "juin",
   "juillet", "aout", "septembre", "octobre", "novembre", "décembre"), sentc="11-septembre-2"
#[1] "11-09-2023"
```

geo_min 45

geo_min geo_min

Description

Return a dataframe containing the nearest geographical points (row) according to established geographical points (column).

Usage

```
geo_min(inpt_datf, established_datf)
```

Arguments

inpt_datf is the input dataframe of the set of geographical points to be classified, its firts column is for latitude, the second for the longitude and the third, if exists, is for the altitude. Each point is one row.

```
established_datf
```

is the dataframe containing the coordinates of the established geographical points

```
in_{-} \leftarrow data.frame(c(11, 33, 55), c(113, -143, 167))
in2_{-} \leftarrow data.frame(c(12, 55), c(115, 165))
print(geo_min(inpt_datf=in_, established_datf=in2_))
#
          X1
                     X2
   245.266
#1
                    NA
#2 24200.143
                     NA
#3
          NA 127.7004
in_{-} \leftarrow data.frame(c(51, 23, 55), c(113, -143, 167), c(6, 5, 1))
in2_{-} \leftarrow data.frame(c(12, 55), c(115, 165), c(2, 5))
print(geo_min(inpt_datf=in_, established_datf=in2_))
         Х1
                   X2
         NA 4343.720
#1
#2 26465.63
             NA
#3
         NA 5825.517
```

46 globe

Description

Allow to get the value of directorie depth from a path.

Usage

```
get_rec(pathc = ".")
```

Arguments

patho is the reference path example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

globe globe

Description

Allow to calculate the distances between a set of geographical points and another established geographical point. If the altitude is not filled, so the result returned won't take in count the altitude.

Usage

```
globe(lat_f, long_f, alt_f = NA, lat_n, long_n, alt_n = NA)
```

Arguments

lat_f	is the latitude of the established geographical point
long_f	is the longitude of the established geographical point
alt_f	is the altitude of the established geographical point, defaults to NA
lat_n	is a vector containing the latitude of the set of points
long_n	is a vector containing the longitude of the set of points
alt_n	is a vector containing the altitude of the set of points, defaults to NA

glue_groupr_v 47

```
glue_groupr_v
```

Description

Takes an input vector and returns the same vector unlike that certain elements will be glued as an unique element according to thoses designated in a special vector, see examples.

Usage

```
glue_groupr_v(inpt_v, group_v = c(), untl)
```

Arguments

```
inpt_v is the input vector

a vector containing all the elements that will be glued in the output vector
```

Examples

```
print(glue_groupr_v(inpt_v = c("o", "-", "-", "u", "i", "-", "n",
    "o", "-", "-", "-", "zz", "/", "/"), group_v = c("-", "/")))

[1] "o" "--" "u" "i" "-" "n" "o" "---" "zz" "//"

print(glue_groupr_v(inpt_v = c("o", "-", "-", "u", "i", "-", "n",
    "o", "-", "-", "-", "-", "zz", "/", "/"), group_v = c("-", "/"), untl = 3))

[1] "o" "--" "u" "i" "-" "n" "o" "---" "-", "u", "i", "-", "n",
    "o", "-", "-", "-", "-", "zz", "/", "/"), group_v = c("-", "/"), untl = 2))

[1] "o" "--" "u" "i" "-" "n" "o" "---" "zz" "//"
```

```
grep_all grep_all
```

Description

Allow to perform a grep function on multiple input elements

Usage

```
grep_all(inpt_v, pattern_v)
```

Arguments

```
inpt_v is the input vectors to grep elements from
pattern_v is a vector containing the patterns to grep
```

48 grep_all2

Examples

grep_all2

grep_all2

Description

Performs the grep_all function with another algorythm, potentially faster

Usage

```
grep_all2(inpt_v, pattern_v)
```

Arguments

inpt_v is the input vectors to grep elements from
pattern_v is a vector containing the patterns to grep

groupr_datf 49

groupr_datf
groupr_datf

Description

Allow to create groups from a dataframe. Indeed, you can create conditions that lead to a flag value for each cell of the input dataframeaccording to the cell value. This function is based on see_datf and nestr datf2 functions.

Usage

```
groupr_datf(
  inpt_datf,
  condition_lst,
  val_lst,
  conjunction_lst,
  rtn_val_pos = c()
)
```

Arguments

```
interactive()
datf1 <- data.frame(c(1, 2, 1), c(45, 22, 88), c(44, 88, 33))
val_lst <- list(list(c(1), c(1)), list(c(2)), list(c(44, 88)))
condition_lst <- list(c(">", "<"), c("%%"), c("==", "=="))
conjunction_lst <- list(c("|"), c(), c("|"))
rtn_val_pos <- c("+", "++", "+++")
print(groupr_datf(inpt_datf=datf1, val_lst=val_lst, condition_lst=condition_lst, conjunction_lst=conjunction_lst, rtn_val_pos=rtn_val_pos))
# X1 X2 X3
#1 <NA> + +++
#2 ++ ++++
```

50 how_normal

```
#3 <NA> +++ +
```

gsub_mult gsub_mult

Description

Performs a gsub operation with n patterns and replacements.

Usage

```
gsub_mult(inpt_v, pattern_v = c(), replacement_v = c())
```

Arguments

inpt_v is a vector containing all the elements that contains expressions to be substituted
pattern_v is a vector containing all the patterns to be substituted in any elements of inpt_v
replacement_v

is a vector containing the expression that are going to substituate those provided by pattern_v

Examples

how_normal

how_normal

Description

Allow to get how much a sequence of numbers fit a normal distribution with chosen parameters, see examples

Usage

```
how_normal(inpt_datf, normalised = TRUE, mean = 0, sd = 1)
```

Arguments

inpt_datf	is the input dataframe containing all the values in the first column and their frequency (normalised or no), in the second column
normalised	is a boolean, takes TRUE if the frequency for each value is divided by n, FALSE if not
mean	is the mean of the normal distribution that the dataset tries to fit
sd	is the standard deviation of the normal distribution the dataset tries to fit

how_normal 51

```
sample_val <- round(rnorm(n = 12000, mean = 6, sd = 1.25), 1)
sample_freq <- unique_total(sample_val)</pre>
datf_test <- data.frame(unique(sample_val), sample_freq)</pre>
print(datf_test)
  unique.sample_val. sample_freq
                6.9
1
                       306
2
                 8.3
                            63
3
                 7.7
                            148
4
                 5.6
                            363
5
                 6.5
                            349
                 4.6
                           202
7
                            324
                 6.6
8
                6.7
                            335
9
                6.0
                            406
10
                5.7
                            365
11
                 7.9
                            109
12
                            420
                 6.2
13
                            386
                 5.9
14
                 4.5
                            185
15
                 5.1
                            326
16
                 6.1
                            360
17
                 5.5
                            346
18
                 6.3
                            375
                            207
19
                 7.4
20
                 7.6
                            162
                            129
21
                 4.2
22
                 3.9
                            102
23
                5.2
                            325
24
                2.3
                             7
25
                5.8
                           387
26
                6.4
                            319
27
                9.1
                            21
28
                 7.0
                            280
29
                8.8
                            27
30
                 4.9
                           218
                            98
31
                8.1
                            25
32
                 3.0
33
                 8.4
                             66
34
                 4.3
                            160
35
                 7.2
                            267
36
                 8.7
                             40
37
                 5.3
                            313
38
                 4.1
                            127
39
                 5.0
                            275
40
                 4.0
                            119
41
                 9.3
                             13
42
                 4.4
                            196
43
                 6.8
                            313
44
                7.1
                            247
45
                 3.5
                             57
46
                 7.8
                            139
47
                 3.6
                             57
48
                 7.5
                            189
                 7.3
                            215
49
```

how_normal

```
230
50
              4.7
51
                        36
              3.2
52
              9.5
                         8
                        79
53
              3.8
54
              8.2
                        62
              5.4
55
                        343
56
              8.5
                        55
57
                       207
              4.8
58
              3.7
                        79
59
              8.6
                        33
60
              3.3
                        38
61
              3.4
                        43
62
              8.9
                        21
              8.0
                       105
63
              3.1
64
                        23
65
              9.0
                        27
66
             10.0
                         5
67
              2.5
                        10
              2.9
                        16
68
              9.7
69
70
              2.7
                        11
71
             10.5
                          1
72
                        13
              9.4
73
              9.2
                         16
74
              2.6
                        16
75
              9.9
                          3
              2.8
76
                        10
77
              2.4
                        10
78
              1.9
                         2
79
              2.0
                         6
80
             10.2
                         2
81
              9.6
                         3
82
             11.3
                         1
                         1
83
              1.8
                         3
84
              2.2
                         2
              2.1
85
                         1
86
              1.6
                         1
87
             10.6
88
              9.8
                          1
89
             10.4
                          1
90
              1.7
print(how_normal(inpt_datf = datf_test,
              normalised = FALSE,
              mean = 6,
              sd = 1))
[1] 9.003683
print(how_normal(inpt_datf = datf_test,
             normalised = FALSE,
              mean = 5,
              sd = 1))
```

[1] 9.098484

how_unif 53

w_unif how_unif
f how_unif

Description

Allow to see how much a sequence of numbers fit a uniform distribution, see examples

Usage

```
how_unif(inpt_v, normalised = TRUE)
```

Arguments

normalised is a boolean, takes TRUE if the frequency for each value is divided by n, FALSE if not
inpt_datf is the input dataframe containing all the values in the first column and their frequency at the second column

```
sample\_val \leftarrow round(runif(n = 12000, min = 24, max = 27), 1)
sample_freq <- unique_total(sample_val)</pre>
datf_test <- data.frame(unique(sample_val), sample_freq)</pre>
print(datf_test)
  unique.sample_val. sample_freq
1
                  24.4
2
                  24.8
                               379
3
                  25.5
                               414
4
                  26.0
                               366
5
                  26.6
                               400
6
                  25.7
                               419
7
                  24.3
                                389
8
                  24.1
                               423
9
                  26.1
                               404
10
                  26.5
                                406
11
                  26.2
                                356
12
                  26.8
                                407
13
                  24.6
                                388
14
                  25.3
                                402
15
                  26.3
                                388
16
                  25.4
                                422
17
                  25.0
                                436
                  25.9
                                373
18
19
                  25.2
                                423
20
                  25.6
                                388
21
                  27.0
                                202
22
                  24.2
                                380
23
                  24.9
                                404
24
                  25.1
                               417
25
                  26.4
                               401
26
                  26.7
                               431
27
                  24.5
                                392
```

54 id_keepr

```
28
                 24.0
                              218
29
                 26.9
                              407
                              371
30
                 25.8
                 24.7
31
                              394
print(how_unif(inpt_datf = datf_test, normalised = FALSE))
[1] 0.0752957
sample_val <- round(rnorm(n = 12000, mean = 24, sd = 7), 1)
sample_freq <- unique_total(sample_val)</pre>
datf_test <- data.frame(unique(sample_val), sample_freq)</pre>
print(how_unif(inpt_datf = datf_test, normalised = FALSE))
[1] 0.7797352
```

id_keepr

id_keepr

Description

Allow to get the original indexes after multiple equality comparaison according to the original number of row

Usage

```
id_keepr(inpt_datf, col_v = c(), el_v = c(), rstr_l = NA)
```

Arguments

inpt_datf	is the input dataframe
col_v	is the vector containing the column numbers or names to be compared to their respective elements in "el_v"
el_v	is a vector containing the elements that may be contained in their respective column described in " col_v "
rstr_l	is a list containing the vector composed of the indexes of the elements chosen for each comparison. If the length of the list is inferior to the length of comparisons, so the last vector of rstr_l will be the same as the last one to fill make rstr_l equal in term of length to col_v and el_v

incr_fillr 55

incr fillr

incr fillr

Description

Take a vector uniquely composed by double and sorted ascendingly, a step, another vector of elements whose length is equal to the length of the first vector, and a default value. If an element of the vector is not equal to its predecessor minus a user defined step, so these can be the output according to the parameters (see example):

Usage

```
incr_fillr(inpt_v, wrk_v = NA, default_val = NA, step = 1)
```

Arguments

inpt_v is the asending double only composed vector
wrk_v is the other vector (size equal to inpt_v), defaults to NA
default_val is the default value put when the difference between two following elements of inpt_v is greater than step, defaults to NA
step is the allowed difference between two elements of inpt_v

56 inner_all

```
#[1] "1" "2" "NAN" "4" "5" "NAN" "NAN" "NAN" "9" "10"
```

```
infinite_char_seq infinite_char_seq
```

Description

Allow to generate an infinite sequence of unique letters

Usage

```
infinite_char_seq(n, base_char = letters)
```

Arguments

n is how many sequence of numbers will be generated

base_char is the vector containing the elements from which the sequence is generated

Examples

```
print(infinite_char_seq(28))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o"
[16] "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "a" "aa" "ab"
```

inner_all inner_all

Description

Allow to apply inner join on n dataframes, datatables, tibble

Usage

```
inner_all(..., keep_val = FALSE, id_v)
```

Arguments

... are all the dataframes etc

keep_val is if you want to keep the id column

id_v is the common id of all the dataframes etc

insert_datf 57

Examples

```
datf1 <- data.frame(
    "id1"=c(1:5),
    "var1"=c("oui", "oui", "oui", "non", "non")
)

datf2 <- data.frame(
    "id1"=c(1, 2, 3, 7, 9),
    "var1"=c("oui2", "oui2", "oui2", "non2", "non2")
)

print(inner_all(datf1, datf2, keep_val=FALSE, id_v="id1"))

id1 var1.x var1.y
1 1 oui oui2
2 2 oui oui2
3 3 oui oui2</pre>
```

insert_datf

insert_datf

Description

Allow to insert dataframe into another dataframe according to coordinates (row, column) from the dataframe that will be inserted

Usage

```
insert_datf(datf_in, datf_ins, ins_loc)
```

Arguments

datf_in is the dataframe that will be inserted
datf_ins is the dataset to be inserted
ins_loc is a vector containg two parameters (row, column) of the begining for the insertion

```
datf1 \leftarrow data.frame(c(1, 4), c(5, 3))
datf2 \leftarrow data.frame(c(1, 3, 5, 6), c(1:4), c(5, 4, 5, "ereer"))
print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(4, 2)))
    c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1
                      1
                1
# 2
                 3
                        2
                                              4
# 3
                 5
                        3
                        1
print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(3, 2)))
```

58 intersect_mod

```
c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1
                 1
             1
# 2
              3
                    2
# 3
             5
                    1
# 4
              6
                    4
                                      3
print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(2, 2)))
 c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1
# 2
             3
                                      5
                   1
# 3
                                      3
             5
                   4
            6 4
# 4
```

Description

Allows to calculate the intersection between n vectors

Usage

```
intersect_all(...)
```

Arguments

. . . is all the vector you want to calculate the intersection from

Examples

```
print(intersect_all(c(1:5), c(1, 2, 3, 6), c(1:4)))
[1] 1 2 3
```

Description

Returns the mods that have elements in common

Usage

```
intersect_mod(datf, inter_col, mod_col, n_min, descendly_ordered = NA)
```

intersect_mod 59

Arguments

inter_col is the column name or the column number of the values that may be commun
betwee the different mods

mod_col is the column name or the column number of the mods in the dataframe

n_min is the minimum elements in common a mod should have to be taken in count
ordered_descendly
in case that the elements in commun are numeric, this option can be enabled by

in case that the elements in commun are numeric, this option can be enabled by giving a value of TRUE or FALSE see examples

Examples

non

4

```
datf <- data.frame("col1"=c("oui", "oui", "oui", "oui", "oui", "oui",</pre>
                     "non", "non", "non", "non", "ee", "ee", "ee"), "col2"=c(1:6, 2:5, 1:
print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=2))
  coll col2
2
   oui
           2
3
   oui
           3
7
   non
           2
8
   non
           3
12
           2
     ee
13
     ee
           3
print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=3))
  coll col2
2.
  oui
           2.
3
  oui
           3
4
           4
  oui
5
  oui
           5
7
           2
  non
8
           3
  non
9
   non
           4
10 non
           5
print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=5))
  col1 col2
1 oui
        1
2
  oui
          2
  oui
          3
  oui
          4
5
  oui
          5
6 oui
datf <- data.frame("col1"=c("non", "non", "oui", "oui", "oui", "oui",</pre>
                      "non", "non", "non", "ee", "ee", "ee"), "col2"=c(1:6, 2:5, 1
print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=3))
   col1 col2
   non
           3
```

60 inter_max

```
10 non 5
3 oui 3
4 oui 4
5 oui 5
```

inter_max

inter_max

Description

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)). The function will return the list of lists altered according to the maximum step found in the input list.

Usage

```
inter_max(inpt_l, max_ = -1000, get_lst = TRUE)
```

Arguments

inpt_l is the input list
max_ is a value you are sure is the minimum step value of all the sub-lists
get_lst is the parameter that, if set to True, will keep the last values of vectors in the return value if the last step exceeds the end value of the vector.

```
print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=TRUE))
#[[1]]
#[1] 0 4
#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1.0 2.3
print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=FALSE))
# [[1]]
#[1] 0 4
#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1
```

inter_min 61

inter_min inter_min

Description

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)). This function will return the list of vectors with the same steps preserving the begin and end value of each interval. The way the algorythmn searches the common step of all the sub-lists is also given by the user as a parameter, see how_to paramaters.

Usage

```
inter_min(
   inpt_l,
   min_ = 1000,
   sensi = 3,
   sensi2 = 3,
   how_to_op = c("divide"),
   how_to_val = c(3)
)
```

Arguments

inpt_l	is the input list containing all the intervals
min_	is a value you are sure is superior to the maximum step value in all the intervals
sensi	is the decimal accuracy of how the difference between each value n to $n+1$ in an interval is calculated
sensi2	is the decimal accuracy of how the value with the common step is calculated in all the intervals
how_to_op	is a vector containing the operations to perform to the pre-common step value, defaults to only "divide". The operations can be "divide", "substract", "multiply" or "add". All type of operations can be in this parameter.
how_to_val	is a vector containing the value relatives to the operations in hot_to_op, defaults to 3 output from ex:

```
print(inter_min(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3))))
# [[1]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
#[20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
#[39] 3.8 3.9 4.0
#
#[[2]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
#[20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
#[39] 3.8 3.9 4.0
#
#[[3]]
```

62 is_divisible

```
# [1] 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1 2.2 2.3
```

Description

Takes a vector as an input and returns all the elements that are not divisible by all choosen numbers from another vector.

Usage

```
isnt_divisible(inpt_v = c(), divisible_v = c())
```

Arguments

```
\label{eq:containing} \begin{array}{ll} \text{inpt\_v} & \text{is the input vector} \\ \text{divisible\_v} & \text{is the vector containing all the numbers that will try to divide those contained in inpt\_v} \end{array}
```

Examples

```
print(isnt_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))
# [1] 1 3 7 9 11 13 17 19 21 23 27 29 31 33 37 39 41 43 47
# [20] 49 51 53 57 59 61 63 67 69 71 73 77 79 81 83 87 89 91 93
# [39] 97 99 101 103 107 109 111
```

```
is_divisible is_divisible
```

Description

Takes a vector as an input and returns all the elements that are divisible by all choosen numbers from another vector.

Usage

```
is\_divisible(inpt\_v = c(), divisible\_v = c())
```

Arguments

```
inpt_v is the input vector
divisible_v is the vector containing all the numbers that will try to divide those contained in inpt_v
```

join_n_lvl 63

Examples

```
print(is_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))
#[1] 20 40 60 80 100
```

join_n_lvl

join_n_lvl

Description

Allow to see the progress of the multi-level joins of the different variables modalities. Here, multi-level joins is a type of join that usually needs a concatenation of two or more variables to make a key. But here, there is no need to proceed to a concatenation. See examples.

Usage

```
join_n_lvl(frst_datf, scd_datf, join_type = c(), lst_pair = list())
```

Arguments

```
is the first data.frame (table)

scd_datf is the second data.frame (table)

join_type is a vector containing all the join type ("left", "inner", "right") for each variable is a lis of vectors. The vectors refers to a multi-level join. Each vector should have a length of 1. Each vector should have a name. Its name refers to the column name of multi-level variable and its value refers to the column name of the join variable.
```

Examples

2

|==| 100%

[1] "pair: vil2 idl2"

```
datf3 <- data.frame("vil"=c("one", "one", "one", "two", "two", "two"),</pre>
                     "charac"=c(1, 2, 2, 1, 2, 2),
                     "rev"=c(1250, 1430, 970, 1630, 2231, 1875),
                     "vil2" = c("one", "one", "one", "two", "two", "two"),
                     "id12" = c(1:6))
datf4 <- data.frame("vil"=c("one", "one", "one", "two", "two", "three"),</pre>
                    "charac"=c(1, 2, 2, 1, 1, 2),
                     "rev"=c(1.250, 1430, 970, 1630, 593, 456),
                     "vil2" = c("one", "one", "one", "two", "two"),
                     "idl2" = c(2, 3, 1, 5, 5, 5))
print(join_n_lvl(frst_datf=datf3, scd_datf=datf4, lst_pair=list(c("charac" = "vil"), c("v
                 join_type=c("inner", "left")))
[1] "pair: charac vil"
     0%
1
|= | 50%
```

64 just_chr

```
just_chr just_chr
```

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_chr(inpt_v, track_ = TRUE, symbol_ = "-")
```

Arguments

```
inpt_v is the input vector
track_ is a boolean, if set to TRUE, the missing numbers are replaced by a symbol
chosen
symbol_ is the chosen symbol to replace numbers
```

just_chr2 65

just_chr2 jus	t_chr2
---------------	--------

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_chr2(inpt_v, track_ = TRUE, symbol_ = "-")
```

Arguments

inpt_v is the input vector

symbol_ is the chosen symbol to replace numbers

track_len is a boolean, if set to TRUE, the chosen symbol will equal the len of the missing

numbers, see examples

Examples

just_nb

just_nb

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_nb(inpt_v, track_ = TRUE, symbol_ = "-")
```

Arguments

inpt_v is the input vector

track_ is a boolean, if set to TRUE, the missing numbers are replaced by a symbol

chosen

symbol_ is the chosen symbol to replace numbers

66 leap_yr

just_nb2

just_nb2

Description

Extract only the letters from all elements of a vector, see examples

Usage

```
just_nb2(inpt_v, track_ = TRUE, symbol_ = "-")
```

Arguments

inpt_v is the input vector

symbol_ is the chosen symbol to replace numbers

track_len is a boolean, if set to TRUE, the chosen symbol will equal the len of the missing

numbers, see examples

Examples

leap_yr

leap_year

Description

Get if the year is leap

Usage

```
leap_yr(year)
```

Arguments

year

is the input year

```
print(leap_yr(year=2024))
#[1] TRUE
```

left_all 67

Description

Allow to apply left join on n dataframes, datatables, tibble

Usage

```
left_all(..., keep_val = FALSE, id_v)
```

Arguments

```
are all the dataframes etckeep_val is if you want to keep the id columnid_v is the common id of all the dataframes etc
```

```
datf1 <- data.frame(</pre>
       "id1"=c(1:5),
       "var1"=c("oui", "oui", "oui", "non", "non")
)
datf2 <- data.frame(</pre>
       "id1"=c(1, 2, 3, 7, 9),
       "var1"=c("oui2", "oui2", "oui2", "non2", "non2")
)
print(left_all(datf1, datf2, datf2, datf2, keep_val=FALSE, id_v="id1"))
 id1 var1.x var1.y var1.x.x var1.y.y
       oui oui2 oui2
  2
       oui oui2
                     oui2
                             oui2
  3
3
                     oui2
       oui oui2
                             oui2
4
   4
       non <NA>
                     <NA>
                              <NA>
   5
            <NA>
                      <NA>
                               <NA># '
        non
print(left_all(datf1, datf2, datf2, keep_val=FALSE, id_v="id1"))
 id1 var1.x var1.y var1
1
       oui oui2 oui2
   1
            oui2 oui2
   2
2
        oui
             oui2 oui2
   3
        oui
   4
        non
              <NA> <NA>
             <NA> <NA>
   5
        non
```

68 list_files

Description

Allow to get the number of a spreadsheet based column by the letter ex: AAA = 703

Usage

```
letter_to_nb(letter)
```

Arguments

letter is the letter (name of the column)

Examples

```
print(letter_to_nb("rty"))
#[1] 12713
```

list_files

list_files

Description

A list.files() based function addressing the need of listing the files with extension a or or extension $b \dots$

Usage

```
list_files(patternc, pathc = ".")
```

Arguments

patternc is a vector containing all the exensions you want

pathc is the path, can be a vector of multiple path because list.files() supports it.

lst_flatnr 69

lst_flatnr

lst_flatnr

Description

Flatten a list to a vector

Usage

```
lst_flatnr(inpt_l)
```

Arguments

inpt_l

is the input list

Examples

```
print(lst_flatnr(inpt_l=list(c(1, 2), c(5, 3), c(7, 2, 7))))
#[1] 1 2 5 3 7 2 7
```

match_by

match_by

Description

Allow to match elements by ids, see examples.

Usage

```
match_by(to_match_v = c(), inpt_v = c(), inpt_ids = c())
```

Arguments

is the vector containing all the elements to match
 is the input vector containing all the elements that could contains the elements to match. Each elements is linked to an element from inpt_ids at any given index, see examples. So inpt_v and inpt_ids must be the same size
 is the vector containing all the ids for the elements in inpt_v. An element is linked to the id x is both are at the same index. So inpt_v and inpt_ids must be

the same size

70 multitud

Examples

multitud

multitud

Description

From a list containing vectors allow to generate a vector following this rule: list(c("a", "b"), c("1", "2"), c("A", "Z", "E")) -> c("a1A", "b1A", "a2A", "b2A", a1Z, ...)

Usage

```
multitud(l, sep_ = "")
```

Arguments

1 is the list

sep_ is the separator between elements (default is set to "" as you see in the example)

```
print(multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")
#[1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
#[8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
#[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
#[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"
```

nb2_follow 71

nb2_follow nb2_follow

Description

Allows to get the number and pattern of potential continuous pattern after an index of a vector, see examples

Usage

```
nb2_follow(inpt_v, inpt_idx, inpt_follow_v = c())
```

Arguments

```
inpt_v is the input vector
inpt_idx is the index
inpt_follow_v
```

is a vector containing the patterns that are potentially just after inpt_nb

Examples

```
print(nb2_follow(inpt_v = c(1:12), inpt_idx = 4, inpt_follow_v = c(5)))

[1] 1 5
# we have 1 times the pattern 5 just after the 4nth index of inpt_v

print(nb2_follow(inpt_v = c(1, "non", "oui", "oui", "oui", "nop", 5), inpt_idx = 2, inpt_
[1] "3" "oui"

# we have 3 times continuously the pattern 'oui' and 0 times the pattern 5 just after the print(nb2_follow(inpt_v = c(1, "non", "5", "5", "5", "nop", 5), inpt_idx = 2, inpt_follow
[1] "3" "5"
```

nb_follow

Description

Allow to get the number of certains patterns that may be after an index of a vector continuously, see examples

Usage

```
nb_follow(inpt_v, inpt_idx, inpt_follow_v = c())
```

nb_follow

72 nb_to_letter

Arguments

```
inpt_v is the input vector
inpt_idx is the index
inpt_follow_v
```

is a vector containing all the potential patterns that may follow the element in the vector at the index inpt_idx

Examples

nb_to_letter

nb_to_letter

Description

Allow to get the letter of a spreadsheet based column by the number ex: 703 = AAA

Usage

```
nb_to_letter(x)
```

Arguments

Х

is the number of the column

```
print (nb_to_letter(5))

[1] "e"

print (nb_to_letter(27))

[1] "aa"

print (nb_to_letter(51))

[1] "ay"

print (nb_to_letter(52))

[1] "az"

print (nb_to_letter(53))
```

nestr_datf1 73

```
[1] "ba"
print(nb_to_letter(675))
[1] "yy"
print(nb_to_letter(676))
[1] "yz"
print(nb_to_letter(677))
[1] "za"
print(nb_to_letter(702))
[1] "zz"
print(nb_to_letter(703))
[1] "aaa"
print(nb_to_letter(18211))
[1] "zxk"
print(nb_to_letter(18277))
[1] "zzy"
print(nb_to_letter(18278))
[1] "zzz"
print(nb_to_letter(18279))
[1] "aaaa"
```

 $nestr_datf1$

nestr_datf1

Description

Allow to write a value (1a) to a dataframe (1b) to its cells that have the same coordinates (row and column) than the cells whose value is equal to a another special value (2a), from another another dataframe (2b). The value (1a) depends of the cell value coordinates of the third dataframe (3b). If a cell coordinates (1c) of the first dataframe (1b) does not correspond to the coordinates of a good returning cell value (2a) from the dataframe (2b), so this cell (1c) can have its value changed to the same cell coordinates value (3a) of a third dataframe (4b), if (4b) is not set to NA.

74 nestr_datf2

Usage

```
nestr_datf1(
   inptf_datf,
   inptt_pos_datf,
   nestr_datf,
   yes_val = TRUE,
   inptt_neg_datf = NA
)
```

Arguments

Examples

```
print(nestr_datf1(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
inptt_neg_datf=data.frame(c(44, 44, 33), c(12, 12, 12)),
nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))
# c.1..2..1. c.1..5..7.
#1
           4 12
#2
          44
                     12
#3
           3
print (nestr_datf1 (inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
inptt_neg_datf=NA,
nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))
#
    c.1..2..1. c.1..5..7.
#1
       4
#2
           2
                      5
#3
```

Description

Allow to write a special value (1a) in the cells of a dataframe (1b) that correspond (row and column) to whose of another dataframe (2b) that return another special value (2a). The cells whose coordinates do not match the coordinates of the dataframe (2b), another special value can be written (3a) if not set to NA.

nest_v 75

Usage

```
nestr_datf2(inptf_datf, rtn_pos, rtn_neg = NA, nestr_datf, yes_val = T)
```

Arguments

```
inptf_datf is the input dataframe (1b)
rtn_pos is the special value (1a)
rtn_neg is the special value (3a)
nestr_datf is the dataframe (2b)
yes_val is the special value (2a)
```

Examples

```
print(nestr_datf2(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)), rtn_pos="yes",
rtn_neg="no", nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val
# c.1..2..1. c.1..5..7.
#1    yes    no
#2    no    no
#3    yes    yes
```

Description

Nest two vectors according to the following parameters.

Usage

```
nest_v(f_v, t_v, step = 1, after = 1)
```

Arguments

f_v is the vector that will welcome the nested vector t_v
t_v is the imbriquator vector
step defines after how many elements of f_v the next element of t_v can be put in the output
after defines after how many elements of f_v, the begining of t_v can be put

76 normal_dens

Description

Returns the indexes of elements contained in "w_v" according to "f_v"

Usage

```
new_ordered(f_v, w_v, nvr_here = NA)
```

Arguments

f_v is the input vector

w_v is the vector containing the elements that can be in f_v

nvr_here is a value you are sure is not present in f_v

Examples

```
print(new_ordered(f_v=c("non", "non", "non", "oui"), w_v=c("oui", "non", "non")))
#[1] 4 1 2
```

normal_dens normal_dens

Description

Calculates the normal distribution probality, see examples

Usage

```
normal_dens(target_v = c(), mean, sd)
```

Arguments

target_v is the target value(s) (one or bounded), see examples

mean is the mean of the normal distribution

is the standard deviation of the normal distribution

occu 77

Examples

```
print(normal_dens(target_v = 13, mean = 12, sd = 2))
[1] 0.1760327
print(normal_dens(target_v = c(9, 11), mean = 12, sd = 1.5, step = 0.01))
[1] 0.2288579
print(normal_dens(target_v = c(1, 18), mean = 12, sd = 1.5, step = 0.01))
[1] 0.9999688
```

occu

occu

Description

Allow to see the occurence of each variable in a vector. Returns a datafame with, as the first column, the all the unique variable of the vector and , in he second column, their occurence respectively.

Usage

```
occu(inpt_v)
```

Arguments

```
inpt_v
```

the input dataframe

Examples

```
old_to_new_idx old_to_new_idx
```

Description

Allow to convert index of elements in a vector $inpt_v$ to index of an vector type 1:sum(nchar(inpt_v)), see examples

Usage

```
old_to_new_idx(inpt_v = c())
```

78 pairs_findr_merger

Arguments

```
inpt_v is the input vector
```

Examples

```
print(old_to_new_idx(inpt_v = c("oui", "no", "eeee")))
[1] 1 1 1 2 2 3 3 3 3
```

pairs_findr

pairs_findr

Description

Takes a character as input and detect the pairs of pattern, like the parenthesis pais if the pattern is "(" and then ")"

Usage

```
pairs_findr(inpt, ptrn1 = "(", ptrn2 = ")")
```

Arguments

inpt is the input characterptrn1 is the first pattern ecountered in the pairptrn2 is the second pattern in the pair

Examples

```
print (pairs_findr(inpt="ze+(yu*45/(jk+zz)*(o()p))-(re*(rt+qs)-fg)"))
[[1]]
[1] 4 1 1 3 2 2 3 4 6 5 5 6
[[2]]
[1] 4 11 17 19 21 22 24 25 27 31 37 41
```

```
pairs_findr_merger pairs_findr_merger
```

Description

Takes two different outputs from pairs_findr and merge them. Can be usefull when the pairs consists in different patterns, for example one output from the pairs_findr function with ptrn1 = "(" and ptrn2 = ")", and a second output from the pairs_findr function with ptrn1 = "" and ptrn2 = "".

Usage

```
pairs_findr_merger(lst1 = list(), lst2 = list())
```

pairs_findr_merger 79

Arguments

is the first ouput from pairs findr function 1st2 is the second ouput from pairs findr function

[1] 1 2 2 3 3 4 4 1 5 5 6 6

```
print(pairs\_findr\_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 8, 9)),\\
                         lst2=list(c(1, 1), c(1, 2)))
[[1]]
[1] 1 1 2 3 4 4 3 2
[[2]]
[1] 1 2 3 4 5 7 8 9
print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 8, 9))),
                        lst2=list(c(1, 1), c(1, 11)))
[[1]]
[1] 1 2 3 4 4 3 2 1
[[2]]
[1] 1 3 4 5 7 8 9 11
print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 8, 10, 11))),\\
                         lst2=list(c(4, 4), c(6, 7)))
[[1]]
[1] 1 2 3 4 4 3 2 1
[[2]]
[1] 3 4 5 6 7 8 10 11
print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 10, 11)))
                         lst2=list(c(4, 4), c(8, 9))))
[[1]]
[1] 1 2 3 3 4 4 2 1
[[2]]
[1] 3 4 5 7 8 9 10 11
print(pairs\_findr\_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 10, 11)),\\
                        lst2=list(c(4, 4), c(18, 19)))
[[1]]
[1] 1 2 3 3 2 1 4 4
[[2]]
[1] 3 4 5 7 10 11 18 19
print(pairs_findr_merger(lst1 = list(c(1, 1, 2, 2, 3, 3), c(1, 25, 26, 32, 33, 38)),
                        1st2 = list(c(1, 1, 2, 2, 3, 3), c(7, 11, 13, 17, 19, 24))))
```

80 pairs_insertr

pairs_insertr

pairs_insertr

Description

Takes a character representing an arbitrary condition (like ReGeX for example) or an information (to a parser for example), vectors containing all the pair of pattern that potentially surrounds condition (flagged_pair_v and corr_v), and a vector containing all the conjuntion character, as input and returns the character with all or some of the condition surrounded by the pair characters. See examples. All the pair characters are inserted according to the closest pair they found priotizing those found next to the condition and on the same depth-level and , if not found, the pair found at the n+1 depth-level.

Usage

```
pairs_insertr(
  inpt,
  algo_used = c(1:3),
  flagged_pair_v = c(")", "]"),
  corr_v = c("(", "["),
  flagged_conj_v = c("&", "|")
)
```

Arguments

inpt is the input character representing an arbitrary condition, like ReGex for example, or information to a parser for example

algo_used

is a vector containing one or more of the 3 algorythms used. The first algorythm will simply put the pair of parenthesis at the condition surrounded and/or after a character flagged (in flagged_conj_v) as a conjunction. The second algorythm

pairs_insertr2 81

will put parenthesis at the condition that are located after other conditions that are surrounded by a pair. The third algorythm will put a pair at all the condition, it is very powerfull but takes a longer time. See examples and make experience to see which combination of algorythm(s) is the most efficient for your use case.

```
flagged_pair_v
is a vector containing all the first character of the pairs

corr_v
is a vector containing all the last character of the pairs

flagged_conj_v
is a vector containing all the conjunction character
```

Examples

```
print(pairs_insertr(inpt = "([one]|two|twob)three(four)", algo_used = c(1)))
[1] "([one]|[two]|[twob])three(four)"
print(pairs_insertr(inpt = "(one|[two]|twob)three(four)", algo_used = c(2)))
[1] "(one|[two]|[twob])(three)(four)"
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2)))
[1] "(oneA|[one]|[two]|[twob])(three)(four)"
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2, 3)))
[1] "([oneA]|[one]|[two]|[twob])(three)(four)"
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(3)))
[1] "([oneA]|[one]|(two)|(twob))(three)(four)"
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three((four))", algo_used = c(3)))
[1] "([oneA]|[(one)]|(two)|(twob))(three)((four))"
```

```
pairs_insertr2 pairs_insertr2
```

Description

Takes a character representing an arbitrary condition (like ReGeX for example) or an information (to a parser for example), vectors containing all the pair of pattern that potentially surrounds condition (flagged_pair_v and corr_v), and a vector containing all the conjuntion character, as input and returns the character with all or some of the condition surrounded by the pair characters. See examples. All the pair characters are inserted according to the closest pair they found priotizing those found next to the condition and on the same depth-level and , if not found, the pair found at the n+1 depth-level.

82 pairs_insertr2

Usage

```
pairs_insertr2(
   inpt,
   algo_used = c(1:3),
   flagged_pair_v = c(")", "]"),
   corr_v = c("(", "["),
   flagged_conj_v = c("&", "|"),
   method = c("(", ")")
)
```

Arguments

inpt is the input character representing an arbitrary condition, like ReGex for exam-

ple, or information to a parser for example

algo_used is a vector containing one or more of the 3 algorythms used. The first algorythm

will simply put the pair of parenthesis at the condition surrounded and/or after a character flagged (in flagged_conj_v) as a conjunction. The second algorythm will put parenthesis at the condition that are located after other conditions that are surrounded by a pair. The third algorythm will put a pair at all the condition, it is very powerfull but takes a longer time. See examples and make experience

to see which combination of algorythm(s) is the most efficient for your use case.

flagged_pair_v

is a vector containing all the first character of the pairs

corr_v is a vector containing all the last character of the pairs

flagged_conj_v

is a vector containing all the conjunction character

method is length 2 vector containing as a first index, the first character of the pair in-

serted, and at the last index, the second and last character of the pair

paste_datf 83

```
[1] "([oneA]|[one]|[two]|[twob])[three](four)"
print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three((four))", algo_used = c(3)))
[1] "((oneA)|[one]|(two)|(twob))(three)((four))"
```

```
paste_datf
```

paste_datf

Description

Return a vector composed of pasted elements from the input dataframe at the same index.

Usage

```
paste_datf(inpt_datf, sep = "")
```

Arguments

```
inpt_datf is the input dataframe
sep is the separator between pasted elements, defaults to ""
```

Examples

```
print(paste_datf(inpt_datf=data.frame(c(1, 2, 1), c(33, 22, 55))))
#[1] "133" "222" "155"
```

```
\verb"pattern_generator" pattern_generator"
```

Description

Allow to create patterns which have a part that is varying randomly each time.

Usage

```
pattern_generator(base_, from_, nb, hmn = 1, after = 1, sep = "")
```

Arguments

base_	is the pattern that will be kept
from_	is the vector from which the elements of the random part will be generated
nb	is the number of random pattern chosen for the varying part
hmn	is how many of varying pattern from the same base will be created
after	is set to 1 by default, it means that the varying part will be after the fixed part, set to 0 if you want the varying part to be before
sep	is the separator between all patterns in the returned value

84 pattern_gettr

Examples

pattern_gettr

pattern_gettr

Description

Search for pattern(s) contained in a vector in another vector and return a list containing matched one (first index) and their position (second index) according to these rules: First case: Search for patterns strictly, it means that the searched pattern(s) will be matched only if the patterns containded in the vector that is beeing explored by the function are present like this c("pattern_searched", "other", ..., "pattern_searched") and not as c("other_thing pattern_searched other_thing", "other", ..., "pattern_searched other_thing") Second case: It is the opposite to the first case, it means that if the pattern is partially present like in the first position and the last, it will be considered like a matched pattern. REGEX can also be used as pattern

Usage

```
pattern_gettr(
  word_,
  vct,
  occ = c(1),
  strict,
  btwn,
  all_in_word = "yes",
  notatall = "###"
)
```

Arguments

word_	is the vector containing the patterns
vct	is the vector being searched for patterns
occ	a vector containing the occurrence of the pattern in word_ to be matched in the vector being searched, if the occurrence is 2 for the nth pattern in word_ and only one occurrence is found in vct so no pattern will be matched, put "forever" to no longer depend on the occurrence for the associated pattern
strict	a vector containing the "strict" condition for each nth vector in word_ ("strict" is the string to activate this option)
btwn	is a vector containing the condition ("yes" to activate this option) meaning that if "yes", all elements between two matched patern in vct will be returned , so the patterns you enter in word_ have to be in the order you think it will appear in vct

pattern_tuning 85

```
all_in_word is a value (default set to "yes", "no" to activate this option) that, if activated, won't authorized a previous matched pattern to be matched again notatall is a string that you are sure is not present in vct
```

Examples

```
print(pattern_gettr(word_=c("oui", "non", "erer"), vct=c("oui", "oui", "non", "oui",
    "non", "opp", "opp", "erer", "non", "ok"), occ=c(1, 2, 1),
    btwn=c("no", "yes", "no"), strict=c("no", "no", "ee")))

#[[1]]
#[1] 1 5 8
#
#[[2]]
#[1] "oui" "non" "opp" "opp" "erer"
```

```
pattern_tuning pattern_tuning
```

Description

Allow to tune a pattern very precisely and output a vector containing its variations n times.

Usage

```
pattern_tuning(
  pattrn,
  spe_nb,
  spe_l,
  exclude_type,
  hmn = 1,
  rg = c(1, nchar(pattrn))
)
```

Arguments

```
pattrn is the character that will be tuned

spe_nb is the number of new character that will be replaced

spe_l is the source vector from which the new characters will replace old ones

exclude_type is character that won't be replaced

hmn is how many output the function will return

rg is a vector with two parameters (index of the first letter that will be replaced, index of the last letter that will be replaced) default is set to all the letters from the source pattern
```

```
print(pattern_tuning(pattrn="oui", spe_nb=2, spe_l=c("e", "r", "T", "O"), exclude_type="out"
#[1] "orT" "oTr" "oOi"
```

86 pre_to_post_idx

Description

Convert a scientific number to a string representing normally the number.

Usage

```
power_to_char(inpt_v = c())
```

Arguments

inpt_v is the input vector containing scientific number, but also other elements that won't be taken in count

Examples

```
print(power_to_char(inpt_v = c(22 * 10000000, 12, 9 * 0.0000002)))
[1] "2200000000" "12" "0.0000018"
```

Description

Allow to convert indexes from a pre-vector to post-indexes based on a current vector, see examples

Usage

```
pre_to_post_idx(inpt_v = c(), inpt_idx = c(1:length(inppt_v)))
```

Arguments

```
inpt_v is the new vector
inpt_idx is the vector containing the pre-indexes
```

```
print(pre_to_post_idx(inpt_v = c("oui", "no", "eee"), inpt_idx = c(1:8)))
[1] 1 1 1 2 2 3 3 3
As if the first vector was c("o", "u", "i", "n", "o", "e", "e", "e")
```

ptrn_switchr 87

Description

Allow to switch, copy pattern for each element in a vector. Here a pattern is the values that are separated by a same separator. Example: "xx-xxx-xx" or "xx/xx/xxxx". The xx like values can be switched or copied from whatever index to whatever index. Here, the index is like this 1-2-3 etcetera, it is relative of the separator.

Usage

```
ptrn_switchr(inpt_l, f_idx_l = c(), t_idx_l = c(), sep = "-", default_val = NA)
```

Arguments

inpt_l	is the input vector
f_idx_l	is a vector containing the indexes of the pattern you want to be altered.
t_idx_l	is a vector containing the indexes to which the indexes in f_idx_l are related.
sep	is the separator, defaults to "-"
default_val	is the default value , if not set to NA, of the pattern at the indexes in f_idx_l . If it is not set to NA, you do not need to fill t_idx_l because this is the vector containing the indexes of the patterns that will be set as new values relatively to the indexes in f_idx_l . Defaults to NA.

Examples

```
print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
   "2022-01-01"), f_idx_l=c(1, 2, 3), t_idx_l=c(3, 2, 1)))
#[1] "11-01-2022" "14-01-2022" "21-01-2022" "01-01-2022"

print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
   "2022-01-01"), f_idx_l=c(1), default_val="ee"))
#[1] "ee-01-11" "ee-01-14" "ee-01-21" "ee-01-01"
```

```
ptrn_twkr ptrn_twkr
```

Description

Allow to modify the pattern length of element in a vector according to arguments. What is here defined as a pattern is something like this xx-xx-xx or xx/xx/xxx... So it is defined by the separator

88 read_edm_parser

Usage

```
ptrn_twkr(
  inpt_l,
  depth = "max",
  sep = "-",
  default_val = "0",
  add_sep = TRUE,
  end_ = TRUE
)
```

Arguments

inpt 1 is the input vector is the number (numeric) of separator it will keep as a result. To keep the numdepth ber of separator of the element that has the minimum amount of separator do depth="min" and depth="max" (character) for the opposite. This value defaults to "max". is the separator of the pattern, defaults to "-" sep is the default val that will be placed between the separator, defaults to "00" default_val defaults to TRUE. If set to FALSE, it will remove the separator for the patterns add_sep that are included in the interval between the depth amount of separator and the actual number of separator of the element. is if the default_val will be added at the end or at the beginning of each element end_ that lacks length compared to depth

Examples

```
v <- c("2012-06-22", "2012-06-23", "2022-09-12", "2022")
ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE)
#[1] "2012-06-22" "2012-06-23" "2022-09-12" "2022-00-00"
ptrn_twkr(inpt_l=v, depth=1, sep="-", default_val="00", add_sep=TRUE)
#[1] "2012-06" "2012-06" "2022-09" "2022-00"
ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE, end_=FALSE)
#[1] "2012-06-22" "2012-06-23" "2022-09-12" "00-00-2022"</pre>
```

```
read_edm_parser
```

Description

Allow to read data from edm parsed dataset, see examples

rearangr_v 89

Usage

```
read_edm_parser(inpt, to_find_v = c())
```

Arguments

```
inpt is the input dataset
to_find_v is the vector containing the path to find the data, see examples
```

Examples

```
print (read_edm_parser("(ok(ee:56)) (ok(oui(rr((rr2:6)(rr:5)))) (oui(bb(rr2:1))) (ee1:4))",
to_find_v = c("ok", "oui", "rr", "rr2")))

[1] "6"

print (read_edm_parser("(ok(ee:56)) (ok(oui(rr((rr2:6)(rr:5)))) (oui(bb(rr2:1))) (ee1:4))", t

[1] "56"

print (read_edm_parser("(ok(ee:56)) (ok(oui(rr((rr2:6)(rr:5))))) (oui(bb(rr2:1))) (ee1:4))", t

[1] "56"
```

rearangr_v

rearangr_v

Description

Reanranges a vector "w_v" according to another vector "inpt_v". inpt_v contains a sequence of number. inpt_v and w_v have the same size and their indexes are related. The output will be a vector containing all the elements of w_v rearanges in descending or asending order according to inpt_v

Usage

```
rearangr_v(inpt_v, w_v, how = "increasing")
```

Arguments

inpt_v is the vector that contains the sequence of number w_v is the vector containing the elements related to inpt_v

how is the way the elements of w_v will be outputed according to if inpt_v will be

sorted ascendigly or descendingly

```
print(rearangr_v(inpt_v=c(23, 21, 56), w_v=c("oui", "peut", "non"), how="decreasing"))
#[1] "non" "oui" "peut"
```

90 regroupr

```
regex_spe_detect    regex_spe_detect
```

Description

Takes a character as input and returns its regex-friendly character for R.

Usage

```
regex_spe_detect(inpt)
```

Arguments

inpt

the input character

Examples

```
print(regex_spe_detect("o"))
[1] "o"

print(regex_spe_detect("("))

[1] "\\(")

print(regex_spe_detect("tr(o)m"))

[1] "tr\\(o\\)m"

print(regex_spe_detect(inpt="fggfg[fggf]fgfg(vg?fgfgf.gf)"))

[1] "fggfg\\[fggf\\]fgfg\\(vg\\?fgfgf\\.gf\\)"

print(regex_spe_detect(inpt = "---"))

[1] "\\-\\-\\-"
```

regroupr

regroupr

Description

Allow to sort data like "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to what you want. For example it can be to "c(X1/Y1/Z1, X1/Y1/Z2, ...)"

Usage

```
regroupr(
  inpt_v,
  sep_ = "-",
  order = c(1:length(unlist(strsplit(x = inpt_v[1], split = sep_)))),
  l_order = NA
)
```

row_to_col 91

Arguments

is the input vector containing all the data you want to sort in a specific way. All the sub-elements should be separated by a unique separator such as "-" or "/" sep_ is the unique separator separating the sub-elements in each elements of inpt_v order is a vector describing the way the elements should be sorted. For example if you want this dataset "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to be sorted by the last element you should have order=c(3:1), for example, and it should returns something like this c(X1/Y1/Z1, X2/Y1/Z1, X1/Y2/Z1, ...) assuming you have only two values for X.

1_order is a list containing the vectors of values you want to order first for each sub-elements

Examples

```
vec <- multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/"</pre>
print (vec)
# [1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
# [8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
#[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
#[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"
print(regroupr(inpt_v=vec, sep_="/"))
                                         "a/1/4/4"
# [1] "a/1/1/1"
                 "a/1/2/2"
                             "a/1/3/3"
                                                    "a/1/5/5"
                                                                "a/1/6/6"
# [7] "a/2/7/7" "a/2/8/8"
                           #[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/1/18/18"
#[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23" "b/2/24/24"
vec <- vec[-2]
print(regroupr(inpt_v=vec, sep_="/"))
# [1] "a/1/1/1"
                 "a/1/2/2"
                             "a/1/3/3"
                                         "a/1/4/4"
                                                    "a/1/5/5"
                                                                "a/1/6/6"
# [7] "a/2/7/7"
                 "a/2/8/8"
                             "a/2/9/9"
                                         "a/2/10/10" "a/2/11/11" "a/2/12/12"
#[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/2/18/18"
#[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23"
print(regroupr(inpt_v=vec, sep_="/", order=c(4:1)))
#[1] "1/1/A/Q"
                "2/2/A/Q"
                                        "4/4/A/Q"
                                                              "6/6/Z/Q"
                            "3/3/A/Q"
                                                   "5/5/Z/Q"
# [7] "7/7/Z/Q"
                 "8/8/Z/Q"
                             "9/9/E/Q"
                                       "10/10/E/Q" "11/11/E/Q" "12/12/E/Q"
#[13] "13/13/A/F" "14/14/A/F" "15/15/A/F" "16/16/A/F" "17/17/Z/F" "18/18/Z/F"
#[19] "19/19/Z/F" "20/20/Z/F" "21/21/E/F" "22/22/E/F" "23/23/E/F" "24/24/E/F"
```

Description

row_to_col

Allow to reverse a dataframe (rows become cols and cols become rows)

row_to_col

92 r_print

Usage

```
row_to_col(inpt_datf)
```

Arguments

```
inpt_datf is the inout dataframe
```

Examples

r_print r_print

Description

Allow to print vector elements in one row.

print(r_print(inpt_v=c(1:33)))

Usage

```
r_print(inpt_v, sep_ = "and", begn = "This is", end = ", voila!")
```

Arguments

inpt_v is the input vector

sep_ is the separator between each elements

begn is the character put at the beginning of the print

end is the character put at the end of the print

```
\#[1] "This is 1 and 2 and 3 and 4 and 5 and 6 and 7 and 8 and 9 and 10 and 11 and 12 and \#[1] and 15 and 16 and 17 and 18 and 19 and 20 and 21 and 22 and 23 and 24 and 25 and \#[1] and 28 and 29 and 30 and 31 and 32 and 33 and , voila!"
```

save_untl 93

```
save_untl save_untl
```

Description

Get the elements in each vector from a list that are located before certain values

Usage

```
save_untl(inpt_l = list(), val_to_stop_v = c())
```

Arguments

```
inpt_1 is the input list containing all the vectors
val_to_stop_v
```

is a vector containing the values that marks the end of the vectors returned in the returned list, see the examples

Examples

```
print(save_untl(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3, 4))
#[[1]]
#[1] 1 2
#
#[[2]]
#[1] 1 1
#
#[[3]]
#[1] 1 2
print(save_untl(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3)))
#[[1]]
#[1] 1 2
#
#[[2]]
#[1] 1 2
#
#[[3]]
#[1] 1 1
```

```
see_datf
```

see_datf

Description

Allow to return a dataframe with special value cells (ex: TRUE) where the condition entered are respected and another special value cell (ex: FALSE) where these are not

94 see_datf

Usage

```
see_datf(
  datf,
  condition_l,
  val_l,
  conjunction_l = c(),
  rt_val = TRUE,
  f_val = FALSE
)
```

Arguments

datf is the input dataframe is the vector of the possible conditions ("==", ">", "<", "!=", "%%", "reg", condition 1 "not_reg", "sup_nchar", "inf_nchar", "nchar") (equal to some elements in a vector, greater than, lower than, not equal to, is divisible by, the regex condition returns TRUE, the regex condition returns FALSE, the length of the elements is strictly superior to X, the length of the element is strictly inferior to X, the length of the element is equal to one element in a vector), you can put the same condition n times. is the list of vectors containing the values or vector of values related to condival_l tion_l (so the vector of values has to be placed in the same order) conjunction_l contains the and or conjunctions, so if the length of condition_l is equal to 3, there will be 2 conjunctions. If the length of conjunction_l is inferior to the length of condition_1 minus 1, conjunction_1 will match its goal length value with its last argument as the last arguments. For example, c("&", "|", "&") with a goal length value of $5 \rightarrow c("\&", "|", "\&", "\&", "\&")$ rt_val is a special value cell returned when the conditions are respected f_val is a special value cell returned when the conditions are not respected

Details

This function will return an error if number only comparative conditions are given in addition to having character values in the input dataframe.

```
datf1 <- data.frame(c(1, 2, 4), c("a", "a", "zu"))
print(see_datf(datf=datf1, condition_l=c("nchar"), val_l=list(c(1))))
# X1    X2
#1 TRUE    TRUE
#2 TRUE    TRUE
#3 TRUE FALSE
print(see_datf(datf=datf1, condition_l=c("=="), val_l=list(c("a", 1))))
# X1    X2
#1 TRUE    TRUE
#2 FALSE    TRUE</pre>
```

see_diff

see_diff

see_diff

Description

Output the opposite of intersect(a, b). Already seen at: https://stackoverflow.com/questions/19797954/function-to-find-symmetric-difference-opposite-of-intersection-in-r

Usage

```
see\_diff(vec1 = c(), vec2 = c())
```

Arguments

vec1 is the first vector vec2 is the second vector

Examples

```
print(see_diff(c(1:7), c(4:12)))
[1] 1 2 3 8 9 10 11 12
```

```
see_diff_all
```

see_diff_all

Description

Allow to perform the opposite of intersect function to n vectors.

Usage

```
see_diff_all(...)
```

96 see_file

Arguments

... are all the input vectors

Examples

```
vec1 <- c(3:6)
vec2 <- c(1:8)
vec3 <- c(12:16)

print(see_diff_all(vec1, vec2))

[1] 1 2 7 8

print(see_diff_all(vec1, vec2, vec3))

[1] 3 4 5 6 1 2 7 8 12 13 14 15 16</pre>
```

see_file see_file

Description

Allow to get the filename or its extension

Usage

```
see_file(string_, index_ext = 1, ext = TRUE)
```

Arguments

is the input string
index_ext is the occurence of the dot that separates the filename and its extension
ext is a boolean that if set to TRUE, will return the file extension and if set to FALSE, will return filename

```
print(see_file(string_="file.abc.xyz"))
#[1] ".abc.xyz"
print(see_file(string_="file.abc.xyz", ext=FALSE))
#[1] "file"
print(see_file(string_="file.abc.xyz", index_ext=2))
#[1] ".xyz"
```

see_idx 97

Description

Returns a boolean vector to see if a set of elements contained in v1 is also contained in another vector (v2)

Usage

```
see_idx(v1, v2)
```

Arguments

```
v1 is the first vector
v2 is the second vector
```

Examples

```
print(see_idx(v1=c("oui", "non", "peut", "oo"), v2=c("oui", "peut", "oui")))
#[1] TRUE FALSE TRUE FALSE
```

see_inside

see_inside

Description

Return a list containing all the column of the files in the current directory with a chosen file extension and its associated file and sheet if xlsx. For example if i have 2 files "out.csv" with 2 columns and "out.xlsx" with 1 column for its first sheet and 2 for its second one, the return will look like this: c(column_1, column_2, column_3, column_4, column_5, unique_separator, "1-2-out.csv", "3-3-sheet_1-out.xlsx", 4-5-sheet_2-out.xlsx)

Usage

```
see_inside(
  pattern_,
  path_ = ".",
  sep_ = c(","),
  unique_sep = "#####",
  rec = FALSE
)
```

98 see_mode

Arguments

pattern_ is a vector containin the file extension of the spreadsheets ("xlsx", "csv"...)

path_ is the path where are located the files

sep_ is a vector containing the separator for each csv type file in order following the

operating system file order, if the vector does not match the number of the csv files found, it will assume the separator for the rest of the files is the same as the last csv file found. It means that if you know the separator is the same for all the

csv type files, you just have to put the separator once in the vector.

unique_sep is a pattern that you know will never be in your input files

rec is a boolean allows to get files recursively if set to TRUE, defaults to TRUE If x

is the return value, to see all the files name, position of the columns and possible

sheet name associanted with, do the following:

see_mode see_mode

Description

Allow to get the mode of a vector, see examples.

Usage

```
see\_mode(inpt\_v = c())
```

Arguments

inpt v is the input vector

```
print(see_mode(inpt_v = c(1, 1, 2, 2, 2, 3, 1, 2)))
[1] 2
print(see_mode(inpt_v = c(1, 1, 2, 2, 2, 3, 1)))
[1] 1
```

selected_char 99

|--|--|--|

Description

Allow to generate a char based on a conbinaison on characters from a vector and a number

Usage

```
selected_char(n, base_char = letters)
```

Arguments

n is how many sequence of numbers will be generated

base_char is the vector containing the elements from which the character is generated

Examples

```
print(selected_char(1222))
[1] "zta"
```

Description

Allow to sort any vector containing a date, from any kind of format (my, hdmy, ymd ...), see examples.

Usage

```
sort_date(inpt_v, frmt, sep_ = "-", ascending = FALSE, give = "value")
```

Arguments

inpt_v is the input vector containing all the dates

frmt is the format of the dates, (any combinaison of letters "s" for second, "n", for

minute, "h" for hour, "d" for day, "m" for month and "y" for year)

sep_ is the separator used for the dates

ascending is the used to sort the dates

give takes only two values "index" or "value", if give == "index", the function will

output the index of sorted dates from inpt_v, if give == "value", the function will output the value, it means directly the sorted dates in inpt_v, see examples

Examples

```
sort_normal_qual sort_normal_qual
```

Description

Sort qualitative modalities that have their frequency normally distributed from an unordered dataset, see examples. This function uses an another algorythm than choose_normal_qual2 which may be faster.

Usage

```
sort_normal_qual(inpt_datf)
```

Arguments

inpt_datf is the input dataframe, containing the values in the first column and their frequency in the second

```
sample_val <- round(rnorm(n = 2000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)
sample_qual <- infinite_char_seq(n = length(sample_freq))
datf_test <- data.frame(sample_qual, sample_freq)
datf_test[, 2] <- datf_test[, 2] / sum(datf_test[, 2]) # optional</pre>
```

print(datf_test)

```
sample_qual sample_freq
            a 0.208695652
            b 0.234782609
             c 0.321739130
4
            d 0.339130435
            e 0.330434783
            f 0.069565217
7
            q 0.234782609
            h 0.400000000
9
            i 0.347826087
10
            j 0.043478261
11
            k 0.278260870
12
            1 0.286956522
13
           m 0.243478261
14
           n 0.147826087
15
           0 0.234782609
           p 0.252173913
16
           q 0.417391304
17
18
            r 0.095652174
19
             s 0.313043478
20
             t 0.008695652
21
             u 0.130434783
22
             v 0.391304348
23
            w 0.113043478
24
            x 0.295652174
25
            y 0.243478261
            z 0.382608696
26
          aa 0.008695652
27
          ab 0.347826087
28
29
          ac 0.330434783
30
          ad 0.321739130
31
          ae 0.347826087
32
          af 0.321739130
          ag 0.173913043
33
34
          ah 0.278260870
          ai 0.278260870
35
          aj 0.347826087
36
          ak 0.026086957
37
          al 0.295652174
38
          am 0.226086957
39
          an 0.295652174
40
           ao 0.234782609
41
42
            ap 0.113043478
43
            aq 0.234782609
44
            ar 0.173913043
45
            as 0.017391304
           at 0.252173913
46
47
           au 0.078260870
48
          av 0.086956522
49
          aw 0.278260870
50
          ax 0.086956522
51
          ay 0.200000000
52
          az 0.295652174
53
          ba 0.052173913
54
          bb 0.165217391
```

55	bc	0.408695652
56	bd	0.269565217
57	be	0.104347826
58	bf	0.391304348
59		0.104347826
	bg	
60	bh	0.043478261
61	bi	0.200000000
62	bј	0.095652174
63	bk	0.191304348
64	bl	0.008695652
65	bm	0.165217391
66	bn	0.226086957
67	bo	0.086956522
68	bp	0.017391304
69	þq	0.121739130
70	br	0.234782609
71	bs	0.121739130
72	bt	0.078260870
73	bu	0.173913043
74	bv	0.104347826
75	bw	0.208695652
76	bx	0.017391304
77		
	by	0.243478261
78	bz	0.034782609
79	са	0.017391304
80	cb	0.008695652
81	CC	0.173913043
82	cd	0.147826087
83	се	0.060869565
84	cf	0.017391304
85	cg	0.060869565
86	ch	0.008695652
87	ci	0.208695652
88	cj	0.043478261
89	ck	0.052173913
90	cl	0.017391304
91	cm	0.017391304
92	cn	0.095652174
93	СО	0.113043478
94	ср	0.017391304
95	cq	0.017391304
96	cr	0.026086957
97	CS	0.034782609
98	ct	0.017391304
99	cu	0.026086957
100	CV	0.026086957
101	CW	0.026086957
102	CX	0.017391304
103	су	0.043478261
104	CZ	0.008695652
105	da	0.034782609
106	db	0.017391304
107	dc	0.060869565
108	dd	0.008695652
		0.008695652
109	de	
110	df	0.017391304
111	dg	0.008695652

112

```
dh 0.008695652
113
             di 0.017391304
114
             dj 0.008695652
             dk 0.008695652
115
print(sort_normal_qual(inpt_datf = datf_test))
0.00869565217391304 0.00869565217391304 0.00869565217391304 0.00869565217391304
              "aa"
                                   "cb"
                                                         "cz"
0.00869565217391304 0.00869565217391304
                                          0.0173913043478261 0.0173913043478261
              "dh"
                                   "dk"
                                                         "bp"
                                                                              "ca"
0.0173913043478261
                    0.0173913043478261
                                          0.0173913043478261
                                                               0.0173913043478261
              "c]"
                                   "ср"
                                                         "ct"
0.0173913043478261
                    0.0260869565217391
                                          0.0260869565217391
                                                               0.0347826086956522
              "di"
                                   "cr"
                                                         "cv"
0.0347826086956522
                                          0.0434782608695652
                    0.0434782608695652
                                                               0.0521739130434783
              "da"
                                   "bh"
                                                         "cy"
                                                                              "ck"
0.0608695652173913
                    0.0695652173913043
                                          0.0782608695652174
                                                               0.0869565217391304
              "cq"
                                     "f"
                                                         "bt"
                                                                              "ax"
0.0956521739130435
                    0.0956521739130435
                                           0.104347826086957
                                                                 0.11304347826087
                "r"
                                    "cn"
                                                         "bq"
  0.11304347826087
                      0.121739130434783
                                           0.147826086956522
                                                                0.165217391304348
               "co"
                                    "bs"
                                                          "n"
                                                                              "bb"
 0.173913043478261
                      0.173913043478261
                                           0.191304347826087
                                                                               0.2
                                                                              "bi"
              "ag"
                                    "bu"
                                                         "bk"
 0.208695652173913
                      0.226086956521739
                                           0.234782608695652
                                                                0.234782608695652
              "bw"
                                    "am"
                                                          "b"
                                                                               " 0 "
                                           0.243478260869565
 0.234782608695652
                      0.243478260869565
                                                                0.252173913043478
               "aq"
                                     "m"
                                                         "bv"
                                                                              "at"
 0.278260869565217
                      0.278260869565217
                                            0.28695652173913
                                                                0.295652173913043
                " k "
                                                          " | "
                                    "ai"
                                                                              "al"
 0.295652173913043
                                           0.321739130434783
                                                                0.330434782608696
                      0.321739130434783
               "az"
                                     "c"
 0.347826086956522
                      0.347826086956522
                                           0.382608695652174
                                                                0.391304347826087
               " i "
                                    "ae"
                                                          "z"
                                                                              "bf"
 0.408695652173913
                      0.417391304347826
                                                          0.4
                                                                0.391304347826087
                                     "q"
                                                          "h"
               "ho"
                                                                               11 77 11
 0.347826086956522
                      0.347826086956522
                                           0.339130434782609
                                                                0.330434782608696
               "aj"
                                    "ab"
                                                          "d"
                                                                               "e"
 0.321739130434783
                       0.31304347826087
                                           0.295652173913043
                                                                0.295652173913043
                                     "s"
               "ad"
                                                         "an"
                                                                               " × "
                      0.278260869565217
 0.278260869565217
                                           0.269565217391304
                                                                0.252173913043478
               "aw"
                                    "ah"
                                                         "bd"
 0.243478260869565
                      0.234782608695652
                                           0.234782608695652
                                                                0.234782608695652
                                   "br"
                                                         "ao"
                                                                               "g"
 0.226086956521739
                                                                               0.2
                      0.208695652173913
                                           0.208695652173913
              "bn"
                                   "ci"
                                                         "a"
                                                                              "ay"
 0.173913043478261
                      0.173913043478261
                                           0.165217391304348
                                                                0.147826086956522
              "cc"
                                    "ar"
                                                         "bm"
                                                                              "cd"
 0.130434782608696
                                            0.11304347826087
                                                                0.104347826086957
                      0.121739130434783
               "u"
                                   "ba"
                                                         "ap"
                                                                              "bv"
 0.104347826086957
                     0.0956521739130435
                                          0.0869565217391304
                                                               0.0869565217391304
              "be"
                                   "bj"
                                                         "bo"
0.0782608695652174
                     0.0608695652173913
                                          0.0608695652173913
                                                               0.0521739130434783
              "au"
                                   "dc"
                                                        "ce"
                     0.0434782608695652
0.0434782608695652
                                          0.0347826086956522
                                                               0.0260869565217391
                                    "j"
              "cj"
                                                         "cs"
                                                                              "CW"
```

```
0.0260869565217391 0.0260869565217391 0.0173913043478261 0.0173913043478261
               "cu"
                                    "ak"
                                                          "df"
0.0173913043478261 \quad 0.0173913043478261 \quad 0.0173913043478261 \quad 0.0173913043478261
              "cq"
                                    "cm"
                                                          "cf"
0.0173913043478261 \ 0.00869565217391304 \ 0.00869565217391304 \ 0.00869565217391304
              "as"
                                    "dj"
                                                          "dq"
                                                                               "dd"
0.00869565217391304 0.00869565217391304 0.00869565217391304
               "ch"
                                    "bl"
```

```
sort_normal_qual2 sort_normal_qual2
```

Description

Sort qualitative modalities that have their frequency normally distributed from an unordered dataset, see examples. This function uses an another algorythm than choose_normal_qual which may be faster.

Usage

```
sort_normal_qual2(inpt_datf)
```

Arguments

inpt_datf is the input dataframe, containing the values in the first column and their frequency in the second

```
sample_val \leftarrow round(rnorm(n = 2000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)</pre>
sample_qual <- infinite_char_seq(n = length(sample_freq))</pre>
datf_test <- data.frame(sample_qual, sample_freq)</pre>
datf_test[, 2] <- datf_test[, 2] / sum(datf_test[, 2])</pre>
print(datf_test)
   sample_qual sample_freq
1
              a 0.208695652
               b 0.234782609
2
3
               c 0.321739130
4
               d 0.339130435
5
               e 0.330434783
6
               f 0.069565217
7
               g 0.234782609
8
               h 0.40000000
9
               i 0.347826087
1.0
               j 0.043478261
11
               k 0.278260870
12
              1 0.286956522
13
              m 0.243478261
              n 0.147826087
15
               o 0.234782609
```

		0.0000000000000000000000000000000000000
16	р	0.252173913
17	q	0.417391304
18	r	0.095652174
19	s	0.313043478
20	t	0.008695652
21	u	0.130434783
22	V	0.391304348
23	W	0.113043478
		0.295652174
24	Х	
25	У	0.243478261
26	Z	0.382608696
27	aa	0.008695652
28	ab	0.347826087
29	ac	0.330434783
30	ad	0.321739130
31	ae	0.347826087
32	af	0.321739130
33		0.173913043
	ag	
34	ah	0.278260870
35	ai	0.278260870
36	аj	0.347826087
37	ak	0.026086957
38		
	al	0.295652174
39	am	0.226086957
40	an	0.295652174
41	ao	0.234782609
42		
	ap	
43	aq	
44	ar	0.173913043
45	as	0.017391304
46	at	0.252173913
47		0.078260870
	au	
48	av	0.086956522
49	aw	0.278260870
50	ax	0.086956522
51	ay	0.200000000
52	_	
	az	0.295652174
53	ba	0.052173913
54	bb	0.165217391
55	bc	0.408695652
56	bd	0.269565217
57		0.104347826
	be	
58	bf	0.391304348
59	bg	0.104347826
60	bh	0.043478261
61	bi	0.200000000
62	bj	0.095652174
63	bk	0.191304348
64	bl	0.008695652
65	bm	0.165217391
66	bn	0.226086957
67	bo	0.086956522
68	bp	0.017391304
69	bq	0.121739130
70	_	
	hr	0.234782609
	br	0.234782609
71 72	br bs bt	0.234782609 0.121739130 0.078260870

```
73
             bu 0.173913043
74
             bv 0.104347826
75
             bw 0.208695652
76
             bx 0.017391304
77
             by 0.243478261
78
             bz 0.034782609
79
             ca 0.017391304
             cb 0.008695652
80
             cc 0.173913043
81
82
            cd 0.147826087
83
            ce 0.060869565
            cf 0.017391304
85
            cg 0.060869565
86
            ch 0.008695652
87
            ci 0.208695652
88
            cj 0.043478261
89
             ck 0.052173913
90
             cl 0.017391304
91
             cm 0.017391304
92
             cn 0.095652174
93
             co 0.113043478
94
             ср 0.017391304
95
             cq 0.017391304
96
             cr 0.026086957
97
             cs 0.034782609
98
             ct 0.017391304
             cu 0.026086957
99
             cv 0.026086957
100
             cw 0.026086957
101
102
            cx 0.017391304
103
            cy 0.043478261
            cz 0.008695652
104
105
            da 0.034782609
106
            db 0.017391304
107
            dc 0.060869565
108
            dd 0.008695652
109
            de 0.008695652
             df 0.017391304
110
             dg 0.008695652
111
             dh 0.008695652
112
113
             di 0.017391304
114
             dj 0.008695652
115
             dk 0.008695652
print(sort_normal_qual2(inpt_datf = datf_test))
0.00869565217391304 \ 0.00869565217391304 \ 0.00869565217391304 \ 0.00869565217391304
              "aa"
                                   "cb"
                                                         "cz"
0.00869565217391304 \ \ 0.00869565217391304 \ \ \ 0.0173913043478261 \ \ \ 0.0173913043478261
               "dh"
                                    "dk"
                                                         "bp"
0.0173913043478261 \quad 0.0173913043478261 \quad 0.0173913043478261 \quad 0.0173913043478261
              "cl"
                                    "cp"
                                                         "ct"
0.0173913043478261 \quad 0.0260869565217391 \quad 0.0260869565217391 \quad 0.0347826086956522
              "di"
                                   "cr"
                                                         "cv"
0.0347826086956522 \quad 0.0434782608695652 \quad 0.0434782608695652 \quad 0.0521739130434783
              "da"
                                   "bh"
                                                         "cy"
```

 $0.0608695652173913 \quad 0.0695652173913043 \quad 0.0782608695652174 \quad 0.0869565217391304$

split_by_step 107

"cg"	"f"	"bt"	"ax"
0.0956521739130435	0.0956521739130435	0.104347826086957	0.11304347826087
"r"	"cn"	"bg"	"M"
0.11304347826087	0.121739130434783	0.147826086956522	0.165217391304348
"co"	"bs"	"n"	"bb"
0.173913043478261 "ag"	0.173913043478261 "bu"	0.191304347826087 "bk"	0.2 "bi"
0.208695652173913	0.226086956521739	0.234782608695652	0.234782608695652
"bw"	"am"	"b"	"0"
0.234782608695652	0.243478260869565	0.243478260869565	0.252173913043478
"aq"	"m"	"by"	"at"
0.278260869565217	0.278260869565217	0.28695652173913	0.295652173913043
"k"	"ai"	"1"	"al"
0.295652173913043	0.321739130434783	0.321739130434783	0.330434782608696
"az" 0.347826086956522	"c" 0.347826086956522	"af" 0.382608695652174	"ac" 0.391304347826087
0.347620060930322 "i"	"ae"	U.302000093032174	"bf"
0.408695652173913	0.417391304347826	0.4	0.391304347826087
"bc"	"q"	"h"	" _V "
0.347826086956522	0.347826086956522	0.339130434782609	0.330434782608696
"aj"	"ab"	"d"	"e"
0.321739130434783	0.31304347826087	0.295652173913043	0.295652173913043
"ad" 0.278260869565217	"s" 0.278260869565217	"an" 0.269565217391304	"x" 0.252173913043478
"aw"	0.276260669363217 "ah"	"bd"	0.232173913043476 "p"
0.243478260869565	0.234782608695652	0.234782608695652	0.234782608695652
"y"	"br"	"ao"	" g"
0.226086956521739	0.208695652173913	0.208695652173913	0.2
"bn"	"ci"	"a"	"ay"
0.173913043478261	0.173913043478261	0.165217391304348	0.147826086956522
"cc" 0.130434782608696	"ar" 0.121739130434783	"bm" 0.11304347826087	"cd" 0.104347826086957
" ₁₁ "	"bq"	"ap"	"bv"
0.104347826086957	0.0956521739130435	0.0869565217391304	0.0869565217391304
"be"	"bj"	"bo"	"av"
0.0782608695652174	0.0608695652173913	0.0608695652173913	0.0521739130434783
"au"	"dc"	"ce"	"ba"
0.0434782608695652	0.0434782608695652	0.0347826086956522	0.0260869565217391
"cj" 0.0260869565217391	"j" 0.0260869565217391	"cs" 0.0173913043478261	"cw" 0.0173913043478261
"cu"	"ak"	"df"	"CX"
0.0173913043478261	0.0173913043478261	0.0173913043478261	0.0173913043478261
"cq"	"cm"	"cf"	"bx"
0.0173913043478261		0.00869565217391304	0.00869565217391304
"as"	"dj"	"dg"	"dd"
		4 0.0086956521739130	4
"ch"	"bl"	"t"	

split_by_step

Description

Allow to split a string or a vector of strings by a step, see examples.

108 str_remove_untl

Usage

```
split_by_step(inpt_v, by)
```

Arguments

```
inpt_v is the input character or vector of characters
by is the step
```

Examples

```
print(split_by_step(inpt_v = c("o", "u", "i", "n", "o", "o", "u", "i", "o", "Z"), by = 2)
[1] "ou" "in" "oo" "ui" "oZ"

print(split_by_step(inpt_v = c("o", "u", "i", "n", "o", "o", "u", "i", "o", "Z"), by = 3)
[1] "oui" "noo" "uio" "Z"

print(split_by_step(inpt_v = c("o", "u", "i", "n", "o", "o", "u", "i", "o", "Z"), by = 4)
[1] "ouin" "ooui" "oZ"

print(split_by_step(inpt_v = 'ouinoouioz', by = 4))
[1] "ouin" "ooui" "oZ"
```

```
str_remove_untl str_remove_untl
```

Description

Allow to remove pattern within elements from a vector precisely according to their occurence.

Usage

```
str_remove_untl(
  inpt_v,
  ptrn_rm_v = c(),
  untl = list(c(1)),
  nvr_following_ptrn = "NA"
)
```

Arguments

sub_mult 109

Examples

```
vec <- c("45/56-/98mm", "45/56-/98mm", "45/56-/98-mm//")
print(str_remove_untl(inpt_v=vec, ptrn_rm_v=c("-", "/"), untl=list(c("max"), c(1))))
#[1] "4556/98mm" "4556/98mm" "4556/98mm//"
print(str_remove_untl(inpt_v=vec, ptrn_rm_v=c("-", "/"), untl=list(c("max"), c(1:2))))
#[1] "455698mm" "455698mm" "455698mm//"
print(str_remove_untl(inpt_v=vec[1], ptrn_rm_v=c("-", "/"), untl=c("max")))
#[1] "455698mm" "455698mm" "455698mm"</pre>
```

sub_mult

sub_mult

Description

Performs a sub operation with n patterns and replacements.

Usage

```
sub_mult(inpt_v, pattern_v = c(), replacement_v = c())
```

Arguments

inpt_v is a vector containing all the elements that contains expressions to be substituted
pattern_v is a vector containing all the patterns to be substituted in any elements of inpt_v
replacement_v

is a vector containing the expression that are going to substituate those provided by pattern_v

110 swipr

```
successive_diff successive_diff
```

Description

Allow to see the difference beteen the suxxessive elements of an numeric vector

Usage

```
successive_diff(inpt_v)
```

Arguments

inpt_v is the input numeric vector

Examples

```
print(successive_diff(c(1:10)))
[1] 1 1 1 1 1
print(successive_diff(c(1:11, 13, 19)))
[1] 1 1 1 1 1 2 6
```

```
swipr swipr
```

Description

Returns an ordered dataframes according to the elements order given. The input datafram has two columns, one with the ids which can be bonded to multiple elements in the other column.

Usage

```
swipr(inpt_datf, how_to = c(), id_w = 2, id_ids = 1)
```

Arguments

inpt_datf	is the input dataframe
how_to	is a vector containing the elements in the order wanted
id_w	is the column number or the column name of the elements
id_ids	is the column number or the column name of the ids

test_order 111

Examples

```
datf <- data.frame("col1"=c("Af", "Al", "Al", "Al", "Arg", "Arg", "Arg", "Arm", "Arm", "A
        "col2"=c("B", "B", "G", "S", "B", "S", "G", "B", "G", "B"))
print(swipr(inpt_datf=datf, how_to=c("G", "S", "B")))
  col1 col2
1
    Af B
2
    Al
          G
3
    Al
          S
4
    Al
          В
5
   Arg
          G
   Arg
7
   Arg
          В
8
   Arm
          G
9
   Arm
          В
10
          В
   Al
```

test_order

test_order

Description

Allow to get if two vectors have their commun elements in the same order, see examples

Usage

```
test_order(inpt_v_from, inpt_v_test)
```

Arguments

the vector we want to test if its commun element with inpt_v_from are in the same order

```
print(test_order(inpt_v_from = c(1:8), inpt_v_test = c(1, 4)))
[1] TRUE
print(test_order(inpt_v_from = c(1:8), inpt_v_test = c(1, 4, 2)))
[1] FALSE
```

112 to_unique

to_unique to_unique

Description

Allow to transform a vector containing elements that have more than 1 occurrence to a vector with only uniques elements.

Usage

```
to_unique(inpt_v, distinct_type = "suffix", distinct_val = "number", sep = "-")
```

Arguments

value) or letter (unique sequence of letters to differenciate each value)

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
                distinct_type = "suffix",
                distinct_val = "number",
                sep = "-"))
[1] "a-1" "a-2" "e" "a-3" "i-1" "i-2"
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
                distinct_type = "suffix",
                distinct_val = "letter",
                sep = "-"))
[1] "a-a" "a-b" "e" "a-c" "i-a" "i-b"
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
                distinct_type = "prefix",
                distinct_val = "number",
                sep = "/"))
[1] "1/a" "2/a" "e"
                      "3/a" "1/i" "2/i"
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
                distinct_type = "prefix",
                distinct_val = "letter",
                sep = "_"))
[1] "a_a" "b_a" "e" "c_a" "a_i" "b_i"
```

union_all 113

union_all

union_all

Description

Allow to perform a union function to n vectors.

Usage

```
union_all(...)
```

Arguments

... are all the input vectors

Examples

```
print(union_all(c(1, 2), c(3, 4), c(1:8)))
[1] 1 2 3 4 5 6 7 8
print(union_all(c(1, 2), c(3, 4), c(7:8)))
[1] 1 2 3 4 7 8
```

union_keep

union_keep

Description

Performs a union operation keeping the number of elements of all input vectors, see examples

Usage

```
union_keep(...)
```

Arguments

... are all the input vectors

```
print(union_keep(c("a", "ee", "ee"), c("p", "p", "a", "i"), c("a", "a", "z")))
[1] "a" "ee" "ee" "p" "p" "i" "z"
print(union_keep(c("a", "ee", "ee"), c("p", "p", "a", "i")))
[1] "a" "ee" "ee" "p" "p" "i"
```

114 unique_datf

unique_	_datf	unique_	_datf
-1			

Description

Returns the input dataframe with the unique columns or rows.

Usage

```
unique_datf(inpt_datf, col = FALSE)
```

Arguments

```
inpt_datf is the input dataframe
col is a parameter that specifies if the dataframe returned should have unique columns
or rows, defaults to F, so the dataframe returned by default has unique rows
```

```
datf1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"))</pre>
print(datf1)
  c.1..2..1..3. c..a...z...a...p.. c.1..2..1..3..1
1
            1
                                а
             2
3
             1
             3
print (unique_datf(inpt_datf=datf1))
   c.1..2..1..3. c..a...z...a...p..
#1
          1
#2
              2
datf1 \leftarrow data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"), c(1, 2, 1, 3))
print(datf1)
  c.1..2..1..3. c..a...z...a...p..
1
       1
2
             2
3
             1
                                  а
print(unique_datf(inpt_datf=datf1, col=TRUE))
# cur_v cur_v
#1
    1 a
      2
#2
#3
      1
#4
      3
```

unique_ltr_from_v 115

```
unique_ltr_from_v
```

Description

Returns the unique characters contained in all the elements from an input vector "inpt_v"

Usage

```
unique_ltr_from_v(inpt_v, keep_v = c("?", "!", ":", "&", ",", ".", letters))
```

Arguments

inpt_v is the input vector containing all the elements

keep_v is the vector containing all the characters that the elements in inpt_v may contain

Examples

```
print(unique_ltr_from_v(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "a
#[1] "b" "o" "n" "j" "u" "r" "l" "p" "e" "c" "a" "v" "i"
```

unique_pos

unique_pos

Description

Allow to find the first index of the unique values from a vector.

Usage

```
unique_pos(vec)
```

Arguments

vec

is the input vector

```
print(unique_pos(vec=c(3, 4, 3, 5, 6)))
#[1] 1 2 4 5
```

116 until_stnl

unique_total

unique_total

Description

Returns a vector with the total amount of occurences for each element in the input vector. The occurences of each element follow the same order as the unique function does, see examples

Usage

```
unique_total(inpt_v = c())
```

Arguments

inpt_v

is the input vector containing all the elements

Examples

```
print (unique_total(inpt_v = c(1:12, 1)))
  [1] 2 1 1 1 1 1 1 1 1 1 1 1

print (unique_total(inpt_v = c(1:12, 1, 11, 11)))
  [1] 2 1 1 1 1 1 1 1 1 1 3 1

vec <- c(1:12, 1, 11, 11)
names(vec) <- c(1:15)
print (unique_total(inpt_v = vec))

1 2 3 4 5 6 7 8 9 10 11 12
2 1 1 1 1 1 1 1 1 3 1</pre>
```

until_stnl

 $until_stnl$

Description

Maxes a vector to a chosen length. ex: if i want my vector c(1, 2) to be 5 of length this function will return me: c(1, 2, 1, 2, 1)

Usage

```
until_stnl(vec1, goal)
```

Arguments

vec1 is the input vector goal is the length to reach

val_replacer 117

Examples

```
print(until_stnl(vec1=c(1, 3, 2), goal=56))
# [1] 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2
```

val_replacer

val_replacer

Description

Allow to replace value from dataframe to another one.

Usage

```
val_replacer(datf, val_replaced, val_replacor = TRUE)
```

Arguments

```
datf is the input dataframe

val_replaced is a vector of the value(s) to be replaced

val_replacor is the value that will replace val_replaced
```

Examples

```
#1 1 NA
#2 004 FALSE
#3 NA NA
#4 FALSE NA
```

vector_replacor

vector_replacor

Description

Allow to replace certain values in a vector.

Usage

```
vector_replacor(inpt_v = c(), sus_val = c(), rpl_val = c(), grep_ = FALSE)
```

118 vec_in_datf

Arguments

inpt_v	is the input vector
sus_val	is a vector containing all the values that will be replaced
rpl_val	is a vector containing the value of the elements to be replaced (sus_val), so sus_val and rpl_val should be the same size
grep_	is if the elements in sus_val should be equal to the elements to replace in inpt_v or if they just should found in the elements

Examples

vec_in_datf vec_in_datf

Description

Allow to get if a vector is in a dataframe. Returns the row and column of the vector in the dataframe if the vector is contained in the dataframe.

Usage

```
vec_in_datf(
  inpt_datf,
  inpt_vec = c(),
  coeff = 0,
  stop_untl = 1,
  conventional = FALSE
)
```

Arguments

inpt_datf is the input dataframe
inpt_vec is the vector that may be in the input dataframe
coeff is the "slope coefficient" of inpt_vec
stop_untl is the maximum number of the input vector the function returns, if in the dataframe
conventional is if a positive slope coefficient means that the vector goes upward or downward

vlookup_datf

Examples

```
datf1 \leftarrow data.frame(c(1:5), c(5:1), c("a", "z", "z", "z", "a"))
print(datf1)
# c.1.5. c.5.1. c..a...z...z...z.........a..
#1
       1
#2
        2
               4
#3
       3
              3
              2
#4
       4
              1
       5
#5
print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 4, "z"), coeff=1))
#NULL
print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=1))
#[1] 5 1
print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(3, "z"), coeff=1))
#[1] 3 2
print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(4, "z"), coeff=-1))
#[1] 2 2
print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(2, 3, "z"), coeff=-1))
#[1] 2 1
print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=-1, conventional=TRUE))
#[1] 5 1
datf1[4, 2] <- 1
print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(1, "z"), coeff=-1, conventional=TRUE, stop_
#[1] 4 2 5 2
```

vlookup_datf

vlookup_datf

Description

Alow to perform a vlookup on a dataframe

Usage

```
vlookup_datf(datf, v_id, col_id = 1, included_col_id = "yes")
```

120 wider_datf

Arguments

```
datf is the input dataframe

v_id is a vector containing the ids

col_id is the column that contains the ids (default is equal to 1)

included_col_id

is if the result should return the col_id (default set to yes)
```

Examples

```
datf1 <- data.frame(c("az1", "az3", "az4", "az2"), c(1:4), c(4:1))</pre>
print(vlookup_datf(datf=datf1, v_id=c("az1", "az2", "az3", "az4")))
    c..az1....az3....az4....az2.. c.1.4. c.4.1.
#2
                               az1
                                       1
#4
                                        4
                                               1
                               az2
#21
                               az3
                                        2
                                               3
#3
                               az4
                                        3
                                               2
```

wider_datf wider_datf

Description

Takes a dataframe as an input and the column to split according to a seprator.

Usage

```
wider_datf(inpt_datf, col_to_splt = c(), sep_ = "-")
```

"k" "11" 2

Arguments

```
inpt_datf is the input dataframe
col_to_splt is a vector containing the number or the colnames of the columns to split according to a separator
sep_ is the separator of the elements to split to new columns in the input dataframe
```

Examples

#k-11 4

wide_to_narrow_idx 121

```
#000-mm 5
              "000" "mm" 1
print(wider_datf(inpt_datf=datf2, col_to_splt=c("col2"), sep_="-"))
       pre_datf X.o. X.y.
              "о" "у"
#о-у
       1
              "hj" "yy"
#hj-yy 2
              "er" "y"
#er-y
      3
#k-11 4
              "k" "11"
              "000" "mm"
#000-mm 5
```

```
wide_to_narrow_idx wide_to_narow_idx
```

Description

Allow to convert the indices of vector ('from_v_ids') which are related to each characters of a vector, to fit the newly established maximum character of the vector, see examples.

Usage

```
wide_to_narrow_idx(from_v_val = c(), from_v_ids = c(), val = 1)
```

Arguments

```
from_v_val is the input vector of elements, or just the total number of characters of the
    elementsq in the vector

from_v_ids is the input vector of indices

val is the value - 1 from which the number of character of an element is too high, so
    the indices in 'from_v_ids' will be modified
```

```
print(wide_to_narrow_idx(from_v_val = c("oui", "no", "oui"), from_v_ids = c(4, 6, 9), val
[1] 2 4 5

print(wide_to_narrow_idx(from_v_val = c("oui", "no", "oui"), from_v_ids = c(4, 6, 9), val
[1] 2 2 3

print(wide_to_narrow_idx(from_v_val = c("oui", "no", "oui"), from_v_ids = c(4, 6, 9), val
[1] 4 6 9
```

122 write_edm_parser

```
write_edm_parser write_edm_parser
```

Description

Allow to write data to edm parsed dataset, see examples

Usage

```
write_edm_parser(inpt, to_write_v, write_data)
```

Arguments

```
inpt is the input dataset
to_write_v is the vector containing the path to write the data, see examples
```

```
print(write_edm_parser("(ok(ee:56)) (ok(oui(rr((rr2:6) (rr:5)))) (oui(bb(rr2:1))) (ee1:4))",
to_write_v = c("ok", "ee"), write_data = c("ii", "olm")))

[1] "(ok(ee:56) (ii:olm)) (ok(oui(rr((rr2:6) (rr:5)))) (oui(bb(rr2:1))) (ee1:4))"

print(write_edm_parser("(ok(ee:56)) (ok(oui(rr((rr2:6) (rr:5)))) (oui(bb(rr2:1))) (ee1:4))",
to_write_v = c("ok", "oui"), write_data = c("ii", "olm")))

[1] "(ok(ee:56)) (ok(oui(rr((rr2:6) (rr:5)))) (ii:olm) (oui(bb(rr2:1))) (ee1:4))"

print(write_edm_parser("(ok(ee:56)) (ok(oui(rr((rr2:6) (rr:5)))) (oui(bb(rr2:1))) (ee1:4))",
to_write_v = c("ok", "oui", "oui"), write_data = c("ii", "olm")))

[1] "(ok(ee:56)) (ok(oui(rr((rr2:6) (rr:5)))) (oui(bb(rr2:1))) (ii:olm) (ee1:4))"

print(write_edm_parser("",
to_write_v = c(), write_data = c("ii", "olm")))

[1] "(ii:olm)"
```

Index

all_stat,4	geo_min,45
any_join_datf,5	get_rec,46
appndr, 7	globe, 46
	glue_groupr_v,47
better_match, 8	grep_all,47
better_split,9	grep_all2,48
better_split_any,9	groupr_datf, 49
better_sub, 10	gsub_mult, 50
better_sub_mult, 11	
better_unique, 12	how_normal, 50
. 10	how_unif,53
can_be_num, 13	
closer_ptrn, 13	id_keepr, 54
closer_ptrn_adv, 16	incr_fillr,55
clusterizer_v,17	infinite_char_seq,56
col_to_row, 20	inner_all,56
colins_datf, 19	insert_datf,57
converter_date, 21	inter_max,60
converter_format, 22	inter_min,61
cost_and_taxes, 22	intersect_all,58
cumulated_rows, 23	intersect_mod, 58
cumulated_rows_na, 24	is_divisible,62
cut_v, 25	isnt_divisible,62
cutr_v, 25	
data con 26	join_n_lvl, 63
data_gen, 26	just_chr,64
data_meshup, 28	just_chr2,65
date_addr, 29	just_nb,65
date_converter_reverse, 30	just_nb2, 66
dcr_untl, 31	leap_yr,66
dcr_val, 32	left_all, 67
depth_pairs_findr, 32	letter_to_nb, 68
diff_datf, 33	
dynamic_idx_convertr, 33	list_files, 68
elements_equalifier, 34	lst_flatnr,69
equalizer_v, 35	match_by,69
extract_normal, 35	multitud, 70
extrt_only_v, 41	marcread, 70
CACIC_OHIY_V, 41	nb2_follow, 71
fillr,42	nb_follow, 71
fixer_nest_v,43	nb_to_letter, 72
fold_rec,43	nest_v, 75
fold_rec2,44	nestr_datf1,73
format_date, 44	nestr_datf2, 74
_	_ , ,

124 INDEX

now ordered 76	wal replacer 117
new_ordered, 76	val_replacer, 117
normal_dens,76	vec_in_datf, 118 vector_replacor, 117
occu, 77	vlookup_datf,119
old_to_new_idx, 77	
pairs_findr,78	<pre>wide_to_narrow_idx, 121 wider_datf, 120</pre>
pairs_findr_merger,78	write_edm_parser,122
pairs_insertr, 80	
pairs_insertr2,81	
paste_datf, 83	
pattern_generator, 83	
pattern_gettr,84	
pattern_tuning, 85	
power_to_char, 86	
pre_to_post_idx, 86	
ptrn_switchr, 87	
ptrn_twkr,87	
r_print,92	
read_edm_parser, 88	
rearangr_v, 89	
regex_spe_detect, 90	
regroupr, 90	
row_to_col, 91	
save_untl,93	
see_datf, 93	
see_diff, 95	
see_diff_all,95	
see_file, 96	
see_idx, 97	
see_inside, 97	
$see_mode, 98$	
selected_char, 99	
sort_date, 99	
sort_normal_qual, 100	
sort_normal_qual2, 104	
split_by_step, 107	
str_remove_untl, 108	
sub_mult, 109	
successive_diff, 110	
swipr, 110	
test_order,111	
to_unique, 112	
union_all, 113	
union_keep, 113	
unique_datf, 114	
unique_ltr_from_v, 115	
unique_pos, 115	
unique_total, 116	
until_stnl, 116	