

# Package ‘edm1’

June 21, 2024

**Title** Simplify Complex Data Manipulation

**Version** 2.0.0.0

**Description** Provides complex sorting algorithms. Provides date manipulation algorithms. In addition to providing handy functions to discretize variables, an SQL joins alternatives, a set of functions to work with geographical coordinates, and other functions to work with text mining.

**License** GPL (==3)

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.1

**Imports** stringr,  
stringi,  
dplyr,  
openxlsx

## Contents

all_stat . . . . .	4
any_join_datf . . . . .	5
appndr . . . . .	7
better_match . . . . .	8
better_split . . . . .	9
better_sub . . . . .	9
better_sub_mult . . . . .	10
better_unique . . . . .	11
can_be_num . . . . .	12
closer_ptrn . . . . .	13
closer_ptrn_adv . . . . .	15
clusterizer_v . . . . .	16
colins_datf . . . . .	19
converter_date . . . . .	20
converter_format . . . . .	21
cost_and_taxes . . . . .	21
cutr_v . . . . .	22
cut_v . . . . .	23
data_gen . . . . .	24
data_meshup . . . . .	26
date_addr . . . . .	27

date_converter_reverse . . . . .	28
dcr_untl . . . . .	29
dcr_val . . . . .	29
depth_pairs_findr . . . . .	30
diff_datf . . . . .	30
elements_equalifier . . . . .	31
equalizer_v . . . . .	32
extract_normal . . . . .	32
extrt_only_v . . . . .	38
fillr . . . . .	39
fixer_nest_v . . . . .	40
fold_rec . . . . .	40
fold_rec2 . . . . .	41
format_date . . . . .	41
geo_min . . . . .	42
get_rec . . . . .	43
globe . . . . .	43
grep_all . . . . .	44
grep_all2 . . . . .	44
groupr_datf . . . . .	45
gsub_mult . . . . .	46
how_normal . . . . .	47
how_unif . . . . .	49
id_keepr . . . . .	50
incr_fillr . . . . .	51
infinite_char_seq . . . . .	52
inner_all . . . . .	53
insert_datf . . . . .	53
intersect_all . . . . .	54
intersect_mod . . . . .	55
inter_max . . . . .	56
inter_min . . . . .	57
isnt_divisible . . . . .	58
is_divisible . . . . .	59
join_n_lvl . . . . .	59
leap_yr . . . . .	60
left_all . . . . .	61
letter_to_nb . . . . .	62
list_files . . . . .	62
lst_flatnr . . . . .	63
match_by . . . . .	63
multitud . . . . .	64
nb2_follow . . . . .	65
nb_follow . . . . .	65
nb_to_letter . . . . .	66
nestr_datf1 . . . . .	67
nestr_datf2 . . . . .	68
nest_v . . . . .	69
new_ordered . . . . .	69
normal_dens . . . . .	70
occu . . . . .	71
old_to_new_idx . . . . .	71

pairs_findr . . . . .	72
pairs_findr_merger . . . . .	72
pairs_insertr . . . . .	74
pairs_insertr2 . . . . .	75
paste_datf . . . . .	77
pattern_generator . . . . .	77
pattern_gettr . . . . .	78
pattern_tuning . . . . .	79
power_to_char . . . . .	80
pre_to_post_idx . . . . .	80
ptrn_switchr . . . . .	81
ptrn_twkr . . . . .	81
rearangr_v . . . . .	82
regex_spe_detect . . . . .	83
regroupr . . . . .	84
r_print . . . . .	85
save_untl . . . . .	85
see_datf . . . . .	86
see_diff . . . . .	88
see_diff_all . . . . .	88
see_file . . . . .	89
see_idx . . . . .	90
see_inside . . . . .	90
see_mode . . . . .	91
selected_char . . . . .	92
sort_date . . . . .	92
sort_normal_qual . . . . .	93
sort_normal_qual2 . . . . .	97
str_remove_untl . . . . .	100
sub_mult . . . . .	101
successive_diff . . . . .	102
swipr . . . . .	102
test_order . . . . .	103
to_unique . . . . .	104
union_all . . . . .	105
union_keep . . . . .	105
unique_datf . . . . .	106
unique_ltr_from_v . . . . .	106
unique_pos . . . . .	107
unique_total . . . . .	107
until_stnl . . . . .	108
val_replacer . . . . .	109
vector_replacor . . . . .	109
vec_in_datf . . . . .	110
vlookup_datf . . . . .	111
wider_datf . . . . .	112

all\_stat

*all\_stat***Description**

Allow to see all the main statistics indicators (mean, median, variance, standard deviation, sum, max, min, quantile) of variables in a dataframe by the modality of a variable in a column of the input datarame. In addition to that, you can get the occurrence of other qualitative variables by your chosen qualitative variable, you have just to precise it in the vector "stat\_var" where all the statistics indicators are given with "occu-var\_you\_want/".

**Usage**

```
all_stat(inpt_v, var_add = c(), stat_var = c(), inpt_datf)
```

**Arguments**

inpt\_v            is the modalities of the variables  
var\_add           is the variables you want to get the stats from  
stat\_var          is the stats indicators you want  
inpt\_datf        is the input dataframe

**Examples**

```
datf <- data.frame("mod"=c("first", "seco", "seco", "first", "first", "third", "first"),
  "var1"=c(11, 22, 21, 22, 22, 11, 9),
  "var2"=c("d", "d", "z", "z", "z", "d", "z"),
  "var3"=c(45, 44, 43, 46, 45, 45, 42),
  "var4"=c("A", "A", "A", "A", "B", "C", "C"))

print(all_stat(inpt_v=c("first", "seco"), var_add = c("var1", "var2", "var3", "var4"),
  stat_var=c("sum", "mean", "median", "sd", "occu-var2/", "occu-var4/", "variance",
"quantile-0.75/"),
  inpt_datf=datf))

#   modal_v var_vector occu sum mean  med standard_devaition      variance
#1    first
#2          var1      64   16 16.5   6.97614984548545 48.66666666666667
#3          var2-d       1
#4          var2-z       3
#5          var3     178 44.5   45   1.73205080756888           3
#6          var4-A       2
#7          var4-B       1
#8          var4-C       1
#9    seco
#10         var1      43 21.5 21.5   0.707106781186548           0.5
#11         var2-d       1
#12         var2-z       1
#13         var3     87 43.5 43.5   0.707106781186548           0.5
#14         var4-A       2
#15         var4-B       0
#16         var4-C       0
#   quantile-0.75
```

```

#1
#2          22
#3
#4
#5          45.25
#6
#7
#8
#9
#10         21.75
#11
#12
#13         43.75
#14
#15
#16

```

---

any_join_datf	<i>any_join_datf</i>
---------------	----------------------

---

## Description

Allow to perform SQL joints with more features

## Usage

```

any_join_datf(
  inpt_datf_l,
  join_type = "inner",
  join_spe = NA,
  id_v = c(),
  excl_col = c(),
  rtn_col = c(),
  d_val = NA
)

```

## Arguments

<code>inpt_datf_l</code>	is a list containing all the dataframe
<code>join_type</code>	is the joint type. Defaults to inner but can be changed to a vector containing all the dataframes you want to take their ids to don external joints.
<code>join_spe</code>	can be equal to a vector to do an external joints on all the dataframes. In this case, <code>join_type</code> should not be equal to "inner"
<code>id_v</code>	is a vector containing all the ids name of the dataframes. The ids names can be changed to number of their columns taking in count their position in <code>inpt_datf_l</code> . It means that if my id is in the third column of the second dataframe and the first dataframe have 5 columns, the column number of the ids is $5 + 3 = 8$
<code>excl_col</code>	is a vector containing the column names to exclude, if this vector is filled so "rtn_col" should not be filled. You can also put the column number in the manner indicated for "id_v". Defaults to <code>c()</code>

`rtn_col` is a vector containing the column names to retain, if this vector is filled so `"excl_col"` should not be filled. You can also put the column number in the manner indicated for `"id_v"`. Defaults to `c()`

`d_val` is the default val when here is no match

### Examples

```
datf1 <- data.frame("val"=c(1, 1, 2, 4), "ids"=c("e", "a", "z", "a"),
  "last"=c("oui", "oui", "non", "oui"),
  "second_ids"=c(13, 11, 12, 8), "third_col"=c(4:1))

datf2 <- data.frame("val"=c(3, 7, 2, 4, 1, 2), "ids"=c("a", "z", "z", "a", "a", "a"),
  "bool"=c(TRUE, FALSE, FALSE, FALSE, TRUE, TRUE),
  "second_ids"=c(13, 12, 8, 34, 22, 12))

datf3 <- data.frame("val"=c(1, 9, 2, 4), "ids"=c("a", "a", "z", "a"),
  "last"=c("oui", "oui", "non", "oui"),
  "second_ids"=c(13, 11, 12, 8))

print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type="inner",
  id_v=c("ids", "second_ids"),
  excl_col=c(), rtn_col=c()))

# ids val ids last second_ids val ids bool second_ids val ids last second_ids
#3 z12 2 z non 12 7 z FALSE 12 2 z non 12

print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type="inner", id_v=c("ids",
  excl_col=c(), rtn_col=c()))

# ids val ids last second_ids val ids bool second_ids val ids last second_ids
#2 a 1 a oui 11 3 a TRUE 13 1 a oui 13
#3 z 2 z non 12 7 z FALSE 12 2 z non 12
#4 a 4 a oui 8 4 a FALSE 34 9 a oui 11

print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type=c(1), id_v=c("ids"),
  excl_col=c(), rtn_col=c()))

# ids val ids last second_ids val ids bool second_ids val ids last
#1 e 1 e oui 13 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#2 a 1 a oui 11 3 a TRUE 13 1 a oui
#3 z 2 z non 12 7 z FALSE 12 2 z non
#4 a 4 a oui 8 4 a FALSE 34 9 a oui
# second_ids
#1 <NA>
#2 13
#3 12
#4 11

print(any_join_datf(inpt_datf_l=list(datf2, datf1, datf3), join_type=c(1, 3),
  id_v=c("ids", "second_ids"),
  excl_col=c(), rtn_col=c()))

# ids val ids bool second_ids val ids last second_ids val ids last
#1 a13 3 a TRUE 13 <NA> <NA> <NA> <NA> 1 a oui
#2 z12 7 z FALSE 12 2 z non 12 2 z non
#3 z8 2 z FALSE 8 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#4 a34 4 a FALSE 34 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
```

```
#5 a22 1 a TRUE 22 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#6 a12 2 a TRUE 12 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#7 a13 <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#8 a11 <NA> <NA> <NA> <NA> 1 a oui 11 9 a oui
#9 z12 <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#10 a8 <NA> <NA> <NA> <NA> 4 a oui 8 4 a oui
# second_ids
#1 13
#2 12
#3 <NA>
#4 <NA>
#5 <NA>
#6 <NA>
#7 <NA>
#8 11
#9 <NA>
#10 8

print(any_join_datf(inpt_datf_l=list(datf1, datf2, datf3), join_type=c(1), id_v=c("ids"),
                    excl_col=c(), rtn_col=c()))

#ids val ids last second_ids val ids bool second_ids val ids last
#1 e 1 e oui 13 <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#2 a 1 a oui 11 3 a TRUE 13 1 a oui
#3 z 2 z non 12 7 z FALSE 12 2 z non
#4 a 4 a oui 8 4 a FALSE 34 9 a oui
# second_ids
#1 <NA>
#2 13
#3 12
#4 11
```

---

appndr	<i>appndr</i>
--------	---------------

---

**Description**

Append to a vector "inpt\_v" a special value "val" n times "mmn". The appending begins at "strt" index.

**Usage**

```
appndr(inpt_v, val = NA, hmn, strt = "max")
```

**Arguments**

- inpt\_v is the input vector
- val is the special value
- hmn is the number of special value element added
- strt is the index from which appending begins, defaults to max which means the end of "inpt\_v"

**Examples**

```
print(appndr(inpt_v=c(1:3), val="oui", hmn=5))

#[1] "1"    "2"    "3"    "oui" "oui" "oui" "oui" "oui"

print(appndr(inpt_v=c(1:3), val="oui", hmn=5, strt=1))

#[1] "1"    "oui" "oui" "oui" "oui" "oui" "2"    "3"
```

---

better_match	<i>better_match</i>
--------------	---------------------

---

**Description**

Allow to get the nth element matched in a vector

**Usage**

```
better_match(inpt_v = c(), ptrn, until = 1, nvr_here = NA)
```

**Arguments**

inpt_v	is the input vector
ptrn	is the pattern to be matched
until	is the maximum number of matched pattern outputed
nvr_here	is a value you are sure is not present in inpt_v

**Examples**

```
print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=1))

#[1] 3

print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=3, until=5))

#[1] 3 13 16

print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=c(3, 4), until=5))

[1] 3 13 16 4 14

print(better_match(inpt_v=c(1:12, 3, 4, 33, 3), ptrn=c(3, 4), until=c(1, 5)))

[1] 3 4 14
```



---

better_split	<i>better_split</i>
--------------	---------------------

---

### Description

Allows to split a string by multiple split, returns a vector and not a list.

### Usage

```
better_split(inpt, split_v = c())
```

### Arguments

inpt	is the input character
split_v	is the vector containing the splits

### Examples

```
print(better_split(inpt = "o-u_i", split_v = c("-")))
[1] "o"    "u_i"

print(better_split(inpt = "o-u_i", split_v = c("-", "_")))
[1] "o" "u" "i"
```

---

better_sub	<i>better_sub</i>
------------	-------------------

---

### Description

Allow to perform a sub operation to a given number of matched patterns, see examples

### Usage

```
better_sub(inpt_v = c(), pattern, replacement, untl_v = c())
```

### Arguments

inpt_v	is a vector containing all the elements that contains expressions to be substituted
pattern	is the expression that will be substituted
replacement	is the expression that will substitute pattern
untl_v	is a vector containing, for each element of inpt_v, the number of pattern that will be substituted

**Examples**

```
print(better_sub(inpt_v = c("yes NAME, i will call NAME and NAME",
                           "yes NAME, i will call NAME and NAME"),
          pattern = "NAME",
          replacement = "Kevin",
          until = c(2)))

[1] "yes Kevin, i will call Kevin and NAME"
[2] "yes Kevin, i will call Kevin and NAME"

print(better_sub(inpt_v = c("yes NAME, i will call NAME and NAME",
                           "yes NAME, i will call NAME and NAME"),
          pattern = "NAME",
          replacement = "Kevin",
          until = c(2, 3)))

[1] "yes Kevin, i will call Kevin and NAME"
[2] "yes Kevin, i will call Kevin and Kevin"

print(better_sub(inpt_v = c("yes NAME, i will call NAME and NAME",
                           "yes NAME, i will call NAME and NAME"),
          pattern = "NAME",
          replacement = "Kevin",
          until = c("max", 3)))

[1] "yes Kevin, i will call Kevin and Kevin"
[2] "yes Kevin, i will call Kevin and Kevin"
```

---

better_sub_mult	<i>better_sub_mult</i>
-----------------	------------------------

---

**Description**

Allow to perform a sub\_mult operation to a given number of matched patterns, see examples

**Usage**

```
better_sub_mult(
  inpt_v = c(),
  pattern_v = c(),
  replacement_v = c(),
  until_v = c()
)
```

**Arguments**

inpt_v	is a vector containing all the elements that contains expressions to be substituted
pattern_v	is a vector containing all the patterns to be substituted in any elements of inpt_v
replacement_v	is a vector containing the expression that are going to substitute those provided by pattern_v
until_v	is a vector containing, for each element of inpt_v, the number of pattern that will be substituted

**Examples**

```
print(better_sub_mult(inpt_v = c("yes NAME, i will call NAME and NAME2",
                                "yes NAME, i will call NAME and NAME2, especially NAME2"),
                    pattern_v = c("NAME", "NAME2"),
                    replacement_v = c("Kevin", "Paul"),
                    until = c(1, 3)))

[1] "yes Kevin, i will call NAME and Paul"
[2] "yes Kevin, i will call NAME and Paul, especially Paul"

print(better_sub_mult(inpt_v = c("yes NAME, i will call NAME and NAME2",
                                "yes NAME, i will call NAME and NAME2, especially NAME2"),
                    pattern_v = c("NAME", "NAME2"),
                    replacement_v = c("Kevin", "Paul"),
                    until = c("max", 3)))

[1] "yes Kevin, i will call Kevin and Kevin2"
[2] "yes Kevin, i will call Kevin and Kevin2, especially Kevin2"
```

---

better_unique	<i>better_unique</i>
---------------	----------------------

---

**Description**

Returns the element that are not unique from the input vector

**Usage**

```
better_unique(inpt_v, occu = ">-1-")
```

**Arguments**

inpt_v	is the input vector containing the elements
occu	is a parameter that specifies the occurrence of the elements that must be returned, defaults to ">-1-" it means that the function will return all the elements that are present more than one time in inpt_v. The syntax is the following "comparaison_type-actual_value-". The comparaison type may be "==" or ">" or "<". Occu can also be a vector containing all the occurrence that must have the elements to be returned.

**Examples**

```
print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non")))

#[1] "oui" "non"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu="=")

#[1] "oui"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=">")
```

```

#[1] "non"

print(better_unique(inpt_v=c("oui", "oui", "non", "non", "peut", "peut1", "non"), occu=c

#[1] "non"      "peut"      "peut1"

print(better_unique(inpt_v = c("a", "b", "c", "c"), occu = "=="-1-"))

[1] "a" "b"

print(better_unique(inpt_v = c("a", "b", "c", "c"), occu = "<-2-"))

[1] "a" "b"

```

---

can\_be\_num

---

*can\_be\_num*


---

## Description

Return TRUE if a variable can be converted to a number and FALSE if not (supports float)

## Usage

```
can_be_num(x)
```

## Arguments

x is the input value

## Examples

```

print(can_be_num("34.677"))

#[1] TRUE

print(can_be_num("34"))

#[1] TRUE

print(can_be_num("3rt4"))

#[1] FALSE

print(can_be_num(34))

#[1] TRUE

```

---

closer_ptrn	<i>closer_ptrn</i>
-------------	--------------------

---

## Description

Take a vector of patterns as input and output each chosen word with their closest patterns from chosen patterns.

## Usage

```
closer_ptrn(
  inpt_v,
  base_v = c("?", letters),
  excl_v = c(),
  rtn_v = c(),
  sub_excl_v = c(),
  sub_rtn_v = c()
)
```

## Arguments

<code>inpt_v</code>	is the input vector containing all the patterns
<code>base_v</code>	must contain all the characters that the patterns are susceptible to contain, defaults to <code>c("?", letters)</code> . "?" is necessary because it is internally the default value added to each element that does not have a sufficient length compared to the longest pattern in <code>inpt_v</code> . If set to NA, the function will find by itself the elements to be filled with but it may take an extra time
<code>excl_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to exclude for comparing them to others patterns. If this parameter is filled, so <code>"rtn_v"</code> must be empty.
<code>rtn_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to keep for comparing them to others patterns. If this parameter is filled, so <code>"rtn_v"</code> must be empty.
<code>sub_excl_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to exclude for using them to compare to another pattern. If this parameter is filled, so <code>"sub_rtn_v"</code> must be empty.
<code>sub_rtn_v</code>	is the vector containing all the patterns from <code>inpt_v</code> to retain for using them to compare to another pattern. If this parameter is filled, so <code>"sub_excl_v"</code> must be empty.

## Examples

```
print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir")
# [[1]]
# [1] "bonjour"
#
# [[2]]
# [1] "lpoerc"    "nonnour"   "bonnour"   "nonjour"   "aurevoir"
#
# [[3]]
# [1] 1 1 2 7 8
```

```

#
#[[4]]
#[1] "lpoerc"
#
#[[5]]
#[1] "bonjour" "nonnour" "bonnour" "nonjour" "aurevoir"
#
#[[6]]
#[1] 7 7 7 7 7
#
#[[7]]
#[1] "nonnour"
#
#[[8]]
#[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"
#
#[[9]]
#[1] 1 1 2 7 8
#
#[[10]]
#[1] "bonnour"
#
#[[11]]
#[1] "bonjour" "lpoerc" "nonnour" "nonjour" "aurevoir"
#
#[[12]]
#[1] 1 1 2 7 8
#
#[[13]]
#[1] "nonjour"
#
#[[14]]
#[1] "bonjour" "lpoerc" "nonnour" "bonnour" "aurevoir"
#
#[[15]]
#[1] 1 1 2 7 8
#
#[[16]]
#[1] "aurevoir"
#
#[[17]]
#[1] "bonjour" "lpoerc" "nonnour" "bonnour" "nonjour"
#
#[[18]]
#[1] 7 8 8 8 8

print(closer_ptrn(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "aurevoir"),
excl_v=c("nonnour", "nonjour"),
      sub_excl_v=c("nonnour")))

#[1] 3 5
#[[1]]
#[1] "bonjour"
#
#[[2]]
#[1] "lpoerc" "bonnour" "nonjour" "aurevoir"
#

```

```

#[[3]]
#[1] 1 1 7 8
#
#[[4]]
#[1] "lpoerc"
#
#[[5]]
#[1] "bonjour" "bonnour" "nonjour" "aurevoir"
#
#[[6]]
#[1] 7 7 7 7
#
#[[7]]
#[1] "bonnour"
#
#[[8]]
#[1] "bonjour" "lpoerc" "bonnour" "nonjour" "aurevoir"
#
#[[9]]
#[1] 0 1 2 7 8
#
#[[10]]
#[1] "aurevoir"
#
#[[11]]
#[1] "bonjour" "lpoerc" "nonjour" "aurevoir"
#
#[[12]]
#[1] 0 7 8 8

```

---

closer_ptrn_adv	<i>closer_ptrn_adv</i>
-----------------	------------------------

---

## Description

Allow to find how patterns are far or near between each other relatively to a vector containing characters at each index ("base\_v"). The function gets the sum of the indexes of each pattern letter relatively to the characters in base\_v. So each pattern can be compared.

## Usage

```

closer_ptrn_adv(
  inpt_v,
  res = "raw_stat",
  default_val = "?",
  base_v = c(default_val, letters),
  c_word = NA
)

```

## Arguments

`inpt_v` is the input vector containing all the patterns to be analyzed

res	is a parameter controlling the result. If set to "raw_stat", each word in inpt_v will come with its score (indexes of its letters relatively to base_v). If set to something else, so "c_word" parameter must be filled.
default_val	is the value that will be added to all patterns that do not equal the length of the longest pattern in inpt_v. Those get this value added to make all patterns equal in length so they can be compared, defaults to "?"
base_v	is the vector from which all pattern get its result (letters indexes for each pattern relatively to base_v), defaults to c("default_val", letters). "default_val" is another parameter and letters is all the western alphabetic letters in a vector
c_word	is a pattern from which the nearest to the farrest pattern in inpt_v will be compared

### Examples

```
print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois", "bonjour"),
  res="word", c_word="bonjour"))

#[[1]]
#[1] 1 5 15 17 38 65
#
#[[2]]
#[1] "bonjour" "bonnour" "aurevoir" "nonnour" "mois" "fin"

print(closer_ptrn_adv(inpt_v=c("aurevoir", "bonnour", "nonnour", "fin", "mois")))

#[[1]]
#[1] 117 107 119 37 64
#
#[[2]]
#[1] "aurevoir" "bonnour" "nonnour" "fin" "mois"
```

---

clusterizer\_v

clusterizer\_v

---

### Description

Allow to output clusters of elements. Takes as input a vector "inpt\_v" containing a sequence of number. Can also take another vector "w\_v" that has the same size of inpt\_v because its elements are related to it. The way the clusters are made is related to an accuracy value which is "c\_val". It means that if the difference between the values associated to 2 elements is superior to c\_val, these two elements are in distinct clusters. The second element of the outputed list is the begin and end value of each cluster.

### Usage

```
clusterizer_v(inpt_v, w_v = NA, c_val)
```

### Arguments

inpt_v	is the vector containing the sequence of number
w_v	is the vector containing the elements related to inpt_v, defaults to NA
c_val	is the accuracy of the clusterization



**Examples**

```

print(clusterizer_v(inpt_v=sample.int(20, 26, replace=TRUE), w_v=NA, c_val=0.9))

# [[1]]
# [[1]][[1]]
# [1] 1
#
# [[1]][[2]]
# [1] 2
#
# [[1]][[3]]
# [1] 3
#
# [[1]][[4]]
# [1] 4
#
# [[1]][[5]]
# [1] 5 5
#
# [[1]][[6]]
# [1] 6 6 6 6
#
# [[1]][[7]]
# [1] 7 7 7
#
# [[1]][[8]]
# [1] 8 8 8
#
# [[1]][[9]]
# [1] 9
#
# [[1]][[10]]
# [1] 10
#
# [[1]][[11]]
# [1] 12
#
# [[1]][[12]]
# [1] 13 13 13
#
# [[1]][[13]]
# [1] 18 18 18
#
# [[1]][[14]]
# [1] 20
#
#
# [[2]]
# [1] "1" "1" "-" "2" "2" "-" "3" "3" "-" "4" "4" "-" "5" "5" "-"
# [16] "6" "6" "-" "7" "7" "-" "8" "8" "-" "9" "9" "-" "10" "10" "-"
# [31] "12" "12" "-" "13" "13" "-" "18" "18" "-" "20" "20"

print(clusterizer_v(inpt_v=sample.int(40, 26, replace=TRUE), w_v=letters, c_val=0.29))

# [[1]]
# [[1]][[1]]

```

```

#[1] "a"
#
#[[1]][[2]]
#[1] "b"
#
#[[1]][[3]]
#[1] "c" "d"
#
#[[1]][[4]]
#[1] "e" "f"
#
#[[1]][[5]]
#[1] "g" "h" "i" "j"
#
#[[1]][[6]]
#[1] "k"
#
#[[1]][[7]]
#[1] "l"
#
#[[1]][[8]]
#[1] "m" "n"
#
#[[1]][[9]]
#[1] "o"
#
#[[1]][[10]]
#[1] "p"
#
#[[1]][[11]]
#[1] "q" "r"
#
#[[1]][[12]]
#[1] "s" "t" "u"
#
#[[1]][[13]]
#[1] "v"
#
#[[1]][[14]]
#[1] "w"
#
#[[1]][[15]]
#[1] "x"
#
#[[1]][[16]]
#[1] "y"
#
#[[1]][[17]]
#[1] "z"
#
#
#[[2]]
# [1] "13" "13" "-" "14" "14" "-" "15" "15" "-" "16" "16" "-" "17" "17" "-"
#[16] "19" "19" "-" "21" "21" "-" "22" "22" "-" "23" "23" "-" "25" "25" "-"
#[31] "27" "27" "-" "29" "29" "-" "30" "30" "-" "31" "31" "-" "34" "34" "-"
#[46] "35" "35" "-" "37" "37"

```

---

colins_datf	<i>colins_datf</i>
-------------	--------------------

---

## Description

Allow to insert vectors into a dataframe.

## Usage

```
colins_datf(inpt_datf, target_col = list(), target_pos = list())
```

## Arguments

inpt_datf	is the dataframe where vectors will be inserted
target_col	is a list containing all the vectors to be inserted
target_pos	is a list containing the vectors made of the columns names or numbers where the associated vectors from target_col will be inserted after

## Examples

```
datf1 <- data.frame("frst_col"=c(1:5), "scd_col"=c(5:1))

print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
  c("u", "z", "z", "z", "u")),
  target_pos=list(c("frst_col", "scd_col"), c("scd_col"))))

#  frst_col cur_col scd_col cur_col.1 cur_col
#1      1      oui      5      oui      u
#2      2      oui      4      oui      z
#3      3      oui      3      oui      z
#4      4      non      2      non      z
#5      5      non      1      non      u

print(colins_datf(inpt_datf=datf1, target_col=list(c("oui", "oui", "oui", "non", "non"),
  c("u", "z", "z", "z", "u")),
  target_pos=list(c(1, 2), c("frst_col"))))

#  frst_col cur_col scd_col cur_col cur_col
#1      1      oui      5      u      oui
#2      2      oui      4      z      oui
#3      3      oui      3      z      oui
#4      4      non      2      z      non
#5      5      non      1      u      non
```

---

converter_date	<i>converter_date</i>
----------------	-----------------------

---

**Description**

Allow to convert any date like second/minute/hour/day/month/year to either second, minute...year. The input date should not necessarily have all its time units (second, minute...) but all the time units according to a format. Example: "snhdmy" is for second, hour, minute, day, month, year. And "mdy" is for month, day, year.

**Usage**

```
converter_date(inpt_date, convert_to, frmt = "snhdmy", sep_ = "-")
```

**Arguments**

- inpt\_date is the input date
- convert\_to is the time unit the input date will be converted ("s", "n", "h", "d", "m", "y")
- frmt is the format of the input date
- sep\_ is the separator of the input date. For example this input date "12-07-2012" has "-" as a separator

**Examples**

```
print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="m"))
#[1] 24299.15

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="y"))
#[1] 2024.929

print(converter_date(inpt_date="14-04-11-2024", sep_="-", frmt="hdmy", convert_to="s"))
#[1] 63900626400

print(converter_date(inpt_date="63900626400", sep_="-", frmt="s", convert_to="y"))
#[1] 2024.929

print(converter_date(inpt_date="2024", sep_="-", frmt="y", convert_to="s"))
#[1] 63873964800
```

---

converter_format	<i>converter_format</i>
------------------	-------------------------

---

### Description

Allow to convert a format to another

### Usage

```
converter_format(inpt_val, sep_ = "-", inpt_frmt, frmt, default_val = "00")
```

### Arguments

inpt_val	is the input value that is linked to the format
sep_	is the separator of the value in inpt_val
inpt_frmt	is the format of the input value
frmt	is the format you want to convert to
default_val	is the default value given to the units that are not present in the input format

### Examples

```
print(converter_format(inpt_val="23-12-05-1567", sep_="-",
                      inpt_frmt="shmy", frmt="snhdmy", default_val="00"))

#[1] "23-00-12-00-05-1567"

print(converter_format(inpt_val="23-12-05-1567", sep_="-",
                      inpt_frmt="shmy", frmt="Pnhdmy", default_val="00"))

#[1] "00-00-12-00-05-1567"
```

---

cost_and_taxes	<i>cost_and_taxes</i>
----------------	-----------------------

---

### Description

Allow to calculate basic variables related to cost and taxes from a bunch of products (elements). So put every variable you know in the following order:

### Usage

```
cost_and_taxes(
  qte = NA,
  pu = NA,
  prix_ht = NA,
  tva = NA,
  prix_ttc = NA,
  prix_tva = NA,
```

```

    pu_ttc = NA,
    adjust = NA,
    prix_d_ht = NA,
    prix_d_ttc = NA,
    pu_d = NA,
    pu_d_ttc = NA
  )

```

### Arguments

qte	is the quantity of elements
pu	is the price of a single elements without taxes
prix_ht	is the duty-free price of the whole set of elements
tva	is the percentage of all taxes
prix_ttc	is the price of all the elements with taxes
prix_tva	is the cost of all the taxes
pu_ttc	is the price of a single element taxes included
adjust	is the discount percentage
prix_d_ht	is the free-duty price of an element after discount
prix_d_ttc	is the price with taxes of an element after discount
pu_d	is the price of a single element after discount and without taxes
pu_d_ttc	is the free-duty price of a single element after discount

### Examples

```

print(cost_and_taxes(pu=45, prix_ttc=2111, qte=23))

# [1] 23.000000 45.000000 45.000000 1.039614 2111.000000 1076.000000
# [7] 45.000000 NA NA NA NA NA

```

---

cutr\_v

*cutr\_v*

---

### Description

Allow to reduce all the elements in a vector to a defined size of nchar

### Usage

```
cutr_v(inpt_v, until = "min")
```

### Arguments

inpt_v	is the input vector
until	is the maximum size of nchar authorized by an element, defaults to "min", it means the shortest element in the list

**Examples**

```
test_v <- c("oui", "nonon", "ez", "aa", "a", "dsfsdsds")

print(cutr_v(inpt_v=test_v, until="min"))

#[1] "o" "n" "e" "a" "a" "d"

print(cutr_v(inpt_v=test_v, until=3))

#[1] "oui" "non" "ez" "aa" "a" "dsf"
```

---

cut\_v

---

*cut\_v*


---

**Description**

Allow to convert a vector to a dataframe according to a separator.

**Usage**

```
cut_v(inpt_v, sep_ = "")
```

**Arguments**

inpt_v	is the input vector
sep_	is the separator of the elements in inpt_v, defaults to ""

**Examples**

```
print(cut_v(inpt_v=c("oui", "non", "oui", "non")))

#      X.o. X.u. X.i.
#oui "o" "u" "i"
#non "n" "o" "n"
#oui "o" "u" "i"
#non "n" "o" "n"

print(cut_v(inpt_v=c("ou-i", "n-on", "ou-i", "n-on"), sep_="-"))

#      X.ou. X.i.
#ou-i "ou" "i"
#n-on "n" "on"
#ou-i "ou" "i"
#n-on "n" "on"
```

data\_gen

*data\_gen***Description**

Allo to generate in a csv all kind of data you can imagine according to what you provide

**Usage**

```
data_gen(
  type_ = c("number", "mixed", "string"),
  strt_l = c(0, 0, 10),
  nb_r = c(50, 10, 40),
  output = NA,
  properties = c("1-5", "1-5", "1-5"),
  type_distri = c("random", "random", "random"),
  str_source = c("a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m",
    "o", "p", "q", "r", "s", "t", "u", "w", "x", "y", "z"),
  round_l = c(0, 0, 0),
  sep_ = ",",
)
```

**Arguments**

type_	is a vector. Its arguments designates a column, a column can be made of numbers ("number"), string ("string") or both ("mixed")
strt_l	is a vector containing for each column the row from which the data will begin to be generated
nb_r	is a vector containing for each column, the number of row full from generated data
output	is the name of the output csv file, defaults to NA so no csv will be outputted by default
properties	is linked to type_distri because it is the parameters ("min_val-max_val") for "random type", ("u-x") for the poisson distribution, ("u-d") for gaussian distribution
type_distri	is a vector which, for each column, associate a type of distribution ("random", "poisson", "gaussian"), it means that not only the number but also the length of the string will be randomly generated according to these distribution laws
str_source	is the source (vector) from which the character creating random string are (default set to the occidental alphabet)
round_l	is a vector which, for each column containing number, associate a round value, if the type of the value is numeric
sep_	is the separator used to write data in the csv

**Value**

new generated data in addition to saving it in the output



**Examples**

```

print(data_gen())

#   X1   X2   X3
#1   4    2 <NA>
#2   2    4 <NA>
#3   5    2 <NA>
#4   2 abcd <NA>
#5   4 abcd <NA>
#6   2    4 <NA>
#7   2  abc <NA>
#8   4  abc <NA>
#9   4    3 <NA>
#10  4  abc abcd
#11  5 <NA>  abc
#12  4 <NA>  abc
#13  1 <NA>   ab
#14  1 <NA> abcde
#15  2 <NA>  abc
#16  4 <NA>    a
#17  1 <NA>  abcd
#18  4 <NA>   ab
#19  2 <NA>  abcd
#20  3 <NA>   ab
#21  3 <NA>  abcd
#22  2 <NA>    a
#23  4 <NA>  abc
#24  1 <NA>  abcd
#25  4 <NA>  abc
#26  4 <NA>   ab
#27  2 <NA>  abc
#28  5 <NA>   ab
#29  3 <NA>  abc
#30  5 <NA>  abcd
#31  2 <NA>  abc
#32  2 <NA>  abc
#33  1 <NA>   ab
#34  5 <NA>    a
#35  4 <NA>   ab
#36  1 <NA>   ab
#37  1 <NA> abcde
#38  5 <NA>  abc
#39  4 <NA>   ab
#40  5 <NA> abcde
#41  2 <NA>   ab
#42  3 <NA>   ab
#43  2 <NA>   ab
#44  4 <NA>  abcd
#45  5 <NA>  abcd
#46  3 <NA>  abcd
#47  2 <NA>  abcd
#48  3 <NA>  abcd
#49  3 <NA>  abcd
#50  4 <NA>    a

print(data_gen(strt_l=c(0, 0, 0), nb_r=c(5, 5, 5)))

```

```
# X1    X2    X3
#1  2      a  abc
#2  3 abcde   ab
#3  4 abcde    a
#4  1      3  abc
#5  3      a abcd
```

---

data\_mesgup

*data\_mesgup*


---

## Description

Allow to automatically arrange 1 dimensional data according to vector and parameters

## Usage

```
data_mesgup(
  data,
  cols = NA,
  file_ = NA,
  sep_ = ";",
  organisation = c(2, 1, 0),
  unic_sep1 = "_",
  unic_sep2 = "-"
)
```

## Arguments

data	is the data provided (vector) each column is separated by a unic separator and each dataset from the same column is separated by another unic separator (ex: <code>c("", c("d", "-", "e", "-", "f"), "", c("a", "a1", "-", "b", "-", "c", "c1"), "_")</code> )
cols	are the colnames of the data generated in a csv
file_	is the file to which the data will be outputed, defaults to NA which means that the functio will return the dataframe generated and won't write it to a csv file
sep_	is the separator of the csv outputed
organisation	is the way variables include themselves, for instance ,resuming precedent example, if organisation=c(1, 0) so the data output will be: d, a d, a1 e, c f, c f, c1
unic_sep1	is the unic separator between variables (default is "_")
unic_sep2	is the unic separator between datasets (default is "-")

## Examples

```
print(data_mesgup(data=c("_", c("-", "d", "-", "e", "-", "f"), "_",
  c("-", "a", "a1", "-", "B", "r", "uy", "-", "c", "c1"), "_"), organisation=c(1, 0)))

# X1 X2
#1 d a
#2 d a1
#3 e B
```

```
#4 e r
#5 e uy
#6 f c
#7 f c1
```

---

date_addr	<i>date_addr</i>
-----------	------------------

---

**Description**

Allow to add or subtract two dates that have the same time unit or not

**Usage**

```
date_addr(  
  date1,  
  date2,  
  add = FALSE,  
  frmt1,  
  frmt2 = frmt1,  
  sep_ = "-",  
  convert_to = "dmy"  
)
```

**Arguments**

- date1 is the date from which the second date will be added or subtracted
- date2 is the date that will be added or will subtract date1
- add equals to FALSE if you want date1 - date2 and TRUE if you want date1 + date2
- frmt1 is the format of date1 (snhdmy) (second, minute, hour, day, monthn year)
- frmt2 is the format of date2 (snhdmy)
- sep\_ is the separator of date1 and date2
- convert\_to is the format of the outputed date

**Examples**

```
print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",  
  convert_to="dmy"))  
  
#[1] "18-2-0"  
  
print(date_addr(date1="25-02", date2="58-12-08", frmt1="dm", frmt2="shd", sep_="-",  
  convert_to="dmy", add=TRUE))  
  
#[1] "3-3-0"  
  
print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",  
  convert_to="dmy", add=TRUE))  
  
#[1] "27-3-2024"
```

```

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="dmy", add=False))

#[1] "23-1-2024"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="n", add=False))

#[1] "1064596320"

print(date_addr(date1="25-02-2024", date2="1-01", frmt1="dmy", frmt2="dm", sep_="-",
               convert_to="s", add=False))

#[1] "63875779200"

```

---

```

date_converter_reverse
      date_converter_reverse

```

---

## Description

Allow to convert single date value like 2025.36 year to a date like second/minutehour/day/month/year (snhdmy)

## Usage

```
date_converter_reverse(inpt_date, convert_to = "dmy", frmt = "y", sep_ = "-")
```

## Arguments

inpt_date	is the input date
convert_to	is the date format the input date will be converted
frmt	is the time unit of the input date
sep_	is the separator of the outputed date

## Examples

```

print(date_converter_reverse(inpt_date="2024.929", convert_to="hmy", frmt="y", sep_="-"))

#[1] "110-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dmy", frmt="y", sep_="-"))

#[1] "4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="hdmy", frmt="y", sep_="-"))

#[1] "14-4-11-2024"

print(date_converter_reverse(inpt_date="2024.929", convert_to="dhym", frmt="y", sep_="-"))

```

```
#[1] "4-14-2024-11"
```

---

<i>dcr_untl</i>	<i>dcr_untl</i>
-----------------	-----------------

---

**Description**

Allow to get the final value of a incremental or decremental loop.

**Usage**

```
dcr_untl(strt_val, cr_val, stop_val = 0)
```

**Arguments**

- strt\_val is the start value
- cr\_val is the incremental (or decremental value)
- stop\_val is the value where the loop has to stop

**Examples**

```
print(dcr_untl(strt_val=50, cr_val=-5, stop_val=5))  
#[1] 9  
  
print(dcr_untl(strt_val=50, cr_val=5, stop_val=450))  
#[1] 80
```

---

<i>dcr_val</i>	<i>dcr_val</i>
----------------	----------------

---

**Description**

Allow to get the end value after an incremental (or decremental loop)

**Usage**

```
dcr_val(strt_val, cr_val, stop_val = 0)
```

**Arguments**

- strt\_val is the start value
- cr\_val is the incremental or decremental value
- stop\_val is the value the loop has to stop

**Examples**

```
print(dcr_val(strt_val=50, cr_val=-5, stop_val=5))

#[1] 5

print(dcr_val(strt_val=47, cr_val=-5, stop_val=5))

#[1] 7

print(dcr_val(strt_val=50, cr_val=5, stop_val=450))

#[1] 450

print(dcr_val(strt_val=53, cr_val=5, stop_val=450))

#[1] 448
```

---

depth\_pairs\_findr    *depth\_pairs\_findr*

---

**Description**

Takes the pair vector as an input and associate to each pair a level of depth, see examples

**Usage**

```
depth_pairs_findr(inpt)
```

**Arguments**

inpt                      is the pair vector

**Examples**

```
print(depth_pairs_findr(c(1, 1, 2, 3, 3, 4, 4, 2, 5, 6, 7, 7, 6, 5)))

[1] 1 1 1 2 2 2 2 1 1 2 3 3 2 1
```

---

diff\_datf                      *diff\_datf*

---

**Description**

Returns a vector with the coordinates of the cell that are not equal between 2 dataframes (row, column).

**Usage**

```
diff_datf(datf1, datf2)
```

**Arguments**

datf1            is an an input dataframe  
 datf2            is an an input dataframe

**Examples**

```
datf1 <- data.frame(c(1:6), c("oui", "oui", "oui", "oui", "oui", "oui"), c(6:1))
datf2 <- data.frame(c(1:7), c("oui", "oui", "oui", "oui", "non", "oui", "zz"))
print(diff_datf(datf1=datf1, datf2=datf2))

#[1] 5 1 5 2
```

---

```
elements_equalifier
               elements_equalifier
```

---

**Description**

Takes an input vector with elements that have different occurrence, and output a vector with all these elements with the same number of occurrence, see examples

**Usage**

```
elements_equalifier(inpt_v, until = 3)
```

**Arguments**

inpt\_v            is the input vector  
 until            is how many times each elements will be in the output vector

**Examples**

```
print(elements_equalifier(letters, until = 2))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s"
[20] "t" "u" "v" "w" "x" "y" "z" "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l"
[39] "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z"

print(elements_equalifier(c(letters, letters[-1]), until = 2))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s"
[20] "t" "u" "v" "w" "x" "y" "z" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m"
[39] "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z" "a"
```

---

equalizer_v	<i>equalizer_v</i>
-------------	--------------------

---

### Description

Takes a vector of character as an input and returns a vector with the elements at the same size. The size can be chosen via depth parameter.

### Usage

```
equalizer_v(inpt_v, depth = "max", default_val = "?")
```

### Arguments

inpt_v	is the input vector containing all the characters
depth	is the depth parameter, defaults to "max" which means that it is equal to the character number of the element(s) in inpt_v that has the most
default_val	is the default value that will be added to the output characters if those has an inferior length (characters) than the value of depth

### Examples

```
print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=2))

#[1] "aa" "zz" "q?"

print(equalizer_v(inpt_v=c("aa", "zzz", "q"), depth=12))

#[1] "aa?????????" "zzz?????????" "q?????????"
```

---

extract_normal	<i>extract_normal</i>
----------------	-----------------------

---

### Description

Allow to extract values that fits a normal distribution from any kind of dataset, see examples and parameters

### Usage

```
extract_normal(
  inpt_datf,
  mean,
  sd,
  accuracy,
  round_value = 1,
  normalised = FALSE,
  n = NA,
  tries = 3
)
```



**Arguments**

inpt_datf	is the input dataset as a dataframe, values/modalities are in the first column and frequency (not normalised) is in the second column
mean	is the mean of the target normal distribution
sd	is the standard deviation of the target normal distribution
accuracy	is how much of a difference between the points of the targeted normal distribution and the actual points is tolerated
round_value	is the round value for the normal distribution used under the hood to compare the dataset and extract the best points, defaults to 1
normalised	is if the input frequency is divided by n, if TRUE the parameter n must be filled
n	is the number of points
tries	is how many normal distributions are used under the hood to compare their points to the those in the input dataset, defaults to 3. The higher it is, the higher the number of different points from the input dataset will be in accordance for the normal distribution the function tries to build from the dataset. It does not increase by a lot but can be non-negligible and note that the higher the number of tries is, the higher the execution time of the function will be.

**Examples**

```
sample_val <- round(rnorm(n = 72000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)
sample_qual <- infinite_char_seq(n = length(sample_freq))
datf_test <- data.frame(sample_qual, sample_freq)
n <- nrow(datf_test)
print(datf_test)
```

	sample_qual	sample_freq
1	a	72
2	b	1155
3	c	1255
4	d	743
5	e	696
6	f	1028
7	g	1160
8	h	1219
9	i	1353
10	j	1336
11	k	1308
12	l	485
13	m	1306
14	n	1429
15	o	623
16	p	1172
17	q	1054
18	r	999
19	s	125
20	t	1461
21	u	1430
22	v	341
23	w	1453
24	x	427
25	y	869

26	z	1395
27	aa	841
28	ab	952
29	ac	246
30	ad	468
31	ae	237
32	af	555
33	ag	1297
34	ah	571
35	ai	349
36	aj	773
37	ak	1086
38	al	1281
39	am	1471
40	an	1236
41	ao	394
42	ap	1433
43	aq	1328
44	ar	976
45	as	640
46	at	308
47	au	698
48	av	864
49	aw	1346
50	ax	1349
51	ay	6
52	az	1071
53	ba	248
54	bb	929
55	bc	925
56	bd	452
57	be	207
58	bf	546
59	bg	62
60	bh	107
61	bi	1184
62	bj	739
63	bk	624
64	bl	850
65	bm	1408
66	bn	620
67	bo	202
68	bp	10
69	bq	700
70	br	397
71	bs	1291
72	bt	178
73	bu	397
74	bv	1089
75	bw	1301
76	bx	328
77	by	1348
78	bz	97
79	ca	1452
80	cb	4
81	cc	100
82	cd	593

83	ce	503
84	cf	164
85	cg	32
86	ch	259
87	ci	1089
88	cj	249
89	ck	165
90	cl	42
91	cm	143
92	cn	467
93	co	347
94	cp	143
95	cq	69
96	cr	18
97	cs	290
98	ct	55
99	cu	141
100	cv	86
101	cw	303
102	cx	88
103	cy	16
104	cz	213
105	da	3
106	db	75
107	dc	32
108	dd	66
109	de	105
110	df	34
111	dg	56
112	dh	17
113	di	22
114	dj	120
115	dk	54
116	dl	9
117	dm	8
118	dn	36
119	do	20
120	dp	26
121	dq	54
122	dr	8
123	ds	10
124	dt	4
125	du	53
126	dv	29
127	dw	1
128	dx	8
129	dy	10
130	dz	4
131	ea	22
132	eb	9
133	ec	17
134	ed	55
135	ee	21
136	ef	6
137	eg	4
138	eh	3
139	ei	7

```

140      ej      1
141      ek      4
142      el      2
143      em      5
144      en      4
145      eo      1
146      ep      2
147      eq      3
148      er      8
149      es      4
150      et      3
151      eu      3
152      ev      2
153      ew      2
154      ex      2
155      ey      1
156      ez      2
157      fa      2
158      fb      1

```

```

teste <- extract_normal(inpt_datf = datf_test,
                        mean = 10,
                        sd = 2,
                        accuracy = .1,
                        round_value = 1,
                        normalised = FALSE,
                        tries = 5)

```

```
print(length(unique(teste[, 1])) / n)
```

```

[1] 0.2848101 # so nearly 28.5 % of the different points were in
#accordance with the construction of the target normal distribution

```

```
print(teste)
```

```

      values      frequency
1      dw 0.0001406866
2      dw 0.0001406866
3      dw 0.0001406866
4      el 0.0002813731
5      el 0.0002813731
6      el 0.0002813731
7      el 0.0002813731
8      da 0.0004220597
9      da 0.0004220597
10     cb 0.0005627462
11     cb 0.0005627462
12     em 0.0007034328
13     ay 0.0008441193
14     ay 0.0008441193
15     ei 0.0009848059
16     ei 0.0009848059
17     ei 0.0009848059
18     dm 0.0011254924
19     bp 0.0014068655
20     cy 0.0022509848
21     cy 0.0022509848

```

22	cy	0.0022509848
23	dh	0.0023916714
24	dh	0.0023916714
25	cr	0.0025323579
26	ee	0.0029544176
27	di	0.0030951041
28	dp	0.0036578503
29	dp	0.0036578503
30	cg	0.0045019696
31	cg	0.0045019696
32	df	0.0047833427
33	dn	0.0050647158
34	cl	0.0059088351
35	cl	0.0059088351
36	du	0.0074563872
37	du	0.0074563872
38	dg	0.0078784468
39	dg	0.0078784468
40	bg	0.0087225661
41	bg	0.0087225661
42	dd	0.0092853123
43	cq	0.0097073720
44	cq	0.0097073720
45	a	0.0101294316
46	cv	0.0120990433
47	cx	0.0123804164
48	cx	0.0123804164
49	bz	0.0136465954
50	cc	0.0140686550
51	bh	0.0150534609
52	bh	0.0150534609
53	dj	0.0168823860
54	s	0.0175858188
55	s	0.0175858188
56	cm	0.0201181767
57	cf	0.0230725943
58	ck	0.0232132808
59	bt	0.0250422060
60	bt	0.0250422060
61	be	0.0291221159
62	be	0.0291221159
63	cz	0.0299662352
64	cz	0.0299662352
65	be	0.0291221159
66	bo	0.0284186832
67	bt	0.0250422060
68	ck	0.0232132808
69	ck	0.0232132808
70	cm	0.0201181767
71	cu	0.0198368036
72	s	0.0175858188
73	dj	0.0168823860
74	bh	0.0150534609
75	bh	0.0150534609
76	de	0.0147720878
77	bz	0.0136465954
78	bz	0.0136465954

```

79      cx 0.0123804164
80      cv 0.0120990433
81      db 0.0105514913
82      a  0.0101294316
83      cq 0.0097073720
84      dd 0.0092853123
85      dd 0.0092853123
86      bg 0.0087225661
87      bg 0.0087225661
88      dg 0.0078784468
89      dk 0.0075970737
90      du 0.0074563872
91      cl 0.0059088351
92      cl 0.0059088351
93      dn 0.0050647158
94      df 0.0047833427
95      df 0.0047833427
96      cg 0.0045019696
97      dv 0.0040799100
98      dp 0.0036578503
99      di 0.0030951041
100     di 0.0030951041
101     ee 0.0029544176
102     cr 0.0025323579
103     dh 0.0023916714
104     cy 0.0022509848
105     cy 0.0022509848
106     cy 0.0022509848
107     cy 0.0022509848
108     dl 0.0012661790
109     dm 0.0011254924
110     ei 0.0009848059
111     ei 0.0009848059
112     ay 0.0008441193
113     ay 0.0008441193
114     em 0.0007034328
115     em 0.0007034328
116     cb 0.0005627462
117     cb 0.0005627462
118     da 0.0004220597
119     da 0.0004220597
120     el 0.0002813731
121     el 0.0002813731
122     el 0.0002813731
123     el 0.0002813731
124     dw 0.0001406866
125     dw 0.0001406866
126     dw 0.0001406866

```

---

extrt\_only\_v

*extrt\_only\_v*

---

### Description

Returns the elements from a vector "inpt\_v" that are in another vector "pttrn\_v"

**Usage**

```
extrt_only_v(inpt_v, pttrn_v)
```

**Arguments**

`inpt_v` is the input vector

`pttrn_v` is the vector contining all the elements that can be in `inpt_v`

**Examples**

```
print(extrt_only_v(inpt_v=c("oui", "non", "peut", "oo", "ll", "oui", "non", "oui", "oui"),
  pttrn_v=c("oui")))

#[1] "oui" "oui" "oui" "oui"
```

---

fillr

---

*fillr*


---

**Description**

Allow to fill a vector by the last element n times

**Usage**

```
fillr(inpt_v, ptrn_fill = "\\..\\.\\.\\.\\.\\d")
```

**Arguments**

`inpt_v` is the input vector

`ptrn_fill` is the pattern used to detect where the function has to fill the vector by the last element n times. It defaults to "...\\d" where "\\d" is the regex for an int value. So this paramater has to have "\\d" which designates n.

**Examples**

```
print(fillr(c("a", "b", "...3", "c")))
```

```
#[1] "a" "b" "b" "b" "b" "c"
```

---

fixer_nest_v	<i>fixer_nest_v</i>
--------------	---------------------

---

### Description

Retur the elements of a vector "wrk\_v" (1) that corresponds to the pattern of elements in another vector "cur\_v" (2) according to another vector "pttrn\_v" (3) that contains the patterof elements.

### Usage

```
fixer_nest_v(cur_v, pttrn_v, wrk_v)
```

### Arguments

cur_v	is the input vector
pttrn_v	is the vector containing all the patterns that may be contained in cur_v
wrk_v	is a vector containing all the indexes of cur_v taken in count in the function

### Examples

```
print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"),
  pttrn_v=c("oui", "non", "peut-etre"),
  wrk_v=c(1, 2, 3, 4, 5, 6)))

#[1] 1 2 3 4 5 6

print(fixer_nest_v(cur_v=c("oui", "non", "peut-etre", "oui", "non", "peut-etre"),
  pttrn_v=c("oui", "non"),
  wrk_v=c(1, 2, 3, 4, 5, 6)))

#[1] 1 2 NA 4 5 NA
```

---

fold_rec	<i>fold_rec</i>
----------	-----------------

---

### Description

Allow to get all the files recursively from a path according to an end and start depth value. If you want to have an other version of this function that uses a more sophisticated algorythm (which can be faster), check file\_rec2. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

### Usage

```
fold_rec(xmax, xmin = 1, pathc = ".")
```

### Arguments

xmax	is the end depth value
xmin	is the start depth value
pathc	is the reference path



---

fold_rec2	<i>fold_rec2</i>
-----------	------------------

---

### Description

Allow to find the directories and the subdirectories with a specified end and start depth value from a path. This function might be more powerfull than file\_rec because it uses a custom algorythm that does not nee to perform a full recursive search before tuning it to only find the directories with a good value of depth. Depth example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

### Usage

```
fold_rec2(xmax, xmin = 1, pathc = ".")
```

### Arguments

xmax	is the depth value
xmin	is the minimum value of depth
pathc	is the reference path, from which depth value is equal to 1

---

format_date	<i>format_date</i>
-------------	--------------------

---

### Description

Allow to convert xx-month-xxxx date type to xx-xx-xxxx

### Usage

```
format_date(f_dialect, sentc, sep_in = "-", sep_out = "-")
```

### Arguments

f_dialect	are the months from the language of which the month come
sentc	is the date to convert
sep_in	is the separator of the dat input (default is "-")
sep_out	is the separator of the converted date (default is "-")

### Examples

```
print(format_date(f_dialect=c("janvier", "février", "mars", "avril", "mai", "juin",
"juillet", "aout", "septembre", "octobre", "novembre", "décembre"), sentc="11-septembre-2
#[1] "11-09-2023"
```

---

geo_min	<i>geo_min</i>
---------	----------------

---

## Description

Return a dataframe containing the nearest geographical points (row) according to established geographical points (column).

## Usage

```
geo_min(inpt_datf, established_datf)
```

## Arguments

`inpt_datf` is the input dataframe of the set of geographical points to be classified, its first column is for latitude, the second for the longitude and the third, if exists, is for the altitude. Each point is one row.

`established_datf` is the dataframe containing the coordinates of the established geographical points

## Examples

```
in_ <- data.frame(c(11, 33, 55), c(113, -143, 167))

in2_ <- data.frame(c(12, 55), c(115, 165))

print(geo_min(inpt_datf=in_, established_datf=in2_))

#           X1           X2
#1    245.266         NA
#2  24200.143         NA
#3           NA  127.7004

in_ <- data.frame(c(51, 23, 55), c(113, -143, 167), c(6, 5, 1))

in2_ <- data.frame(c(12, 55), c(115, 165), c(2, 5))

print(geo_min(inpt_datf=in_, established_datf=in2_))

#           X1           X2
#1           NA  4343.720
#2  26465.63         NA
#3           NA  5825.517
```

---

get\_rec

*get\_rec*


---

**Description**

Allow to get the value of directorie depth from a path.

**Usage**

```
get_rec(pathc = ".")
```

**Arguments**

pathc is the reference path example: if i have dir/dir2/dir3, dir/dir2b/dir3b, i have a depth equal to 3

---

globe

*globe*


---

**Description**

Allow to calculate the distances between a set of geographical points and another established geographical point. If the altitude is not filled, so the result returned won't take in count the altitude.

**Usage**

```
globe(lat_f, long_f, alt_f = NA, lat_n, long_n, alt_n = NA)
```

**Arguments**

lat\_f is the latitude of the established geographical point  
long\_f is the longitude of the established geographical point  
alt\_f is the altitude of the established geographical point, defaults to NA  
lat\_n is a vector containing the latitude of the set of points  
long\_n is a vector containing the longitude of the set of points  
alt\_n is a vector containing the altitude of the set of points, defaults to NA

**Examples**

```
print(globe(lat_f=23, long_f=112, alt_f=NA, lat_n=c(2, 82), long_n=c(165, -55), alt_n=NA))
#[1] 6342.844 7059.080

print(globe(lat_f=23, long_f=112, alt_f=8, lat_n=c(2, 82), long_n=c(165, -55), alt_n=c(8, 8)))
#[1] 6342.844 7059.087
```

---

```
grep_all
```

```
grep_all
```

---

### Description

Allow to perform a grep function on multiple input elements

### Usage

```
grep_all(inpt_v, pattern_v)
```

### Arguments

`inpt_v` is the input vectors to grep elements from  
`pattern_v` is a vector containing the patterns to grep

### Examples

```
print(grep_all(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "4")))

[1] 15 23 25 4 14 19

print(grep_all(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "^4$")))

[1] 15 23 25 4 19

print(grep_all(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z")))

[1] 15 23 25
```

---

```
grep_all2
```

```
grep_all2
```

---

### Description

Performs the `grep_all` function with another algorithm, potentially faster

### Usage

```
grep_all2(inpt_v, pattern_v)
```

### Arguments

`inpt_v` is the input vectors to grep elements from  
`pattern_v` is a vector containing the patterns to grep

**Examples**

```
print(grep_all2(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "4")))

[1] 15 23 25  4 14 19

print(grep_all2(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z", "^4$")))

[1] 15 23 25  4 19

print(grep_all2(inpt_v = c(1:14, "z", 1:7, "z", "a", "z"),
               pattern_v = c("z")))

[1] 15 23 25
```

groupr\_datf

*groupr\_datf***Description**

Allow to create groups from a dataframe. Indeed, you can create conditions that lead to a flag value for each cell of the input dataframe according to the cell value. This function is based on `see_datf` and `nestr_datf2` functions.

**Usage**

```
groupr_datf(
  inpt_datf,
  condition_lst,
  val_lst,
  conjunction_lst,
  rtn_val_pos = c()
)
```

**Arguments**

<code>inpt_datf</code>	is the input dataframe
<code>condition_lst</code>	is a list containing all the condition as a vector for each group
<code>val_lst</code>	is a list containing all the values associated with <code>condition_lst</code> as a vector for each group
<code>conjunction_lst</code>	is a list containing all the conjunctions associated with <code>condition_lst</code> and <code>val_lst</code> as a vector for each group
<code>rtn_val_pos</code>	is a vector containing all the group flag value like this ex: <code>c("flag1", "flag2", "flag3")</code>

**Examples**

```

interactive()

datf1 <- data.frame(c(1, 2, 1), c(45, 22, 88), c(44, 88, 33))

val_lst <- list(list(c(1), c(1)), list(c(2)), list(c(44, 88)))

condition_lst <- list(c(">", "<"), c("%%", "==" , "=="))

conjunction_lst <- list(c("|"), c(), c("|"))

rtn_val_pos <- c("+", "++", "+++")

print(groupr_datf(inpt_datf=datf1, val_lst=val_lst, condition_lst=condition_lst,
conjunction_lst=conjunction_lst, rtn_val_pos=rtn_val_pos))

#      X1  X2  X3
#1 <NA>   +  +++
#2   ++  ++  +++
#3 <NA> +++   +

```

---

gsub\_mult*gsub\_mult*

---

**Description**

Performs a gsub operation with n patterns and replacements.

**Usage**

```
gsub_mult(inpt_v, pattern_v = c(), replacement_v = c())
```

**Arguments**

`inpt_v` is a vector containing all the elements that contains expressions to be substituted

`pattern_v` is a vector containing all the patterns to be substituted in any elements of `inpt_v`

`replacement_v` is a vector containing the expression that are going to substitute those provided by `pattern_v`

**Examples**

```

print(gsub_mult(inpt_v = c("X and Y programming languages are great", "More X, more X!"),
  pattern_v = c("X", "Y", "Z"),
  replacement_v = c("C", "R", "GO")))
[1] "C and R programming languages are great"
[2] "More C, more C!"

```

---

how_normal	<i>how_normal</i>
------------	-------------------

---

### Description

Allow to get how much a sequence of numbers fit a normal distribution with chosen parameters, see examples

### Usage

```
how_normal(inpt_datf, normalised = TRUE, mean = 0, sd = 1)
```

### Arguments

inpt_datf	is the input dataframe containing all the values in the first column and their frequency (normalised or no), in the second column
normalised	is a boolean, takes TRUE if the frequency for each value is divided by n, FALSE if not
mean	is the mean of the normal distribution that the dataset tries to fit
sd	is the standard deviation of the normal distribution the dataset tries to fit

### Examples

```
sample_val <- round(rnorm(n = 12000, mean = 6, sd = 1.25), 1)
sample_freq <- unique_total(sample_val)
datf_test <- data.frame(unique(sample_val), sample_freq)
print(datf_test)
```

```
unique.sample_val. sample_freq
1          6.9         306
2          8.3          63
3          7.7         148
4          5.6         363
5          6.5         349
6          4.6         202
7          6.6         324
8          6.7         335
9          6.0         406
10         5.7         365
11         7.9         109
12         6.2         420
13         5.9         386
14         4.5         185
15         5.1         326
16         6.1         360
17         5.5         346
18         6.3         375
19         7.4         207
20         7.6         162
21         4.2         129
22         3.9         102
23         5.2         325
24         2.3           7
```

25	5.8	387
26	6.4	319
27	9.1	21
28	7.0	280
29	8.8	27
30	4.9	218
31	8.1	98
32	3.0	25
33	8.4	66
34	4.3	160
35	7.2	267
36	8.7	40
37	5.3	313
38	4.1	127
39	5.0	275
40	4.0	119
41	9.3	13
42	4.4	196
43	6.8	313
44	7.1	247
45	3.5	57
46	7.8	139
47	3.6	57
48	7.5	189
49	7.3	215
50	4.7	230
51	3.2	36
52	9.5	8
53	3.8	79
54	8.2	62
55	5.4	343
56	8.5	55
57	4.8	207
58	3.7	79
59	8.6	33
60	3.3	38
61	3.4	43
62	8.9	21
63	8.0	105
64	3.1	23
65	9.0	27
66	10.0	5
67	2.5	10
68	2.9	16
69	9.7	7
70	2.7	11
71	10.5	1
72	9.4	13
73	9.2	16
74	2.6	16
75	9.9	3
76	2.8	10
77	2.4	10
78	1.9	2
79	2.0	6
80	10.2	2
81	9.6	3



```

82          11.3          1
83          1.8          1
84          2.2          3
85          2.1          2
86          1.6          1
87         10.6          1
88          9.8          1
89         10.4          1
90          1.7          1

print(how_normal(inpt_datf = datf_test,
                 normalised = FALSE,
                 mean = 6,
                 sd = 1))

[1] 9.003683

print(how_normal(inpt_datf = datf_test,
                 normalised = FALSE,
                 mean = 5,
                 sd = 1))

[1] 9.098484

```

---

how\_unif

*how\_unif*


---

## Description

Allow to see how much a sequence of numbers fit a uniform distribution, see examples

## Usage

```
how_unif(inpt_v, normalised = TRUE)
```

## Arguments

normalised	is a boolean, takes TRUE if the frequency for each value is divided by n, FALSE if not
inpt_datf	is the input dataframe containing all the values in the first column and their frequency at the second column

## Examples

```

sample_val <- round(runif(n = 12000, min = 24, max = 27), 1)
sample_freq <- unique_total(sample_val)
datf_test <- data.frame(unique(sample_val), sample_freq)

print(datf_test)

  unique.sample_val. sample_freq
1             24.4          400
2             24.8          379

```

3	25.5	414
4	26.0	366
5	26.6	400
6	25.7	419
7	24.3	389
8	24.1	423
9	26.1	404
10	26.5	406
11	26.2	356
12	26.8	407
13	24.6	388
14	25.3	402
15	26.3	388
16	25.4	422
17	25.0	436
18	25.9	373
19	25.2	423
20	25.6	388
21	27.0	202
22	24.2	380
23	24.9	404
24	25.1	417
25	26.4	401
26	26.7	431
27	24.5	392
28	24.0	218
29	26.9	407
30	25.8	371
31	24.7	394

```
print(how_unif(inpt_datf = datf_test, normalised = FALSE))
```

```
[1] 0.0752957
```

```
sample_val <- round(rnorm(n = 12000, mean = 24, sd = 7), 1)
sample_freq <- unique_total(sample_val)
datf_test <- data.frame(unique(sample_val), sample_freq)
```

```
print(how_unif(inpt_datf = datf_test, normalised = FALSE))
```

```
[1] 0.7797352
```

---

id\_keepr

---

id\_keepr

---

## Description

Allow to get the original indexes after multiple equality comparison according to the original number of row

## Usage

```
id_keepr(inpt_datf, col_v = c(), el_v = c(), rstr_l = NA)
```

**Arguments**

<code>inpt_datf</code>	is the input dataframe
<code>col_v</code>	is the vector containing the column numbers or names to be compared to their respective elements in "el_v"
<code>el_v</code>	is a vector containing the elements that may be contained in their respective column described in "col_v"
<code>rstr_l</code>	is a list containing the vector composed of the indexes of the elements chosen for each comparison. If the length of the list is inferior to the length of comparisons, so the last vector of <code>rstr_l</code> will be the same as the last one to fill make <code>rstr_l</code> equal in term of length to <code>col_v</code> and <code>el_v</code>

**Examples**

```
datf1 <- data.frame(c("oui", "oui", "oui", "non", "oui"),
  c("opui", "op", "op", "zez", "zez"), c(5:1), c(1:5))

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op")))

#[1] 2 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"),
  rstr_l=list(c(1:5), c(3, 2, 2, 2, 3))))

#[1] 2 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"),
  rstr_l=list(c(1:5), c(3))))

#[1] 3

print(id_keepr(inpt_datf=datf1, col_v=c(1, 2), el_v=c("oui", "op"), rstr_l=list(c(1:5))))

#[1] 2 3
```

---

incr\_fillr

*incr\_fillr*


---

**Description**

Take a vector uniquely composed by double and sorted ascendingly, a step, another vector of elements whose length is equal to the length of the first vector, and a default value. If an element of the vector is not equal to its predecessor minus a user defined step, so these can be the output according to the parameters (see example):

**Usage**

```
incr_fillr(inpt_v, wrk_v = NA, default_val = NA, step = 1)
```

**Arguments**

<code>inpt_v</code>	is the ascending double only composed vector
<code>wrk_v</code>	is the other vector (size equal to <code>inpt_v</code> ), defaults to NA
<code>default_val</code>	is the default value put when the difference between two following elements of <code>inpt_v</code> is greater than <code>step</code> , defaults to NA
<code>step</code>	is the allowed difference between two elements of <code>inpt_v</code>

**Examples**

```
print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
                wrk_v=NA,
                default_val="increasing"))

#[1] 1 2 3 4 5 6 7 8 9 10

print(incr_fillr(inpt_v=c(1, 1, 2, 4, 5, 9),
                wrk_v=c("ok", "ok", "ok", "ok", "ok"),
                default_val=NA))

#[1] "ok" "ok" "ok" NA "ok" "ok" NA NA NA

print(incr_fillr(inpt_v=c(1, 2, 4, 5, 9, 10),
                wrk_v=NA,
                default_val="NAN"))

#[1] "1" "2" "NAN" "4" "5" "NAN" "NAN" "NAN" "9" "10"
```

---

`infinite_char_seq` *infinite\_char\_seq*

---

**Description**

Allow to generate an infinite sequence of unique letters

**Usage**

```
infinite_char_seq(n, base_char = letters)
```

**Arguments**

<code>n</code>	is how many sequence of numbers will be generated
<code>base_char</code>	is the vector containing the elements from which the sequence is generated

**Examples**

```
print(infinite_char_seq(28))

[1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o"
[16] "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "a" "aa" "ab"
```

---

*inner\_all*

---

*inner\_all***Description**

Allow to apply inner join on n dataframes, datatables, tibble

**Usage**

```
inner_all(..., keep_val = FALSE, id_v)
```

**Arguments**

`...` are all the dataframes etc  
`keep_val` is if you want to keep the id column  
`id_v` is the common id of all the dataframes etc

**Examples**

```
datf1 <- data.frame(  
  "id1"=c(1:5),  
  "var1"=c("oui", "oui", "oui", "non", "non")  
)  
  
datf2 <- data.frame(  
  "id1"=c(1, 2, 3, 7, 9),  
  "var1"=c("oui2", "oui2", "oui2", "non2", "non2")  
)  
  
print(inner_all(datf1, datf2, keep_val=FALSE, id_v="id1"))  
  
id1 var1.x var1.y  
1 1 oui oui2  
2 2 oui oui2  
3 3 oui oui2
```

---

*insert\_datf*

---

*insert\_datf***Description**

Allow to insert dataframe into another dataframe according to coordinates (row, column) from the dataframe that will be inserted

**Usage**

```
insert_datf(datf_in, datf_ins, ins_loc)
```

**Arguments**

`datf_in` is the dataframe that will be inserted

`datf_ins` is the dataset to be inserted

`ins_loc` is a vector containg two parameters (row, column) of the begining for the insertion

**Examples**

```
datf1 <- data.frame(c(1, 4), c(5, 3))

datf2 <- data.frame(c(1, 3, 5, 6), c(1:4), c(5, 4, 5, "ereer"))

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(4, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1             1      1                    5
# 2             3      2                    4
# 3             5      3                    5
# 4             6      1                    5

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(3, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1             1      1                    5
# 2             3      2                    4
# 3             5      1                    5
# 4             6      4                    3

print(insert_datf(datf_in=datf2, datf_ins=datf1, ins_loc=c(2, 2)))

#   c.1..3..5..6. c.1.4. c.5..4..5...ereer..
# 1             1      1                    5
# 2             3      1                    5
# 3             5      4                    3
# 4             6      4                ereer
```

---

`intersect_all`
`intersect_all`


---

**Description**

Allows to calculate the intersection between n vectors

**Usage**

```
intersect_all(...)
```

**Arguments**

`...` is all the vector you want to calculate the intersection from

**Examples**

```
print(intersect_all(c(1:5), c(1, 2, 3, 6), c(1:4)))

[1] 1 2 3
```

---

intersect_mod	<i>intersect_mod</i>
---------------	----------------------

---

**Description**

Returns the mods that have elements in common

**Usage**

```
intersect_mod(datf, inter_col, mod_col, n_min, descendly_ordered = NA)
```

**Arguments**

datf	is the input dataframe
inter_col	is the column name or the column number of the values that may be commun between the different mods
mod_col	is the column name or the column number of the mods in the dataframe
n_min	is the minimum elements in common a mod should have to be taken in count
ordered_descendly	in case that the elements in commun are numeric, this option can be enabled by giving a value of TRUE or FALSE see examples

**Examples**

```
datf <- data.frame("col1"=c("oui", "oui", "oui", "oui", "oui", "oui",
                             "non", "non", "non", "non", "ee", "ee", "ee"), "col2"=c(1:6, 2:5, 1:3))

print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=2))

  col1 col2
2   oui   2
3   oui   3
7  non    2
8  non    3
12  ee    2
13  ee    3

print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=3))

  col1 col2
2   oui   2
3   oui   3
4   oui   4
5   oui   5
7  non    2
8  non    3
```

```
9   non      4
10  non      5

print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=5))

  coll col2
1  oui     1
2  oui     2
3  oui     3
4  oui     4
5  oui     5
6  oui     6

datf <- data.frame("coll"=c("non", "non", "oui", "oui", "oui", "oui",
                           "non", "non", "non", "non", "ee", "ee", "ee"), "col2"=c(1:6, 2:5, 1:6))

print(intersect_mod(datf=datf, inter_col=2, mod_col=1, n_min=3))

  coll col2
8   non     3
9   non     4
10  non     5
3   oui     3
4   oui     4
5   oui     5
```

---

<i>inter_max</i>	<i>inter_max</i>
------------------	------------------

---

**Description**

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)). The function will return the list of lists altered according to the maximum step found in the input list.

**Usage**

```
inter_max(inpt_l, max_ = -1000, get_lst = TRUE)
```

**Arguments**

- inpt\_l is the input list
- max\_ is a value you are sure is the minimum step value of all the sub-lists
- get\_lst is the parameter that, if set to True, will keep the last values of vectors in the return value if the last step exceeds the end value of the vector.

**Examples**

```
print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=TRUE))

#[[1]]
#[1] 0 4
```



```

#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1.0 2.3

print(inter_max(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)), get_lst=FALSE))

# [[1]]
#[1] 0 4
#
#[[2]]
#[1] 0 4
#
#[[3]]
#[1] 1

```

---

inter\_min

---

inter\_min

---

## Description

Takes as input a list of vectors composed of ints or floats ascendly ordered (intervals) that can have a different step to one of another element ex: list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3)). This function will return the list of vectors with the same steps preserving the begin and end value of each interval. The way the algorithm searches the common step of all the sub-lists is also given by the user as a parameter, see `how_to` paramaters.

## Usage

```

inter_min(
  inpt_l,
  min_ = 1000,
  sensi = 3,
  sensi2 = 3,
  how_to_op = c("divide"),
  how_to_val = c(3)
)

```

## Arguments

<code>inpt_l</code>	is the input list containing all the intervals
<code>min_</code>	is a value you are sure is superior to the maximum step value in all the intervals
<code>sensi</code>	is the decimal accuracy of how the difference between each value $n$ to $n+1$ in an interval is calculated
<code>sensi2</code>	is the decimal accuracy of how the value with the common step is calculated in all the intervals
<code>how_to_op</code>	is a vector containing the operations to perform to the pre-common step value, defaults to only "divide". The operations can be "divide", "subtract", "multiply" or "add". All type of operations can be in this parameter.

`how_to_val` is a vector containing the value relatives to the operations in `hot_to_op`, defaults to 3 output from `ex`:

**Examples**

```
print(inter_min(inpt_l=list(c(0, 2, 4), c(0, 4), c(1, 2, 2.3))))

# [[1]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
#[20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
#[39] 3.8 3.9 4.0
#
# [[2]]
# [1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8
#[20] 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7
#[39] 3.8 3.9 4.0
#
# [[3]]
# [1] 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1 2.2 2.3
```

---

<code>isnt_divisible</code>	<i>isnt_divisible</i>
-----------------------------	-----------------------

---

**Description**

Takes a vector as an input and returns all the elements that are not divisible by all choosen numbers from another vector.

**Usage**

```
isnt_divisible(inpt_v = c(), divisible_v = c())
```

**Arguments**

`inpt_v` is the input vector  
`divisible_v` is the vector containing all the numbers that will try to divide those contained in `inpt_v`

**Examples**

```
print(isnt_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

# [1] 1 3 7 9 11 13 17 19 21 23 27 29 31 33 37 39 41 43 47
#[20] 49 51 53 57 59 61 63 67 69 71 73 77 79 81 83 87 89 91 93
#[39] 97 99 101 103 107 109 111
```

---

is_divisible	<i>is_divisible</i>
--------------	---------------------

---

### Description

Takes a vector as an input and returns all the elements that are divisible by all choosen numbers from another vector.

### Usage

```
is_divisible(inpt_v = c(), divisible_v = c())
```

### Arguments

inpt_v	is the input vector
divisible_v	is the vector containing all the numbers that will try to divide those contained in inpt_v

### Examples

```
print(is_divisible(inpt_v=c(1:111), divisible_v=c(2, 4, 5)))

#[1] 20 40 60 80 100
```

---

join_n_lvl	<i>join_n_lvl</i>
------------	-------------------

---

### Description

Allow to see the progress of the multi-level joins of the different variables modalities. Here, multi-level joins is a type of join that usually needs a concatenation of two or more variables to make a key. But here, there is no need to proceed to a concatenation. See examples.

### Usage

```
join_n_lvl(frst_datf, scd_datf, join_type = c(), lst_pair = list())
```

### Arguments

frst_datf	is the first data.frame (table)
scd_datf	is the second data.frame (table)
join_type	is a vector containing all the join type ("left", "inner", "right") for each variable
lst_pair	is a lis of vectors. The vectors refers to a multi-level join. Each vector should have a length of 1. Each vector should have a name. Its name refers to the column name of multi-level variable and its value refers to the column name of the join variable.

Examples

```
datf3 <- data.frame("vil"=c("one", "one", "one", "two", "two", "two"),
                    "charac"=c(1, 2, 2, 1, 2, 2),
                    "rev"=c(1250, 1430, 970, 1630, 2231, 1875),
                    "vil2" = c("one", "one", "one", "two", "two", "two"),
                    "idl2" = c(1:6))
datf4 <- data.frame("vil"=c("one", "one", "one", "two", "two", "three"),
                    "charac"=c(1, 2, 2, 1, 1, 2),
                    "rev"=c(1.250, 1430, 970, 1630, 593, 456),
                    "vil2" = c("one", "one", "one", "two", "two", "two"),
                    "idl2" = c(2, 3, 1, 5, 5, 5))

print(join_n_lvl(frst_datf=datf3, scd_datf=datf4, lst_pair=list(c("charac" = "vil"), c("vil2" = "idl2")),
                join_type=c("inner", "left"))

[1] "pair: charac vil"
| | 0%
1
|= | 50%
2
|==| 100%
[1] "pair: vil2 idl2"
| | 0%
one
|= | 50%
two
|==| 100%

main_id.x vil.x charac.x rev.x vil2.x idl2.x main_id.y vil.y charac.y rev.y
1 loneone1 one 1 1250 one 1 <NA> <NA> NA NA
2 2oneone2 one 2 1430 one 2 <NA> <NA> NA NA
3 2oneone3 one 2 970 one 3 2oneone3 one 2 1430
4 1twotwo4 two 1 1630 two 4 <NA> <NA> NA NA
vil2.y idl2.y
1 <NA> NA
2 <NA> NA
3 one 3
4 <NA> NA
```

---

leap_yr	<i>leap_year</i>
---------	------------------

---

Description

Get if the year is leap

Usage

```
leap_yr(year)
```

Arguments

year is the input year

Examples

```
print(leap_yr(year=2024))

#[1] TRUE
```

---

left_all	<i>left_all</i>
----------	-----------------

---

Description

Allow to apply left join on n dataframes, datatables, tibble

Usage

```
left_all(..., keep_val = FALSE, id_v)
```

Arguments

- ... are all the dataframes etc
- keep\_val is if you want to keep the id column
- id\_v is the common id of all the dataframes etc

Examples

```
datf1 <- data.frame(
  "id1"=c(1:5),
  "var1"=c("oui", "oui", "oui", "non", "non")
)

datf2 <- data.frame(
  "id1"=c(1, 2, 3, 7, 9),
  "var1"=c("oui2", "oui2", "oui2", "non2", "non2")
)

print(left_all(datf1, datf2, datf2, datf2, keep_val=FALSE, id_v="id1"))

  id1 var1.x var1.y var1.x.x var1.y.y
1   1   oui  oui2   oui2   oui2
2   2   oui  oui2   oui2   oui2
3   3   oui  oui2   oui2   oui2
4   4  non <NA>   <NA>   <NA>
5   5  non <NA>   <NA>   <NA>#'
print(left_all(datf1, datf2, datf2, keep_val=FALSE, id_v="id1"))

  id1 var1.x var1.y var1
1   1   oui  oui2 oui2
2   2   oui  oui2 oui2
3   3   oui  oui2 oui2
4   4  non  <NA> <NA>
5   5  non  <NA> <NA>
```

---

letter_to_nb	<i>letter_to_nb</i>
--------------	---------------------

---

**Description**

Allow to get the number of a spreadsheet based column by the letter ex: AAA = 703

**Usage**

```
letter_to_nb(letter)
```

**Arguments**

letter            is the letter (name of the column)

**Examples**

```
print(letter_to_nb("rty"))  
  
#[1] 12713
```

---

list_files	<i>list_files</i>
------------	-------------------

---

**Description**

A list.files() based function addressing the need of listing the files with extension a or or extension b ...

**Usage**

```
list_files(patternc, pathc = ".")
```

**Arguments**

patternc            is a vector containing all the extensions you want  
pathc                is the path, can be a vector of multiple path because list.files() supports it.

---

lst_flatnr	<i>lst_flatnr</i>
------------	-------------------

---

### Description

Flatten a list to a vector

### Usage

```
lst_flatnr(inpt_l)
```

### Arguments

`inpt_l` is the input list

### Examples

```
print(lst_flatnr(inpt_l=list(c(1, 2), c(5, 3), c(7, 2, 7))))
#[1] 1 2 5 3 7 2 7
```

---

match_by	<i>match_by</i>
----------	-----------------

---

### Description

Allow to match elements by ids, see examples.

### Usage

```
match_by(to_match_v = c(), inpt_v = c(), inpt_ids = c())
```

### Arguments

<code>to_match_v</code>	is the vector containing all the elements to match
<code>inpt_v</code>	is the input vector containong all the elements that could contains the elements to match. Each elements is linked to an element from <code>inpt_ids</code> at any given index, see examples. So <code>inpt_v</code> and <code>inpt_ids</code> must be the same size
<code>inpt_ids</code>	is the vector containing all the ids for the elements in <code>inpt_v</code> . An element is linked to the id <code>x</code> is both are at the same index. So <code>inpt_v</code> and <code>inpt_ids</code> must be the same size

Examples

```
print(match_by(to_match_v = c("a"), inpt_v = c("a", "z", "a", "p", "p", "e", "e", "a"),
             inpt_ids = c(1, 1, 1, 2, 2, 3, 3, 3)))

[1] 1 8

print(match_by(to_match_v = c("a"), inpt_v = c("a", "z", "a", "a", "p", "e", "e", "a"),
             inpt_ids = c(1, 1, 1, 2, 2, 3, 3, 3)))

[1] 1 4 8

print(match_by(to_match_v = c("a", "e"), inpt_v = c("a", "z", "a", "a", "p", "e", "e", "a"),
             inpt_ids = c(1, 1, 1, 2, 2, 3, 3, 3)))

[1] 1 4 8 6
```

---

multitud	<i>multitud</i>
----------	-----------------

---

Description

From a list containing vectors allow to generate a vector following this rule: list(c("a", "b"), c("1", "2"), c("A", "Z", "E")) -> c("a1A", "b1A", "a2A", "b2A", "a1Z, ...)

Usage

```
multitud(l, sep_ = "")
```

Arguments

- l is the list
- sep\_ is the separator between elements (default is set to "" as you see in the example)

Examples

```
print(multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")

#[1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
#[8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
#[15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
#[22] "b/1/E/F" "a/2/E/F" "b/2/E/F"
```



---

nb2_follow	<i>nb2_follow</i>
------------	-------------------

---

### Description

Allows to get the number and pattern of potential continuous pattern after an index of a vector, see examples

### Usage

```
nb2_follow(inpt_v, inpt_idx, inpt_follow_v = c())
```

### Arguments

`inpt_v` is the input vector  
`inpt_idx` is the index  
`inpt_follow_v` is a vector containing the patterns that are potentially just after `inpt_nb`

### Examples

```
print(nb2_follow(inpt_v = c(1:12), inpt_idx = 4, inpt_follow_v = c(5)))
```

```
[1] 1 5
```

```
print(nb2_follow(inpt_v = c(1, "non", "oui", "oui", "oui", "nop", 5), inpt_idx = 2, inpt_follow_v = c(3, "oui")))
```

```
[1] "3" "oui"
```

---

nb_follow	<i>nb_follow</i>
-----------	------------------

---

### Description

Allow to get the number of certain patterns that may be after an index of a vector, see examples

### Usage

```
nb_follow(inpt_v, inpt_idx, inpt_follow_v = c())
```

### Arguments

`inpt_v` is the input vector  
`inpt_idx` is the index  
`inpt_follow_v` is a vector containing all the potential patterns that may follow the element in the vector at the index `inpt_idx`

**Examples**

```
print(nb_follow(inpt_v = c(1:13), inpt_idx = 6, inpt_follow_v = c(5:9)))

[1] 3

print(nb_follow(inpt_v = c("ou", "nn", "pp", "zz", "zz", "ee", "pp"), inpt_idx = 2,
  inpt_follow_v = c("pp", "zz")))

[1] 3
```

---

nb_to_letter	<i>nb_to_letter</i>
--------------	---------------------

---

**Description**

Allow to get the letter of a spreadsheet based column by the number ex: 703 = AAA

**Usage**

```
nb_to_letter(x)
```

**Arguments**

x is the number of the column

**Examples**

```
print(nb_to_letter(5))

[1] "e"

print(nb_to_letter(27))

[1] "aa"

print(nb_to_letter(51))

[1] "ay"

print(nb_to_letter(52))

[1] "az"

print(nb_to_letter(53))

[1] "ba"

print(nb_to_letter(675))

[1] "yy"

print(nb_to_letter(676))
```

```

[1] "yz"

print(nb_to_letter(677))

[1] "za"

print(nb_to_letter(702))

[1] "zz"

print(nb_to_letter(703))

[1] "aaa"

print(nb_to_letter(18211))

[1] "zxk"

print(nb_to_letter(18277))

[1] "zzy"

print(nb_to_letter(18278))

[1] "zzz"

print(nb_to_letter(18279))

[1] "aaaa"

```

---

nestr\_datf1

*nestr\_datf1*


---

## Description

Allow to write a value (1a) to a dataframe (1b) to its cells that have the same coordinates (row and column) than the cells whose value is equal to a another special value (2a), from another another dataframe (2b). The value (1a) depends of the cell value coordinates of the third dataframe (3b). If a cell coordinates (1c) of the first dataframe (1b) does not correspond to the coordinates of a good returning cell value (2a) from the dataframe (2b), so this cell (1c) can have its value changed to the same cell coordinates value (3a) of a third dataframe (4b), if (4b) is not set to NA.

## Usage

```

nestr_datf1(
  inptf_datf,
  inptt_pos_datf,
  nestr_datf,
  yes_val = TRUE,
  inptt_neg_datf = NA
)

```

### Arguments

`inptf_datf` is the input dataframe (1b)  
`inptt_pos_datf` is the dataframe (2b) that corresponds to the (1a) values  
`nestr_datf` is the dataframe (2b) that has the special value (2a)  
`yes_val` is the special value (2a)  
`inptt_neg_datf` is the dataframe (4b) that has the (3a) values, defaults to NA

### Examples

```
print(nestr_datf1(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_datf=data.frame(c(44, 44, 33), c(12, 12, 12)),
  nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))

#   c.1..2..1. c.1..5..7.
#1           4          12
#2          44          12
#3           3           2

print(nestr_datf1(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)),
  inptt_pos_datf=data.frame(c(4, 4, 3), c(2, 1, 2)),
  inptt_neg_datf=NA,
  nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=TRUE))

#   c.1..2..1. c.1..5..7.
#1           4           1
#2           2           5
#3           3           2
```

---

<code>nestr_datf2</code>	<i>nestr_datf2</i>
--------------------------	--------------------

---

### Description

Allow to write a special value (1a) in the cells of a dataframe (1b) that correspond (row and column) to those of another dataframe (2b) that return another special value (2a). The cells whose coordinates do not match the coordinates of the dataframe (2b), another special value can be written (3a) if not set to NA.

### Usage

```
nestr_datf2(inptf_datf, rtn_pos, rtn_neg = NA, nestr_datf, yes_val = T)
```

### Arguments

`inptf_datf` is the input dataframe (1b)  
`rtn_pos` is the special value (1a)  
`rtn_neg` is the special value (3a)  
`nestr_datf` is the dataframe (2b)  
`yes_val` is the special value (2a)

Examples

```
print(nestr_datf2(inptf_datf=data.frame(c(1, 2, 1), c(1, 5, 7)), rtn_pos="yes",
rtn_neg="no", nestr_datf=data.frame(c(TRUE, FALSE, TRUE), c(FALSE, FALSE, TRUE)), yes_val=1,
no_val=0)

# c.1..2..1. c.1..5..7.
#1          yes          no
#2          no           no
#3          yes          yes
```

---

nest_v	<i>nest_v</i>
--------	---------------

---

Description

Nest two vectors according to the following parameters.

Usage

```
nest_v(f_v, t_v, step = 1, after = 1)
```

Arguments

- f\_v is the vector that will welcome the nested vector t\_v
- t\_v is the imbricator vector
- step defines after how many elements of f\_v the next element of t\_v can be put in the output
- after defines after how many elements of f\_v, the begining of t\_v can be put

Examples

```
print(nest_v(f_v=c(1, 2, 3, 4, 5, 6), t_v=c("oui", "oui2", "oui3", "oui4", "oui5", "oui6"),
step=2, after=2))

#[1] "1" "2" "oui" "3" "4" "oui2" "5" "6" "oui3" "oui4"
```

---

new_ordered	<i>new_ordered</i>
-------------	--------------------

---

Description

Returns the indexes of elements contained in "w\_v" according to "f\_v"

Usage

```
new_ordered(f_v, w_v, nvr_here = NA)
```

**Arguments**

`f_v` is the input vector  
`w_v` is the vector containing the elements that can be in `f_v`  
`nvr_here` is a value you are sure is not present in `f_v`

**Examples**

```
print(new_ordered(f_v=c("non", "non", "non", "oui"), w_v=c("oui", "non", "non")))
#[1] 4 1 2
```

---

normal\_dens

normal\_dens

---

**Description**

Calculates the normal distribution probability, see examples

**Usage**

```
normal_dens(target_v = c(), mean, sd)
```

**Arguments**

`target_v` is the target value(s) (one or bounded), see examples  
`mean` is the mean of the normal distribution  
`sd` is the standard deviation of the normal distribution

**Examples**

```
print(normal_dens(target_v = 13, mean = 12, sd = 2))
[1] 0.1760327

print(normal_dens(target_v = c(9, 11), mean = 12, sd = 1.5, step = 0.01))
[1] 0.2288579

print(normal_dens(target_v = c(1, 18), mean = 12, sd = 1.5, step = 0.01))
[1] 0.9999688
```

---

 occu

---

*occu*


---

### Description

Allow to see the occurrence of each variable in a vector. Returns a dataframe with, as the first column, the all the unique variable of the vector and , in he second column, their occurrence respectively.

### Usage

```
occu(inpt_v)
```

### Arguments

`inpt_v` the input dataframe

### Examples

```
print(occu(inpt_v=c("oui", "peut", "peut", "non", "oui")))

#   var occurrence
#1  oui          2
#2  peut         2
#3  non          1
```

---

 old\_to\_new\_idx

---

*old\_to\_new\_idx*


---

### Description

Allow to convert index of elements in a vector `inpt_v` to index of an vector type `1:sum(nchar(inpt_v))`, see examples

### Usage

```
old_to_new_idx(inpt_v = c())
```

### Arguments

`inpt_v` is the input vector

### Examples

```
print(old_to_new_idx(inpt_v = c("oui", "no", "eeee")))

[1] 1 1 1 2 2 3 3 3 3
```

---

pairs_findr	<i>pairs_findr</i>
-------------	--------------------

---

### Description

Takes a character as input and detect the pairs of pattern, like the parenthesis pairs if the pattern is "(" and then ")"

### Usage

```
pairs_findr(inpt, ptrn1 = "(", ptrn2 = ")")
```

### Arguments

inpt	is the input character
ptrn1	is the first pattern encountered in the pair
ptrn2	is the second pattern in the pair

### Examples

```
print(pairs_findr(inpt="ze+(yu*45/(jk+zz)*(o()p))-(re*(rt+qs)-fg)"))

[[1]]
[1] 4 1 1 3 2 2 3 4 6 5 5 6

[[2]]
[1] 4 11 17 19 21 22 24 25 27 31 37 41
```

---

pairs_findr_merger	<i>pairs_findr_merger</i>
--------------------	---------------------------

---

### Description

Takes two different outputs from pairs\_findr and merge them. Can be useful when the pairs consists in different patterns, for example one output from the pairs\_findr function with ptrn1 = "(" and ptrn2 = ")", and a second output from the pairs\_findr function with ptrn1 = "" and ptrn2 = "".

### Usage

```
pairs_findr_merger(lst1 = list(), lst2 = list())
```

### Arguments

lst1	is the first output from pairs findr function
lst2	is the second output from pairs findr function



**Examples**

```

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 8, 9)),
                        lst2=list(c(1, 1), c(1, 2))))

[[1]]
[1] 1 1 2 3 4 4 3 2

[[2]]
[1] 1 2 3 4 5 7 8 9

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 8, 9)),
                        lst2=list(c(1, 1), c(1, 11))))

[[1]]
[1] 1 2 3 4 4 3 2 1

[[2]]
[1] 1 3 4 5 7 8 9 11

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 8, 10, 11)),
                        lst2=list(c(4, 4), c(6, 7))))

[[1]]
[1] 1 2 3 4 4 3 2 1

[[2]]
[1] 3 4 5 6 7 8 10 11

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 10, 11)),
                        lst2=list(c(4, 4), c(8, 9))))

[[1]]
[1] 1 2 3 3 4 4 2 1

[[2]]
[1] 3 4 5 7 8 9 10 11

print(pairs_findr_merger(lst1=list(c(1, 2, 3, 3, 2, 1), c(3, 4, 5, 7, 10, 11)),
                        lst2=list(c(4, 4), c(18, 19))))

[[1]]
[1] 1 2 3 3 2 1 4 4

[[2]]
[1] 3 4 5 7 10 11 18 19

print(pairs_findr_merger(lst1 = list(c(1, 1, 2, 2, 3, 3), c(1, 25, 26, 32, 33, 38)),
                        lst2 = list(c(1, 1, 2, 2, 3, 3), c(7, 11, 13, 17, 19, 24))))

[[1]]
[1] 1 2 2 3 3 4 4 1 5 5 6 6

[[2]]
[1] 1 7 11 13 17 19 24 25 26 32 33 38

print(pairs_findr_merger(lst1 = list(c(1, 1, 2, 2, 3, 3), c(2, 7, 9, 10, 11, 15)),

```

```

lst2 = list(c(3, 2, 1, 1, 2, 3, 4, 4), c(1, 17, 18, 22, 23, 29,

[[1]]
[1] 6 5 1 1 2 2 3 3 4 4 5 6 7 7

[[2]]
[1] 1 2 7 9 10 11 15 17 18 22 23 29 35 40

print(pairs_findr_merger(lst1 = list(c(1, 1), c(22, 23)),
                          lst2 = list(c(1, 1, 2, 2), c(3, 21, 27, 32))))

[[1]]
[1] 1 1 2 2 3 3

[[2]]
[1] 3 21 22 23 27 32

```

---

pairs\_insertr

---

*pairs\_insertr*


---

## Description

Takes a character representing an arbitrary condition (like ReGeX for example) or an information (to a parser for example), vectors containing all the pair of pattern that potentially surrounds condition (flagged\_pair\_v and corr\_v), and a vector containing all the conjunction character, as input and returns the character with all or some of the condition surrounded by the pair characters. See examples. All the pair characters are inserted according to the closest pair they found prioritizing those found next to the condition and on the same depth-level and , if not found, the pair found at the n+1 depth-level.

## Usage

```

pairs_insertr(
  inpt,
  algo_used = c(1:3),
  flagged_pair_v = c(")", "["),
  corr_v = c("(", "["),
  flagged_conj_v = c("&", "|")
)

```

## Arguments

inpt	is the input character representing an arbitrary condition, like ReGex for example, or information to a parser for example
algo_used	is a vector containing one or more of the 3 algorithms used. The first algorithm will simply put the pair of parenthesis at the condition surrounded and/or after a character flagged (in flagged_conj_v) as a conjunction. The second algorithm will put parenthesis at the condition that are located after other conditions that are surrounded by a pair. The third algorithm will put a pair at all the condition, it is very powerfull but takes a longer time. See examples and make experience to see which combination of algorithm(s) is the most efficient for your use case.

flagged\_pair\_v  
is a vector containing all the first character of the pairs

corr\_v  
is a vector containing all the last character of the pairs

flagged\_conj\_v  
is a vector containing all the conjunction character

### Examples

```
print(pairs_insertr(inpt = "([one]|two|twob)three(four)", algo_used = c(1)))

[1] "([one]| [two]| [twob])three(four) "
```

```
print(pairs_insertr(inpt = "(one|[two]|twob)three(four)", algo_used = c(2)))

[1] "(one|[two]| [twob]) (three) (four) "
```

```
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2)))

[1] "(oneA|[one]| [two]| [twob]) (three) (four) "
```

```
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2, 3)))

[1] "([oneA]| [one]| [two]| [twob]) (three) (four) "
```

```
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(3)))

[1] "([oneA]| [one]| (two) | (twob)) (three) (four) "
```

```
print(pairs_insertr(inpt = "(oneA|[one]|two|twob)three((four))", algo_used = c(3)))

[1] "([oneA]| [(one)] | (two) | (twob)) (three) ((four)) "
```

---

pairs_insertr2	<i>pairs_insertr2</i>
----------------	-----------------------

---

### Description

Takes a character representing an arbitrary condition (like ReGeX for example) or an information (to a parser for example), vectors containing all the pair of pattern that potentially surrounds condition (flagged\_pair\_v and corr\_v), and a vector containing all the conjunction character, as input and returns the character with all or some of the condition surrounded by the pair characters. See examples. All the pair characters are inserted according to the closest pair they found prioritizing those found next to the condition and on the same depth-level and , if not found, the pair found at the n+1 depth-level.

### Usage

```
pairs_insertr2(
  inpt,
  algo_used = c(1:3),
  flagged_pair_v = c(")", "["),
  corr_v = c("(", "["),
```

```

    flagged_conj_v = c("&", "|"),
    method = c("(", ")")
)

```

### Arguments

<code>inpt</code>	is the input character representing an arbitrary condition, like ReGex for example, or information to a parser for example
<code>algo_used</code>	is a vector containing one or more of the 3 algorithms used. The first algorithm will simply put the pair of parenthesis at the condition surrounded and/or after a character flagged (in <code>flagged_conj_v</code> ) as a conjunction. The second algorithm will put parenthesis at the condition that are located after other conditions that are surrounded by a pair. The third algorithm will put a pair at all the condition, it is very powerfull but takes a longer time. See examples and make experience to see which combination of algorithm(s) is the most efficient for your use case.
<code>flagged_pair_v</code>	is a vector containing all the first character of the pairs
<code>corr_v</code>	is a vector containing all the last character of the pairs
<code>flagged_conj_v</code>	is a vector containing all the conjunction character
<code>method</code>	is length 2 vector containing as a first index, the first character of the pair inserted, and at the last index, the second and last character of the pair

### Examples

```

print(pairs_insertr2(inpt = "([one]|two|twob)three(four)", algo_used = c(1), method = c(
[1] "([one]|(two)|(twob))three(four)"

print(pairs_insertr2(inpt = "([one]|two|twob)three(four)", algo_used = c(1), method = c(
[1] "([one]|[two]|[twob])three(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2)))
[1] "(oneA|[one]|(two)|(twob))(three)(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2), meth
    flagged_pair_v = c(")", "[", "#"), corr_v = c("(", "[", "-"))
[1] "(oneA|[one]|-two#|-twob#)-three#(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(1, 2, 3)))
[1] "((oneA|[one]|(two)|(twob))(three)(four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three(four)", algo_used = c(3), method
[1] "([oneA|[one]|two]|[twob])[three](four)"

print(pairs_insertr2(inpt = "(oneA|[one]|two|twob)three((four))", algo_used = c(3)))
[1] "((oneA|[one]|(two)|(twob))(three)((four))"

```

---

paste_datf	<i>paste_datf</i>
------------	-------------------

---

### Description

Return a vector composed of pasted elements from the input dataframe at the same index.

### Usage

```
paste_datf(inpt_datf, sep = "")
```

### Arguments

inpt_datf	is the input dataframe
sep	is the separator between pasted elements, defaults to ""

### Examples

```
print(paste_datf(inpt_datf=data.frame(c(1, 2, 1), c(33, 22, 55))))
#[1] "133" "222" "155"
```

---

pattern_generator	<i>pattern_generator</i>
-------------------	--------------------------

---

### Description

Allow to create patterns which have a part that is varying randomly each time.

### Usage

```
pattern_generator(base_, from_, nb, hmn = 1, after = 1, sep = "")
```

### Arguments

base_	is the pattern that will be kept
from_	is the vector from which the elements of the random part will be generated
nb	is the number of random pattern chosen for the varying part
hmn	is how many of varying pattern from the same base will be created
after	is set to 1 by default, it means that the varying part will be after the fixed part, set to 0 if you want the varying part to be before
sep	is the separator between all patterns in the returned value

## Examples

```
print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=1, hmn=3))

# [1] "ouier" "ouire" "ouier"

print(pattern_generator(base_="oui", from_=c("er", "re", "ere"), nb=2, hmn=3, after=0, se

# [1] "er-re-o-u-i" "ere-re-o-u-i" "ere-er-o-u-i"
```

---

pattern\_gettr

*pattern\_gettr*

---

## Description

Search for pattern(s) contained in a vector in another vector and return a list containing matched one (first index) and their position (second index) according to these rules: First case: Search for patterns strictly, it means that the searched pattern(s) will be matched only if the patterns contained in the vector that is being explored by the function are present like this c("pattern\_searched", "other", ..., "pattern\_searched") and not as c("other\_thing pattern\_searched other\_thing", "other", ..., "pattern\_searched other\_thing") Second case: It is the opposite to the first case, it means that if the pattern is partially present like in the first position and the last, it will be considered like a matched pattern. REGEX can also be used as pattern

## Usage

```
pattern_gettr(
  word_,
  vct,
  occ = c(1),
  strict,
  btwn,
  all_in_word = "yes",
  notatall = "###"
)
```

## Arguments

word_	is the vector containing the patterns
vct	is the vector being searched for patterns
occ	a vector containing the occurrence of the pattern in word_ to be matched in the vector being searched, if the occurrence is 2 for the nth pattern in word_ and only one occurrence is found in vct so no pattern will be matched, put "forever" to no longer depend on the occurrence for the associated pattern
strict	a vector containing the "strict" condition for each nth vector in word_ ("strict" is the string to activate this option)
btwn	is a vector containing the condition ("yes" to activate this option) meaning that if "yes", all elements between two matched pattern in vct will be returned, so the patterns you enter in word_ have to be in the order you think it will appear in vct

`all_in_word` is a value (default set to "yes", "no" to activate this option) that, if activated, won't authorized a previous matched pattern to be matched again

`notatall` is a string that you are sure is not present in `vct`

### Examples

```
print(pattern_gettr(word=c("oui", "non", "erer"), vct=c("oui", "oui", "non", "oui",
  "non", "opp", "opp", "erer", "non", "ok"), occ=c(1, 2, 1),
  btwn=c("no", "yes", "no"), strict=c("no", "no", "ee")))

#[[1]]
#[1] 1 5 8
#
#[[2]]
#[1] "oui" "non" "opp" "opp" "erer"
```

---

`pattern_tuning`      *pattern\_tuning*

---

### Description

Allow to tune a pattern very precisely and output a vector containing its variations `n` times.

### Usage

```
pattern_tuning(
  pattn,
  spe_nb,
  spe_l,
  exclude_type,
  hmn = 1,
  rg = c(1, nchar(pattn))
)
```

### Arguments

`pattn` is the character that will be tuned

`spe_nb` is the number of new character that will be replaced

`spe_l` is the source vector from which the new characters will replace old ones

`exclude_type` is character that won't be replaced

`hmh` is how many output the function will return

`rg` is a vector with two parameters (index of the first letter that will be replaced, index of the last letter that will be replaced) default is set to all the letters from the source pattern

### Examples

```
print(pattern_tuning(pattn="oui", spe_nb=2, spe_l=c("e", "r", "T", "O"), exclude_type="o")

#[1] "orT" "oTr" "oOi"
```

---

power_to_char	<i>power_to_char</i>
---------------	----------------------

---

### Description

Convert a scientific number to a string representing normally the number.

### Usage

```
power_to_char(inpt_v = c())
```

### Arguments

inpt_v	is the input vector containing scientific number, but also other elements that won't be taken in count
--------	--

### Examples

```
print(power_to_char(inpt_v = c(22 * 10000000, 12, 9 * 0.0000002)))
[1] "22000000000" "12" "0.00000018"
```

---

pre_to_post_idx	<i>pre_to_post_idx</i>
-----------------	------------------------

---

### Description

Allow to convert indexes from a pre-vector to post-indexes based on a current vector, see examples

### Usage

```
pre_to_post_idx(inpt_v = c(), inpt_idx = c(1:length(inppt_v)))
```

### Arguments

inpt_v	is the new vector
inpt_idx	is the vector containing the pre-indexes

### Examples

```
print(pre_to_post_idx(inpt_v = c("oui", "no", "eee"), inpt_idx = c(1:8)))
[1] 1 1 1 2 2 3 3 3
As if the first vector was c("o", "u", "i", "n", "o", "e", "e", "e")
```



---

ptrn_switchr	<i>ptrn_switchr</i>
--------------	---------------------

---

## Description

Allow to switch, copy pattern for each element in a vector. Here a pattern is the values that are separated by a same separator. Example: "xx-xxx-xx" or "xx/xx/xxxx". The xx like values can be swiched or copied from whatever index to whatever index. Here, the index is like this 1-2-3 etcetera, it is relative of the separator.

## Usage

```
ptrn_switchr(inpt_l, f_idx_l = c(), t_idx_l = c(), sep = "-", default_val = NA)
```

## Arguments

inpt_l	is the input vector
f_idx_l	is a vector containing the indexes of the pattern you want to be altered.
t_idx_l	is a vector containing the indexes to which the indexes in f_idx_l are related.
sep	is the separator, defaults to "-"
default_val	is the default value , if not set to NA, of the pattern at the indexes in f_idx_l. If it is not set to NA, you do not need to fill t_idx_l because this is the vector containing the indexes of the patterns that will be set as new values relatively to the indexes in f_idx_l. Defaults to NA.

## Examples

```
print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1, 2, 3), t_idx_l=c(3, 2, 1)))

#[1] "11-01-2022" "14-01-2022" "21-01-2022" "01-01-2022"

print(ptrn_switchr(inpt_l=c("2022-01-11", "2022-01-14", "2022-01-21",
"2022-01-01"), f_idx_l=c(1), default_val="ee"))

#[1] "ee-01-11" "ee-01-14" "ee-01-21" "ee-01-01"
```

---

ptrn_twkr	<i>ptrn_twkr</i>
-----------	------------------

---

## Description

Allow to modify the pattern length of element in a vector according to arguments. What is here defined as a pattern is something like this xx-xx-xx or xx/xx/xxx... So it is defined by the separator

**Usage**

```
ptrn_twkr(
  inpt_l,
  depth = "max",
  sep = "-",
  default_val = "0",
  add_sep = TRUE,
  end_ = TRUE
)
```

**Arguments**

<code>inpt_l</code>	is the input vector
<code>depth</code>	is the number (numeric) of separator it will keep as a result. To keep the number of separator of the element that has the minimum amount of separator do <code>depth="min"</code> and <code>depth="max"</code> (character) for the opposite. This value defaults to "max".
<code>sep</code>	is the separator of the pattern, defaults to "-"
<code>default_val</code>	is the default val that will be placed between the separator, defaults to "00"
<code>add_sep</code>	defaults to TRUE. If set to FALSE, it will remove the separator for the patterns that are included in the interval between the depth amount of separator and the actual number of separator of the element.
<code>end_</code>	is if the default_val will be added at the end or at the beginning of each element that lacks length compared to depth

**Examples**

```
v <- c("2012-06-22", "2012-06-23", "2022-09-12", "2022")

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE)

#[1] "2012-06-22" "2012-06-23" "2022-09-12" "2022-00-00"

ptrn_twkr(inpt_l=v, depth=1, sep="-", default_val="00", add_sep=TRUE)

#[1] "2012-06" "2012-06" "2022-09" "2022-00"

ptrn_twkr(inpt_l=v, depth="max", sep="-", default_val="00", add_sep=TRUE, end_=FALSE)

#[1] "2012-06-22" "2012-06-23" "2022-09-12" "00-00-2022"
```

---

rearangr\_v

---

*rearangr\_v*


---

**Description**

Rearranges a vector "w\_v" according to another vector "inpt\_v". inpt\_v contains a sequence of number. inpt\_v and w\_v have the same size and their indexes are related. The output will be a vector containing all the elements of w\_v rearranges in descending or ascending order according to inpt\_v

**Usage**

```
rearangr_v(inpt_v, w_v, how = "increasing")
```

**Arguments**

inpt_v	is the vector that contains the sequence of number
w_v	is the vector containing the elements related to inpt_v
how	is the way the elements of w_v will be outputed according to if inpt_v will be sorted ascendigly or descendigly

**Examples**

```
print(rearangr_v(inpt_v=c(23, 21, 56), w_v=c("oui", "peut", "non"), how="decreasing"))
#[1] "non" "oui" "peut"
```

---

regex_spe_detect	<i>regex_spe_detect</i>
------------------	-------------------------

---

**Description**

Takes a character as input and returns its regex-friendly character for R.

**Usage**

```
regex_spe_detect(inpt)
```

**Arguments**

inpt	the input character
------	---------------------

**Examples**

```
print(regex_spe_detect("o"))
[1] "o"

print(regex_spe_detect("("))
[1] "\\("

print(regex_spe_detect("tr(o)m"))
[1] "tr\\(o\\)m"

print(regex_spe_detect(inpt="fggfg[fggf]fgfg(vg?fgfgf.gf)"))
[1] "fggfg\\[fggf\\]fgfg\\(vg\\?fgfgf\\.gf\\)"
```

regroupr

*regroupr***Description**

Allow to sort data like "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to what you want. For example it can be to "c(X1/Y1/Z1, X1/Y1/Z2, ...)"

**Usage**

```
regroupr(
  inpt_v,
  sep_ = "-",
  order = c(1:length(unlist(strsplit(x = inpt_v[1], split = sep_)))),
  l_order = NA
)
```

**Arguments**

<code>inpt_v</code>	is the input vector containing all the data you want to sort in a specific way. All the sub-elements should be separated by a unique separator such as "-" or "/"
<code>sep_</code>	is the unique separator separating the sub-elements in each elements of <code>inpt_v</code>
<code>order</code>	is a vector describing the way the elements should be sorted. For example if you want this dataset "c(X1/Y1/Z1, X2/Y1/Z2, ...)" to be sorted by the last element you should have <code>order=c(3:1)</code> , for example, and it should returns something like this <code>c(X1/Y1/Z1, X2/Y1/Z1, X1/Y2/Z1, ...)</code> assuming you have only two values for X.
<code>l_order</code>	is a list containing the vectors of values you want to order first for each sub-elements

**Examples**

```
vec <- multitud(l=list(c("a", "b"), c("1", "2"), c("A", "Z", "E"), c("Q", "F")), sep_="/")

print(vec)

# [1] "a/1/A/Q" "b/1/A/Q" "a/2/A/Q" "b/2/A/Q" "a/1/Z/Q" "b/1/Z/Q" "a/2/Z/Q"
# [8] "b/2/Z/Q" "a/1/E/Q" "b/1/E/Q" "a/2/E/Q" "b/2/E/Q" "a/1/A/F" "b/1/A/F"
# [15] "a/2/A/F" "b/2/A/F" "a/1/Z/F" "b/1/Z/F" "a/2/Z/F" "b/2/Z/F" "a/1/E/F"
# [22] "b/1/E/F" "a/2/E/F" "b/2/E/F"

print(regroupr(inpt_v=vec, sep_="/"))

# [1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
# [7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
# [13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/1/18/18"
# [19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23" "b/2/24/24"

vec <- vec[-2]

print(regroupr(inpt_v=vec, sep_="/"))
```

```
# [1] "a/1/1/1" "a/1/2/2" "a/1/3/3" "a/1/4/4" "a/1/5/5" "a/1/6/6"
# [7] "a/2/7/7" "a/2/8/8" "a/2/9/9" "a/2/10/10" "a/2/11/11" "a/2/12/12"
#[13] "b/1/13/13" "b/1/14/14" "b/1/15/15" "b/1/16/16" "b/1/17/17" "b/2/18/18"
#[19] "b/2/19/19" "b/2/20/20" "b/2/21/21" "b/2/22/22" "b/2/23/23"

print(regrouppr(inpt_v=vec, sep_="/", order=c(4:1)))

#[1] "1/1/A/Q" "2/2/A/Q" "3/3/A/Q" "4/4/A/Q" "5/5/Z/Q" "6/6/Z/Q"
# [7] "7/7/Z/Q" "8/8/Z/Q" "9/9/E/Q" "10/10/E/Q" "11/11/E/Q" "12/12/E/Q"
#[13] "13/13/A/F" "14/14/A/F" "15/15/A/F" "16/16/A/F" "17/17/Z/F" "18/18/Z/F"
#[19] "19/19/Z/F" "20/20/Z/F" "21/21/E/F" "22/22/E/F" "23/23/E/F" "24/24/E/F"
```

r\_print

*r\_print***Description**

Allow to print vector elements in one row.

**Usage**

```
r_print(inpt_v, sep_ = "and", begn = "This is", end = ", voila!")
```

**Arguments**

inpt_v	is the input vector
sep_	is the separator between each elements
begn	is the character put at the beginning of the print
end	is the character put at the end of the print

**Examples**

```
print(r_print(inpt_v=c(1:33)))

#[1] "This is 1 and 2 and 3 and 4 and 5 and 6 and 7 and 8 and 9 and 10 and 11 and 12 and
#and 14 and 15 and 16 and 17 and 18 and 19 and 20 and 21 and 22 and 23 and 24 and 25 and
#and 27 and 28 and 29 and 30 and 31 and 32 and 33 and , voila!"
```

save\_until

*save\_until***Description**

Get the elements in each vector from a list that are located before certain values

**Usage**

```
save_until(inpt_l = list(), val_to_stop_v = c())
```

**Arguments**

`inpt_l` is the input list containing all the vectors

`val_to_stop_v` is a vector containing the values that marks the end of the vectors returned in the returned list, see the examples

**Examples**

```
print(save_until(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3, 4))

#[[1]]
#[1] 1 2
#
#[[2]]
#[1] 1 1
#
#[[3]]
#[1] 1 2

print(save_until(inpt_l=list(c(1:4), c(1, 1, 3, 4), c(1, 2, 4, 3)), val_to_stop_v=c(3)))

#[[1]]
#[1] 1 2
#
#[[2]]
#[1] 1 1
#
#[[3]]
#[1] 1 2 4
```

---

see\_datf

---

see\_datf

---

**Description**

Allow to return a dataframe with special value cells (ex: TRUE) where the condition entered are respected and another special value cell (ex: FALSE) where these are not

**Usage**

```
see_datf(
  datf,
  condition_l,
  val_l,
  conjunction_l = c(),
  rt_val = TRUE,
  f_val = FALSE
)
```

## Arguments

<code>datf</code>	is the input dataframe
<code>condition_l</code>	is the vector of the possible conditions (" <code>==</code> ", " <code>&gt;</code> ", " <code>&lt;</code> ", " <code>!=</code> ", " <code>%%</code> ", " <code>reg</code> ", " <code>not_reg</code> ", " <code>sup_nchar</code> ", " <code>inf_nchar</code> ", " <code>nchar</code> ") (equal to some elements in a vector, greater than, lower than, not equal to, is divisible by, the regex condition returns TRUE, the regex condition returns FALSE, the length of the elements is strictly superior to X, the length of the element is strictly inferior to X, the length of the element is equal to one element in a vector), you can put the same condition n times.
<code>val_l</code>	is the list of vectors containing the values or vector of values related to <code>condition_l</code> (so the vector of values has to be placed in the same order)
<code>conjunction_l</code>	contains the and or conjunctions, so if the length of <code>condition_l</code> is equal to 3, there will be 2 conjunctions. If the length of <code>conjunction_l</code> is inferior to the length of <code>condition_l</code> minus 1, <code>conjunction_l</code> will match its goal length value with its last argument as the last arguments. For example, <code>c("&amp;", "l", "&amp;")</code> with a goal length value of 5 -> <code>c("&amp;", "l", "&amp;", "&amp;", "&amp;")</code>
<code>rt_val</code>	is a special value cell returned when the conditions are respected
<code>f_val</code>	is a special value cell returned when the conditions are not respected

## Details

This function will return an error if number only comparative conditions are given in addition to having character values in the input dataframe.

## Examples

```
datf1 <- data.frame(c(1, 2, 4), c("a", "a", "zu"))

print(see_datf(datf=datf1, condition_l=c("nchar"), val_l=list(c(1))))

#      X1      X2
#1 TRUE   TRUE
#2 TRUE   TRUE
#3 TRUE FALSE

print(see_datf(datf=datf1, condition_l=c("=="), val_l=list(c("a", 1))))

#      X1      X2
#1 TRUE   TRUE
#2 FALSE  TRUE
#3 FALSE FALSE

print(see_datf(datf=datf1, condition_l=c("nchar"), val_l=list(c(1, 2))))

#      X1      X2
#1 TRUE   TRUE
#2 TRUE   TRUE
#3 TRUE   TRUE

print(see_datf(datf=datf1, condition_l=c("not_reg"), val_l=list("[a-z]")))
```

```
#      X1      X2
#1 TRUE FALSE
#2 TRUE FALSE
#3 TRUE FALSE
```

---

see\_diff

*see\_diff*


---

### Description

Output the opposite of intersect(a, b). Already seen at: <https://stackoverflow.com/questions/19797954/function-to-find-symmetric-difference-opposite-of-intersection-in-r>

### Usage

```
see_diff(vec1 = c(), vec2 = c())
```

### Arguments

```
vec1          is the first vector
vec2          is the second vector
```

### Examples

```
print(see_diff(c(1:7), c(4:12)))

[1] 1 2 3 8 9 10 11 12
```

---

see\_diff\_all

*see\_diff\_all*


---

### Description

Allow to perform the opposite of intersect function to n vectors.

### Usage

```
see_diff_all(...)
```

### Arguments

```
...          are all the input vectors
```



**Examples**

```
vec1 <- c(3:6)
vec2 <- c(1:8)
vec3 <- c(12:16)

print(see_diff_all(vec1, vec2))

[1] 1 2 7 8

print(see_diff_all(vec1, vec2, vec3))

[1] 3 4 5 6 1 2 7 8 12 13 14 15 16
```

---

see\_file

*see\_file*


---

**Description**

Allow to get the filename or its extension

**Usage**

```
see_file(string_, index_ext = 1, ext = TRUE)
```

**Arguments**

string_	is the input string
index_ext	is the occurrence of the dot that separates the filename and its extension
ext	is a boolean that if set to TRUE, will return the file extension and if set to FALSE, will return filename

**Examples**

```
print(see_file(string_="file.abc.xyz"))

#[1] ".abc.xyz"

print(see_file(string_="file.abc.xyz", ext=FALSE))

#[1] "file"

print(see_file(string_="file.abc.xyz", index_ext=2))

#[1] ".xyz"
```

---

see\_idx

see\_idx

---

### Description

Returns a boolean vector to see if a set of elements contained in v1 is also contained in another vector (v2)

### Usage

```
see_idx(v1, v2)
```

### Arguments

v1	is the first vector
v2	is the second vector

### Examples

```
print(see_idx(v1=c("oui", "non", "peut", "oo"), v2=c("oui", "peut", "oui")))

#[1]  TRUE FALSE  TRUE  FALSE
```

---

see\_inside

see\_inside

---

### Description

Return a list containing all the column of the files in the current directory with a chosen file extension and its associated file and sheet if xlsx. For example if i have 2 files "out.csv" with 2 columns and "out.xlsx" with 1 column for its first sheet and 2 for its second one, the return will look like this: c(column\_1, column\_2, column\_3, column\_4, column\_5, unique\_separator, "1-2-out.csv", "3-3-sheet\_1-out.xlsx", 4-5-sheet\_2-out.xlsx)

### Usage

```
see_inside(
  pattern_,
  path_ = ".",
  sep_ = c(", "),
  unique_sep = "#####",
  rec = FALSE
)
```

**Arguments**

pattern_	is a vector containin the file extension of the spreadsheets ("xlsx", "csv"...)
path_	is the path where are located the files
sep_	is a vector containing the separator for each csv type file in order following the operating system file order, if the vector does not match the number of the csv files found, it will assume the separator for the rest of the files is the same as the last csv file found. It means that if you know the separator is the same for all the csv type files, you just have to put the separator once in the vector.
unique_sep	is a pattern that you know will never be in your input files
rec	is a boolean allows to get files recursively if set to TRUE, defaults to TRUE If x is the return value, to see all the files name, position of the columns and possible sheet name associantied with, do the following:

---

see\_mode

---

see\_mode

---

**Description**

Allow to get the mode of a vector, see examples.

**Usage**

```
see_mode(inpt_v = c())
```

**Arguments**

inpt\_v is the input vector

**Examples**

```
print(see_mode(inpt_v = c(1, 1, 2, 2, 2, 3, 1, 2)))
[1] 2

print(see_mode(inpt_v = c(1, 1, 2, 2, 2, 3, 1)))
[1] 1
```

---

selected_char	<i>selected_char</i>
---------------	----------------------

---

### Description

Allow to generate a char based on a combinaison on characters from a vector and a number

### Usage

```
selected_char(n, base_char = letters)
```

### Arguments

n	is how many sequence of numbers will be generated
base_char	is the vector containing the elements from which the character is generated

### Examples

```
print(selected_char(1222))

[1] "zta"
```

---

sort_date	<i>sort_date</i>
-----------	------------------

---

### Description

Allow to sort any vector containing a date, from any kind of format (my, hdmy, ymd ...), see examples.

### Usage

```
sort_date(inpt_v, frmt, sep_ = "-", ascending = FALSE, give = "value")
```

### Arguments

inpt_v	is the input vector containing all the dates
frmt	is the format of the dates, (any combinaison of letters "s" for second, "n", for minute, "h" for hour, "d" for day, "m" for month and "y" for year)
sep_	is the separator used for the dates
ascending	is the used to sort the dates
give	takes only two values "index" or "value", if give == "index", the function will output the index of sorted dates from inpt_v, if give == "value", the function will output the value, it means directly the sorted dates in inpt_v, see examples

**Examples**

```
print(sort_date(inpt_v = c("01-11-2025", "08-08-1922", "12-04-1966")
, frmt = "dmy", sep_ = "-", ascending = TRUE, give = "value"))

[1] "08-08-1922" "12-04-1966" "01-11-2025"

print(sort_date(inpt_v = c("01-11-2025", "08-08-1922", "12-04-1966")
, frmt = "dmy", sep_ = "-", ascending = FALSE, give = "value"))

[1] "01-11-2025" "12-04-1966" "08-08-1922"

print(sort_date(inpt_v = c("01-11-2025", "08-08-1922", "12-04-1966")
, frmt = "dmy", sep_ = "-", ascending = TRUE, give = "index"))

[1] 2 3 1

print(sort_date(inpt_v = c("22-01-11-2025", "11-12-04-1966", "12-12-04-1966")
, frmt = "hdmy", sep_ = "-", ascending = FALSE, give = "value"))

[1] "22-01-11-2025" "12-12-04-1966" "11-12-04-1966"

print(sort_date(inpt_v = c("03-22-01-11-2025", "56-11-12-04-1966", "23-12-12-04-1966")
, frmt = "nhdmy", sep_ = "-", ascending = FALSE, give = "value"))

[1] "03-22-01-11-2025" "23-12-12-04-1966" "56-11-12-04-1966"
```

---

sort_normal_qual	<i>sort_normal_qual</i>
------------------	-------------------------

---

**Description**

Sort qualitative modalities that have their frequency normally distributed from an unordered dataset, see examples. This function uses an another algorithym than choose\_normal\_qual2 which may be faster.

**Usage**

```
sort_normal_qual(inpt_datf)
```

**Arguments**

`inpt_datf` is the input dataframe, containing the values in the first column and their frequency in the second

**Examples**

```
sample_val <- round(rnorm(n = 2000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)
sample_qual <- infinite_char_seq(n = length(sample_freq))
datf_test <- data.frame(sample_qual, sample_freq)
datf_test[, 2] <- datf_test[, 2] / sum(datf_test[, 2]) # optional
```

```
print(datf_test)
```

```

    sample_qual sample_freq
1             a 0.208695652
2             b 0.234782609
3             c 0.321739130
4             d 0.339130435
5             e 0.330434783
6             f 0.069565217
7             g 0.234782609
8             h 0.400000000
9             i 0.347826087
10            j 0.043478261
11            k 0.278260870
12            l 0.286956522
13            m 0.243478261
14            n 0.147826087
15            o 0.234782609
16            p 0.252173913
17            q 0.417391304
18            r 0.095652174
19            s 0.313043478
20            t 0.008695652
21            u 0.130434783
22            v 0.391304348
23            w 0.113043478
24            x 0.295652174
25            y 0.243478261
26            z 0.382608696
27           aa 0.008695652
28           ab 0.347826087
29           ac 0.330434783
30           ad 0.321739130
31           ae 0.347826087
32           af 0.321739130
33           ag 0.173913043
34           ah 0.278260870
35           ai 0.278260870
36           aj 0.347826087
37           ak 0.026086957
38           al 0.295652174
39           am 0.226086957
40           an 0.295652174
41           ao 0.234782609
42           ap 0.113043478
43           aq 0.234782609
44           ar 0.173913043
45           as 0.017391304
46           at 0.252173913
47           au 0.078260870
48           av 0.086956522
49           aw 0.278260870
50           ax 0.086956522
51           ay 0.200000000
52           az 0.295652174
53           ba 0.052173913
54           bb 0.165217391

```

55	bc	0.408695652
56	bd	0.269565217
57	be	0.104347826
58	bf	0.391304348
59	bg	0.104347826
60	bh	0.043478261
61	bi	0.200000000
62	bj	0.095652174
63	bk	0.191304348
64	bl	0.008695652
65	bm	0.165217391
66	bn	0.226086957
67	bo	0.086956522
68	bp	0.017391304
69	bq	0.121739130
70	br	0.234782609
71	bs	0.121739130
72	bt	0.078260870
73	bu	0.173913043
74	bv	0.104347826
75	bw	0.208695652
76	bx	0.017391304
77	by	0.243478261
78	bz	0.034782609
79	ca	0.017391304
80	cb	0.008695652
81	cc	0.173913043
82	cd	0.147826087
83	ce	0.060869565
84	cf	0.017391304
85	cg	0.060869565
86	ch	0.008695652
87	ci	0.208695652
88	cj	0.043478261
89	ck	0.052173913
90	cl	0.017391304
91	cm	0.017391304
92	cn	0.095652174
93	co	0.113043478
94	cp	0.017391304
95	cq	0.017391304
96	cr	0.026086957
97	cs	0.034782609
98	ct	0.017391304
99	cu	0.026086957
100	cv	0.026086957
101	cw	0.026086957
102	cx	0.017391304
103	cy	0.043478261
104	cz	0.008695652
105	da	0.034782609
106	db	0.017391304
107	dc	0.060869565
108	dd	0.008695652
109	de	0.008695652
110	df	0.017391304
111	dg	0.008695652

```

112          dh 0.008695652
113          di 0.017391304
114          dj 0.008695652
115          dk 0.008695652

```

```
print(sort_normal_qual(inpt_datf = datf_test))
```

```

0.00869565217391304 0.00869565217391304 0.00869565217391304 0.00869565217391304
      "aa"          "cb"          "cz"          "de"
0.00869565217391304 0.00869565217391304 0.0173913043478261 0.0173913043478261
      "dh"          "dk"          "bp"          "ca"
0.0173913043478261 0.0173913043478261 0.0173913043478261 0.0173913043478261
      "cl"          "cp"          "ct"          "db"
0.0173913043478261 0.0260869565217391 0.0260869565217391 0.0347826086956522
      "di"          "cr"          "cv"          "bz"
0.0347826086956522 0.0434782608695652 0.0434782608695652 0.0521739130434783
      "da"          "bh"          "cy"          "ck"
0.0608695652173913 0.0695652173913043 0.0782608695652174 0.0869565217391304
      "cg"          "f"          "bt"          "ax"
0.0956521739130435 0.0956521739130435 0.104347826086957 0.11304347826087
      "r"          "cn"          "bg"          "w"
0.11304347826087 0.121739130434783 0.147826086956522 0.165217391304348
      "co"          "bs"          "n"          "bb"
0.173913043478261 0.173913043478261 0.191304347826087 0.2
      "ag"          "bu"          "bk"          "bi"
0.208695652173913 0.226086956521739 0.234782608695652 0.234782608695652
      "bw"          "am"          "b"          "o"
0.234782608695652 0.243478260869565 0.243478260869565 0.252173913043478
      "aq"          "m"          "by"          "at"
0.278260869565217 0.278260869565217 0.28695652173913 0.295652173913043
      "k"          "ai"          "l"          "al"
0.295652173913043 0.321739130434783 0.321739130434783 0.330434782608696
      "az"          "c"          "af"          "ac"
0.347826086956522 0.347826086956522 0.382608695652174 0.391304347826087
      "i"          "ae"          "z"          "bf"
0.408695652173913 0.417391304347826 0.4 0.391304347826087
      "bc"          "q"          "h"          "v"
0.347826086956522 0.347826086956522 0.339130434782609 0.330434782608696
      "aj"          "ab"          "d"          "e"
0.321739130434783 0.31304347826087 0.295652173913043 0.295652173913043
      "ad"          "s"          "an"          "x"
0.278260869565217 0.278260869565217 0.269565217391304 0.252173913043478
      "aw"          "ah"          "bd"          "p"
0.243478260869565 0.234782608695652 0.234782608695652 0.234782608695652
      "y"          "br"          "ao"          "g"
0.226086956521739 0.208695652173913 0.208695652173913 0.2
      "bn"          "ci"          "a"          "ay"
0.173913043478261 0.173913043478261 0.165217391304348 0.147826086956522
      "cc"          "ar"          "bm"          "cd"
0.130434782608696 0.121739130434783 0.11304347826087 0.104347826086957
      "u"          "bq"          "ap"          "bv"
0.104347826086957 0.0956521739130435 0.0869565217391304 0.0869565217391304
      "be"          "bj"          "bo"          "av"
0.0782608695652174 0.0608695652173913 0.0608695652173913 0.0521739130434783
      "au"          "dc"          "ce"          "ba"
0.0434782608695652 0.0434782608695652 0.0347826086956522 0.0260869565217391
      "cj"          "j"          "cs"          "cw"

```



```

0.0260869565217391 0.0260869565217391 0.0173913043478261 0.0173913043478261
      "cu"          "ak"          "df"          "cx"
0.0173913043478261 0.0173913043478261 0.0173913043478261 0.0173913043478261
      "cq"          "cm"          "cf"          "bx"
0.0173913043478261 0.00869565217391304 0.00869565217391304 0.00869565217391304
      "as"          "dj"          "dg"          "dd"
0.00869565217391304 0.00869565217391304 0.00869565217391304
      "ch"          "bl"          "t"

```

---

```
sort_normal_qual2  sort_normal_qual2
```

---

## Description

Sort qualitative modalities that have their frequency normally distributed from an unordered dataset, see examples. This function uses an another algorithm than choose\_normal\_qual which may be faster.

## Usage

```
sort_normal_qual2(inpt_datf)
```

## Arguments

`inpt_datf` is the input dataframe, containing the values in the first column and their frequency in the second

## Examples

```

sample_val <- round(rnorm(n = 2000, mean = 12, sd = 2), 1)
sample_freq <- unique_total(sample_val)
sample_qual <- infinite_char_seq(n = length(sample_freq))
datf_test <- data.frame(sample_qual, sample_freq)
datf_test[, 2] <- datf_test[, 2] / sum(datf_test[, 2])

print(datf_test)

```

```

      sample_qual sample_freq
1              a 0.208695652
2              b 0.234782609
3              c 0.321739130
4              d 0.339130435
5              e 0.330434783
6              f 0.069565217
7              g 0.234782609
8              h 0.400000000
9              i 0.347826087
10             j 0.043478261
11             k 0.278260870
12             l 0.286956522
13             m 0.243478261
14             n 0.147826087
15             o 0.234782609

```

16	p	0.252173913
17	q	0.417391304
18	r	0.095652174
19	s	0.313043478
20	t	0.008695652
21	u	0.130434783
22	v	0.391304348
23	w	0.113043478
24	x	0.295652174
25	y	0.243478261
26	z	0.382608696
27	aa	0.008695652
28	ab	0.347826087
29	ac	0.330434783
30	ad	0.321739130
31	ae	0.347826087
32	af	0.321739130
33	ag	0.173913043
34	ah	0.278260870
35	ai	0.278260870
36	aj	0.347826087
37	ak	0.026086957
38	al	0.295652174
39	am	0.226086957
40	an	0.295652174
41	ao	0.234782609
42	ap	0.113043478
43	aq	0.234782609
44	ar	0.173913043
45	as	0.017391304
46	at	0.252173913
47	au	0.078260870
48	av	0.086956522
49	aw	0.278260870
50	ax	0.086956522
51	ay	0.200000000
52	az	0.295652174
53	ba	0.052173913
54	bb	0.165217391
55	bc	0.408695652
56	bd	0.269565217
57	be	0.104347826
58	bf	0.391304348
59	bg	0.104347826
60	bh	0.043478261
61	bi	0.200000000
62	bj	0.095652174
63	bk	0.191304348
64	bl	0.008695652
65	bm	0.165217391
66	bn	0.226086957
67	bo	0.086956522
68	bp	0.017391304
69	bq	0.121739130
70	br	0.234782609
71	bs	0.121739130
72	bt	0.078260870

```

73      bu 0.173913043
74      bv 0.104347826
75      bw 0.208695652
76      bx 0.017391304
77      by 0.243478261
78      bz 0.034782609
79      ca 0.017391304
80      cb 0.008695652
81      cc 0.173913043
82      cd 0.147826087
83      ce 0.060869565
84      cf 0.017391304
85      cg 0.060869565
86      ch 0.008695652
87      ci 0.208695652
88      cj 0.043478261
89      ck 0.052173913
90      cl 0.017391304
91      cm 0.017391304
92      cn 0.095652174
93      co 0.113043478
94      cp 0.017391304
95      cq 0.017391304
96      cr 0.026086957
97      cs 0.034782609
98      ct 0.017391304
99      cu 0.026086957
100     cv 0.026086957
101     cw 0.026086957
102     cx 0.017391304
103     cy 0.043478261
104     cz 0.008695652
105     da 0.034782609
106     db 0.017391304
107     dc 0.060869565
108     dd 0.008695652
109     de 0.008695652
110     df 0.017391304
111     dg 0.008695652
112     dh 0.008695652
113     di 0.017391304
114     dj 0.008695652
115     dk 0.008695652

```

```
print(sort_normal_qual2(inpt_datf = datf_test))
```

```

0.00869565217391304 0.00869565217391304 0.00869565217391304 0.00869565217391304
      "aa"          "cb"          "cz"          "de"
0.00869565217391304 0.00869565217391304 0.0173913043478261 0.0173913043478261
      "dh"          "dk"          "bp"          "ca"
0.0173913043478261 0.0173913043478261 0.0173913043478261 0.0173913043478261
      "cl"          "cp"          "ct"          "db"
0.0173913043478261 0.0260869565217391 0.0260869565217391 0.0347826086956522
      "di"          "cr"          "cv"          "bz"
0.0347826086956522 0.0434782608695652 0.0434782608695652 0.0521739130434783
      "da"          "bh"          "cy"          "ck"
0.0608695652173913 0.0695652173913043 0.0782608695652174 0.0869565217391304

```

"cg"	"f"	"bt"	"ax"
0.0956521739130435	0.0956521739130435	0.104347826086957	0.11304347826087
"r"	"cn"	"bg"	"w"
0.11304347826087	0.121739130434783	0.147826086956522	0.165217391304348
"co"	"bs"	"n"	"bb"
0.173913043478261	0.173913043478261	0.191304347826087	0.2
"ag"	"bu"	"bk"	"bi"
0.208695652173913	0.226086956521739	0.234782608695652	0.234782608695652
"bw"	"am"	"b"	"o"
0.234782608695652	0.243478260869565	0.243478260869565	0.252173913043478
"aq"	"m"	"by"	"at"
0.278260869565217	0.278260869565217	0.28695652173913	0.295652173913043
"k"	"ai"	"l"	"al"
0.295652173913043	0.321739130434783	0.321739130434783	0.330434782608696
"az"	"c"	"af"	"ac"
0.347826086956522	0.347826086956522	0.382608695652174	0.391304347826087
"i"	"ae"	"z"	"bf"
0.408695652173913	0.417391304347826	0.4	0.391304347826087
"bc"	"q"	"h"	"v"
0.347826086956522	0.347826086956522	0.339130434782609	0.330434782608696
"aj"	"ab"	"d"	"e"
0.321739130434783	0.31304347826087	0.295652173913043	0.295652173913043
"ad"	"s"	"an"	"x"
0.278260869565217	0.278260869565217	0.269565217391304	0.252173913043478
"aw"	"ah"	"bd"	"p"
0.243478260869565	0.234782608695652	0.234782608695652	0.234782608695652
"y"	"br"	"ao"	"g"
0.226086956521739	0.208695652173913	0.208695652173913	0.2
"bn"	"ci"	"a"	"ay"
0.173913043478261	0.173913043478261	0.165217391304348	0.147826086956522
"cc"	"ar"	"bm"	"cd"
0.130434782608696	0.121739130434783	0.11304347826087	0.104347826086957
"u"	"bq"	"ap"	"bv"
0.104347826086957	0.0956521739130435	0.0869565217391304	0.0869565217391304
"be"	"bj"	"bo"	"av"
0.0782608695652174	0.0608695652173913	0.0608695652173913	0.0521739130434783
"au"	"dc"	"ce"	"ba"
0.0434782608695652	0.0434782608695652	0.0347826086956522	0.0260869565217391
"cj"	"j"	"cs"	"cw"
0.0260869565217391	0.0260869565217391	0.0173913043478261	0.0173913043478261
"cu"	"ak"	"df"	"cx"
0.0173913043478261	0.0173913043478261	0.0173913043478261	0.0173913043478261
"cq"	"cm"	"cf"	"bx"
0.0173913043478261	0.00869565217391304	0.00869565217391304	0.00869565217391304
"as"	"dj"	"dg"	"dd"
0.00869565217391304	0.00869565217391304	0.00869565217391304	
"ch"	"bl"	"t"	

str\_remove\_untl

str\_remove\_untl

## Description

Allow to remove pattern within elements from a vector precisely according to their occurrence.

**Usage**

```
str_remove_until(
  inpt_v,
  ptrn_rm_v = c(),
  until = list(c(1)),
  nvr_following_ptrn = "NA"
)
```

**Arguments**

`inpt_v` is the input vector

`ptrn_rm_v` is a vector containing the patterns to remove

`until` is a list containing the occurrence(s) of each pattern to remove in the elements.

`nvr_following_ptrn` is a sequel of characters that you are sure is not present in any of the elements in `inpt_v`

**Examples**

```
vec <- c("45/56-/98mm", "45/56-/98mm", "45/56-/98-mm//")

print(str_remove_until(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1))))

#[1] "4556/98mm" "4556/98mm" "4556/98mm//"

print(str_remove_until(inpt_v=vec, ptrn_rm_v=c("-", "/"), until=list(c("max"), c(1:2))))

#[1] "455698mm" "455698mm" "455698mm//"

print(str_remove_until(inpt_v=vec[1], ptrn_rm_v=c("-", "/"), until=c("max")))

#[1] "455698mm" "455698mm" "455698mm"
```

sub\_mult

*sub\_mult***Description**

Performs a sub operation with n patterns and replacements.

**Usage**

```
sub_mult(inpt_v, pattern_v = c(), replacement_v = c())
```

**Arguments**

`inpt_v` is a vector containing all the elements that contains expressions to be substituted

`pattern_v` is a vector containing all the patterns to be substituted in any elements of `inpt_v`

`replacement_v` is a vector containing the expression that are going to substitute those provided by `pattern_v`

**Examples**

```
print(sub_mult(inpt_v = c("X and Y programming languages are great", "More X, more X!"),
              pattern_v = c("X", "Y", "Z"),
              replacement_v = c("C", "R", "GO")))

[1] "C and R programming languages are great"
[2] "More C, more X!"
```

---

successive_diff	<i>successive_diff</i>
-----------------	------------------------

---

**Description**

Allow to see the difference between the successive elements of an numeric vector

**Usage**

```
successive_diff(inpt_v)
```

**Arguments**

`inpt_v` is the input numeric vector

**Examples**

```
print(successive_diff(c(1:10)))

[1] 1 1 1 1 1

print(successive_diff(c(1:11, 13, 19)))

[1] 1 1 1 1 1 2 6
```

---

swipr	<i>swipr</i>
-------	--------------

---

**Description**

Returns an ordered dataframes according to the elements order given. The input dataframe has two columns, one with the ids which can be bonded to multiple elements in the other column.

**Usage**

```
swipr(inpt_datf, how_to = c(), id_w = 2, id_ids = 1)
```

**Arguments**

`inpt_datf` is the input dataframe  
`how_to` is a vector containing the elements in the order wanted  
`id_w` is the column number or the column name of the elements  
`id_ids` is the column number or the column name of the ids

**Examples**

```
datf <- data.frame("col1"=c("Af", "Al", "Al", "Al", "Arg", "Arg", "Arg", "Arm", "Arm", "A",
                             "col2"=c("B", "B", "G", "S", "B", "S", "G", "B", "G", "B"))

print(swipr(inpt_datf=datf, how_to=c("G", "S", "B")))
```

```
      col1 col2
1      Af    B
2      Al    G
3      Al    S
4      Al    B
5     Arg    G
6     Arg    S
7     Arg    B
8     Arm    G
9     Arm    B
10     Al    B
```

test\_order

*test\_order***Description**

Allow to get if two vectors have their commun elements in the same order, see examples

**Usage**

```
test_order(inpt_v_from, inpt_v_test)
```

**Arguments**

`is` the vector we want to test if its commun element with `inpt_v_from` are in the same order

**Examples**

```
print(test_order(inpt_v_from = c(1:8), inpt_v_test = c(1, 4)))

[1] TRUE

print(test_order(inpt_v_from = c(1:8), inpt_v_test = c(1, 4, 2)))

[1] FALSE
```

to\_unique

*to\_unique***Description**

Allow to transform a vector containing elements that have more than 1 occurrence to a vector with only unique elements.

**Usage**

```
to_unique(inpt_v, distinct_type = "suffix", distinct_val = "number", sep = "-")
```

**Arguments**

`inpt_v` is the input vectors

`distinct_type` takes two values: suffix or prefix

`distinct_val` takes two values: number (unique sequence of number to differentiate each value) or letter (unique sequence of letters to differentiate each value)

**Examples**

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "suffix",
  distinct_val = "number",
  sep = "-"))
```

```
[1] "a-1" "a-2" "e"   "a-3" "i-1" "i-2"
```

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "suffix",
  distinct_val = "letter",
  sep = "-"))
```

```
[1] "a-a" "a-b" "e"   "a-c" "i-a" "i-b"
```

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "prefix",
  distinct_val = "number",
  sep = "/"))
```

```
[1] "1/a" "2/a" "e"   "3/a" "1/i" "2/i"
```

```
print(to_unique(inpt_v = c("a", "a", "e", "a", "i", "i"),
  distinct_type = "prefix",
  distinct_val = "letter",
  sep = "_"))
```

```
[1] "a_a" "b_a" "e"   "c_a" "a_i" "b_i"
```



---

union\_all

*union\_all*


---

**Description**

Allow to perform a union function to n vectors.

**Usage**

```
union_all(...)
```

**Arguments**

... are all the input vectors

**Examples**

```
print(union_all(c(1, 2), c(3, 4), c(1:8)))
[1] 1 2 3 4 5 6 7 8

print(union_all(c(1, 2), c(3, 4), c(7:8)))
[1] 1 2 3 4 7 8
```

---

union\_keep

*union\_keep*


---

**Description**

Performs a union operation keeping the number of elements of all input vectors, see examples

**Usage**

```
union_keep(...)
```

**Arguments**

... are all the input vectors

**Examples**

```
print(union_keep(c("a", "ee", "ee"), c("p", "p", "a", "i"), c("a", "a", "z")))
[1] "a" "ee" "ee" "p" "p" "i" "z"

print(union_keep(c("a", "ee", "ee"), c("p", "p", "a", "i")))
[1] "a" "ee" "ee" "p" "p" "i"
```

---

unique_datf	<i>unique_datf</i>
-------------	--------------------

---

**Description**

Returns the input dataframe with the unique columns or rows.

**Usage**

```
unique_datf(inpt_datf, col = FALSE)
```

**Arguments**

- inpt\_datf is the input dataframe
- col is a parameter that specifies if the dataframe returned should have unique columns or rows, defaults to F, so the dataframe returned by default has unique rows

**Examples**

```
datf1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"))

print(unique_datf(inpt_datf=datf1))

#   c.1..2..1..3. c..a....z....a....p..
#1           1           a
#2           2           z
#4           3           p

datf1 <- data.frame(c(1, 2, 1, 3), c("a", "z", "a", "p"), c(1, 2, 1, 3))

print(unique_datf(inpt_datf=datf1, col=TRUE))

#   cur_v cur_v
#1     1     a
#2     2     z
#3     1     a
#4     3     p
```

---

unique_ltr_from_v	<i>unique_ltr_from_v</i>
-------------------	--------------------------

---

**Description**

Returns the unique characters contained in all the elements from an input vector "inpt\_v"

**Usage**

```
unique_ltr_from_v(inpt_v, keep_v = c("?", "!", ":", "&", ",", ".", letters))
```

**Arguments**

`inpt_v` is the input vector containing all the elements  
`keep_v` is the vector containing all the characters that the elements in `inpt_v` may contain

**Examples**

```
print(unique_ltr_from_v(inpt_v=c("bonjour", "lpoerc", "nonnour", "bonnour", "nonjour", "a  

#[1] "b" "o" "n" "j" "u" "r" "l" "p" "e" "c" "a" "v" "i"
```

---

unique_pos	<i>unique_pos</i>
------------	-------------------

---

**Description**

Allow to find the first index of the unique values from a vector.

**Usage**

```
unique_pos(vec)
```

**Arguments**

`vec` is the input vector

**Examples**

```
print(unique_pos(vec=c(3, 4, 3, 5, 6)))  

#[1] 1 2 4 5
```

---

unique_total	<i>unique_total</i>
--------------	---------------------

---

**Description**

Returns a vector with the total amount of occurrences for each element in the input vector. The occurrences of each element follow the same order as the unique function does, see examples

**Usage**

```
unique_total(inpt_v = c())
```

**Arguments**

`inpt_v` is the input vector containing all the elements

**Examples**

```
print(unique_total(inpt_v = c(1:12, 1)))

[1] 2 1 1 1 1 1 1 1 1 1 1 1

print(unique_total(inpt_v = c(1:12, 1, 11, 11)))

[1] 2 1 1 1 1 1 1 1 1 1 3 1

vec <- c(1:12, 1, 11, 11)
names(vec) <- c(1:15)
print(unique_total(inpt_v = vec))

  1  2  3  4  5  6  7  8  9 10 11 12
2  1  1  1  1  1  1  1  1  1  3  1
```

---

<code>until_stnl</code>	<i>until_stnl</i>
-------------------------	-------------------

---

**Description**

Maxes a vector to a chosen length. ex: if i want my vector `c(1, 2)` to be 5 of length this function will return me: `c(1, 2, 1, 2, 1)`

**Usage**

```
until_stnl(vec1, goal)
```

**Arguments**

- `vec1` is the input vector
- `goal` is the length to reach

**Examples**

```
print(until_stnl(vec1=c(1, 3, 2), goal=56))

# [1] 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3
#[39] 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3 2 1 3
```

---

val_replacer	<i>val_replacer</i>
--------------	---------------------

---

**Description**

Allow to replace value from dataframe to another one.

**Usage**

```
val_replacer(datf, val_replaced, val_replacor = TRUE)
```

**Arguments**

`datf` is the input dataframe  
`val_replaced` is a vector of the value(s) to be replaced  
`val_replacor` is the value that will replace `val_replaced`

**Examples**

```
print(val_replacer(datf=data.frame(c(1, "oo4", TRUE, FALSE), c(TRUE, FALSE, TRUE, TRUE)),
  val_replaced=c(TRUE), val_replacor="NA"))

#  c.1...oo4...T..F. c.T..F..T..T.
#1              1      NA
#2              oo4     FALSE
#3              NA      NA
#4             FALSE     NA
```

---

vector_replacor	<i>vector_replacor</i>
-----------------	------------------------

---

**Description**

Allow to replace certain values in a vector.

**Usage**

```
vector_replacor(inpt_v = c(), sus_val = c(), rpl_val = c(), grep_ = FALSE)
```

**Arguments**

`inpt_v` is the input vector  
`sus_val` is a vector containing all the values that will be replaced  
`rpl_val` is a vector containing the value of the elements to be replaced (`sus_val`), so `sus_val` and `rpl_val` should be the same size  
`grep_` is if the elements in `sus_val` should be equal to the elements to replace in `inpt_v` or if they just should found in the elements

Examples

```
print(vector_replacor(inpt_v=c(1:15), sus_val=c(3, 6, 8, 12),
  repl_val=c("oui", "non", "e", "a")))

# [1] "1" "2" "oui" "4" "5" "non" "7" "e" "9" "10" "11" "a"
#[13] "13" "14" "15"

print(vector_replacor(inpt_v=c("non", "zez", "pp a ftf", "fdatfd", "assistance",
  "ert", "repas", "repos"),
  sus_val=c("pp", "as", "re"), repl_val=c("oui", "non", "zz"), grep_=TRUE))

#[1] "non" "zez" "oui" "fdatfd" "non" "ert" "non" "zz"
```

---

vec_in_datf	<i>vec_in_datf</i>
-------------	--------------------

---

Description

Allow to get if a vector is in a dataframe. Returns the row and column of the vector in the dataframe if the vector is contained in the dataframe.

Usage

```
vec_in_datf(
  inpt_datf,
  inpt_vec = c(),
  coeff = 0,
  stop_until = 1,
  conventional = FALSE
)
```

Arguments

- inpt\_datf is the input dataframe
- inpt\_vec is the vector that may be in the input dataframe
- coeff is the "slope coefficient" of inpt\_vec
- stop\_until is the maximum number of the input vector the function returns, if in the dataframe
- conventional is if a positive slope coefficient means that the vector goes upward or downward

Examples

```
datf1 <- data.frame(c(1:5), c(5:1), c("a", "z", "z", "z", "a"))

print(datf1)

# c.1.5. c.5.1. c..a....z....z....z....a..
#1      1      5      a
#2      2      4      z
#3      3      3      z
#4      4      2      z
```

```

#5      5      1      a

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 4, "z"), coeff=1))

#NULL

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=1))

#[1] 5 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(3, "z"), coeff=1))

#[1] 3 2

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(4, "z"), coeff=-1))

#[1] 2 2

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(2, 3, "z"), coeff=-1))

#[1] 2 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(5, 2, "z"), coeff=-1, conventional=TRUE))

#[1] 5 1

datf1[4, 2] <- 1

print(vec_in_datf(inpt_datf=datf1, inpt_vec=c(1, "z"), coeff=-1, conventional=TRUE, stop_

#[1] 4 2 5 2

```

---

vlookup\_datf

*vlookup\_datf*


---

## Description

Allow to perform a vlookup on a dataframe

## Usage

```
vlookup_datf(datf, v_id, col_id = 1, included_col_id = "yes")
```

## Arguments

datf	is the input dataframe
v_id	is a vector containing the ids
col_id	is the column that contains the ids (default is equal to 1)
included_col_id	is if the result should return the col_id (default set to yes)

Examples

```
datf1 <- data.frame(c("az1", "az3", "az4", "az2"), c(1:4), c(4:1))

print(vlookup_datf(datf=datf1, v_id=c("az1", "az2", "az3", "az4")))
```

```
#   c..az1....az3....az4....az2.. c.1.4. c.4.1.
#2                                az1      1      4
#4                                az2      4      1
#21                               az3      2      3
#3                                az4      3      2
```

---

wider_datf	<i>wider_datf</i>
------------	-------------------

---

Description

Takes a dataframe as an input and the column to split according to a separator.

Usage

```
wider_datf(inpt_datf, col_to_splt = c(), sep_ = "-")
```

Arguments

- inpt\_datf is the input dataframe
- col\_to\_splt is a vector containing the number or the colnames of the columns to split according to a separator
- sep\_ is the separator of the elements to split to new columns in the input dataframe

Examples

```
datf1 <- data.frame(c(1:5), c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"), c(5:1))

datf2 <- data.frame("col1"=c(1:5), "col2"=c("o-y", "hj-yy", "er-y", "k-ll", "ooo-mm"))

print(wider_datf(inpt_datf=datf1, col_to_splt=c(2), sep_="-"))
```

```
#      pre_datf X.o.  X.y.
#o-y    1      "o"   "y"   5
#hj-yy  2      "hj"  "yy"  4
#er-y   3      "er"  "y"   3
#k-ll   4      "k"   "ll"  2
#ooo-mm 5      "ooo" "mm"  1
```

```
print(wider_datf(inpt_datf=datf2, col_to_splt=c("col2"), sep_="-"))
```

```
#      pre_datf X.o.  X.y.
#o-y    1      "o"   "y"
#hj-yy  2      "hj"  "yy"
#er-y   3      "er"  "y"
#k-ll   4      "k"   "ll"
#ooo-mm 5      "ooo" "mm"
```



# Index

all\_stat, [4](#)  
any\_join\_datf, [5](#)  
appndr, [7](#)  
  
better\_match, [8](#)  
better\_split, [9](#)  
better\_sub, [9](#)  
better\_sub\_mult, [10](#)  
better\_unique, [11](#)  
  
can\_be\_num, [12](#)  
closer\_ptrn, [13](#)  
closer\_ptrn\_adv, [15](#)  
clusterizer\_v, [16](#)  
colins\_datf, [19](#)  
converter\_date, [20](#)  
converter\_format, [21](#)  
cost\_and\_taxes, [21](#)  
cut\_v, [23](#)  
cutr\_v, [22](#)  
  
data\_gen, [24](#)  
data\_meshup, [26](#)  
date\_addr, [27](#)  
date\_converter\_reverse, [28](#)  
dcr\_untl, [29](#)  
dcr\_val, [29](#)  
depth\_pairs\_findr, [30](#)  
diff\_datf, [30](#)  
  
elements\_equalifier, [31](#)  
equalizer\_v, [32](#)  
extract\_normal, [32](#)  
extrt\_only\_v, [38](#)  
  
fillr, [39](#)  
fixer\_nest\_v, [40](#)  
fold\_rec, [40](#)  
fold\_rec2, [41](#)  
format\_date, [41](#)  
  
geo\_min, [42](#)  
get\_rec, [43](#)  
globe, [43](#)  
grep\_all, [44](#)  
grep\_all2, [44](#)  
groupr\_datf, [45](#)  
gsub\_mult, [46](#)  
  
how\_normal, [47](#)  
how\_unif, [49](#)  
  
id\_keep, [50](#)  
incr\_fillr, [51](#)  
infinite\_char\_seq, [52](#)  
inner\_all, [53](#)  
insert\_datf, [53](#)  
inter\_max, [56](#)  
inter\_min, [57](#)  
intersect\_all, [54](#)  
intersect\_mod, [55](#)  
is\_divisible, [59](#)  
isnt\_divisible, [58](#)  
  
join\_n\_lvl, [59](#)  
  
leap\_yr, [60](#)  
left\_all, [61](#)  
letter\_to\_nb, [62](#)  
list\_files, [62](#)  
lst\_flatnr, [63](#)  
  
match\_by, [63](#)  
multitud, [64](#)  
  
nb2\_follow, [65](#)  
nb\_follow, [65](#)  
nb\_to\_letter, [66](#)  
nest\_v, [69](#)  
nestr\_datf1, [67](#)  
nestr\_datf2, [68](#)  
new\_ordered, [69](#)  
normal\_dens, [70](#)  
  
occu, [71](#)  
old\_to\_new\_idx, [71](#)  
  
pairs\_findr, [72](#)  
pairs\_findr\_merger, [72](#)  
pairs\_insertr, [74](#)

pairs\_insertr2, 75  
paste\_datf, 77  
pattern\_generator, 77  
pattern\_gettr, 78  
pattern\_tuning, 79  
power\_to\_char, 80  
pre\_to\_post\_idx, 80  
ptrn\_switchr, 81  
ptrn\_twkr, 81  
  
r\_print, 85  
rearangr\_v, 82  
regex\_spe\_detect, 83  
regroupr, 84  
  
save\_untl, 85  
see\_datf, 86  
see\_diff, 88  
see\_diff\_all, 88  
see\_file, 89  
see\_idx, 90  
see\_inside, 90  
see\_mode, 91  
selected\_char, 92  
sort\_date, 92  
sort\_normal\_qual, 93  
sort\_normal\_qual2, 97  
str\_remove\_untl, 100  
sub\_mult, 101  
successive\_diff, 102  
swipr, 102  
  
test\_order, 103  
to\_unique, 104  
  
union\_all, 105  
union\_keep, 105  
unique\_datf, 106  
unique\_ltr\_from\_v, 106  
unique\_pos, 107  
unique\_total, 107  
until\_stnl, 108  
  
val\_replacer, 109  
vec\_in\_datf, 110  
vector\_replacor, 109  
vlookup\_datf, 111  
  
wider\_datf, 112