Cybersecurity Incident Report:
Network Traffic Analysis

Part 1:
The UDP protocol reveals that DNS requests are being sent from the user's computer to the DNS server using UDP, but the requests are not reaching the DNS service successfully. This is based on the results of the network analysis, which show that the ICMP echo reply returned the error message: "UDP port 53 unreachable" The port noted in the error message is used for: Port 53 is commonly used by the DNS service to resolve domain names into IP addresses The DNS service on the destination server is unavailable or is not listening on UDP port 53. This prevents the user's computer from resolving the domain name yummyrecipesforme.com and accessing the website.

Part 2:
Time incident occurred: The first recorded event occurred at 13:24:32.192571. The IT team became aware of the incident after multiple customers reported that they could not access www.yummyrecipesforme.com and received a "Destination port unreachable" error. The IT team used tcpdump to capture and analyze network traffic while attempting to access the website. They examined the DNS requests sent over UDP and the ICMP error messages returned by the DNS server. The investigation found that the user's computer, with IP address 192.51.100.15, sent DNS requests to the DNS server at 203.0.113.2 over UDP port 53. The server returned ICMP error messages stating "UDP port 53 unreachable." The same error occurred repeatedly, indicating that DNS resolution was failing. A likely cause is that the DNS service on the destination server was stopped, unavailable, or not listening on UDP port 53. A firewall or network configuration issue could also be blocking DNS requests. Further investigation is needed to confirm the root cause.