

Class 08 - Breast Cancer Mini Project

Juliette Bokor (PID: A16808121)

About

In today's lab, we will work with fine needle aspiration (FNA) of breast mass data from the University of Wisconsin.

##Data Import

```
wisc.df <- read.csv("WisconsinCancer.csv", row.names = 1)
head(wisc.df)
```

	diagnosis	radius_mean	texture_mean	perimeter_mean	area_mean
842302	M	17.99	10.38	122.80	1001.0
842517	M	20.57	17.77	132.90	1326.0
84300903	M	19.69	21.25	130.00	1203.0
84348301	M	11.42	20.38	77.58	386.1
84358402	M	20.29	14.34	135.10	1297.0
843786	M	12.45	15.70	82.57	477.1

	smoothness_mean	compactness_mean	concavity_mean	concave.points_mean
842302	0.11840	0.27760	0.3001	0.14710
842517	0.08474	0.07864	0.0869	0.07017
84300903	0.10960	0.15990	0.1974	0.12790
84348301	0.14250	0.28390	0.2414	0.10520
84358402	0.10030	0.13280	0.1980	0.10430
843786	0.12780	0.17000	0.1578	0.08089

	symmetry_mean	fractal_dimension_mean	radius_se	texture_se	perimeter_se
842302	0.2419	0.07871	1.0950	0.9053	8.589
842517	0.1812	0.05667	0.5435	0.7339	3.398
84300903	0.2069	0.05999	0.7456	0.7869	4.585
84348301	0.2597	0.09744	0.4956	1.1560	3.445
84358402	0.1809	0.05883	0.7572	0.7813	5.438
843786	0.2087	0.07613	0.3345	0.8902	2.217

	area_se	smoothness_se	compactness_se	concavity_se	concave.points_se
--	---------	---------------	----------------	--------------	-------------------

842302	153.40	0.006399	0.04904	0.05373	0.01587
842517	74.08	0.005225	0.01308	0.01860	0.01340
84300903	94.03	0.006150	0.04006	0.03832	0.02058
84348301	27.23	0.009110	0.07458	0.05661	0.01867
84358402	94.44	0.011490	0.02461	0.05688	0.01885
843786	27.19	0.007510	0.03345	0.03672	0.01137
symmetry_se fractal_dimension_se radius_worst texture_worst					
842302	0.03003	0.006193	25.38	17.33	
842517	0.01389	0.003532	24.99	23.41	
84300903	0.02250	0.004571	23.57	25.53	
84348301	0.05963	0.009208	14.91	26.50	
84358402	0.01756	0.005115	22.54	16.67	
843786	0.02165	0.005082	15.47	23.75	
perimeter_worst area_worst smoothness_worst compactness_worst					
842302	184.60	2019.0	0.1622	0.6656	
842517	158.80	1956.0	0.1238	0.1866	
84300903	152.50	1709.0	0.1444	0.4245	
84348301	98.87	567.7	0.2098	0.8663	
84358402	152.20	1575.0	0.1374	0.2050	
843786	103.40	741.6	0.1791	0.5249	
concavity_worst concave.points_worst symmetry_worst					
842302	0.7119	0.2654	0.4601		
842517	0.2416	0.1860	0.2750		
84300903	0.4504	0.2430	0.3613		
84348301	0.6869	0.2575	0.6638		
84358402	0.4000	0.1625	0.2364		
843786	0.5355	0.1741	0.3985		
fractal_dimension_worst					
842302	0.11890				
842517	0.08902				
84300903	0.08758				
84348301	0.17300				
84358402	0.07678				
843786	0.12440				

Q. How many patients.individuals/samples are in this data set?

```
nrow(wisc.df)
```

```
[1] 569
```

Q. How many of the observations have a malignant diagnosis?

```
table(wisc.df$diagnosis)
```

```
B    M  
357 212
```

Q. How many variables/features in the data are suffixed with `_mean`?

```
ncol(wisc.df)
```

```
[1] 31
```

```
colnames(wisc.df)
```

```
[1] "diagnosis"           "radius_mean"  
[3] "texture_mean"        "perimeter_mean"  
[5] "area_mean"           "smoothness_mean"  
[7] "compactness_mean"    "concavity_mean"  
[9] "concave.points_mean" "symmetry_mean"  
[11] "fractal_dimension_mean" "radius_se"  
[13] "texture_se"          "perimeter_se"  
[15] "area_se"             "smoothness_se"  
[17] "compactness_se"      "concavity_se"  
[19] "concave.points_se"   "symmetry_se"  
[21] "fractal_dimension_se" "radius_worst"  
[23] "texture_worst"       "perimeter_worst"  
[25] "area_worst"          "smoothness_worst"  
[27] "compactness_worst"   "concavity_worst"  
[29] "concave.points_worst" "symmetry_worst"  
[31] "fractal_dimension_worst"
```

```
inds <- grep("_mean", colnames(wisc.df), value =T)  
inds
```

```
[1] "radius_mean"           "texture_mean"           "perimeter_mean"  
[4] "area_mean"             "smoothness_mean"        "compactness_mean"  
[7] "concavity_mean"        "concave.points_mean"    "symmetry_mean"  
[10] "fractal_dimension_mean"
```

```
length(inds)
```

```
[1] 10
```

```
#used to find the number of terms
```

Initial Analysis

Clustering

Before analysis I want to make a new data set, removing the first column (diagnosis), which is essentially the answer.

```
diagnosis <- as.factor(wisc.df$diagnosis)
#using as.factor stores the data as a "factor", shows the levels at the bottom
diagnosis
```

```
[1] M M M M M M M M M M M M M M M M M M B B B M M M M M M M M M M M M M
[38] B M M M M M M M M B M B B B B B M M B M M B B B B M B M M B B B B M B M M
[75] B M B M M B B B M M B M M M B B B M B B M M B B B M M B B B B M B B M B B
[112] B B B B B B M M M B M M B B B M M B M B M M B M M B B M B B M B B B B M B
[149] B B B B B B B B M B B B B M M B M B B M M B B M M B B B B M B B M M M B M
[186] B M B B B M B B M M B M M M M B M M M B M B M B B M B M M M M B B M M B B
[223] B M B B B B B M M B B M B B M M B M B B B B M B B B B B M B M M M M M M M
[260] M M M M M M M B B B B B B M B M B B M B B M B M M B B B B B B B B B B B
[297] B M B B M B M B B B B B B B B B B B B B B M B M B B B B M M M B B
[334] B B M B M B M B B B M B B B B B B B M M M B B B B B B B B B B M M B M M
[371] M B M M B B B B B M B B B B B M B B B M B B M M B B B B B M B B B B B B
[408] B M B B B B B M B B M B B B B B B B B B B B M B M M B M B B B B B M B B
[445] M B M B B M B M B B B B B B B B M M B B B B B B M B B B B B B B B B B M B
[482] B B B B B B M B M B B M B B B B B M M B M B M B B B B M B B M B M B M M
[519] B B B M B B B B B B B B B B B M B M M B B B B B B B B B B B B B B B B
[556] B B B B B B B M M M M M M B
Levels: B M
```

```
wisc.data <- wisc.df[,-1]
head(wisc.data)
```

	radius_mean	texture_mean	perimeter_mean	area_mean	smoothness_mean
842302	17.99	10.38	122.80	1001.0	0.11840
842517	20.57	17.77	132.90	1326.0	0.08474
84300903	19.69	21.25	130.00	1203.0	0.10960
84348301	11.42	20.38	77.58	386.1	0.14250
84358402	20.29	14.34	135.10	1297.0	0.10030
843786	12.45	15.70	82.57	477.1	0.12780
	compactness_mean	concavity_mean	concave.points_mean	symmetry_mean	
842302	0.27760	0.3001	0.14710	0.2419	
842517	0.07864	0.0869	0.07017	0.1812	
84300903	0.15990	0.1974	0.12790	0.2069	
84348301	0.28390	0.2414	0.10520	0.2597	
84358402	0.13280	0.1980	0.10430	0.1809	
843786	0.17000	0.1578	0.08089	0.2087	
	fractal_dimension_mean	radius_se	texture_se	perimeter_se	area_se
842302	0.07871	1.0950	0.9053	8.589	153.40
842517	0.05667	0.5435	0.7339	3.398	74.08
84300903	0.05999	0.7456	0.7869	4.585	94.03
84348301	0.09744	0.4956	1.1560	3.445	27.23
84358402	0.05883	0.7572	0.7813	5.438	94.44
843786	0.07613	0.3345	0.8902	2.217	27.19
	smoothness_se	compactness_se	concavity_se	concave.points_se	
842302	0.006399	0.04904	0.05373	0.01587	
842517	0.005225	0.01308	0.01860	0.01340	
84300903	0.006150	0.04006	0.03832	0.02058	
84348301	0.009110	0.07458	0.05661	0.01867	
84358402	0.011490	0.02461	0.05688	0.01885	
843786	0.007510	0.03345	0.03672	0.01137	
	symmetry_se	fractal_dimension_se	radius_worst	texture_worst	
842302	0.03003	0.006193	25.38	17.33	
842517	0.01389	0.003532	24.99	23.41	
84300903	0.02250	0.004571	23.57	25.53	
84348301	0.05963	0.009208	14.91	26.50	
84358402	0.01756	0.005115	22.54	16.67	
843786	0.02165	0.005082	15.47	23.75	
	perimeter_worst	area_worst	smoothness_worst	compactness_worst	
842302	184.60	2019.0	0.1622	0.6656	
842517	158.80	1956.0	0.1238	0.1866	
84300903	152.50	1709.0	0.1444	0.4245	
84348301	98.87	567.7	0.2098	0.8663	
84358402	152.20	1575.0	0.1374	0.2050	
843786	103.40	741.6	0.1791	0.5249	
	concavity_worst	concave.points_worst	symmetry_worst		

842302	0.7119	0.2654	0.4601
842517	0.2416	0.1860	0.2750
84300903	0.4504	0.2430	0.3613
84348301	0.6869	0.2575	0.6638
84358402	0.4000	0.1625	0.2364
843786	0.5355	0.1741	0.3985
fractal_dimension_worst			
842302	0.11890		
842517	0.08902		
84300903	0.08758		
84348301	0.17300		
84358402	0.07678		
843786	0.12440		

We can try a `kmeans()` clustering first

```
km <- kmeans(wisc.data, centers=2)
#to find how many are in each cluster using table()
table(km$cluster)
```

```
1  2
131 438
```

Cross-table

```
table(km$cluster, diagnosis)
```

```
diagnosis
      B   M
1     1 130
2    356  82
```


```
#shows the number of malignant/benign in each cluster - this is not what we want; we want
```

Let's try `hclust()` the key input required is a distance matrix as produced by the `dist()` function.

```
hc <- hclust(dist(wisc.data))
```

I can make the dendrogram

```
plot(hc)
```



```
dist(wisc.data)
hclust (*, "complete")
```

```
#this is not actually that useful, almost all the data is in a singular cluster, benign an
```

PCA

Do we need to scale the data?

We can look at the sd of each column (original variable)

```
round(apply(wisc.data, 2, sd))
```

radius_mean	texture_mean	perimeter_mean
4	4	24
area_mean	smoothness_mean	compactness_mean
352	0	0
concavity_mean	concave.points_mean	symmetry_mean
0	0	0
fractal_dimension_mean	radius_se	texture_se
0	0	1

perimeter_se	area_se	smoothness_se
2	45	0
compactness_se	concavity_se	concave.points_se
0	0	0
symmetry_se	fractal_dimension_se	radius_worst
0	0	5
texture_worst	perimeter_worst	area_worst
6	34	569
smoothness_worst	compactness_worst	concavity_worst
0	0	0
concave.points_worst	symmetry_worst	fractal_dimension_worst
0	0	0

Yes we need to scale the data. We will run `prcomp()` with `scale=True`.

```
wisc.pr <- prcomp(wisc.data, scale=TRUE)
summary(wisc.pr)
```

Importance of components:


	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	3.6444	2.3857	1.67867	1.40735	1.28403	1.09880	0.82172
Proportion of Variance	0.4427	0.1897	0.09393	0.06602	0.05496	0.04025	0.02251
Cumulative Proportion	0.4427	0.6324	0.72636	0.79239	0.84734	0.88759	0.91010
	PC8	PC9	PC10	PC11	PC12	PC13	PC14
Standard deviation	0.69037	0.6457	0.59219	0.5421	0.51104	0.49128	0.39624
Proportion of Variance	0.01589	0.0139	0.01169	0.0098	0.00871	0.00805	0.00523
Cumulative Proportion	0.92598	0.9399	0.95157	0.9614	0.97007	0.97812	0.98335
	PC15	PC16	PC17	PC18	PC19	PC20	PC21
Standard deviation	0.30681	0.28260	0.24372	0.22939	0.22244	0.17652	0.1731
Proportion of Variance	0.00314	0.00266	0.00198	0.00175	0.00165	0.00104	0.0010
Cumulative Proportion	0.98649	0.98915	0.99113	0.99288	0.99453	0.99557	0.9966
	PC22	PC23	PC24	PC25	PC26	PC27	PC28
Standard deviation	0.16565	0.15602	0.1344	0.12442	0.09043	0.08307	0.03987
Proportion of Variance	0.00091	0.00081	0.0006	0.00052	0.00027	0.00023	0.00005
Cumulative Proportion	0.99749	0.99830	0.9989	0.99942	0.99969	0.99992	0.99997
	PC29	PC30					
Standard deviation	0.02736	0.01153					
Proportion of Variance	0.00002	0.00000					
Cumulative Proportion	1.00000	1.00000					

Generate our main PCA plot (score plot, PC1 vs PC2 plot)..


```
library(ggplot2)

res <- as.data.frame(wisc.pr$x)

#making a ggplot coloring by diagnosis, under aes instead of geom
ggplot(res) +
  aes(PC1, PC2, col=diagnosis) +
  geom_point()
```




We see a visual separation of the two diagnoses based on a “line” when plotting PC1 vs PC2; it is separating out the cancer (malignant) from non-cancer (benign).

Combining Methods: Clustering on PCA results

Using the minimum number of principal components required to describe at least 90% of the variability in the data, create a hierarchical clustering model with the linkage method=“ward.D2”. We use Ward’s criterion here because it is based on multidimensional variance like principal components analysis. Assign the results to `wisc.pr.hclust`.

```
#doing it on PC1-PC3, not all the PCs (first three columns), need it as a distance vector
#covering 90% of the variability would require us to plot PC1 through PC7.
d <- dist(wisc.pr$x[,1:3])
hc <- hclust(d, method="ward.D2")
plot(hc)
```



To get my clustering result/membership vector I need to “cut” the tree with the `cutree()` function.


```
# you can use the argument k= to define the number of branches you want to cut the tree in
grps <- cutree(hc, h=80)
```

Q. How many patients are in each cluster group?

```
table(grps)
```

```
grps
 1    2
203 366
```

```
plot(res$PC1, res$PC2, col=grps)
```



Prediction

We can use our PCA result (model) to do predictions, that is take new unseen data and project it onto our new PC variables.

```
url <- "https://tinyurl.com/new-samples-CSV"
new <- read.csv(url)
npc <- predict(wisc.pr, newdata=new)
npc
```

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
[1,]	2.576616	-3.135913	1.3990492	-0.7631950	2.781648	-0.8150185	-0.3959098
[2,]	-4.754928	-3.009033	-0.1660946	-0.6052952	-1.140698	-1.2189945	0.8193031
	PC8	PC9	PC10	PC11	PC12	PC13	PC14
[1,]	-0.2307350	0.1029569	-0.9272861	0.3411457	0.375921	0.1610764	1.187882
[2,]	-0.3307423	0.5281896	-0.4855301	0.7173233	-1.185917	0.5893856	0.303029
	PC15	PC16	PC17	PC18	PC19	PC20	
[1,]	0.3216974	-0.1743616	-0.07875393	-0.11207028	-0.08802955	-0.2495216	

```


[2,] 0.1299153 0.1448061 -0.40509706 0.06565549 0.25591230 -0.4289500
      PC21      PC22      PC23      PC24      PC25      PC26
[1,] 0.1228233 0.09358453 0.08347651 0.1223396 0.02124121 0.078884581
[2,] -0.1224776 0.01732146 0.06316631 -0.2338618 -0.20755948 -0.009833238
      PC27      PC28      PC29      PC30
[1,] 0.220199544 -0.02946023 -0.015620933 0.005269029
[2,] -0.001134152 0.09638361 0.002795349 -0.019015820

```

```

plot(res$PC1, res$PC2, col=grps)
points(npc[,1], npc[,2], col="blue", pch=16, cex=3)
text(npc[,1], npc[,2], labels=c(1,2), col="white")

```



Summary

Principal Component Analysis (PCA) is a super useful method for analyzing large datasets. It works by finding new variables (PCs) that capture the most variance from the original variables in your dataset.

Q17. Which of your analysis procedures resulted in a clustering model with the best specificity? How about sensitivity?

The hierarchical clustering of the PCA results has the best specificity and sensitivity of the analysis procedures that we ran.

Q18. Which of these new patients should we prioritize for follow up based on your results?

Patient 2 should be prioritized, they are in the cluster of the malignant data, indicating that they likely have a malignant cancer.