EcommerceGlobal Payment Integration Guide

Integrate Your Order page with Our Payment page

Version: 06.16.05

Table of Contents

I) Introduction To Payment Integration	(3)
1.1) Company Overview	
1.2) Payment Integration Overview	(3)
	` '
II) Payment Process Overview	(4)
2.1) Diagrammatic Representation	(4)
2.2) Process Explanation	(5)
III) Data Format	(5)
3.1) Data sent to the payment page by the Merchant(
3.2) Data sent to the Merchant from our bank	(6)
IV) Transaction Process	7)
4.1) Test transaction techniques	(7)
4.2) Live transaction techniques	
,	` '
V) How to Integrate	(8)
5.1) Integration Example	(8)
, ,	` /
VI) Appendix –A	(9)
/ II	$\overline{}$

Introduction To Payment Integration

1.1) Company Overview

As truly one of the most unique international payment processors, EcommerceGlobal is a worldwide leader in Online Payment Processing.


1.2) Payment Integration Overview

The Payment Integration Guide provides information about the payment process, and instructions for using these features to meet your online payment needs.

Use the Integration Guide to:

- ◆ Quickly and easily setup eCommerce sites with our payment process. For example, learn how to integrate our payment system with your sites shopping cart.
- ◆ Learn more advanced and simple techniques to get most out of Our product. For example, how to set up an Instant payment notifications to integrate Order page.
- ◆ Understand what process your customers see when they pay with Our payment system.
- View various product flows to better visualize your end product.

Payment Process Overview 2.1) Diagrammatic Representation



2.2) Process Explanation

- 1. The end-user submits the form.
- 2. The Merchant sends the data to our Order Page.
- 3. We check the Card Number and Check transaction parameters with Anti-fraud System and sends the payment to Bank.
- 4. The bank response will be updated with the Our Database.
- 5. We send the response to the Merchant on the return url you assign for that website in your backend.
- 6. The return URL of the Merchant updates the Merchant database.

Data Format

3.1) Data sent to us by the Merchant

You have to post these data to the our order page.

1. mt reference id

- Description Reference number given by Our administrator
- Content Unique alphanumeric string

2. mt_transaction_type

- Description Type of transaction.
- Content Check or Credit

3. mt_subAccount

- Description Merchant charge subAccount
- Content Unique account number to identify purchase amount/purchase schedule.

4. mt_prod_desc

- Description Description about the product
- Content Alphanumeric string which describes about the product purchased.

5. mt_product_id

- Description Description about the product
- Content Alphanumeric string which describes about the product purchased.

6. mt amount

- Description **Optional** Charge Amount
- Content This option is only available when your processor gives you permission to do so. If Independent Pricing is enabled for your company, you may enter any value you wish to charge here without prior defining of a Price Point.

7. Any extra parameters: ex. param_1, param_2, param_3

- Description **Optional** Parameters
- Content You may pass whatever data you like with any number of extra parameters. This data will be returned to your website on the final post form along with the above data. This can be used to keep track of orders/IDs.

8. mt_checksum

- Description **Optional** Charge Amount Verification Checksum
- Content This option is only used when Independent Pricing is used. This option verifys the charge amount on our end so that the price you intend to charge is not bypassed or changed by a hacker.

NOTE: IF YOU USE INDEPENDENT PRICING, THIS VERIFICATION SYSTEM IS HIGHLY RECOMMENDED. This is the only way for you to verify the information sent to you from our server.

To Achive this value, you can use this formula:

MD5(Secret Key + Website Reference ID +

Amount to Charge + Product ID)

3.1.8) Integration Example

Use this method on your order page to calculate the checksum on the fly.

```
<?php
$amountToCharge = 24.99;
$secretKey='ZQ3dku3QM6EwSxkw';
$mt_reference_id='40EEEF366DC2';
$mt_product_id='Prod_02';
$mt_checksum=
md5($secretKey.$mt_reference_id.$amountToCharge.$mt_product_id);
?>
<input type='hidden' name='mt_checksum'
value='<?=$mt_checksum?>'>
<input type='hidden' name='mt_reference_id'
value='<?=$mt_reference_id?>'>
<input type='hidden' name='mt_amount'
value='<?=$mt_reference_id?>'>
<input type='hidden' name='mt_amount'
value='<?=$amountToCharge?>'>
<input type='hidden' name='mt_product_id'
value='<?=$mt_product_id?>'>
```

3.2) Data sent to the Merchant from our server The response file will post these details to the Merchant URL.

1. mt transaction result

- Description Transaction Status
- Content Return code given below in Appendix-A.

2. mt total amount

- Description Total transaction Amount
- Content Numeric string up to 10 maximum, the amount paid through Our order page.

3. mt reference number

- Description Transaction Reference Number.
- Content Unique transaction number used to identify the order.

4. mt useremail

- Description Email user registered with
- Content This value represents the email the user registered the transaction with.

5. Extra parameters: ex. param_1, param_2, param_3

- Description **Optional** Parameters
- Content Any Data you passed through these parameters initially in the last section will be returned here. This is useful for keeping track of orders or user accounts.

6. mt_username, mt_password

- Description Circumstantial Parameters
- Content If a website is enabled with the password management system, the customer will be asked to assign a username and password. They will appear here.

7. verify_checksum

- Description Circumstantial Parameters
- Content Use this value to verify the Independent Price that we charged your customer. You can check it against the md5 checksum you generated on your order page.

Transaction Process

The transaction should be made live only after completing the entire process. The Transactions should be tested using the TEST URL before getting live.

4.1) Testing Transaction:

For testing the transaction POST the transaction messages to the URL:

https://safe.ecommerceglobal.com/secure/testintegration.php

4.2) Live Transaction:

For Live transaction POST the transaction messages to the URL:

https://safe.ecommerceglobal.com/secure/integration.php

How to Integrate using Price Points:

5.1) Integration Example

The following details have to be sent to Our order page:

```
<html>
<head>
<title>Payment Gateway</title>
</head>
<body>
<form name='FrmPayment'</pre>
action='https://safe.ecommerceglobal.com/secure/integration.php'
method='POST'>
<input type='hidden' name='mt reference id' value='0A137B375CC3'>
<select name="mt transaction type" size="3">
  <option value="Credit" selected>Credit Card</option>
  <option value="Check">Check</option>
  <option value="WEB900">WEB900
</select>
<input type='hidden' name='mt subAccount' value='240-00102'>
<input type='hidden' name='mt prod desc' value='Car Rental'>
<input type='hidden' name='param 1' value='Extra Parameter'>
<input name="" type="submit">
</form>
</body>
</html>
```

This example allows for charging an the customer with a Price Point Sub Account. Sub Accounts must be set up in the Web Setup page before they can be used. In this example, the subAccount '00102' specifies a product trial price, trial period, and optional recurring billing information for that product. This method is far more secure than Independent billing.

How to Integrate using independent Pricing:

5.1) Integration Example

The following details have to be sent to Our order page:

```
<html>
<head>
<title>Payment Gateway</title>
</head>
<form name='FrmPayment'</pre>
action='https://safe.ecommerceglobal.com/secure/integration.php'
method='POST'>
<input type='hidden' name='mt reference id' value='01234ABCDE'>
<select name="mt transaction type" size="3">
  <option value="Credit" selected>Credit Card</option>
  <option value="Check">Check</option>
  <option value="WEB900">WEB900</option>
</select>
<input type='hidden' name='mt amount' value='24.99'>
<input type='hidden' name='mt subAccount' value='-1'>
<input type='hidden' name='mt prod desc' value='Sun Glasses'>
<input type='hidden' name='mt_checksum'</pre>
value='5a51cf045196bf68f9af9225f5212ce6'>
<input name="" type="submit">
</form>
</body>
</ht.ml>
```

This example allows for charging an arbitrary value to the customer. No Price points have to be created beforehand.

Note: in this example, an Independent Price Point Verification Checksum is used. This checksum was created by:

MD5(Secret Key + Reference ID + Amount to Charge + Product ID)

You may also use our checksum generator provided to you on your Pricing Setup Page to generate a valid checksum.

DON"T LET YOUR CUSTOMERS KNOW YOUR SECRET KEY!

Appendix - A

Return code for the transaction:

Type Description

INT Internal Error Occurred.

UIN Invalid User.

SUP Suspended User by the administrator.

VID Invalid Voice Authorization Id.

SUC Transaction Success.

DEC Declined Transaction.

INV Invalid Price Point SubAccount

DIS Disabled Transaction Type

REF Invalid Reference Website

Examples for posting the values from the Integration page using Price Points:

Field Name Value

mt reference id MF724431KW

mt_transaction_type Check(For Check Transactions)
mt_transaction_type Credit(For Credit transactions)

mt subAccount 240-00101

mt product desc Products Purchased

mt product id Prod 01

This will charge the customer with the one time or recurring payment plan defined by the Sub Account. Note: Price Points will not work unless you set up Price Points in your Web Setup beforehand.

Examples for posting the values from the Integration page using Independent Pricing:

Field Name Value

mt reference id MF724431KW

mt_checksum 5a51cf045196bf68f9af9225f5212ce6

mt subAccount -1 (This should be -1 or blank if you are using Independent

Pricing

mt product desc Products Purchased

mt_product_id Prod_01 mt_amount 24.99

This will charge the customer with the one time payment of 24.99.