

Evapotranspiration Modeling in ECHSE: Documentation

Julius Eberhard

December 12, 2016

Contents

1	Introduction	3
1.1	Model overview – parameter overview	3
1.2	Study areas – available data	4
1.2.1	Portugal	4
1.2.2	Morocco	4
2	Aims	6
3	Parameter estimation: methods and results	7
3.1	Aerodynamic parameters	7
3.2	Geographical parameters	7
3.3	Radiation parameters	7
3.3.1	alb	7
3.3.2	emis_a, emis_b: estimation methods	7
3.3.3	emis_a, emis_b: Portugal	7
3.3.4	emis_a, emis_b: Morocco	7
3.3.5	f_day, f_night: estimation methods	7
3.3.6	f_day, f_night: Portugal	8
3.3.7	f_day, f_night: Morocco	8
3.3.8	fcorr_a, fcorr_b: estimation methods	8
3.3.9	fcorr_a, fcorr_b: Portugal	8
3.3.10	fcorr_a, fcorr_b: Morocco	8
3.3.11	glo_half	8
3.3.12	radex_a, radex_b: estimation methods	8
3.3.13	radex_a, radex_b: Portugal	9
3.3.14	radex_a, radex_b: Morocco	9
3.4	Soil hydraulic parameters	9
3.5	Vegetation parameters	9
4	Comparison of evapotranspiration models	11
5	Sensitivity analysis	12
6	Evaluation of ECHSE methods	13
6.1	Global radiation glorad	13
6.1.1	glorad: Portugal	13
6.1.2	glorad: Morocco	13
6.2	Net incoming radiation rad_net	13
6.2.1	rad_net: Portugal	13
6.3	Soilheat flux soilheat	13
6.3.1	soilheat: Portugal	13
7	Results: overview	19
7.1	Parameters	19
8	Conclusion	22

1 Introduction

This is a documentation of my work done in exploring some aspects of the way how evapotranspiration is simulated in the *Eco-Hydrological Simulation Environment* (ECHSE, Kneis 2015) with methods, classes, and engines written by Tobias Pilz. ECHSE is a model framework, i.e. a software providing calculation methods that can be composed modularly to form model engines. These engines can be compiled and be run as independent models with input data. ECHSE is used in the field of (eco-)hydrology and therefore comes with a collection of methods especially relevant for issues in this field. The goal of the bigger project is to apply with ECHSE different ways of determining the potential (et_{pot}) and the actual evapotranspiration (et_{act}). These are, as of the date of this documentation:

- the simple model of Makink (1957),
- the equation of Penman & Monteith (Monteith, 1965),
- the FAO equation for reference evaporation,
- the equation of Shuttleworth & Wallace (Shuttleworth and Wallace, 1985).

The engine-specific names of variables and parameters are written in **fixed-width** whereas the physical symbols of variables, constants and parameters are written in *italics*. E.g., extraterrestrial radiation = R_{ex} = **radex**. Terms that describe parts of the ECHSE architecture are written in sans-serif.

1.1 Model overview – parameter overview

The engine parameters can be grouped into

- aerodynamic parameters,
- geographical parameters,
- radiation parameters,
- soil hydraulic parameters,
- vegetation parameters,

according to their physical role, and will be discussed in this order in chapter 3. Within the ECHSE engines, parameters are grouped into the types

- **paramNum** (object-specific scalar parameters),
- **sharedParamNum** (group-specific scalar parameters),
- **inputExt** (group-specific time-dependent scalar parameters treated as external input variables),

according to their role in the computation process. Tab. 1.1 contains an overview of the variables and parameters and whether they are used in the different *et* models (Mak = Makink, PM = Penman-Monteith, FAO = FAO reference, SW = Shuttleworth-Wallace model). The parameters in this overview are grouped into the types **paramNum**, **sharedParamNum**. Parameters of the **inputExt** type can be found together with the actual external input variables.

In chapter 7, an overview of the estimated parameter values is given, grouped into the **paramNum**, **sharedParamNum**, and **inputExt** parameter types.

1.2 Study areas – available data

1.2.1 Portugal

The *Machoqueira do Grou* area is a 2.500 ha sized woodland in the Santarém district, between the towns of Coruche and Foros do Arrão, Portugal. The vegetation is dominated by cork oak trees and grasses. Data come from two measurement stations within the woodland, which were set up for measuring eddy covariance data with measurement towers and other meteorological variables. One station is located between trees under the open sky (*Hauptstation*, HS), the other was set up under a cork oak (*Nebenstation A*, NSA). The data include net radiation, air temperature, soil moisture content, sensible heat flux, latent heat flux, vapor pressure deficit, and vapor pressure, and were recorded hourly. An evaporation flux was determined from energy balance considerations.

Additional meteorological data come from a nearby weather station. Those include photosynthetically active radiation (PAR), incoming short-wave radiation, outgoing long-wave radiation, air temperature, relative humidity, rainfall, and atmospheric pressure, and were recorded half-hourly.

1.2.2 Morocco

Table 1.1: External input variables, parameters and their usage in the *et* models. For abbreviations, see text. \bullet : required by engine primarily, (\bullet) : required only in cases when primary input is missing.

<i>et_{pot}</i>				<i>et_{act}</i>			ECHSE name
Makk	PM	FAO	SW	PM	FAO	SW	
							inputExt
	(\bullet)	(\bullet)	(\bullet)				alb
\bullet	\bullet	\bullet	\bullet				apress
	\bullet		\bullet				cano.height
(\bullet)	(\bullet)	(\bullet)	(\bullet)				cloud*
(\bullet)	(\bullet)	(\bullet)	(\bullet)				doy
\bullet	\bullet	(\bullet)	\bullet				glorad
	(\bullet)	(\bullet)	(\bullet)				glorad.max
(\bullet)	(\bullet)	(\bullet)	(\bullet)				hour
	\bullet		\bullet				lai
	(\bullet)	(\bullet)	(\bullet)				rad.long
	\bullet	\bullet	\bullet				rad.net
	(\bullet)	(\bullet)	\bullet				rad.net.soil
	\bullet	\bullet	\bullet				rhum
	\bullet		\bullet				soilheat
(\bullet)	(\bullet)	(\bullet)	(\bullet)				sundur
(\bullet)	(\bullet)	(\bullet)	(\bullet)				temp.max
(\bullet)	(\bullet)	(\bullet)	(\bullet)				temp.min
\bullet	\bullet	\bullet	\bullet				temper
			\bullet				totalheat
(\bullet)	(\bullet)	(\bullet)	(\bullet)				utc.add
							wc.vol.root
							wc.vol.top
	\bullet	\bullet	\bullet				wind
							paramNum
	\bullet		\bullet				bubble
		\bullet					crop_faoref
\bullet							crop_makk
(\bullet)	(\bullet)	(\bullet)	(\bullet)				elev
	\bullet		\bullet				glo_half
(\bullet)	(\bullet)	(\bullet)	(\bullet)				lat
	(\bullet)	(\bullet)	(\bullet)				lon
				\bullet		\bullet	par_stressHum
				\bullet		\bullet	pores_ind
	\bullet		\bullet				res_leaf_min
			\bullet				soil.dens
							wc.etmax
							wc.pwp
							wc.res
							wc.sat
							wstressmax
							wstressmin
							sharedParamNum
\bullet	\bullet	\bullet	\bullet				choice_et
	(\bullet)	(\bullet)	(\bullet)				choice_gloradmax
	\bullet		\bullet				choice_plantDispl
	\bullet		\bullet				choice_rcs
	\bullet		\bullet				choice_roughLen
	\bullet		\bullet				drag_coef
			\bullet				eddy_decay
	(\bullet)	(\bullet)	(\bullet)				emis_a
	(\bullet)	(\bullet)	(\bullet)				emis_b
	\bullet		\bullet				ext
	(\bullet)	(\bullet)	\bullet				f_day
	(\bullet)	(\bullet)	\bullet				f_night
	(\bullet)	(\bullet)	(\bullet)				fcorr_a
	(\bullet)	(\bullet)	(\bullet)				fcorr_b
	\bullet		\bullet				h_humMeas
	\bullet		\bullet				h_tempMeas
	\bullet	\bullet	\bullet				h_windMeas
(\bullet)	(\bullet)	(\bullet)	(\bullet)				radex_a
(\bullet)	(\bullet)	(\bullet)	(\bullet)				radex_b
			\bullet				res_b
	\bullet		\bullet				rough_bare
			\bullet				rss_a
			\bullet				rss_b
							*currently not used

2 Aims

- Estimation of engine parameters through transfer functions and model calibration (chapter 3),
- comparison of the different *et* models (chapter 4),
- sensitivity analysis of engine parameters (chapter 5),
- evaluation of single methods employed in the *et* models (chapter 6).
- Which input data do we still need? (chapter 8)

3 Parameter estimation: methods and results

3.1 Aerodynamic parameters

`h_tempMeas`, `h_humMeas`, `h_windMeas`, `res_b`, `drag_coef`, `rough_bare`, `eddy_decay`.

3.2 Geographical parameters

The models employ 3 geographical parameters for calculating the radiation balance: latitude φ (`lat`), longitude L_m (`lon`), elevation h (`elev`). For the sites in Portugal, the locations were given as GIS data from which I could derive `lat` = 39.14° and `lon` = 8.33° for both field stations using *Google Maps*. A common value for `elev` of the Portugal sites was estimated from local elevation maps (floodmap.net). For Morocco, `lat` and `lon` were derived from the location descriptions in Mroos (2014) while `elev` was also estimated from floodmap.net.

3.3 Radiation parameters

3.3.1 alb

3.3.2 emis_a, emis_b: estimation methods

3.3.3 emis_a, emis_b: Portugal

I chose default values of `emis_a` = 0.34 and `emis_b` = -0.14, as suggested for average conditions by Maidment (Ed.). The values could not be estimated individually because the data from Portugal were not sufficient.

3.3.4 emis_a, emis_b: Morocco

I chose default values of `emis_a` = 0.34 and `emis_b` = -0.14, as suggested for average conditions by Maidment (Ed.). The emissivity parameters could not be determined because the data from Morocco were not sufficient.

3.3.5 f_day, f_night: estimation methods

Within the ECHSE engines, the sub-daily soil heat flux is currently calculated as

$$G_{soil} = f_{day} R_{net} \text{ during daytime,} \quad (3.1)$$

$$G_{soil} = f_{night} R_{net} \text{ during nighttime.} \quad (3.2)$$

with

G_{soil} : soil heat flux (`soilheat`), in W m^{-2} ,

f_{day} , f_{night} : soil heat factors (`f_day`, `f_night`), no unit,

R_{net} : net incoming short-wave and long-wave radiation (`rad_net`), in W ms^{-2} .

3.3.6 f_day, f_night: Portugal

Since the data didn't include measurements of R_{net} , I used the results of internally calculated values of R_{net} and measurements of G_{soil} for calculating f_{day} , f_{night} hourly. The distinction into daytime and nighttime was made using the *RAtmosphere::suncalc* procedure by Gionata Biavati. Averaging over all hours gave the results.

3.3.7 f_day, f_night: Morocco

3.3.8 fcorr_a, fcorr_b: estimation methods

3.3.9 fcorr_a, fcorr_b: Portugal

The cloudiness correction factors could not be determined because the data from Portugal were not sufficient.

3.3.10 fcorr_a, fcorr_b: Morocco

The cloudiness correction factors could not be determined because the data from Morocco were not sufficient.

3.3.11 glo_half

3.3.12 radex_a, radex_b: estimation methods

The estimation of the Ångström parameters is based on the equation

$$\langle R_{inS} \rangle = \left(a_s + b_s \frac{n}{N} \right) \langle R_{ex} \rangle, \quad (3.3)$$

with

R_{inS} : incoming short-wave radiation (global radiation, **glorad**), in W m^{-2} ,

R_{ex} : extraterrestrial short-wave radiation (**radex**), in W m^{-2} ,

a_s , b_s : Ångström parameters (**radex_a**, **radex_b**), no unit,

n : sunshine duration of current day (time for which $\langle R_{inS} \rangle \geq 120 \text{ W m}^2$, **sundur**), in hours,

N : maximum possible sunshine duration, in hours.

Since R_{ex} and N are calculated internally, the uncertainty of the estimation should only depend on the observed global radiation (by definition, n follows from R_{inS}). Note that the equation as written represents only daily mean values of R_{inS} : The parameters are weighted depending on the daily ratio n/N in order to account for cloudiness. Thus,

$$a_s + b_s = \frac{R_{inS}}{R_{ex}} \text{ on days when } n = N, \quad (3.4)$$

$$a_s = \frac{R_{inS}}{R_{ex}} \text{ on days when } n = 0. \quad (3.5)$$

In both cases the parameters can be found for any given day with known values of n and R_{inS} . Averaging over all days would then determine the parameters. Problem: It is difficult to find either days when $n = N$ or days when $n = 0$.

Another way of estimating a_s and b_s based on shorter time intervals (in our case, hourly) would be

$$a_s + b_s = \max_{h=1, \dots, 24} \left\{ \frac{R_{inS}(h)}{R_{ex}(h)} \right\}, \quad (3.6)$$

$$a_s = \min_{h=1, \dots, 24} \left\{ \frac{R_{inS}(h)}{R_{ex}(h)} \right\}. \quad (3.7)$$

For finding unique solutions, both (3.6) and (3.7) need to be determined because the equations are no longer dependent on n . The biggest problem of estimating the parameters with subdaily data is that extreme values (max, min) can result from measuring errors and statistical outliers. Taking very low quantiles of the R_{inS}/R_{ex} distribution and applying an upper limit for max ($a_s + b_s$ can't be greater than 1) would probably avoid estimating a_s as too low and b_s as too high.

3.3.13 radex_a, radex_b: Portugal

Global radiation was measured hourly at the local weather station in Portugal. Therefore I chose to estimate **radex_a** and **radex_b** with (3.6) and (3.7). The R_{inS}/R_{ex} ratio was calculated for daytime hours between 6:00 and 18:00 local time. This assured that only radiation between sunrise and sunset was taken into account for all of the simulation period. For the determination of reasonable values I chose the lower 5-percentile of the R_{inS}/R_{ex} distribution as the minimum and the maximum value of $\{R_{inS}/R_{ex} < 1\}$ as the maximum over the whole period in which R_{inS} observations were available. These choices proved successful in computing clear-sky radiation that didn't exceed the observed global radiation and therefore fulfilled the physical conditions.




Figure 3.1: Histogram of the ratio R_{inS}/R_{ex} for values less than 1 in Portugal.

3.3.14 radex_a, radex_b: Morocco

3.4 Soil hydraulic parameters

wc_sat, wc_res, wc_pwp, wc_etmax, bubble, pores_ind, wstressmin, wstressmax, soil_dens, rss_a, rss_b.

3.5 Vegetation parameters

ext, par_stressHum, crop_makk, crop_faoref, res_leaf_min, lai, cano_height.




Figure 3.2: R_{inS}/R_{ex} ratio dependent on hour of day. The shift of higher values toward early hours may indicate either a small temporal deviation between the simulated and the actual R_{ex} , or a local effect that weakens R_{inS} during afternoon, or both. The dashed line marks the 5-percentile of the total distribution.

4 Comparison of evapotranspiration models

5 Sensitivity analysis

6 Evaluation of ECHSE methods

6.1 Global radiation glorad

6.1.1 glorad: Portugal




Figure 6.1: .

6.1.2 glorad: Morocco

6.2 Net incoming radiation rad_net

6.2.1 rad_net: Portugal

6.3 Soilheat flux soilheat

6.3.1 soilheat: Portugal




Figure 6.2: .




Figure 6.3: .




Figure 6.4: .




Figure 6.5: .




Figure 6.6: .

7 Results: overview

7.1 Parameters

An overview of the parameters is given for the **paramNum** group (object-specific scalar parameters, HS Portugal: Tab. 7.1, NSA Portugal: Tab. 7.2, Morocco: Tab.), the **sharedParamNum** group (group-specific scalar parameters, HS Portugal: Tab. 7.3, NSA Portugal: Tab. 7.4, Morocco: Tab.), and the **inputExt** group (group-specific scalar parameters given as time series, HS Portugal: Tab. 7.5, NSA Portugal: Tab. 7.6, Morocco: Tab.).

Table 7.1: Object-specific scalar parameters (**paramNum**), HS Portugal

Parameter	Value	Unit
bubble	8.08	hPa
crop_faoref	1.00	–
crop_makk	0.80	–
elev	160.00	m
glo_half	200.00	W m ⁻²
lat	39.14	
lon	8.33	
par_stressHum	0.03	hPa ⁻¹
pores_ind	0.45	–
res_leaf_min	50.00	s m ⁻¹
soil_dens	1500.00	kg m ⁻³
wc_etmax	0.13	–
wc_pwp	0.07	–
wc_res	0.05	–
wc_sat	0.39	–
wstressmax	10000.00	hPa
wstressmin	100.00	hPa

Table 7.2: Object-specific scalar parameters (**paramNum**), NSA Portugal

Parameter	Value	Unit
bubble	8.08	hPa
crop_faoref	1.00	–
crop_makk	0.80	–
elev	160.00	m
glo_half	200.00	W m ⁻²
lat	39.14	
lon	8.33	
par_stressHum	0.03	hPa ⁻¹
pores_ind	0.45	–
res_leaf_min	50.00	s m ⁻¹
soil_dens	1500.00	kg m ⁻³
wc_etmax	0.13	–
wc_pwp	0.07	–
wc_res	0.05	–
wc_sat	0.39	–
wstressmax	10000.00	hPa
wstressmin	100.00	hPa

Table 7.3: Group-specific scalar parameters (**sharedParamNum**), HS Portugal

Parameter	Value	Unit
drag_coef	0.07	–
eddy_decay	2.50	–
emis_a	0.34	–
emis_b	-0.14	–
ext	0.40	–
f_day	0.10	–
f_night	0.70	–
fcorr_a	1.35	–
fcorr_b	-0.35	–
h_humMeas	2.00	m
h_tempMeas	2.00	m
h_windMeas	2.00	m
radex_a	0.14	–
radex_b	0.67	–
res_b	25.00	s m ⁻¹
rough_bare	0.01	m
rss_a	37.50	–
rss_b	-1.23	–

Table 7.4: Group-specific scalar parameters (`sharedParamNum`), NSA Portugal

Parameter	Value	Unit
<code>drag_coef</code>	0.07	–
<code>eddy_decay</code>	2.50	–
<code>emis_a</code>	0.34	–
<code>emis_b</code>	-0.14	–
<code>ext</code>	0.40	–
<code>f_day</code>	0.10	–
<code>f_night</code>	0.70	–
<code>fcorr_a</code>	1.35	–
<code>fcorr_b</code>	-0.35	–
<code>h_humMeas</code>	4.84	m
<code>h_tempMeas</code>	4.84	m
<code>h_windMeas</code>	4.84	m
<code>radex_a</code>	0.14	–
<code>radex_b</code>	0.67	–
<code>res_b</code>	25.00	s m ⁻¹
<code>rough_bare</code>	0.01	m
<code>rss_a</code>	37.50	–
<code>rss_b</code>	-1.23	–

Table 7.5: Time-dependent parameters (`inputExt`), HS Portugal

Parameter	Value	Unit
<code>alb</code>	0.30	–
<code>cano_height</code>	0.20	m
<code>lai</code>	0.78	–

Table 7.6: Time-dependent parameters (`inputExt`), NSA Portugal

Parameter	Value	Unit
<code>alb</code>	0.30	–
<code>cano_height</code>	4.84	m
<code>lai</code>	1.40	–

8 Conclusion

- Soil heat flux needs a better model.

Bibliography

- D. Kneis. A lightweight framework for rapid development of object-based hydrological model engines. *Environmental Modelling & Software*, 68:110–121, 2015.
- D. R. Maidment (Ed.). *Handbook of Hydrology*. McGraw-Hill, Inc., 1993.
- G. F. Makkink. Testing the penman formula by means of lysimeters. *International Journal of Water Engineering*, 11:277–288, 1957.
- J. L. Monteith. Evaporation and environment. *Symposia of the Society for Experimental Biology*, 19: 205–224, 1965.
- K. Mroos. *Assessment of the soil water balance and irrigation recharge by combination of cosmic ray neutron sensing and eddy covariance technique on a citrus orchard in the Haouz plain, Morocco*. Universität Potsdam, 2014.
- W. J. Shuttleworth and J. S. Wallace. Evaporation from sparse crops – an energy combination theory. *Quarterly Journal of the Royal Meteorological Society*, 111:839–855, 1985. doi: 10.1002/qj.49711146910.