

IE 498 - HW1

Julius Olson

Implementation

Instructions & requirements

```
# Train
python3 nn.py train

# Load and evaluate
python3 nn.py load

# More advanced usage to customize settings

usage: nn.py [-h] [--hidden HIDDEN] [--epochs EPOCHS] [--data DATA]
            [--model MODEL]
            {train,load}
```

Neural Network

positional arguments:
 {train,load} Run NN training or load existing model

optional arguments:
 -h, --help show this [help](#) message and [exit](#)
 --hidden HIDDEN Number of hidden layers
 --epochs EPOCHS Number of epochs
 --data DATA Dataset destination
 --model MODEL .npy model destination

Requires python ver 3.6 or higher (due to usage of f-string formatting) and numpy.

Implementation

The main part of the program is the class `NeuralNetwork`, which contains all relevant methods needed for training and evaluating the network. Other than that, auxiliary functions include different activation functions and a function for loading the data set from file.

Both the forward and backward algorithm utilize vectorization via numpy for faster calculations. The training is carried out using stochastic gradient descent.

Forward

```
"""
    Forward propagate
"""
def forward(self, x):
    self.Z = np.dot(self.W, x) + self.b1
    self.H = sigmoid(self.Z)
    self.U = np.dot(self.C, self.H) + self.b2
    return softmax(self.U)
```

Backward

```
def backpropagate(self, x, y, out):
    dPdU = out
    dPdU[y] -= 1
    dPdB2 = dPdU
    dPdC = np.dot(dPdU, self.H.T)
    Sigma = np.dot(self.C.T, dPdU)
    dPdB1 = Sigma * back_sigmoid(self.Z)
    dPdW = np.dot(dPdB1, x.T)
    return dPdW, dPdB1, dPdB2, dPdC, Sigma
```

Result

An accuracy of 97.4% was reached using the following settings.

Param	Value
d_hidden	100
epochs	10
LR	Piecewise constant (see code)
Activation	sigmoid