





Somerville italic H scripts: Micro






User opsz: 5. Target internal opsz: 5.
With avar 2: target STYA=5, STYB=5. Without: STYA=STYB=5 (target internal opsz).
With avar 2, STYA/STYB inputs remain 5. Set at 12pt, enlarged 1.5 times.
All bases and scripts use italic H. First row: superscript, subscript, both. Second row: nested scripts testing the second script level.
Internal targets are approximate because of avar rounding.
Overlay: red = without avar 2; black = with avar 2, both at 50 percent opacity. Each formula shares the same origin and baseline.

Weight (user wght)	Without / with avar 2 overlay		
Semilight (360)			
			
Regular (400)			
			
Bold (700)			
			

Fonts: SomervilleMathVF-withoutavar2.ttf and SomervilleMathVF.ttf.

Somerville italic H scripts: Caption





User opsz: 8. Target internal opsz: 400.
With avar 2: target STYA=278, STYB=165. Without: STYA=STYB=400 (target internal opsz).
With avar 2, STYA/STYB inputs remain 5. Set at 12pt, enlarged 1.5 times.
All bases and scripts use italic H. First row: superscript, subscript, both. Second row: nested scripts testing the second script level.
Internal targets are approximate because of avar rounding.
Overlay: red = without avar 2; black = with avar 2, both at 50 percent opacity. Each formula shares the same origin and baseline.

Weight (user wght)	Without / with avar 2 overlay		
Semilight (360)			
			
Regular (400)			
			
Bold (700)			
			

Fonts: SomervilleMathVF-withoutavar2.ttf and SomervilleMathVF.ttf.

Somerville italic H scripts: Regular




User opsz: 12. Target internal opsz: 550.
With avar 2: target STYA=375, STYB=246. Without: STYA=STYB=550 (target internal opsz).
With avar 2, STYA/STYB inputs remain 5. Set at 12pt, enlarged 1.5 times.
All bases and scripts use italic H. First row: superscript, subscript, both. Second row: nested scripts testing the second script level.
Internal targets are approximate because of avar rounding.
Overlay: red = without avar 2; black = with avar 2, both at 50 percent opacity. Each formula shares the same origin and baseline.

Weight (user wght)	Without / with avar 2 overlay		
Semilight (360)			
			
Regular (400)			
			
Bold (700)			
			

Fonts: SomervilleMathVF-withoutavar2.ttf and SomervilleMathVF.ttf.

Somerville italic H scripts: Subheading




User opsz: 21. Target internal opsz: 700.
With avar 2: target STYA=585, STYB=451. Without: STYA=STYB=700 (target internal opsz).
With avar 2, STYA/STYB inputs remain 5. Set at 12pt, enlarged 1.5 times.
All bases and scripts use italic H. First row: superscript, subscript, both. Second row: nested scripts testing the second script level.
Internal targets are approximate because of avar rounding.
Overlay: red = without avar 2; black = with avar 2, both at 50 percent opacity. Each formula shares the same origin and baseline.

Weight (user wght)	Without / with avar 2 overlay		
Semilight (360)			
			
Regular (400)			
			
Bold (700)			
			

Fonts: SomervilleMathVF-withoutavar2.ttf and SomervilleMathVF.ttf.

Somerville italic H scripts: Display

User opsz: 48. Target internal opsz: 900.
With avar 2: target STYA=818, STYB=711. Without: STYA=STYB=900 (target internal opsz).
With avar 2, STYA/STYB inputs remain 5. Set at 12pt, enlarged 1.5 times.
All bases and scripts use italic H. First row: superscript, subscript, both. Second row: nested scripts testing the second script level.
Internal targets are approximate because of avar rounding.
Overlay: red = without avar 2; black = with avar 2, both at 50 percent opacity. Each formula shares the same origin and baseline.

Weight (user wght)	Without / with avar 2 overlay		
Semilight (360)			
			
Regular (400)			
			
Bold (700)			
			

Fonts: SomervilleMathVF-withoutavar2.ttf and SomervilleMathVF.ttf.

Somerville italic H scripts: Needlepoint

User opsz: 1200. Target internal opsz: 1200.
With avar 2: target STYA=1150, STYB=1100. Without: STYA=STYB=1200 (target internal opsz).
With avar 2, STYA/STYB inputs remain 5. Set at 12pt, enlarged 1.5 times.
All bases and scripts use italic H. First row: superscript, subscript, both. Second row: nested scripts testing the second script level.
Internal targets are approximate because of avar rounding.
Overlay: red = without avar 2; black = with avar 2, both at 50 percent opacity. Each formula shares the same origin and baseline.

Weight (user wght)	Without / with avar 2 overlay		
Semilight (360)			
			
Regular (400)			
			
Bold (700)			
			

Fonts: SomervilleMathVF-withoutavar2.ttf and SomervilleMathVF.ttf.