Solve the following exercise (you can do it with one of your classmates), and hand in the solution at the beginning of the lecture on "Distributed Query Processing":

Consider the following distributed schema for the Project relation (primary key underlined).

Project(pno, name, head, budget, city):

- P1 =  $\sigma_{budget < 100000}(Project)$
- P2 =  $\sigma_{100000 \leq budget \leq 500000}(Project)$
- P3 =  $\sigma_{budget>500000}(Project)$



You can assume that this fragmentation strategy is correct (i.e., complete, disjoint and reconstructible). Given the following query:

SELECT \* FROM Project WHERE budget > 90000 AND budget < 200000;

Reproduce the data location (i.e., express the query in terms of fragments) and determine which steps the reduction phase would follow.

Q1 = 6 90000 < budget < 200000

Q'1 = 690000 = budaet = 200000 (P, UP V) P3)

- \* Grace c budget < haceo (P1) U Grace < budget < 200000 (P3) U Grace < budget < 200000 (P3)
- <sup>5</sup> 6 cond ( 6 kindiget < 100000 ) U 6 cond ( 0 1000000 ≤ kindiget ≤ 500000 ) U 6 cond ( 0 500000 < kindiget)
  </p>
- \* O cocco A cocco A budget A budget Cocco A cocco on hull

per rimplifical, const = 90000 < bulget < 200000

Franco : marget A tradiget 600000 A 90000 < tradiget A tradiget < 200000 → 100 multi

- a source rapides v doors rapides v probles yours un us for forto-
- = <sup>6</sup> 40000 € Propose € Propose € Propose € Propose € Propose € €)
- ° विकार कार्यक्रम (१९) त क्षेत्रक्षिर चळळळ (१३)

Per tount, la nove query serà: Q, = 0,0000 < budget (P) U o budget < 200000 (P)