

Project title :Implementation Client Script UI Policy

Phase 3: Project Design phase

1. Project Design Phase

Architectural Design Pattern The configuration utilizes ServiceNow's native client-side rendering architecture. Execution flows down two tracks:

1. Declarative UI Policies: Configured via the UI Engine for visibility, read-only status, and mandatory fields

2. Imperative Client Scripts: Written in JavaScript utilizing the g_form API for active script hooks (onChange, onSubmit, onCellEdit)

2. Data Rules and Logical Matrix

Field Name: Assignment group
Trigger Condition: Impact = 1 - High
UI Behavior / Rule Applied: Mandatory = True
System Execution Type: UI Policy

Field Name: Urgency
Trigger Condition: Impact = 1 - High
UI Behavior / Rule Applied: Read-only = True
System Execution Type: UI Policy Action

Field Name: Urgency
Trigger Condition: Impact = 1 - High
UI Behavior / Rule Applied: Auto-populate Value = "1"
System Execution Type: onChange Client Script

Field Name: Assigned to
Trigger Condition: Form Submission
UI Behavior / Rule Applied: Abort Save if empty when
Impact = 1
System Execution Type: onSubmit Client Script

Field Name: State
Trigger Condition: Inline List Edit
UI Behavior / Rule Applied: Prevent modification and throw
Alert
System Execution Type: onCellEdit Client Script

The screenshot shows the ServiceNow UI Policy configuration interface. The top navigation bar includes 'Client Script UI Policy Introduction', 'Non-Functional Requirements', 'ServiceNow Developers', and 'High Impact Control | UI Policy'. The main content area is titled 'UI Policy - High Impact Control' and contains a 'When to Apply' section with a 'Script' tab. The 'Conditions' section shows a rule: 'If selected, the UI Policy applies to all form views; otherwise the UI Policy is view-specific'. The 'Actions' section shows a rule: 'Apply the UI policy actions when the form is loaded and when the user changes values on the form'. Below the actions, there is a table titled 'UI Policy Related List Actions' with columns for 'Field name', 'Mandatory', 'Mobile', and 'Read only'. The table contains two rows: one for 'assignment_group' and one for 'assignment_group'.

Field name	Mandatory	Mobile	Read only
assignment_group	Leave alone	Leave alone	True
assignment_group	True	Leave alone	False

Client Script UI Policy Introduct...Non-Functional RequirementsServiceNow DevelopersClient Scripts | ServiceNow

dev430484.service-now.com/now/nav/ui/classic/params/target/sys_script_client_list.do%3Fsysparm_query%3Dsys_class_name%253Dsys_script_client%255EEQ...

servicenowAll Favorites History Workspaces AdminClient Scripts

Client Scriptsfor textSearch

Actions on selected rows...New

All > Class = Client Script

Name	Active	Table	Application	View	Type	Updated
EF - Show Error Prefix Format Info	true	Error Source Application [sys_error_appl]	Global		onLoad	2026-09-25 00:19:21
Maximum Duration Range Check	true	Transaction Quota Rule [sysrule_quota]	Global		onChange	2012-05-30 14:47:01
Create default value	true	Response Template Channel [sn_templated_snip_channel]	Templated Snippets		onChange	2020-09-22 17:06:27
Show overlap field based on data labels	true	Widgets [pa_widgets]	Global		onChange	2021-04-23 02:59:51
Set protocol based on auth type	false	HTTP(s) Connection [http_connection]	Global		onChange	2017-06-02 15:49:24
Set default values for OIDC PKCE flow	true	OAuth OIDC Entity [oauth_oidc_entity]	Global		onChange	2020-02-28 00:59:58
Make notification read only	true	Additional Notification Recipients [sys_notification_recipient]	Global		onLoad	2021-02-05 22:42:13
Deprecated - SN - Make serial number man	false	Asset [alm_asset]	Global		onChange	2025-03-06 00:42:54
Validate StatefulSet Name	true	MID K8s Deployment Request [mid_k8s_deployment]	Global		onChange	2022-10-09 23:18:07
Set Use current record if delete	true	Action item [sys_sg_write_back_action_item]	Global		onChange	2019-04-14 07:30:02
Warning when no destination type enabled	true	Notification [sys_notification]	Global		onLoad	2021-05-13 04:51:51
Sync Status Change Handler	true	Advanced Portal Navigation [sn_ex_sp_portal_extensible_navigation]	Employee Center		onChange	2024-12-23 03:29:15
Populate, hide/show relation cons table	true	Finding Constraint [promin_finding_def_constraint]	Global		onChange	2025-07-23 03:05:08

1 to 20 of 2,659

Search

ENG IN56%12:5729-09-2026

Client Script UI Policy Introduct...Non-Functional RequirementsServiceNow DevelopersPrevent state change via list edit

dev430484.service-now.com/now/nav/ui/classic/params/target/sys_script_client.do%3Fsys_id%3D5019ca652fa4310064771ba6fa4e3bf%26sysparm_view%26sys...

servicenowAll Favorites History Workspaces AdminClient Script - Prevent state change via list edit

Client Script - Prevent state change via list editSearch

Update Delete

Related LinksRun Post-Script

Update Versions

Version

Recorded at

State

Source

Reverted from

sys_script_client_5019ca652fa4310064771ba6fa4e3bf

2026-09-25 07:44:44

Current

Update Set: Default

Attempt

1 to 1 of 1

New client scripts are run in child nodes, with direct DOM access disabled. Access to jQuery, prototype and the window object are browser disabled. To disable this on a per-script basis, configure this form and add the "Disable script" field. To disable this feature for all new global-scoped client-side scripts, set the system property "global.script.disable.global" to false.

Name

Prevent state change via list edit

Application

Global

Table

Incident [incident]

Active

☒

UI Type

Desktop

Inherited

☐

Type

onClient

Global

☒

Field name

State

Disable script

☒

Description

Messages

Script

```
1 function onClientReady(csysobj, table, tableobj, rowobj, callback) {
2
3   alert("State cannot be updated using list editing. Please open the incident.");
4
5   callback(false);
6
7 }
```

Update

Delete

Search

Actions on selected rows...New

ENG IN56%13:0129-09-2026