



Subjective Rating Scale

1 Scope

Note: Nothing in the specification supersedes applicable laws and regulations unless specific exemption has been obtained.

Note: In the event of conflict between the English and domestic language, the English language shall take precedence.

1.1 Purpose. To provide a uniform scale for all types of subjective evaluations.

2 References

Note: Only the latest approved standards are applicable unless otherwise specified.

2.1 External Standards/Specifications.

None

2.2 GM Standards/Specifications.

None

3 Resources

3.1 Facilities. Not applicable.

3.2 Equipment. A copy of the subjective rating scale is attached. See Table 1.

3.3 Test Vehicle/Test Piece. Not applicable.

3.4 Test Time. Not applicable.

3.5 Test Required Information. Not applicable.

3.6 Personnel/Skills. Not applicable.

4 Procedure

4.1 Preparation. Not applicable.

4.2 Conditions.

4.2.1 Environmental Conditions.

4.2.2 Test Conditions. Deviations from the requirements of the procedure shall have been agreed upon. Such requirements shall be specified on component drawings, test certificates, reports, etc.

4.3 Instructions.

4.3.1 Subjective rating methods should be used only when state of the art or other circumstance

precludes objective evaluation methods and/or measurements.

4.3.2 The PERFORMANCE section of the scale should be used to rate such items as ride, handling, radio performance, and so on.

4.3.3 The DISTURBANCE section of the scale should be used to rate such items as axle noise, shake, wind noise, and tire roughness.

4.3.3.1 The shaded scale indicates estimated complaint level:

White – None Grey – Some Black – Many

4.3.4 The “0” section is to be used to indicate that a component is not functioning, not on the vehicle, etc, and, therefore, cannot be rated.

4.3.5 Additional Uses for Rating Scale Concept. Other applications of the rating scale are shown in the following example. See Table 2.

Table 1: Subjective Rating Scale ^{Note 1}

	Performance	Note 2	Disturbance
10	EXCELLENT		NONE
9			
8	GOOD		TRACE
7			
6	FAIR		MODERATE
5			
4	POOR		ANNOYING
3			
2	BAD		SEVERE
1			
0 ^{Note 3}	NOT APPLICABLE		

Note 1: Subjective rating methods should be used only when state-of-the-art or other circumstance precludes objective evaluation methods.

Note 2: The shaded scale indicates estimated complaint level:

WHITE–NONE GREY–SOME BLACK–MANY

Note 3: The 0 Section is to be used to indicate that a component is not functioning, not on the vehicle, etc., and therefore cannot be rated.

**Table 2: Subjective Rating Scale
Leak Application**

	Performance		Disturbance
10	NO LEAKAGE		NONE
9	DRY FILM ON PART		
8	WET DEPOSIT THIN		TRACE
7	WET DEPOSIT MEDIUM		
6	WET DEPOSIT THICK		MODERATE
5	WET DEPOSIT SAGS		
4	WET DEPOSIT RUNS		ANNOYING
3	FLUID POOLS ON PARTS		
2	FLUID DRIPS ON OTHER COMPONENTS		SEVERE
1	FLUID RUNS ON TO OTHER COMPONENTS		
0	NOT APPLICABLE		

5 Data

Not applicable.

6 Safety

This procedure may involve hazardous materials, operations, and equipment. This method does not propose to address all the safety problems associated with its use. It is the responsibility of the user of the method to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

7 Notes

Not applicable.

8 Coding System

This standard shall be referenced in other documents, drawings, VTS, CTS, etc. as follows:

Evaluate to GMW14264

9 Release and Revisions

9.1 Release. This standard originated in August 2005, replacing GMN7000. It was first approved by the Global Standards Committee and the GMW Implementation Project Decision Panel in January 2006. It was first published in January 2006.