

Preparation of Operation Standard Procedure

Process 1	Preparation of operation standard	Personnel resource	Cross-Functional Team
		Personal resource	No designation
INPUT			
The suppliers shall include the following items in operation standard, but are not limited to the following:			
a) Product name b) Components to use (if applicable, including how to identify them from similar products) c) Working name d) Work procedures and work key points (If different work is described for each product, identification shall be indicated.) e) Precautions for thorough compliance with operation standard (Statement to prohibit operations other than in the operation standard) f) Control items g) Control methods h) Quality characteristics and criteria (include limit sample, master sample) i) Identification for items indicated ㊦ by Honda in drawings and product specifications (Honda designated symbol ㊦) j) Identification for special characteristics as defined by the supplier (symbols other than ㊦) k) Inspection methods l) Past problem history (PPH), and control points m) Workplace requirements n) Name and usage of equipment/tools (including identification methods to prevent misuse) o) Methods of managing consumables and auxiliary materials, etc. (Expiration date, identification method, etc.) p) All critical points of the manufacturing process, including - Failure mode in case of non-compliance with operation standard - Failure effects of nonconformity on the vehicle q) Lot control methods r) FIFO methods (Transportation, storage, and delivery of products between processes, etc.) s) Inspection methods, frequency, and items to be checked for containers and carts that are used repeatedly t) Method of handling abnormalities, including the following - How to deal with specific abnormal cases - Precautions for prohibiting abnormality handling at the discretion of the workers - Containment methods for unidentified and suspect products (Includes identification and quarantine of products, identification of the scope, and trace back confirmation.) - Escalation rules and routes (Include relevant departments/roles and how to respond in the absence of the responsible person) - Quality checks for unplanned production shutdowns (Preventing process skips, checking first products, etc.) - In case of special characteristics, approval of manufacturing process restart by the supplier representative - Recording method of abnormality handling results - Criteria for deciding whether or not to dispose of nonconforming products, and disposal method u) Set-up methods, including - Check equipment/jigs and tools before and after setup (Include methods for removal of residual auxiliary materials, etc.) - Validation of components and raw materials - Confirmation of first/end product after setup v) Equipment checking and maintenance procedures (See SQM 2.5 Requirements for the Production Facility, Mold, Jig and Tool, etc.)			
Process 2	Verification of operation standard	Personnel resource	Cross-Functional Team
		Material resource	No designation
INPUT			
The suppliers shall ensure that operation standard satisfy the following			
a) Describe quality characteristics and criteria as quantitatively as possible b) Language shall be understandable by workers c) Provide audiovisual explanations and concrete expressions by means of diagrams/photographs, etc. d) Check multiple times for assembly processes that could contribute to serious malfunctions (e.g. cotter pin insertion, etc.), as possible e) Check if recurrence prevention measures are in place for both hardware and software for work involves important safety parts (e.g. bolt fastening for important safety parts installation). f) If the description includes tentative items, identify them as tentative g) Unify the forms h) Review difficult work and incomprehensible expressions throughout the production preparation			