



TRANSLATION HANKOOK

PORSCHE Inspection Catalog Chassis: Tires

Testing Procedure F.360.501

Dry Handling Lane Change

Test Carrier:	Vehicle
Testing Facility:	Circuit
Status (Porsche):	2020
Author:	M.Funke
Translated:	H.Irmler
(see target data sheet / "Zieldatenblatt")	

1 Purpose

This test method specifies a procedure for assessing driving safety and handling on dry roads.

2 Field of Application

This test method is valid for:

- Approval tests
- Series Monitoring

3 Definition of Terms

N/A

4 Responsibility

Approval tests:

The test for approval is carried out and documented by Porsche. The results are made available to the tire manufacturer if required.

Retesting:

Retesting of approval tires can be arranged by the Porsche specialist department if required.

5 Description of the Testing Procedure

5.1 Measuring Equipment

5.1.1 Measured Variables / Assessment Variables

see assessment sheet in the appendix

Rating scale PBI:

3	4	5	6	7	8	9	10
Not sufficient	deficient	Not satisfactory	Improvement necessary	satisfactory	good	very good	Exceeds expectations

5.1.2 Test Track

On test sites where the criteria listed in the subjective assessment sheets can be tested, here called "test track".

5.1.3 Data Processing

N/A

5.2 Test Conditions

- Ambient temperature for summer tires $>10^{\circ}\text{C}$
- Ambient temperature for winter tires $<15^{\circ}\text{C}$
- Ambient temperature for all-season tires $>0^{\circ}\text{C}$
- Tires should be mounted 48h before
- air pressure settings according to test program

5.3 Test Carrier / Test Set-Up

- Wheel loads of the vehicle according to target data sheet (full tank with driver)
- Rim width, diameter and contour at the rim seat of the test rim must correspond to the respective Original Porsche wheel (see target data sheet)

5.4 Test Procedure

- With each set of tires to be tested, the test track is driven over the entire speed range up to the maximum speed.
- The driver tries to use the entire adhesion potential in the longitudinal and lateral directions at the maximum possible speed.
- As far as possible, special driving maneuvers are performed in suitable sections of the route (wagging, lane changes, steering stimulation, etc.).
- Meanwhile, the driver obtains a driving impression according to the individual criteria listed in the assessment sheet in the appendix.
- On the Nürburgring-Nordschleife, two laps are generally completed per set of tires. During the tire change, the driver notes his assessment of the tire driven according to the assessment criteria of the test protocol in the appendix.
- For the evaluation, he has a rating scale from 10 to 3 ("exceeds expectations" to "Not sufficient") at his disposal, with which he must evaluate each listed individual criterion accordingly. (Definition of the grading scale is included in the test protocol, see appendix).
- Furthermore, the driver has the option of supplementing the grading of the individual criteria with explanatory text in a supplementary sheet (see appendix).

6 Documentation

6.1 Data Analysis

Using a predefined weighting (see appendix) of the individual criteria, a spreadsheet program calculates the tire's overall subjective score from the individual scores. The overall assessment result of the tire set in relation to the reference set consists of two parts:

- Individual scores of the evaluation criteria + weighted overall score subjective
- explanatory text on the subjective impression

Ambient temperature, pavement temperature, weather and track condition at the test site shall be recorded.

6.2 Presentation of the results

In the form of a test protocol

6.3 Requirements

The tire must achieve the values specified in the target data sheet.

7 Applicable Documents

Appendix 1: Assessment Sheet Dry Handling
 Assessment Sheet Lane Change

8 Distributor

EFF