



TRANSLATION HANKOOK

PORSCHE Inspection Catalog Chassis: Tires

Testing Procedure F.360.503

Driving Comfort Dry

Test Carrier:	Vehicle
Testing Facility:	Street
Status (Porsche):	07.06.2005
Author:	M.Bauer
Translated:	H.Irmler
(see target data sheet / "Zieldatenblatt")	

1 Purpose

This test method specifies a procedure for assessing driving comfort on dry roads.

2 Field of Application

This test method is valid for:

- Approval tests
- Series Monitoring

3 Definition of Terms

N/A

4 Responsibility

Approval tests:

The test for approval is carried out and documented by Porsche. The results are made available to the tire manufacturer if required.

Retesting:

Retesting of approval tires can be arranged by the Porsche specialist department if required.

5 Description of the Testing Procedure

5.1 Measuring Equipment

5.1.1 Measured Variables / Assessment Variables

see assessment sheet in the appendix

Rating scale:

-3	-2	-1	0	+1	+2	+3
Not sufficient	deficient	Not satisfactory	satisfactory	good satisfactory	good	very good

5.1.2 Test Track

Selected PAG tire comfort route or a comparable driving route where the criteria listed in the assessment sheet can be tested.

5.1.3 Data Processing

N/A

5.2 Test Conditions

- Ambient temperature for summer tires $>10^{\circ}\text{C}$
- Ambient temperature for winter tires $<15^{\circ}\text{C}$

5.3 Test Carrier / Test Set-Up

- Wheel loads of the vehicle according to target data sheet (partially loaded)
- Rim width, diameter and contour at the rim seat of the test rim must correspond to the respective Original Porsche wheel (see target data sheet)
- Driving is done with an appropriate vehicle with current chassis status

5.4 Test Procedure

- The track is run through once with each tire

- During the drive, the specified individual criteria are checked on the corresponding sections according to the subjective impressions.
- Rolling noise on various surfaces, vertical bump on various "road imperfections" and handling comfort such as steering bump, straight-line stability and highway lane changes are assessed.
- During the tire change, the driver notes his evaluation of the tire driven according to the evaluation criteria of the test protocol in the appendix.
- For the evaluation he has a grading scale from +3 to -3 ("very good" to "not sufficient") at his disposal, with which he must evaluate each listed individual criterion accordingly (definition of the grading scale is included in the test protocol).
- Furthermore, the driver has the option of supplementing the grading of the individual criteria with explanatory text in a supplementary sheet (see appendix).

6 Documentation

6.1 Data Analysis

Using a predefined weighting (see assessment sheet in appendix) of the individual criteria, a spreadsheet program calculates the tire's overall subjective score from the individual scores. The overall assessment result of the tire set in relation to the reference set consists of two parts:

- Individual scores of the evaluation criteria + weighted overall score subjective,
- explanatory text on the subjective impression

Ambient temperature, pavement temperature, weather and track condition at the test site shall be recorded.

6.2 Presentation of the results

In the form of an assessment sheet

6.3 Requirements

The tire must achieve the values specified in the target data sheet.

7 Applicable Documents

Appendix 1:	Assessment Sheet Comfort Sports Car
Appendix 2:	Assessment Sheet Comfort SUVs

8 Distributor

EMF