1. Select all the conditional structures that exist in JavaScript. Select all that apply.

   1 / 1 point

   ☑ logical && operator

   > ✓ **Correct**
   > Correct. The logical && operator is one of the conditional structures available in JavaScript.

   ☑ ternary operator

   > ✓ **Correct**
   > Correct. The ternary operator is one of the conditional structures available in JavaScript.

   ☑ if-else statement

   > ✓ **Correct**
   > Correct. The if-else statement is one of the conditional structures available in JavaScript.

   ☑ switch statement

   > ✓ **Correct**
   > Correct. The switch statement is one of the conditional structures available in JavaScript.

2. What will be the output if you ran this code in the browser console:

   1 / 1 point

   true && 5

   ○ false

   ○ undefined

   ◉ 5

   ○ true

   > ✓ **Correct**
   > That's correct! The value that gets output is: 5.

3. If the value of the test variable evaluates to true, what will the following code render?

   1 / 1 point

```
1   < div > {
2        test && < h1 > Hello < /h1>} World</div >
```

○ An empty div

○ World

○ Hello

◉ Hello World

✓ **Correct**
  That's correct! The value of test is true, so <div><h1>Hello</h1>World</div> will be rendered.

4. If the value of morning is false, what will the following code render?   1 / 1 point

```
1   {
2       morning ? < h2 > Breakfast time! < /h2> : <h2>Lunch time!</h2 >
3   }
```

○ Breakfast time!

◉ Lunch time!

✓ **Correct**
  That's right! The returned value will be "Lunch time!".

5. Choose the correct syntax to build a new Date object in JavaScript?   1 / 1 point

○ Date();

○ New Date();

○ new Date;

◉ new Date();

✓ **Correct**
  That's correct. This code will result in a new object instance of the Date constructor.