



DATA STRUCTURES AND ALGORITHMS


Lecture 13: Graphs

Lecturer: Mohsin Abbas

National University of Modern Languages, Islamabad


GRAPHS

- Consider this collection of vertices
 - $V = \{v_1, v_2, \dots, v_9\}$
 - Where $|V| = n$




UNDIRECTED GRAPHS

- Associated with these vertices are $|E| = 5$ edges
 - $E = \{\{v_1, v_2\}, \{v_3, v_5\}, \{v_4, v_8\}, \{v_4, v_9\}, \{v_6, v_9\}\}$
- Pair $\{v_j, v_k\}$ indicates following relations
 - Vertex v_j is adjacent to vertex v_k
 - Vertex v_k is adjacent to vertex v_j



UNDIRECTED GRAPHS – EXAMPLE

- Given $|V| = 7$ vertices and $|E| = 9$ edges
 - $V = \{A, B, C, D, E, F, G\}$
 - $E = \{\{A, B\}, \{A, D\}, \{A, E\}, \{B, C\}, \{B, D\}, \{B, E\}, \{C, E\}, \{C, F\}, \{D, E\}\}$




APPLICATIONS OF GRAPHS

- Driving Map
 - Vertex = Intersection, destinations
 - Edge = Road
- Airline Traffic
 - Vertex = Cities serviced by the airline
 - Edge = Flight exists between two cities
- Computer networks
 - Vertex = Server nodes, end devices, routers
 - Edge = Data link

APPLICATIONS OF GRAPHS

- Many real-world applications concern large graphs
- Web document graph - 1 trillion webpages
 - Vertex = Webpage
 - Edge = Hyperlink
- Social networks - 1.3 billion users
 - Vertex = Users
 - Edge = Friendship relation



UNDIRECTED GRAPHS – DEFINITION


- An **undirected Graph** is defined as $G=(V,E)$ consisting of
 - Set V of **vertices**: $V = \{v_1, v_2, \dots, v_n\}$
 - Number of vertices is denoted by $|V| = n$
 - Set E of unordered pairs $\{v_i, v_j\}$ termed **edges**
 - Edges connect the vertices
- **Maximum number of edges** in an undirected graph is $O(|V|^2)$

$$|E| \leq \binom{|V|}{2} = \frac{|V|(|V| - 1)}{2} = O(|V|)^2$$

- Assumption: A vertex is never adjacent to itself
 - For example, $\{v_1, v_1\}$ will not define an edge
- Many data structures can implement abstract undirected graphs
 - Adjacency matrices, Adjacency lists

DEGREE



- Degree of a vertex is defined as the number of adjacent vertices
 - $\text{degree}(A) = \text{degree}(D) = \text{degree}(C) = 3$
 - $\text{degree}(B) = \text{degree}(E) = 4$
 - $\text{degree}(F) = 1$
 - $\text{degree}(G) = 0$



- Vertices adjacent to a given vertex are its neighbors


SUBGRAPH

- A sub-graph of a graph G is defined by
 - Subset of the vertices
 - Subset of the edges that connected the subset of vertices in the original graph
- Every graph is a subgraph of itself




PATH

- Path in an undirected graph is an ordered sequence of vertices
 - Consecutive vertices are connected through edges
- Path from vertex 0 to vertex k is $(v_0, v_1, v_2, \dots, v_k)$
 - where $\{v_{j-1}, v_j\}$ is an edge for $j = 1, \dots, k$
- Length of a path is equal to the number of edges
- Example: Path from A to F
 - Path: (A, B, E, C, F)
 - Length of the path is 4




PATH – EXAMPLE

- Path of length 5: (A, B, E, C, B, D)
 - Repetition of vertex B



PATH – EXAMPLE

- A trivial path of length 0: (A)




SIMPLE PATH


- A simple path has no repetitions other than perhaps the first and last vertices
- A simple cycle is a simple path of at least two vertices with the first and last vertices equal
 - Note: these definitions are not universal
- A loop is an edge from a vertex onto itself

CONNECTEDNESS

- Two vertices v_i, v_j are said to be connected if there exists a path from v_i to v_j
- A graph is connected if there exists a path from every vertex to every other vertex




A connected graph



An unconnected graph


WEIGHTED GRAPHS

- A weight may be associated with each edge in a graph
 - This could represent distance, energy consumption, cost, etc.
 - Such a graph is called a weighted graph
- Pictorially, we will represent weights by numbers next to the edges




WEIGHTED GRAPHS

- Length of a path within a weighted graph is the sum of all of the edges which make up the path
- The length of the path (A, D, G) in the following graph is 8.8




WEIGHTED GRAPHS – EXAMPLE

- Different paths may have different weights
 - Another path is (A, C, F, G) with length $1.2 + 1.4 + 4.5 = 7.1$




WEIGHTED GRAPHS – EXAMPLE

- Find the shortest path between two vertices A and G
- Shortest path is (A, C, F, D, E, G) with length 5.7



TREES

- A graph is a tree if it satisfies the following two conditions
 - Graph is connected
 - There is a unique path between any two vertices




- Consequences
 - The number of edges is $|E| = |V| - 1$
 - The graph is acyclic, that is, it does not contain any cycles
 - Adding one more edge must create a cycle
 - Removing any one edge creates two disjoint non-empty sub-graphs


Three trees on
same 8 vertices

TREES

- Any tree can be converted into a rooted tree by
 - Choosing any vertex to be the root
 - Defining its neighboring vertices as its children
- Recursively defining
 - All neighboring vertices other than that one designated as parent to be that vertex children




Unrooted Tree




Tree rooted at A

TREES – EXAMPLE




Unrooted Tree




Tree rooted at C

TREES – EXAMPLE



Unrooted Tree




Tree rooted at B

FOREST

- A forest is any graph that has no cycles
- Consequences
 - The number of edges is $|E| < |V|$
 - The number of trees is $|V| - |E|$
 - Removing any one edge adds one more tree to the forest

- Forest with 22 vertices and 18 edges
 - Four trees




DIRECTED GRAPHS

- In a directed graph, the edges on a graph are associated with a direction
 - Edges are ordered pairs (v_j, v_k) denoting a connection from v_j to v_k
 - The edge (v_j, v_k) is different from the edge (v_k, v_j)
- Streets are directed graphs
 - In most cases, you can go two ways unless it is a one-way street


DIRECTED GRAPHS

- Given our graph of nine vertices $V = \{v_1, v_2, \dots, v_9\}$
 - These six pairs (v_j, v_k) are directed edges
 - $E = \{(v_1, v_2), (v_3, v_5), (v_5, v_3), (v_6, v_9), (v_8, v_4), (v_9, v_4)\}$




IN AND OUT DEGREE

- Degree of a vertex must be modified to consider both cases:
 - **Out-degree** of a vertex is the number of vertices which are adjacent to the given vertex
 - Number of outgoing edges
 - **In-degree** of a vertex is the number of vertices which this vertex is adjacent to
 - Number of incoming edges
- In this graph:
 - $\text{In-degree}(v_1) = 0$ $\text{out-degree}(v_1) = 2$
 - $\text{In-degree}(v_5) = 2$ $\text{out-degree}(v_5) = 3$




PATH

- A path in a directed graph is an ordered sequence of vertices
 - $(v_0, v_1, v_2, \dots, v_k)$
 - where (v_{j-1}, v_j) is an edge for $j = 1, \dots, k$
- A path of length 5 in this graph is
 - $(v_1, v_4, v_5, v_3, v_5, v_2)$
- A simple cycle of length 3 is
 - (v_8, v_4, v_5, v_8)




CONNECTEDNESS

- Two vertices v_j, v_k are said to be connected if there exists a path from v_j to v_k
 - A graph is **strongly connected** if there exists a directed path between any two vertices
 - A graph is **weakly connected** if there exists a path between any two vertices that ignores the direction




CONNECTEDNESS – EXAMPLE

- The sub-graph $\{v_3, v_4, v_5, v_8\}$ is strongly connected
- The sub-graph $\{v_1, v_2, v_3, v_4, v_5, v_8\}$ is weakly connected




WEIGHTED DIRECTED GRAPHS

- Each edge is associated with a value
- If both (v_j, v_k) and (v_k, v_j) are edges
 - It is not required that they have the same weight



REPRESENTATION


- How do we store the adjacency relations?
 - Adjacency matrix
 - Adjacency list



ADJACENCY MATRIX

- Two dimensional matrix of size $n \times n$ where $n = |V|$
- $a[i, j] = 0$ (F) if there is no edge between vertices v_i
- $a[i, j] = 1$ (T) if there is an edge between vertices v_i
- Adjacency matrix of undirected graphs is symmetric
 - $a[i, j] = a[j, i]$


	0	1	2	3	4	5
0		T	F	T	F	T
1	T		T	T	T	T
2	F	T		T	F	F
3	T	T	T		T	F
4	F	T	F	T		F
5	T	T	F	F	F	



ADJACENCY MATRIX – WEIGHTED GRAPH

- The matrix entry $[j, k]$ is set to the weight of the edge (v_j, v_k)
- How to indicate absence of an edge in the graph?


	0	1	2	3	4	5
0		0.83		0.65		0.51
1	0.83		0.67	0.72	0.46	0.90
2		0.67		0.39		
3	0.65	0.72	0.39		0.24	
4		0.46		0.24		
5	0.51	0.90				



ADJACENCY MATRIX – DIRECTED GRAPH

- For directed graph the matrix would not necessarily be symmetric


	0	1	2	3	4	5
0				0.65		
1	0.83			0.72	0.46	0.90
2		0.67		0.39		
3					0.24	
4				0.24		
5	0.51					



ADJACENCY MATRIX – DIRECTED GRAPH


- For directed graph the matrix would not necessarily be symmetric

	0	1	2	3	4	5
0				0.65		
1	0.83			0.72	0.46	0.90
2		0.67		0.39		
3					0.24	
4				0.24		
5	0.51					



ADJACENCY MATRIX – ANALYSIS

	1	2	3	4	5	6	7	8	9
1		1		1					
2									
3					1				
4		1			1				
5		1	1					1	
6									1
7									1
8				1					
9									




- Requires memory : $O(|V|^2)$
- Determining if v_j is adjacent to v_k : $O(1)$
- Finding all neighbors of v_j : $O(|V|)$

ADJACENCY MATRIX – PROBLEM

- Very sparsely populated
 - Out of 81 cells only 11 are 1 (or T)


	1	2	3	4	5	6	7	8	9
1		1		1					
2									
3					1				
4		1			1				
5		1	1					1	
6									1
7									1
8				1					
9									



ADJACENCY LIST

- Each vertex is associated with a list of its neighbors
 - A vertex w is inserted in the list for vertex v if edge (v, w) exists


1	• → 2 → 4
2	•
3	• → 5
4	• → 2 → 5
5	• → 2 → 3 → 8
6	• → 9
7	• → 9
8	• → 4
9	•



- Requires memory : $O(|V| + |E|)$

ADJACENCY LIST – WEIGHTED GRAPHS

- An adjacency list for a weighted graph contains two elements
 - First element for the vertex
 - Second element for the weight of that edge



- When the vertices are identified by a name (i.e., string)
 - Hash-table of lists is used to implement the adjacency list

CONCLUSION

- In this lecture we have studied:
 - Graph
 - Undirected and Directed Graph
 - Weighted Graph
 - Adjacency Matrix and Adjacency List

Question?