

RFQ NEG260010373

Title **PR 14550946 SWING CHECK VALVE**

Synopsis **Dear Supplier,**

Please provide your complete techno-commercial offer for the requirement of Ship Repair BW Maromba of below items and refer Attached Documents

1) CHECK VALVE, SWING; CLASS: 150LB; SIZE: 6"; BODY: ASTM A216 GR. WCB; DISC: ASTM A182 F51 +HARD FACED; SEAT : ASTM A182 F51 +HARD FACED; DIMENSIONAL STANDARD:ASME B16.10, ASME B16.5, ASME B16.34; END CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5011; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION -⌘ A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.- S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.- S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

2) CHECK VALVE, SWING; CLASS: 150LB; SIZE: 6"; BODY: ASTM A216 GR. WCB; DISC: ASTM A182 F51 +HARD FACED; SEAT : ASTM A182 F51 +HARD FACED; DIMENSIONAL STANDARD:ASME B16.10, ASME B16.5, ASME B16.34; END CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5012; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION -⌘ A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.- S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.- S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

3) CHECK VALVE, SWING; CLASS: 150LB; SIZE: 6"; BODY: ASTM A216 GR. WCB; DISC: ASTM A182 F51 +HARD FACED; SEAT : ASTM A182 F51 +HARD FACED; DIMENSIONAL STANDARD:ASME B16.10, ASME B16.5, ASME B16.34; END CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5013; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION -⌘ A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS:

A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.-S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.-S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

Preview Date
Close Date **30/08/26 11:55 PM**
Time Zone **Gulf Standard Time**

Open Date **26/08/26 12:23 PM**
Award Date

Submit your response to the following contact.

Company **AEDXB - Dubai Drydocks**
 Buyer **Ankur Gupta**
 Location **United Arab Emirates**
Dubai
Dubai
Jumeira Beach Road - Al MINA
Port Rashid
DUBAI MARITIME CITY
 Phone
 Fax
 E-mail **ankur.gupta@drydocks.gov.ae**

When submitting your response, include the following information.

Your Company Name	
Company Site (Optional)	
Address	
Contact Details	
Response Valid Until (Optional)	
Response Type	☐ Primary ☐ Alternate <i>(This negotiation allows you to submit multiple responses. Mark this as your primary response or an alternate one.)</i>

This document has important legal consequences. The information contained in this document is proprietary of AEDXB - Dubai Drydocks. It shall not be used, reproduced, or disclosed to others without the express and written consent of AEDXB - Dubai Drydocks.

Table of Contents

1 Overview.....	5
1.1 General Information.....	5
1.2 Schedule.....	6
1.3 Negotiation Controls.....	6
1.4 Response Rules.....	6
1.5 Terms.....	6
1.6 Attachments.....	7
2 Requirements.....	8
2.1 Section 1. Commercial Terms and Conditions.....	8
3 Lines.....	9
3.1 Line Information.....	9
3.2 Line Details.....	10
3.2.1 Line 1.....	10
3.2.2 Line 2.....	11
3.2.3 Line 3.....	12

1 Overview

1.1 General Information

Title PR 14550946 SWING CHECK VALVE
Synopsis Dear Supplier,
 Please provide your complete techno-commercial offer for the requirement of Ship Repair BW Maromba of below items and refer Attached Documents

1) CHECK VALVE, SWING; CLASS: 150LB; SIZE: 6"; BODY: ASTM A216 GR. WCB; DISC: ASTM A182 F51 +HARD FACED; SEAT : ASTM A182 F51 +HARD FACED; DIMENSIONAL STANDARD:ASME B16.10, ASME B16.5, ASME B16.34; END CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5011; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION -⌘ A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.-S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.-S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

2) CHECK VALVE, SWING; CLASS: 150LB; SIZE: 6"; BODY: ASTM A216 GR. WCB; DISC: ASTM A182 F51 +HARD FACED; SEAT : ASTM A182 F51 +HARD FACED; DIMENSIONAL STANDARD:ASME B16.10, ASME B16.5, ASME B16.34; END CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5012; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION -⌘ A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.-S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.-S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

3) CHECK VALVE, SWING; CLASS: 150LB; SIZE: 6"; BODY: ASTM A216 GR. WCB; DISC: ASTM A182 F51 +HARD FACED; SEAT : ASTM A182 F51 +HARD FACED; DIMENSIONAL STANDARD:ASME B16.10, ASME B16.5, ASME B16.34; END CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN

PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5013; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION - A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.-S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.-S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

Buyer **Ankur Gupta**
E-Mail **ankur.gupta@drydocks.gov.ae**

Outcome **Purchase Order**

1.2 Schedule

Preview Date
Close Date **30/08/26 11:55 PM**
Time Zone **Gulf Standard Time**

Open Date **26/08/26 12:23 PM**
Award Date

1.3 Negotiation Controls

Response Visibility **Sealed**

Lines Settings

Rank Indicator **1,2,3...**
Ranking Method **Price only**

1.4 Response Rules

This negotiation is governed by all the rules displayed below.

	Rule
☒	Negotiation is restricted to invited suppliers
☐	Suppliers are allowed to view other suppliers' notes and attachments
☒	Suppliers are allowed to respond to selected lines
☒	Suppliers are required to respond with full quantity on each line
☒	Suppliers are allowed to provide multiple responses
☒	Suppliers are allowed to revise their submitted response

1.5 Terms

Payment Terms **Net 90**
Shipping Method
Negotiation Currency **AED (UAE Dirham)**

Freight Terms **DDP(DeliveryDutyPaid)**
FOB
Price Precision **2**

Eligible Response Currencies

Check the one currency in which you will enter your response.

	Response Currency	Description	Price Precision
☐	AED	UAE Dirham	2
☐	EUR	Pan-European Currency	2
☐	GBP	Pound Sterling	2
☐	NOK	Norwegian Krone	2
☐	SGD	Singapore Dollar	2
☐	USD	US Dollar	2

1.6 Attachments

File Name or URL	Type	Description
Attachments.zip	File	

2 Requirements

**Response is required*

2.1 Section 1. Commercial Terms and Conditions

*1. Please confirm the Payment term proposed for this bid

Response attachments are optional.

*2. Please confirm the delivery incoterm for the submitted bid

Comments:

*3. Vendor to submit complete techno-commercial offer

Response attachments are required.

*4. Vendor to submit filled TBE (mandatory) as per attached document

Attachments:

File Name or URL	Type	Description
TBE NEG260010373 PR 14550946 .	File	

Response attachments are required.

3 Lines

3.1 Line Information

Line	Target Quantity	UOM	Response Quantity	Response Price	Line Amount	Promised Date
1-6", SWING CHECK VALVE, 150#, FLANGED RF, BDY: ASTM A216 GR. WCB; DISC: ASTM A182 F51+HF; SEAT ASTM A182 F51 +HARD FACED; STD ASME B16.10, EN 10204 3.2, ASME B16.34 ; ABS APPROVED; TAG: 71-CHV- 5011.	1	Each				
2-6", SWING CHECK VALVE, 150#, FLANGED RF, BDY: ASTM A216 GR. WCB; DISC: ASTM A182 F51+HF; SEAT ASTM A182 F51 +HARD FACED; STD ASME B16.10, EN 10204 3.2, ASME B16.34 ; ABS APPROVED; TAG: 71-CHV- 5012.	1	Each				

Line	Target Quantity	UOM	Response Quantity	Response Price	Line Amount	Promised Date
3-6", SWING CHECK VALVE, 150#, FLANGED RF, BDY: ASTM A216 GR. WCB; DISC: ASTM A182 F51+HF; SEAT ASTM A182 F51 +HARD FACED; STD ASME B16.10, EN 10204 3.2, ASME B16.34 ; ABS APPROVED; TAG: 71-CHV-5013.	1	Each				

3.2 Line Details

3.2.1 Line 1 6", SWING CHECK VALVE, 150#, FLANGED RF, BDY: ASTM A216 GR. WCB; DISC: ASTM A182 F51+HF; SEAT ASTM A182 F51 +HARD FACED; STD ASME B16.10, EN 10204 3.2, ASME B16.34 ; ABS APPROVED; TAG: 71-CHV-5011.

Category Name **Ball Valve**
Item **DDD-NONCD100126-1**

Revision

Requested Date **05/09/26**

Location **United Arab Emirates
Dubai
Dubai
Jumeirah Beach Rd**

Start Price (AED)

Note **CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5011; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION -A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.-S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.-S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.**

Attributes

Supplier Additional Information
Technical Deviation Response Optional Value Type Text Value only Provide your answer below
Lead Time Response Optional Value Type Text Value only Provide your answer below
Make & Origin Response Optional Value Type Text Value only Provide your answer below
Supplier Comments Response Optional Value Type Text Value only Provide your answer below

3.2.2 Line 2 6", SWING CHECK VALVE, 150#, FLANGED RF, BDY: ASTM A216 GR. WCB; DISC: ASTM A182 F51+HF; SEAT ASTM A182 F51 +HARD FACED; STD ASME B16.10, EN 10204 3.2, ASME B16.34 ; ABS APPROVED; TAG: 71-CHV-5012.

Category Name	Ball Valve	Revision	
Item	DDD-NONCD100126-1		
Requested Date	05/09/26	Location	United Arab Emirates Dubai Dubai Jumeirah Beach Rd
Start Price (AED)			

Note **CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5012; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL**

NOTES: 1) ABS CLASS NOTATION -# A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.-S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.-S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

Attributes

Supplier Additional Information
Technical Deviation Response Optional Value Type Text Value only Provide your answer below
Lead Time Response Optional Value Type Text Value only Provide your answer below
Make & Origin Response Optional Value Type Text Value only Provide your answer below
Supplier Comments Response Optional Value Type Text Value only Provide your answer below

3.2.3 Line 3 6", SWING CHECK VALVE, 150#, FLANGED RF, BDY: ASTM A216 GR. WCB; DISC: ASTM A182 F51+HF; SEAT ASTM A182 F51 +HARD FACED; STD ASME B16.10, EN 10204 3.2, ASME B16.34 ; ABS APPROVED; TAG: 71-CHV-5013.

Category Name **Ball Valve**
 Item **DDD-NONCD100126-1**
 Requested Date **05/09/26**

Revision

Location **United Arab Emirates
Dubai
Dubai
Jumeirah Beach Rd**

Start Price (AED)

Note CONNECTION: FLANGED RF; ABS PIPING CLASS: CLASS III; CERTIFICATION: ABS TYPE APPROVED, EN 10204 3.2; SHIP SIDE VALVE WITH ABS CLASS TEST CERT, WITH FIRE SAFE DESIGN; FIRE TEST CERTIFICATE: API 6FA; WITH NR-13 CLASSIFICATION; FLUID CLASS-D, GROUP-2; MATERIALS SHALL BE FROM ABS APPROVED MILL, DESIGN PRESSURE- 15 BAR; DESIGN TEMPERATURE- 100 DEG C; VALVE TAG:71-CHV-5013; VALVE SHALL COME WITH BRASS / BRONZE VALVE TAG, SYSTEM: FIRE WATER MAIN; GENERAL NOTES: 1) ABS CLASS NOTATION -A1 OFFSHORE INSTALLATION (SELF INSTALLING UNIT), HYDROCARBON, (S) MAROMBA FIELD, BRAZIL, RFL(15), 204X, CRC(OC), UWILD FILE ATTACHMENTS: A) BRAZILIAN REGULATION RELATED COMPILLATION DOCUMENT (DOC NO.-S18132-DD-000-PI-003_REV A. B) QUALITY AND GENERAL REQUIREMENT (DOC NO.-S18132-DD-000-PI-002_REV A). C) REFER ATTACHED VALVE TAG & NAME PLATE DETAILS.

Attributes

Supplier Additional Information
Technical Deviation ResponseOptional Value Type Text Value only Provide your answer below
Lead Time ResponseOptional Value Type Text Value only Provide your answer below
Make & Origin ResponseOptional Value Type Text Value only Provide your answer below
Supplier Comments ResponseOptional Value Type Text Value only Provide your answer below

