

Technical drawing of a grease trap assembly, showing two views: a cross-section (SECTION A-A) and a side view.

SECTION A-A (Top View):

- Dimensions:** Overall width is 570. Internal width is 380. Inlet/outlet diameter is 82Ø. Vertical dimensions include 670, 450, 620, 115, 425, 200, 150, and 311.
- Components:**
 - Ø55 (2") VENT PIPE** at the top.
 - LIFTING HANDLE** on the top cover.
 - 670 x 670 x 15 mm THICK GRP SEALED COVER** on top.
 - 10 x 30 BRASS BOLT & NUT** and **5mm THICK NEOPRENE GASKET** for the cover.
 - 450 x 280 x 450 DEEP REMOVABLE PVC PERFORATED BUCKET** with **25Ø HOLES IN FOUR ROWS EACH SIDE**.
 - 31Ø HOLES IN TWO ROWS 8 Nos. IN EACH ROW** in the side walls.
 - BAFFLE** in the outlet pipe.
 - SUPPORT FOR BUCKET SEATING** at the bottom.
- Flow:** **INLET** on the left, **OUTLET** on the right.
- Variables:** $X1 \text{ MIN} = 50$, $X1 \text{ MAX} = 200$, and $(X2 = X1 + 50)$.

Side View (Bottom View):

- Dimensions:** Overall width is 570. Inlet/outlet diameter is 82Ø. Vertical dimensions include 50mm GAP, 150, 66, and 570.
- Components:**
 - 55Ø (2") PIPE** at the top.
 - 570 x 570 GREASE TRAP FABRICATED WITH 8 mm THICK PVC SHEETS** forming the main body.
- Flow:** **INLET** on the left, **OUTLET** on the right.
- Section Line:** Indicated by **A** at both ends.

TITLE:	UPVC GREASE TRAP TYPE - A
DWG. NO.:	HEP/PVC-FAB/2623