

Technical drawing of a 300mm diameter manhole assembly, showing a cross-section view. The drawing includes the following components and dimensions:

- Top Structure:** CI CHANNEL GRATING & FRAME WITH 300 x 300 CLEAR OPENING (NOT INCLUDED). The opening diameter is $\varnothing 295$.
- Lifting Handle:** 10 X 40 mm LIFTING HANDLE.
- Basket:** GRP PERFORATED BASKET THICKNESS = 4 mm (Code: FGFSB003). It features 20 mm DIA HOLES X 2 ROWS.
- Drainage Pipe:** PVC DRAINAGE PIPE THICKNESS = 7.5 mm.
- Outlet:** 110 mm $\varnothing$ OUTLET.
- Dimensions:**
 - Overall height: 400 mm.
 - Height from top frame to bottom of basket: 300 mm.
 - Height from bottom of basket to bottom of pipe: 170 mm.
 - Inner diameter of the basket: 255 mm.
 - Inner diameter of the pipe: 215 mm.
 - Overall inner diameter: $\varnothing 300$ ID.
 - Overall outer diameter: $\varnothing 315$ OD.
 - Bottom slope: 2mm TO 3mm SLOPE.
 - Bottom holes: 6 NO. 4mm - 5mm HOLES PCD 160mm.

- 1.) DESIGNED FOR SURFACE DRAIN OUT AREA = 230 SQ.M
- 2.) PIPE OUTLET SIZE = 110mm DIA.
- 3.) FLOW RATE OF 110mm DIA. PIPE = 8 LIT/SEC OR 105 GALLON/MIN
(DISCHARGE RUNNING FULL AT 1:100 GRADIENT)

**DESIGNED BY: RASHID AL SUWAIDI /
SAEED ANWAR HAYAT**

+GF+ CORYS

PREPARED		CHECKED		APPROVED		SCALE
NAME	DATE	NAME	DATE	NAME	DATE	
Rajkumar	14.12.23	Sogy T	14.12.23	Sogy T	14.12.23	N.T.S.
ISSUED FOR APPROVAL			FOLIO/PAPER SIZE: A4			00

TITLE:
**UPVC CATCH BASIN
DETAIL (STANDARD)**

DWG. NO.:HEP/PVC-FAB/4377