

CERTIFICATE OF CONFORMITY

This certificate confirms the declared products meet stated: performance capabilities, material standards and product standards where applicable and are rigorously subject to 3rd-party assessment by internationally renowned certification bodies.

Description

Product Series: 901 Pegler Prestex Float Valves

Size range: ½" to 1" (Brass CW617N)
1.1/4" to 6" (Bronze CC499K)

Pressure Rating: 10 bar

Material

Body Material: Brass CW617N (BS EN 12164) – controlled between limits in table below

Composition % (mass fraction)											
Grade	Element	Cu	Al	As	Fe	Mn	Ni	Pb	Sn	Zn	Others
CW617N	Min	57.0	-	-	-	-	-	1.6	-	Rem.	-
	Max	59.0	0.05	-	0.3	-	0.3	2.2	0.3	-	0.2

Body Material: Gunmetal CC499K (EN 1982) – controlled between limits in table below

Composition % (mass fraction)													
Grade	Element	Cu	Fe	Si	P	S	Cr	Al	As	Zn	Cd	Sn	Sb
CC499K	Min	84.0	-	-	-	-	-	-	-	4.0	-	4.0	-
	Max	88.0	0.3	0.01	0.04	0.04	0.02	0.01	0.03	6.0	0.02	6.0	0.1

Sealing washer Material: EPDM (material is UKReg4 approved)

Piston washer material: EPDM (material is UKReg4 approved)

Test Details

Shell Test Pressure: 15 bar

Certifications & Testing

- **ISO 9001** – products supplied by Aalberts Integrated Piping Systems are done so under a quality management system approved to BS EN ISO 9001: 2015 by an independent 3rd party certification body (Certificate Number FM 00305).

- **WRAS & Regulation 4** - manufactured and tested to the appropriate quality and standards as required in the Water Supply (Water Fittings) Regulations and Scottish Water Byelaws.

For Aalberts Integrated Piping Systems Ltd.



Gavin Peters – Approvals Engineer