

Data Mining

Classification: Basic Concepts and Techniques

Lecture Notes for Chapter 3

Introduction to Data Mining, 2nd Edition

by


Tan, Steinbach, Karpatne, Kumar

Example of a Decision Tree

categorical
categorical
continuous
class

Tid	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Training Data




Model: Decision Tree

Another Example of Decision Tree

categorical
categorical
continuous
class

<i>Tid</i>	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



There could be more than one tree that fits the same data!


Decision Tree Classification Task

Tid	Attrib1	Attrib2	Attrib3	Class
1	Yes	Large	125K	No
2	No	Medium	100K	No
3	No	Small	70K	No
4	Yes	Medium	120K	No
5	No	Large	95K	Yes
6	No	Medium	60K	No
7	Yes	Large	220K	No
8	No	Small	85K	Yes
9	No	Medium	75K	No
10	No	Small	90K	Yes

Training Set


Tid	Attrib1	Attrib2	Attrib3	Class
11	No	Small	55K	?
12	Yes	Medium	80K	?
13	Yes	Large	110K	?
14	No	Small	95K	?
15	No	Large	67K	?

Test Set



Apply Model to Test Data

Start from the root of tree.




Test Data

Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?

Apply Model to Test Data

Test Data


Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



Apply Model to Test Data

Test Data


Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



Apply Model to Test Data

Test Data



Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



Apply Model to Test Data

Test Data


Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



Apply Model to Test Data

Test Data

Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



Assign Cheat to "No"


Decision Tree Classification Task

Tid	Attrib1	Attrib2	Attrib3	Class
1	Yes	Large	125K	No
2	No	Medium	100K	No
3	No	Small	70K	No
4	Yes	Medium	120K	No
5	No	Large	95K	Yes
6	No	Medium	60K	No
7	Yes	Large	220K	No
8	No	Small	85K	Yes
9	No	Medium	75K	No
10	No	Small	90K	Yes

Training Set

Tid	Attrib1	Attrib2	Attrib3	Class
11	No	Small	55K	?
12	Yes	Medium	80K	?
13	Yes	Large	110K	?
14	No	Small	95K	?
15	No	Large	67K	?


Test Set



General Structure


- Let D_t be the set of training records that reach a node t
- **General Procedure:**
 - If D_t contains records that belong the same class y_t , then t is a leaf node labeled as y_t
 - If D_t contains records that belong to more than one class, use an attribute to split the data into smaller subsets. Recursively apply the procedure to each subset

<i>Tid</i>	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



Example

Tid	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



Tree Induction


- **Greedy strategy**
 - Split the records based on an attribute test that optimizes certain criterion
- **Issues**
 - Determine how to split the records
 - How to specify the attribute test condition?
 - How to determine the best split?
 - Determine when to stop splitting

How to Specify Test Condition?


- **Depends on attribute types**
 - Nominal
 - Ordinal
 - Continuous
- **Depends on number of ways to split**
 - 2-way split
 - Multi-way split

Splitting Based on Nominal Attributes


- **Multi-way split:** Use as many partitions as distinct values



- **Binary split:** Divides values into two subsets
Need to find optimal partitioning




OR




Splitting Based on Ordinal Attributes


- **Multi-way split:** Use as many partitions as distinct values.




- **Binary split:** Divides values into two subsets
Need to find optimal partitioning



OR




- What about this split?




Splitting Based on Continuous Attributes

- Different ways of handling
 - **Discretization** to form an ordinal categorical attribute
 - **Binary Decision:** $(A < v)$ or $(A \geq v)$
 - consider all possible splits and finds the best cut
 - can be more computation intensive

Splitting Based on Continuous Attributes



(i) Binary split






(ii) Multi-way split

Tree Induction

- **Greedy strategy**
 - Split the records based on an attribute test that optimizes certain criterion.
- **Issues**
 - Determine how to split the records
 - How to specify the attribute test condition?
 - **How to determine the best split?**
 - Determine when to stop splitting

How to determine the Best Split

Before Splitting: 10 records of class 0,
10 records of class 1



Which test condition is the best?

How to determine the Best Split

- **Greedy approach:**
 - Nodes with **homogeneous** class distribution are preferred
- **Need a measure of node impurity:**

C0: 5
C1: 5

Non-homogeneous,
High degree of impurity

C0: 9
C1: 1


Homogeneous,
Low degree of impurity

How to Find the Best Split

Before Splitting:

C0	N00
C1	N01

→ M0



C0	N10
C1	N11


C0	N20
C1	N21

↓
M1

↓
M2



M12



C0	N30
C1	N31

C0	N40
C1	N41

↓
M3

↓
M4



M34

Gain = M0 – M12 vs M0 – M34

Measures of Node Impurity

- Gini Index
- Entropy
- Misclassification error

Measure of Impurity: GINI

- Gini Index for a given node t :

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

(NOTE: $p(j | t)$ is the relative frequency of class j at node t).

- Maximum $(1 - 1/n_c)$ when records are equally distributed among all classes, implying least interesting information
- Minimum (0) when all records belong to one class, implying most useful information

C1	0
C2	6
Gini=0.000	

C1	1
C2	5
Gini=0.278	

C1	2
C2	4
Gini=0.444	

C1	3
C2	3
Gini=0.500	

Examples for computing GINI

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Gini = 1 - P(C1)^2 - P(C2)^2 = 1 - 0 - 1 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Gini = 1 - (1/6)^2 - (5/6)^2 = 0.278$$

C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Gini = 1 - (2/6)^2 - (4/6)^2 = 0.444$$

Entropy

- Entropy at a given node t:

$$Entropy(t) = -\sum_j p(j | t) \log p(j | t)$$

(NOTE: $p(j | t)$ is the relative frequency of class j at node t).

- Measures purity of a node

- Maximum ($\log n_c$) when records are equally distributed among all classes implying least information
- Minimum (0.0) when all records belong to one class, implying most information

Examples for computing Entropy

$$Entropy(t) = -\sum_j p(j | t) \log_2 p(j | t)$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Entropy = -0 \log 0 - 1 \log 1 = -0 - 0 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Entropy = - (1/6) \log_2 (1/6) - (5/6) \log_2 (5/6) = 0.65$$

C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Entropy = - (2/6) \log_2 (2/6) - (4/6) \log_2 (4/6) = 0.92$$

Splitting Criteria based on Classification Error

- Classification error at a node t :

$$Error(t) = 1 - \max_i P(i | t)$$

- Measures misclassification error made by a node.
 - Maximum $(1 - 1/n_c)$ when records are equally distributed among all classes, implying least interesting information
 - Minimum (0.0) when all records belong to one class, implying most interesting information

Examples for Computing Error

$$Error(t) = 1 - \max_i P(i | t)$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Error = 1 - \max(0, 1) = 1 - 1 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Error = 1 - \max(1/6, 5/6) = 1 - 5/6 = 1/6$$

C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Error = 1 - \max(2/6, 4/6) = 1 - 4/6 = 1/3$$

Computing Gain

- **Gain:**

$$GAIN_{split} = Measure(p) - \left(\sum_{i=1}^k \frac{n_i}{n} Measure(i) \right)$$


Parent Node p is split into k partitions;

n_i is number of records in partition i

- Measures reduction in impurity measure achieved because of the split. Choose the split that achieves most reduction (maximizes GAIN)

Binary Attributes: Computing GINI Index

- Splits into two partitions
- Effect of Weighing partitions:
 - Larger and Purer Partitions are sought for



$$\begin{aligned} \text{Gini}(N1) &= 1 - (5/7)^2 - (2/7)^2 \\ &= 0.408 \end{aligned}$$

$$\begin{aligned} \text{Gini}(N2) &= 1 - (1/5)^2 - (4/5)^2 \\ &= 0.32 \end{aligned}$$

	N1	N2
C1	5	1
C2	2	4
Gini=0.333		

	Parent
C1	6
C2	6
Gini = 0.500	

$$\begin{aligned} \text{Gini(Children)} &= 7/12 * 0.408 + \\ &\quad 5/12 * 0.32 \\ &= 0.371 \end{aligned}$$

$$\begin{aligned} \text{Gain} &= 0.5 - \\ &\quad 0.371 = 0.129 \end{aligned}$$

Tree Induction

- **Greedy strategy**
 - Split the records based on an attribute test that optimizes certain criterion.
- **Issues**
 - Determine how to split the records
 - How to specify the attribute test condition?
 - How to determine the best split?
 - **Determine when to stop splitting**

Stopping Criteria for Tree Induction

- Stop expanding a node when all the records belong to the same class
- Stop expanding a node when all the attributes have been used
- Early termination (to be discussed later)