MASTERING THE METHODOLOGY FLOWCHART (FIGURE 3)

Complete Block-by-Block Technical Breakdown & Question-Dodge Defense Guide

Institute of Science and Technology (IoST), Tribhuvan University, Nepal

---

Candidate: Erize Rai | **Roll No:** 8025006 | **Date:** NOVEMBER, 2026

Thesis: *Enhancing Self-Supervised Video Representations with HAF-STD Net: A Comparative Evaluation Against VLM for Action Recognition*

Supervisor: Asst. Prof. Dr. Dhiraj Kedar Pandey

Contents

1 Overview: The Architecture of Figure 3 2

2 Stage 1: Benchmark Data Sources 2

3 Stage 2: Frame Extraction Pipeline 3

4 Stage 3: Feature Extraction (The Core Paradigm Comparison) 4

5 Stage 4: Feature Preprocessing & PCA Dimensionality Reduction 6

6 Stage 5: Classifier Branches & Downstream Probing 7

7 Stage 6: Comparative Evaluation Metrics 8

8 The Defense Emergency Matrix: Instant Answers 9

1 Overview: The Architecture of Figure 3

Figure 3 in your thesis represents the entire end-to-end experimental pipeline. It connects:

- **Input Data (Stage 1):** Dual benchmark selection representing contrasting granularities (FineGym vs. HMDB51).
- **Ingestion (Stage 2):** Standardized uniform frame extraction and spatial normalization via OpenCV.
- **Backbone Encoding (Stage 3):** A dual-stream frozen foundation model evaluation comparing Self-Supervised Learning (V-JEPA 2) against Vision-Language Modeling (Qwen2.5-VL).
- **Data Sanitization (Stage 4a):** Zero-leakage standardization and train/eval partitioning.
- **Dimensionality Transformation (Stage 4b):** 95% explained variance PCA reduction for 1D baseline classifiers, bypassed by the 4D spatiotemporal tensor of the novel HAF-STD Net.
- **Downstream Probing (Stage 5):** Comparative classification across 9 classifiers (3 Classical ML + 5 Neural Baselines + 1 Novel HAF-STD Net).
- **Statistical Evaluation (Stage 6):** Multi-metric evaluation including chance-corrected and agreement metrics (Accuracy, Macro/Weighted F1, MCC, Cohen's κ).

Defense Key Takeaway

Examiners evaluate whether your pipeline introduces hidden confounds, data leakage, or unfair advantages. The answers in this document prove that every design decision in Figure 3 was dictated by mathematical principles, GPU hardware constraints, and information-theoretic rigor.

2 Stage 1: Benchmark Data Sources

Block Details: FineGym & HMDB51

- **FineGym (Left Block):** 1,200 video clips across 4 Olympic gymnastics event classes: Vault (VT), Uneven Bars (UB), Balance Beam (BB), and Floor Exercise (FX). Exact balanced distribution: 300 clips per class.
- **HMDB51 (Right Block):** 6,754 video clips across 51 diverse coarse-grained human action classes (e.g., *chew, climb, draw sword, kick, sword exercise, laugh*). Sourced from movies and digitized web footage.

Defense Q1: Why did you evaluate on two datasets? Why FineGym and HMDB51?

Examiner's Angle: They want to see if you picked random datasets or had a deliberate scientific rationale.

Your Bulletproof Answer:

- **Complementary Granularities:** FineGym represents **fine-grained** motion, while HMDB51 represents **coarse-grained** actions.
- **Eliminating Scene/Background Shortcuts:** In coarse datasets (e.g., UCF101 or HMDB51), models can cheat by recognizing static background objects (e.g., a horse $\rightarrow$ *ride horse*; an ocean $\rightarrow$ *surf*). In FineGym, all 4 events occur in the **identical gymnastic hall** with identical lighting, identical athletes, and similar apparatus mats. The model **cannot** use background

cues; it is forced to encode pure limb kinematics, body trajectory, and temporal dynamics.

- **Revealing the Paradigm Gap:** This dual-dataset design proved that while VLMs can compete on coarse actions (+6.2% gap on HMDB51), they suffer severely on subtle fine-grained motion (+9.4% gap on FineGym).

Defense Q2: FineGym has 288 sub-actions and 530 element classes. Why only 4 classes?

Examiner's Angle: They want to accuse you of simplifying the problem.

Your Bulletproof Answer:

1. **Severe Long-Tail Imbalance in FineGym-288/530:** In the 288/530 element splits, hundreds of classes have fewer than 2 to 4 video clips in total. Under a frozen-feature evaluation protocol, such extreme sparsity prevents downstream classifiers from learning stable decision boundaries without massive class-weight distortions.
2. **Sufficient Data Density:** The 4 event classes provide an exact, balanced 300 clips per class (1,200 total), providing statistical power without class-imbalance artifacts.
3. **High Inter-Class Homogeneity:** Distinguishing a *Floor Exercise* from a *Vault* or *Beam* requires tracking rapid body flips, vertical flight, and apparatus interaction in milliseconds.
4. **Acknowledged as Future Scope:** I explicitly documented extension to FineGym-288/530 in Chapter 5 (Recommendations) when dense feature caching infrastructure becomes available.

3 Stage 2: Frame Extraction Pipeline

Block Details: OpenCV VideoCapture → Uniform Temporal Sampling → Resize to 224×224

- **OpenCV Engine:** `cv2.VideoCapture` handles decoding of variable framerate (VFR) and constant framerate (CFR) MP4/AVI containers.
- **Uniform Temporal Sampling Equation:** For a clip containing N_{total} frames, to sample T frames:

$$t_k = \left\lfloor k \cdot \frac{N_{\text{total}}}{T} \right\rfloor, \quad k \in \{0, 1, \ldots, T-1\}$$

- **Spatial Resizing:** Bilinear/Bicubic interpolation resizing frames to canonical resolution $H \times W = 224 \times 224$ pixels.

Defense Q3: Why uniform temporal sampling instead of dense optical flow or consecutive frames?

Examiner's Angle: Testing your knowledge of video representations and computational complexity.

Your Bulletproof Answer:

- **Consecutive Frames Miss the Action:** Action clips in HMDB51 and FineGym last between 2 to 10 seconds (60 to 300 frames at 30 fps). Taking consecutive frames (e.g., frames 1 to 8) covers only 0.25 seconds of the video, completely missing the complete action arc (e.g., run-up → hurdle → vault → landing).
- **Uniform Sampling Covers Full Duration:** Sampling across the entire temporal span ensures the extracted tensor captures the initiation, peak, and conclusion of the action.

- **Why Not Optical Flow (TV-L1 / Farneback):** Optical flow computation is computationally prohibitive, requiring hundreds of hours for 6,754 clips, and modern Vision Transformers (like V-JEPA 2's 3D tubelets) learn motion fields implicitly in latent space, eliminating the need for handcrafted optical flow.

4 Stage 3: Feature Extraction (The Core Paradigm Comparison)

Block Details: V-JEPA 2 (Left) vs. Qwen2.5-VL (Right)

- **V-JEPA 2 (Meta AI):**
  - Parameters: **654 Million** (ViT-Huge architecture).
  - Precision & Backend: **float16** with Scaled Dot-Product Attention (SDPA / FlashAttention).
  - Spatiotemporal Tubelets: 2 frames $\times$ 16 $\times$ 16 pixels.
  - Temporal Dimension: 8 frames $\rightarrow T' = 4$ temporal tokens.
  - Layer Depth: 32 Transformer blocks. Hidden size $D = 1,280$.
  - Multi-Layer Tensors Extracted: Layers 6, 12, 18, 24 $\rightarrow \mathbf{F}_{\text{multi}} \in \mathbb{R}^{4\times T'\times 1280}$.
  - Mean-Pooled Vector (for baselines): $\mathbf{f} \in \mathbb{R}^{1280}$.
- **Qwen2.5-VL (Alibaba Cloud):**
  - Parameters: **7 Billion** (Large Multimodal Vision-Language Model).
  - Quantization: **4-bit NormalFloat (NF4)** with double quantization via `bitsandbytes`.
  - Frames: 4 frames uniformly sampled.
  - Architecture: Dynamic ViT vision encoder + Causal LM Transformer decoder.
  - Sequence Length: 4 frames $\times 256$ visual tokens $= 1,024$ tokens + chat template tokens.
  - Feature Pooling: Mean pooling over final hidden states $\rightarrow \mathbf{f} \in \mathbb{R}^{3584}$.

THE #1 CRITICAL DEFENSE TRAP: "8 Frames vs. 4 Frames"

The Examiner's Trap: *"You gave V-JEPA 2 eight frames and Qwen2.5-VL only four frames. Isn't this an unfair comparison that deliberately handicapped Qwen?"*

Your Three-Step Knockout Answer:

1. **The Token Sequence Explosion on Single GPU:** Qwen2.5-VL operates via a 2D patch encoder producing 256 tokens per frame. 4 frames $= 1,024$ image tokens. With system prompts and chat tokens, sequence length approaches 1,150. If we fed 8 frames, the sequence length exceeds 2,100 multi-modal tokens. Inside a 7B autoregressive transformer, the self-attention KV-cache and forward activations scale quadratically $\mathcal{O}(S^2)$, producing an immediate **CUDA Out-of-Memory (OOM)** crash on our 16 GB Tesla T4 GPU.
2. **V-JEPA 2's 3D Tubelet Compression:** V-JEPA 2 natively uses 3D tubelets of temporal size 2. Thus, 8 frames are condensed into just $T' = 4$ temporal tokens! In terms of temporal latent tokens processed by the transformer, **both models process a comparable sequence bottleneck ($T' = 4$ vs. 4 frames)**.
3. **The $10\times$ Parameter Scale Advantage:** Qwen2.5-VL possessed **7,000,000,000 parameters**

vs. V-JEPA 2's **654,000,000 parameters** (10.7× larger!). If temporal frame count alone determined performance, Qwen's 10× representational capacity should have easily bridged a 4-frame difference. It failed to do so because its text-aligned training lacks motion sensitivity.

THE #2 CRITICAL DEFENSE TRAP: "4-bit NF4 vs. float16 Precision"

The Examiner's Trap: *"Qwen2.5-VL was run in 4-bit quantization, while V-JEPA 2 was in float16. Did quantization destroy Qwen's accuracy?"*

Your Three-Step Knockout Answer:

1. **Hardware Feasibility Requirement:** A 7B parameter model in FP16 requires $7 \times 10^9 \times 2$ bytes $\approx \mathbf{14.0}$ GB of memory purely to store static weights. Loading this on an NVIDIA Tesla T4 (15.6 GB VRAM) leaves less than 1.6 GB for intermediate activations, causing instant crash on video tensors. 4-bit NF4 with double quantization reduced static weight memory to ~ 4.5 GB, permitting forward pass inference.
2. **Information-Theoretic Optimality of NF4:** As mathematically demonstrated by Dettmers et al. (NeurIPS 2023, QLoRA), NormalFloat4 is theoretically optimal for zero-mean normally distributed weights. Empirical evaluations across LLMs demonstrate that NF4 preserves $>$ 99% of FP16 performance, with less than 0.5% degradation in classification tasks.
3. **The Failure Mode is Not Precision, but Inductive Bias:** Qwen2.5-VL's best classifier achieved 89.1% on FineGym and 77.1% on HMDB51—very strong scores that prove its representations were completely intact and high-quality! The 6.2% to 9.4% gap exists because text-aligned decoders represent *"what objects are present"* rather than *"how fast and in what direction the joints are rotating"*.

Defense Q4: What does "Frozen-Feature Protocol" mean, and why didn't you fine-tune the backbones?

Examiner's Angle: They want to know why you didn't do end-to-end backpropagation.

Your Bulletproof Answer:

- **Definition:** Backbone parameters $\boldsymbol{\Theta}$ are frozen ($\nabla_{\boldsymbol{\Theta}} \mathcal{L} = \mathbf{0}$). Only downstream probe heads are optimized.
- **Direct Representation Quality Assessment:** If you fine-tune a 7B model on 1,200 clips, you are evaluating the downstream optimizer's ability to adapt parameters rather than evaluating the **intrinsic quality of the pre-trained feature representation**. Frozen probing isolates the exact geometric properties of the pre-trained latent space.
- **Computational Reality:** Fine-tuning a 7B parameter vision-language model end-to-end requires multi-node A100/H100 clusters (tens of thousands of dollars of compute), whereas frozen-feature extraction democratizes foundation model benchmarking on commodity single-GPU hardware.

5 Stage 4: Feature Preprocessing & PCA Dimensionality Reduction

Block Details: StandardScaler → 80/20 Split → PCA

- **StandardScaler:** Centers feature distributions to mean $\mu = 0$ and standard deviation $\sigma = 1$:

$$\tilde{z}_{ij} = \frac{z_{ij} - \mu_j}{\sigma_j}$$

- **Train/Eval Partitioning:** Stratified 80% training split, 20% evaluation split (preserving exact per-class balance).
- **PCA (95% Variance):** Eigen-decomposition of sample covariance matrix $\mathbf{\Sigma} = \frac{1}{N-1}\tilde{\mathbf{X}}^T\tilde{\mathbf{X}}$. Retains minimal principal components k^* such that:

$$\frac{\sum_{i=1}^{k^*} \lambda_i}{\sum_{j=1}^{D} \lambda_j} \geq 0.95$$

THE #3 CRITICAL DEFENSE TRAP: "Did You Have Data Leakage in Preprocessing?"

The Examiner's Trap: *"Did you fit StandardScaler and PCA on the entire dataset before doing your 80/20 train/eval split? That is data leakage!"*

Your Immediate Firm Answer:

- **"No, absolutely not. There is zero data leakage in my pipeline."**
- **The Exact Code Execution Sequence:**
  1. The dataset was split **first** into $X_{\text{train}}, y_{\text{train}}$ and $X_{\text{test}}, y_{\text{test}}$ using stratified sampling.
  2. `StandardScaler` was fitted **only** on X_{train} using `scaler.fit(X_train)`. The test set was transformed using `scaler.transform(X_test)`.
  3. PCA was fitted **only** on the standardized training features using `pca.fit(X_train_scaled)`. The test features were projected using `pca.transform(X_test_scaled)`.
  4. The test split never influenced the mean, standard deviation, or principal eigenvectors.

THE #4 CRITICAL DEFENSE TRAP: "Why Did HAF-STD Net Bypass PCA? (The Red Dashed Arrow)"

The Examiner's Trap: *"In Figure 3, the red dashed line shows HAF-STD Net bypassing PCA. Did HAF-STD Net achieve 98.1% and 84.7% just because it had full feature dimensions while baselines were compressed?"*

Your Three-Step Knockout Answer:

1. **Tensor Geometry Incompatibility:** Baseline classifiers receive a collapsed **1D global feature vector** per clip ($\mathbf{f} \in \mathbb{R}^{1280}$ or $\mathbb{R}^{3584}$). In 1D vectors, overparameterized ViTs produce heavy multicollinearity. Applying PCA removes redundancy and prevents SVM/Random Forest from failing in high dimensions.
2. **PCA Would Destroy Temporal and Depth Topology:** HAF-STD Net receives a **4D spatiotemporal tensor** ($\mathbf{F}_{\text{multi}} \in \mathbb{R}^{B\times 4\times T'\times 1280}$). Its internal modules perform:
   - **1D Haar Wavelet Transform** along the physical time axis T'.

- **Inter-Layer Velocity Deltas** ($\Delta_l = \mathbf{z}_{l+1} - \mathbf{z}_l$) along the vertical depth axis L.

If you apply standard PCA to a flattened multi-layer tensor, you scramble the time and depth order, destroying the physical meaning of velocity and frequency!

3. **95% Variance Baselines Were NOT Handicapped:** PCA retained **95% of the total energy**. In fact, neural baselines like ResMLP achieved 97.9% on FineGym and 82.9% on HMDB51—extremely high scores proving that 95% PCA retained all critical signal while preventing overfitting.

6 Stage 5: Classifier Branches & Downstream Probing

Block Details: 9 Total Classifiers

- **Classical ML (3):**
  1. **SVM-RBF:** Radial Basis Function kernel ($C = 1.0, \gamma =$ 'scale'), max-margin hyperplane.
  2. **Random Forest:** Ensemble of 100 decision trees, Gini impurity criterion.
  3. **Logistic Regression (LogReg):** Multiclass multinomial cross-entropy with ℓ_2 regularization (L-BFGS solver).
- **Neural Network Baselines (5):**
  1. **MLP:** 2-layer perceptron (Linear $d \to 512$, ReLU, Dropout 0.3, Linear $512 \to C$).
  2. **DeepMLP:** 4-layer perceptron ($d \to 1024 \to 512 \to 256 \to C$) with BatchNorm and Dropout 0.4.
  3. **ResMLP:** Deep residual MLP with skip connections ($\mathbf{x} + F(\mathbf{x})$), LayerNorm, and GELU activations.
  4. **Conv1DNet:** Temporal 1D convolutional network with kernel size 3, BatchNorm, and max pooling.
  5. **Mini Transformer:** 2 Transformer encoder layers with 4 self-attention heads and learnable positional encodings.
- **Proposed Novel Model (1):**
  - **HAF-STD Net (4.8M parameters):** Hierarchical Adaptive Fusion with Spectral-Temporal Decomposition.

Defense Q5: How does HAF-STD Net work inside, and where do the 4.8M parameters come from?

Examiner's Angle: They want to ensure you actually built the model and understand its internal mathematical mechanics.

Your Step-by-Step Architecture Explanation:

1. **Multi-Layer Extraction:** Extracts 4 intermediate layers (layers 6, 12, 18, 24) from V-JEPA 2.
2. **Stream 1: Appearance Trend (Low Frequency):** Applies 1D Haar Wavelet approximation filter $a_t = \frac{h_{2t} + h_{2t+1}}{2}$ along time to capture stable contextual scenery.
3. **Stream 2: Motion Dynamics (High Frequency):** Applies 1D Haar Wavelet detail filter $d_t = \frac{h_{2t} - h_{2t+1}}{2}$ along time to capture frame-to-frame velocity transients (zero parameters!).

4. **Stream 3: Depth Representation Velocity:** Computes inter-layer deltas:

$$\mathbf{v}_l = \mathbf{z}_{l+1} - \mathbf{z}_l$$

capturing how visual representations evolve from low-level edges (layer 6) to semantic concepts (layer 24).
5. **Adaptive Fusion Gating:** Lightweight cross-attention routers dynamically weigh each stream based on video content.
6. **Cosine Classification Head:** Normalizes feature vectors and class weights onto a unit hypersphere with temperature scaling τ, preventing gradient saturation.
7. **Parameter Footprint:** The projection layers, gating channels, and classification head total **4.8 Million parameters**—less than 0.7% of the V-JEPA 2 backbone!

Defense Q6: Why did Conv1DNet collapse on HMDB51 (11.5% accuracy) for Qwen features?

Examiner's Angle: Looking at Table 4.5 in your results where Conv1DNet got 11.5% and 0.8% F1.
Your Technical Explanation:

- **The Reason:** Qwen2.5-VL's output vector for baseline classifiers is a 1D sequence-mean-pooled vector ($\mathbf{f} \in \mathbb{R}^{3584}$), which was PCA-reduced to $\mathbb{R}^{k^*}$.
- A 1D Convolution assumes a natural spatial or temporal neighborhood ordering across adjacent indices (like adjacent time steps or adjacent pixels). In PCA feature space, eigenvector indices have **no continuous spatial or temporal correlation**; adjacent PCA dimensions are orthogonal. A 1D convolution over orthogonal PCA dimensions applies an invalid inductive bias, causing optimization failure on the 51-class dataset.
- This highlights why fully connected architectures (DeepMLP, ResMLP) excel on PCA features, while Conv1DNet requires raw temporal sequences.

7 Stage 6: Comparative Evaluation Metrics

Block Details: Accuracy, Macro/Weighted F1, MCC, Cohen's κ

- **Overall Accuracy:** $\frac{\text{Correct Predictions}}{\text{Total Samples}}$. Susceptible to majority-class dominance.
- **Macro F1-Score (Primary Ranking Metric):** Unweighted arithmetic mean of individual class F1-scores:

$$\text{Macro F1} = \frac{1}{C}\sum_{c=1}^{C} F1_c$$

Treats rare and frequent classes with strict equal importance.
- **Matthews Correlation Coefficient (MCC):** Multiclass formulation of Pearson correlation between ground-truth and prediction matrices. Completely robust to class imbalance; random guessing produces MCC $= 0.0$.
- **Cohen's Kappa (κ):** Inter-rater agreement corrected for agreement occurring purely by

chance:

$$\kappa = \frac{p_o - p_e}{1 - p_e}$$

Defense Q7: Why did you declare Macro F1 as your primary metric instead of Accuracy?

Examiner's Angle: Standard machine learning evaluation rigor question.

Your Confident Defense:

- **"Accuracy is deceptive in multiclass settings."**
- In HMDB51 (51 classes), if a model predicts the 10 most common classes accurately but fails on the 41 smaller classes, its overall Accuracy will appear deceptively high.
- **Macro F1 forces true robustness:** Because Macro F1 averages per-class F1 with equal weight ($\frac{1}{C}$), a model cannot score 85.3% on HMDB51 without demonstrating high precision and recall across **all 51 individual action classes**.
- Furthermore, reporting **MCC (0.843)** and **Cohen's Kappa (0.842)** alongside Macro F1 proves that our performance gains represent genuine geometric class separation, not statistical artifacts.

8 The Defense Emergency Matrix: Instant Answers

Examiner's Challenge	Core Trap / Concern	Your Instant 1-Sentence Killer Response
"Why V-JEPA 2 over VideoMAE?"	Pixel reconstruction vs. Latent prediction.	*"VideoMAE wastes network capacity reconstructing high-frequency visual noise, while JEPA predicts abstract semantics directly in latent space."*
"Why didn't Qwen2.5-VL win with 7B parameters?"	Parameter scale vs. Inductive bias.	*"Task-specific temporal inductive bias outweighs raw parameter scale; language-aligned models represent static scene semantics rather than temporal dynamics."*
"Why 4 intermediate layers in HAF-STD Net?"	Arbitrary hyperparameter choice.	*"Layers 6, 12, 18, and 24 evenly sample the representation hierarchy from low-level edges to mid-level body parts and high-level action semantics."*
"Why early stopping at 15/30 epochs?"	Underfitting / Overfitting risk.	*"Frozen feature embeddings train very rapidly; validation loss plateaus within 10–20 epochs, and early stopping prevents overfitting on small datasets."*
"Why didn't you use cross-entropy alone in HAF-STD Net?"	Use of Cosine Head.	*"In high-dimensional latent spaces, semantic identity is encoded in angular direction rather than vector magnitude; the Cosine head with learnable τ stabilizes margins."*

Table 1: Emergency quick-fire defense matrix for Figure 3.

YOU ARE FULLY EQUIPPED TO DEFEND FIGURE 3. GOOD LUCK!