



Product Specification

M270HAN01.2

AU OPTRONICS CORPORATION

() Preliminary Specification
(V) Final Specification

Module	27" Color TFT-LCD
Model Name	M270HAN01.2 open cell

<table><tr><td>Customer</td><td>Date</td></tr><tr><td> </td><td> </td></tr><tr><td>Approved by</td><td></td></tr><tr><td> </td><td> </td></tr></table>	Customer	Date			Approved by				<table><tr><td>Approved by</td><td>Date</td></tr><tr><td><u>CH Lin</u></td><td><u>Mar 27, 2019</u></td></tr><tr><td>Prepared by</td><td>Date</td></tr><tr><td><u>Vincent Hsu</u></td><td><u>Mar 27, 2019</u></td></tr></table>	Approved by	Date	<u>CH Lin</u>	<u>Mar 27, 2019</u>	Prepared by	Date	<u>Vincent Hsu</u>	<u>Mar 27, 2019</u>
Customer	Date																
Approved by																	
Approved by	Date																
<u>CH Lin</u>	<u>Mar 27, 2019</u>																
Prepared by	Date																
<u>Vincent Hsu</u>	<u>Mar 27, 2019</u>																
Note: This Specification is subject to change without notice.	AU Optronics corporation																

Contents

1 Handling Precautions	4
2 General Description	5
2.1 Display Characteristics	5
2.2 Absolute Maximum Rating of Environment.....	6
2.3 Optical Characteristics	7
3 TFT-LCD Module.....	11
3.1 Block Diagram	11
3.2 Interface Connection.....	12
3.2.1 Connector Type.....	12
3.2.2 Connector Pin Assignment	12
3.3 Electrical Characteristics.....	14
3.3.1 Absolute Maximum Rating	14
3.3.2 Recommended Operating Condition	14
3.3.3 Input control signal threshold voltage definition.....	15
3.3.4 Write Protection mode selection	15
3.3.5 Input equivalent impedance	15
3.4 Signal Characteristics.....	15
3.4.1 LCD Pixel Format.....	15
3.4.2 LVDS Data Format.....	16
3.4.3 Color versus Input Data.....	17
3.4.4 LVDS Specification	18
3.4.5 Input Timing Specification	20
3.4.6 Input Timing Diagram	21
3.4.7 I2C Electrical Characteristics.....	22
3.5 Power ON/OFF Sequence.....	23
3.6 Vcom adjustment flow.....	24
4 Reliability Test	27
5 Shipping Label	28
6 Mechanical Characteristic	29
7 Packing Specification	30
7.1 Packing Flow	30
7.2 Pallet and shipment information.....	31

Record of Revision

Version	Date	Page	Old description	New Description	Remark
1.0	2019/03/27	All		New release	

I Handling Precautions

- 1) Since polarizer is easily damaged, do not touch or press the surface of polarizer with hand.
- 2) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 3) When the cell surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 4) Since the cell is made of glass, it may break or crack if dropped or bumped on hard surface.
- 5) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 6) Do not press or pat the panel surface by fingers, hand or tooling.
- 7) Please handle TFT cell with care. The FPCs can only sustain for quite limited stress.
- 8) The cell package tray is packed in clean room. Please do pack & unpack it in clean room.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT cell.
- 10) Pls avoid touching COF position while you are doing mechanical design.
- 11) When storing modules as spares for a long time, the following precaution is necessary: Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
- 12) Do not apply the same pattern for a long time, it will enhance relevant defect.



2 General Description

This specification applies to the 27 inch wide Color a-Si TFT-LCD Module M270HAN01.2. The display supports the Full HD - 1920(H) x 1080(V) screen format and 16.7M colors (6-bits+Hi-FRC). The input interface is Dual channel LVDS.

2.1 Display Characteristics

The following items are characteristics summary on the table under 25°C condition:

ITEMS	Unit	SPECIFICATIONS	
Screen Diagonal	[mm]	685.99 (27")	
Active Area	[mm]	597.888 (H) x 336.312 (V)	
Pixels H x V	-	1920(x3) x 1080	
Pixel Pitch	[um]	311.4 (per one triad) x311.4	
Pixel Arrangement	-	R.G.B. Vertical Stripe	
Display Mode	-	AHVA Mode(Advanced Hyper-Viewing Angle), Normally Black	
Response Time	[msec]	14 (Typ., GTG)	
Power Consumption	[Watt]	1.85 (Typ.)@ White pattern,Fv=60Hz	
Weight	[Grams]	634	
Electrical Interface	-	Dual channel LVDS	
Support Color	-	16.7M colors (6-bits +Hi-FRC)	
Surface Treatment	-	Anti-Glare , 3H	
Temperature Range Operating Storage (Shipping)	[°C]	0 to +50 -20 to +60	
Cell transmittance	[%]	5.0 (Typ.)	Base on AUO LED Backlight
		4.5 (Min.)	
Cell thickness	[mm]	1.31 (Thickness of polarizer film: 0.16 mm each side)	


2.2 Absolute Maximum Rating of Environment

Permanent damage may occur if exceeding the following maximum rating.

Symbol	Description	Min.	Max.	Unit	Remark
TOP	Operating Temperature	0	+50	[°C]	Note 2-1
TGS	Glass surface temperature (operation)	0	+65	[°C]	Note 2-1 Function judged only
HOP	Operation Humidity	5	90	[%RH]	Note 2-1
TST	Storage Temperature	-20	+60	[°C]	
HST	Storage Humidity	5	90	[%RH]	

Note 2-1: Temperature and relative humidity range are shown as the below figure.


1. 90% RH Max ($T_a \leq 39^\circ\text{C}$)
2. Max wet-bulb temperature at 39°C or less. ($T_a \leq 39^\circ\text{C}$)
3. No condensation



Operating Range



Storage Range



2.3 Optical Characteristics


The optical characteristics are measured on the following test condition.

Test Condition:

1. Equipment setup: Please refer to **Note 2-2**.
2. Panel Lighting time: 30 minutes
3. VDD=5.0V, Fv=60Hz, Is=60mA, Ta=25°C

Symbol	Description		Min	Typ.	Max	Unit	Remark
CR	Contrast Ratio (Center of screen)		600	1000	-	-	Note 2-3 Base on AUO LED Backlight
θ_R	Horizontal Viewing Angle (CR=10)	Right	80	89	-	[degree]	Note 2-4 By SR-3 (Base on AUO backlight design)
θ_L		Left	80	89	-		
Φ_H	Vertical Viewing Angle (CR=10)	Up	80	89	-		
Φ_L		Down	80	89	-		
θ_R	Horizontal Viewing Angle (CR=5)	Right	80	89	-		
θ_L		Left	80	89	-		
Φ_H	Vertical Viewing Angle (CR=5)	Up	80	89	-		
Φ_L		Down	80	89	-		
T_{GTG}	Response Time	Gray To Gray	-	14	-	[msec]	Note 2-5 By TRD-100
R_x	Color Coordinates (CIE 1931)	Red x	0.623	0.653	0.683		Base on C light
R_y		Red y	0.298	0.328	0.358		
G_x		Green x	0.248	0.278	0.308		
G_y		Green y	0.567	0.597	0.627		
B_x		Blue x	0.105	0.135	0.165		
B_y		Blue y	0.07	0.1	0.13		
W_x		White x	0.297	0.327	0.357		
W_y		White y	0.339	0.369	0.399		
CT	Crosstalk		-	-	1.5	[%]	Note 2-6 By SR-3

Note 2-2: Equipment setup :



Note 2-3: Contrast Ratio Measurement

Definition:

$$\text{Contrast Ratio} = \frac{\text{Luminance of White pattern}}{\text{Luminance of Black pattern}}$$


a. Measured position: Center of screen (P5) & perpendicular to the screen ($\theta=\Phi=0^\circ$)

Note 2-4: Viewing angle measurement

Definition: The angle at which the contrast ratio is greater than 10 & 5 .

a. Horizontal view angle: Divide to left & right (θ_L & θ_R)


Vertical view angle: Divide to up & down (ϕ_H & ϕ_L)



Note 2-5: Response measurement

time

The output signals of photo detector are measured when the input signals are changed from “Gray level A” to “Gray level B” (falling time, T_f), and from “Gray level B” to “Gray level A” (rising time, T_r), respectively. The response time is interval between the 10% and 90% of optical response.



The gray to gray response time is defined as the following table.

Gray Level to Gray Level		Target gray level				
		L0	L63	L127	L191	L255
Start gray level	L0					
	L63					
	L127					
	L191					
	L255					

■ T_{GTG_typ} is the total average time at rising time and falling time of gray to gray.

Note 2-6: Crosstalk measurement

Definition:

$$CT = \text{Max. } (CT_H, CT_V);$$

Where

a. Maximum Horizontal Crosstalk :


$$CT_H = \text{Max. } (|Y_{BL} - Y_{AL}| / Y_{AL} \times 100 \%, |Y_{BR} - Y_{AR}| / Y_{AR} \times 100 \%);$$

Maximum Vertical Crosstalk:

$$CT_V = \text{Max. } (|Y_{BU} - Y_{AU}| / Y_{AU} \times 100 \%, |Y_{BD} - Y_{AD}| / Y_{AD} \times 100 \%);$$

b. Y_{AU} , Y_{AD} , Y_{AL} , Y_{AR} = Luminance of measured location without Black pattern


Y_{BU} , Y_{BD} , Y_{BL} , Y_{BR} = Luminance of measured location with Black pattern



3 TFT-LCD Module

3.1 Block Diagram

The following shows the block diagram of the 27 inch Color TFT-LCD Module.



3.2 Interface Connection


3.2.1 Connector Type

TFT-LCD Connector	Manufacturer	P-TWO	STM
	Part Number	I87034-3009	MSBKT2407P30HB
Mating Connector	Manufacturer	JAE or Compatible	
	Part Number	FI-X30HL (Locked Type)	

3.2.2 Connector Pin Assignment

PIN #	Symbol	Description	Remark
1	RxO0-	Negative LVDS differential data input (Odd data)	
2	RxO0+	Positive LVDS differential data input (Odd data)	
3	RxO1-	Negative LVDS differential data input (Odd data)	
4	RxO1+	Positive LVDS differential data input (Odd data)	
5	RxO2-	Negative LVDS differential data input (Odd data)	
6	RxO2+	Positive LVDS differential data input (Odd data)	
7	GND	Ground	
8	RxOCLK-	Negative LVDS differential clock input (Odd clock)	
9	RxOCLK+	Positive LVDS differential clock input (Odd clock)	
10	RxO3-	Negative LVDS differential data input (Odd data)	
11	RxO3+	Positive LVDS differential data input (Odd data)	
12	RxE0-	Negative LVDS differential data input (Even data)	
13	RxE0+	Positive LVDS differential data input (Even data)	
14	GND	Ground	
15	RxE1-	Negative LVDS differential data input (Even data)	
16	RxE1+	Positive LVDS differential data input (Even data)	
17	GND	Ground	
18	RxE2-	Negative LVDS differential data input (Even data)	
19	RxE2+	Positive LVDS differential data input (Even data)	
20	RxECLK-	Negative LVDS differential clock input (Even clock)	
21	RxECLK+	Positive LVDS differential clock input (Even clock)	
22	RxE3-	Negative LVDS differential data input (Even data)	
23	RxE3+	Positive LVDS differential data input (Even data)	
24	WP	Digital-Vcom write protection	
25	NC	No connection (for AUO test only. Do not connect)	
26	I2C_SCL	I2C-Compatible Serial-Clock Input for Vcom adjust	

27	I2C_SDA	I2C-Compatible Serial-Data Input / Output for Vcom adjust	
28	VDD	Power Supply Input Voltage	
29	VDD	Power Supply Input Voltage	
30	VDD	Power Supply Input Voltage	



3.3 Electrical Characteristics

3.3.1 Absolute Maximum Rating

Permanent damage may occur if exceeding the following maximum rating.



Symbol	Description	Min	Max	Unit	Remark
VDD	Power Supply Input Voltage	GND-0.3	6.0	[Volt]	Ta=25°C
SCL,SD A,WP	I2C input Voltage	GND-0.3	4.0	[Volt]	Ta=25°C

3.3.2 Recommended Operating Condition

Symbol	Description	Min	Typ	Max	Unit	Remark
VDD	Power supply Input voltage	4.5	5.0	5.5	[Volt]	
IDD	Power supply Input Current (RMS)	-	0.37	0.85	[A]	VDD= 5.0V, White Pattern, Fv=60Hz
			0.39	1.00	[A]	VDD= 5.0V, White Pattern, Fv=75Hz
PDD	VDD Power Consumption	-	1.85	4.25	[Watt]	VDD= 5.0V, White Pattern, Fv=60Hz
			1.95	5.00	[Watt]	VDD= 5.0V, White Pattern, Fv=75Hz
IRush	Inrush Current	-	-	3.0	[A]	<i>Note 3-1</i>
VDDrp	Allowable VDD Ripple Voltage	-	-	500	[mV]	VDD= 5.0V, White Pattern, Fv=75Hz

Note 3-1: Inrush Current measurement:

Test circuit:



The duration of VDD rising time: 470us.

3.3.3 Input control signal threshold voltage definition


Item	Symbol	Min.	Typ.	Max.	Unit
Input High Threshold Voltage	VIH	2.7	-	3.6	V
Input Low Threshold Voltage	VIL	0	-	0.6	V

3.3.4 Write Protection mode selection


WP	Note
L or OPEN	Protection
H	Writable

3.3.5 Input equivalent impedance

1. Input equivalent impedance of WP pin



2. Input equivalent impedance of SDA/SCL pin




3.4 Signal Characteristics

3.4.1 LCD Pixel Format

	1			2															1919			1920		
1st Line	R	G	B	R	G	B	. .																	

3.4.2 LVDS Data Format



8 Bit Color Bit Order			
MSB	R7	G7	B7
	R6	G6	B6
	R5	G5	B5
	R4	G4	B4
	R3	G3	B3
	R2	G2	B2
	R1	G1	B1
LSB	R0	G0	B0

Note 3-2:

- O = "Odd Pixel Data" E = "Even Pixel Data"
- Refer to 3.4.1 LCD pixel format, the 1st data is 1 (Odd Pixel Data), the 2nd data is 2 (Even Pixel Data) and the last data is 1920 (Even Pixel Data).

3.4.3 Color versus Input Data

The following table is for color versus input data (8bit). The higher the gray level, the brighter the color.

Color	Gray Level	Color Input Data																								Remark
		RED data (MSB :R7, LSB :R0)								GREEN data (MSB :G7, LSB :G0)								BLUE data (MSB :B7, LSB :B0)								
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0	
Black	-	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
White	-	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
Gray 127	-	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	
Red	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black	
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	L255	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
Green	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black	
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	L255	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0		
Blue	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black	
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	L255	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1		


3.4.4 LVDS Specification

a. DC Characteristics:

Symbol	Description	Min	Typ	Max	Units	Condition
V_{TH}	LVDS Differential Input High Threshold	-	-	+100	[mV]	$V_{CM} = 1.2V$
V_{TL}	LVDS Differential Input Low Threshold	-100	-	-	[mV]	$V_{CM} = 1.2V$
$ V_{ID} $	LVDS Differential Input Voltage	100	-	600	[mV]	
V_{CM}	LVDS Common Mode Voltage	+1.0	+1.2	+1.5	[V]	$V_{TH} - V_{TL} = 200mV$


LVDS Signal Waveform:

Use RxOCLK- & RxOCLK+ as example.



b. AC Characteristics:

Symbol	Description	Min	Max	Unit	Remark
F_{DEV}	Maximum deviation of input clock frequency during Spread Spectrum	-	± 3	%	
F_{MOD}	Maximum modulation frequency of input clock during Spread Spectrum	-	200	KHz	



Fclk: LVDS Clock Frequency

3.4.5 Input Timing Specification

It only support DE mode, and the input timing are shown as the following table.

Symbol	Description		Min.	Typ.	Max.	Unit	Remark
Tv	Vertical Section	Period	1094	1130	1914	Th	
Tdisp (v)		Active	1080	1080	1080	Th	
Tblk (v)		Blanking	14	50	834	Th	
Fv		Frequency	47	60	76	Hz	Note 3-3
Th	Horizontal Section	Period	1000	1050	1678	Tclk	
Tdisp (h)		Active	960	960	960	Tclk	
Tblk (h)		Blanking	40	90	718	Tclk	
Fh		Frequency	51.5	67.8	90.0	KHz	Note 3-4
Tclk	LVDS Clock	Period	11.2	14.0	19.4	ns	1/Fclk
Fclk		Frequency	51.5	71.2	90.0	MHz	Note 3-5

Note 3-3: The optimal Vertical Frequency is 50~76 Hz for best picture.

Note 3-4: The equation is listed as following. Please don't exceed the above recommended value.

$$Fh \text{ (Min.)} = Fclk \text{ (Min.)} / Th \text{ (Min.)};$$

$$Fh \text{ (Typ.)} = Fclk \text{ (Typ.)} / Th \text{ (Typ.)};$$

$$Fh \text{ (Max.)} = Fclk \text{ (Max.)} / Th \text{ (Min.)};$$


Note 3-5: The equation is listed as following. Please don't exceed the above recommended value.

$$Fclk \text{ (Min.)} = Fv \text{ (Min.)} \times Th \text{ (Min.)} \times Tv \text{ (Min.)};$$

$$Fclk \text{ (Typ.)} = Fv \text{ (Typ.)} \times Th \text{ (Typ.)} \times Tv \text{ (Typ.)};$$


$$Fclk \text{ (Max.)} = Fv \text{ (Max.)} \times Th \text{ (Typ.)} \times Tv \text{ (Typ.)};$$

3.4.6 Input Timing Diagram




3.4.7 I2C Electrical Characteristics (VDD=5V, VSDA/VSCL=3.3V, TA=25°C)

Parameter	Symbol	Min.	Typ.	Max	Unit
SCL clock frequency	fSCL	-	-	350	kHz
Clock Pulse Width Low	tLOW	1.85	-	-	us
Clock Pulse Width High	tHIGH	0.4	-	-	us
Clock Low to Data Output Valid	tAA	1.76	-	-	us
Start Setup Time	tSTASU	0.6	-	-	us
Start Hold Time	tSTAHD	0.6	-	-	us
Stop Setup Time	tSTOSU	0.6	-	-	us
Data In Setup Time	tDSU	0.1	-	-	us
Data In Hold Time	tDHD	0	-	-	us
SCL/SDA Rise Time	tR	-	-	0.3	us
SCL/SDA Fall Time	tF	-	-	0.3	us



3.5 Power ON/OFF Sequence

VDD power, LVDS signal and backlight on/off sequence are as following. LVDS signals from any system shall be Hi-Z state when VDD is off.



Power Sequence Timing

Symbol	Value			Unit	Remark
	Min.	Typ.	Max.		
T1	0.5	-	10	[ms]	
T2	0	-	50	[ms]	
T3	500	-	-	[ms]	
T4	100	-	-	[ms]	
T5	0		50	[ms]	<i>Note 3-6</i> <i>Note 3-7</i>
T6	0		200	[ms]	<i>Note 3-7</i> <i>Note 3-8</i>
T7	1000	-	-	[ms]	

Note 3-6 : Recommend setting T5 = 0ms to avoid electronic noise when VDD is off.

Note 3-7 : During T5 and T6 period , please keep the level of input LVDS signals with Hi-Z state.

Note 3-8 : Voltage of VDD must decay smoothly after power-off. (customer system decide this value)


3.6 Vcom adjustment flow

A. Flicker Pattern

DOT (1V) G92




B. Vcom is optimization when minimized flicker phenomenon of location P5 (as below figure)




C. Tuning Step

VCOM I2C Tuning Step



D. Interval of Step to Step



E. I2C Protocol Define

DVCOM IC address (slave) : 1110100 (0x74)

Step1 Reset Command

Start	Slave Address							W R	ACK	Index Address 0								ACK	Control Byte								ACK	Stop
	1	1	1	0	1	0	0	0		0	0	0	0	0	0	0	0		0	0	0	1	0	0	1	0		
	0xE8									0x00									0x12									
	Device Address + W									Control Address									Reset + OUT_EN									

Step2 Read Vcom Command

Start	Slave Address							W R	ACK	Index Address 0							ACK	Start	Slave Address							W R	ACK	VCOM data							ACK	Stop						
	1	1	1	0	1	0	0	0		0	0	0	0	0	1	1			1	0	1	0	0	1	X	X		X	X	X	X	X										
	0xE8									0x01									0xE9									0~127														
	Device Address + W									VCOM Address									Device Address + R									DATA														

Step3 Adjust Vcom Command

Start	Slave Address							W R	ACK	Index Address 1							ACK	VCOM data							ACK	Stop	
	1	1	1	0	1	0	0	0		0	0	0	0	0	0	1		X	X	X	X	X	X	X			N
	0xE8							0x01							0~127							A					
	Device Address + W							VCOM Address							VCOM Value												

Step4 Write Vcom Command

Start	Slave Address								W R	ACK	Index Address 0								ACK	Control Byte								ACK	Stop	
	1	1	1	0	1	0	0	0	0		0	0	0	0	0	0	0	0		0	0	0	1	0	1	0				
	0xE8										0x00										0x0A									
	Device Address + W										Control Address										Write DAC to NVM									

Step5 Reset Command

Start	Slave Address							W R	ACK	Index Address 0							ACK	Control Byte							ACK	Stop		
	1	1	1	0	1	0	0	0		0	0	0	0	0	0	0		0	0	0	0	1	0	0			1	0
	0xE8									0x00									0x12									
	Device Address + W									Control Address									Reset + OUT_EN									

4 Reliability Test

AUO reliability test items are listed as following table. (*Bare Panel only*)

Items	Condition	Remark
Temperature Humidity Bias (THB)	Ta= 50℃ , 80%RH, 300hours	
High Temperature Operation (HTO)	Ta= 50℃ , 50%RH, 300hours	
Low Temperature Operation (LTO)	Ta= 0℃ , 300hours	
High Temperature Storage (HTS)	Ta= 60℃ , 300hours	
Low Temperature Storage (LTS)	Ta= -20℃ , 300hours	
Thermal Shock Test (TST)	-20℃/30min, 60℃/30min, 100 cycles	Note 4-1

- Note 4-1:** a. A cycle of rapid temperature change consists of varying the temperature from -20℃ to 60℃, and back again. Power is not applied during the test.
b. After finish temperature cycling, the unit is placed in normal room ambient for at least 4 hours before power on.

5 Shipping Label

5.1 Small Shipping Label

The label is on the PCBA as shown below :



5.2 Run Card Label

The label is on the panel as shown below :

M270HAN01-x/xx
xx:xxxxxxxxxx
Remark : X

0



SKD

S/N
xxxxxxxxxxxxxx (xxxxx)
Z
P
N
V

XXXXX	XXXXX	XXXXX		
XXXXX	XXXXX	XXXXX		
XXXXX	XXXXX	XXXXX		
XXXXX	XXXXX	XXXXX		



Avoid touching COF position when doing mechanical design

COMPONENTS SIDE(FACE UP)


NOTE:
 1. THE THICKNESS OF PCB IS 0.8mm.
 2. ... COMPONENTS FORBIDDEN AREA.
 3. ... BONDING AREA.
 4. ... LONG PATTERN.
 5. ... NO COMPONENT AREA.
 6. ... WHITE PATTERN.
 7. THE HEIGHT OF COMPONENTS ON PCB IS 2.2mm(MAX).
 8. ... SIDE SEALANT.

REV	REV NO.	DESCRIPTION	DATE
1	1	Rev. Release	10/10/2019



REV	REV NO.	DESCRIPTION	DATE
1	1	Rev. Release	10/10/2019

7 Packing Specification

7.1 Packing Flow



- Open cell : 18 (pcs/Box)
- Spacer : 19 (pcs/Box)



- 2 (Box/Layer)
- 10 (Layer/Pallet)

7.2 Pallet and shipment information

Item	Specification			Remark
	Q'ty	Dimension	Weight(kg)	
Box	1	780(L)mm x 545(W)mm x 161(H)mm	2.26	without cell & spacer
Packing Box	18pcs/Box	780(L)mm x 545(W)mm x 161(H)mm	14.09	with cell & Box & spacer
Pallet	1	1150(L)mm x 840(W)mm x 132(H)mm	13.6	
Pallet after Packing	20 boxes/pallet	1150(L)mm x 840(W)mm x 1330(H)mm	295.4	