On Uncertainty Estimation by Tree-based Surrogate Models in Sequential Model-based Optimization



Jungtaek Kim (POSTECH)

Seungjin Choi (BARO AI)



Introduction

- GP regression is a popular choice as a surrogate model, because of its capability of calculating uncertainties analytically.
- On the other hand, an ensemble of randomized trees is another option and has practical merits over GPs due to its scalability and easiness of handling continuous/discrete mixed variables.
- We revisit various ensembles of randomized trees to investigate their behavior in the perspective of prediction uncertainty estimation.
- Then, we propose our own tree-based model, referred to as BwO forest.

Uncertainty Estimation by Tree-based Models

• Sum-of-Trees Model: Posterior mean and variance functions are

$$\mu(\mathbf{x}; \{\mathcal{T}_b\}_{b=1}^B, \mathbf{X}, \mathbf{y}) = \frac{1}{B} \sum_{b=1}^B \sum_{\tau \in \boldsymbol{\tau}_{b,l}} \mu_{\tau} 1_{\mathbf{x} \in \tau},$$

$$\sigma^2(\mathbf{x}; \{\mathcal{T}_b\}_{b=1}^B, \mathbf{X}, \mathbf{y})$$

$$= \frac{1}{B} \sum_{b=1}^B \left(\left(\sum_{\tau \in \boldsymbol{\tau}_{b,l}} \sigma_{\tau} 1_{\mathbf{x} \in \tau} \right)^2 + \left(\sum_{\tau \in \boldsymbol{\tau}_{b,l}} \mu_{\tau} 1_{\mathbf{x} \in \tau} \right)^2 \right)$$

$$- \mu(\mathbf{x}; \{\mathcal{T}_b\}_{b=1}^B, \mathbf{X}, \mathbf{y})^2.$$
(iv)

• Gradient Boosting Models: It updates parameters θ using their gradients in terms of the objective of parametric dist., e.g., likelihood function.




Figure 1: Results with GP regression and tree-based models such as random forest, extremely randomized trees, BART, Mondrian forest, NGBoost, and BwO forest (ours).

Tree Construction

- The uncertainty of an ensemble is derived from the randomness of individual trees:
- (i) **bagging**: it samples a bootstrap sample with replacement and then aggregates base estimators;
- (ii) random feature selection: this technique randomly selects a feature from a set of dimensions;
- random split location: it randomly selects a split location between lower and upper bounds of the selected dimension;
- (iv) random tree sampling: this strategy randomly samples a tree under the assumption on a prior distribution.
- Random forest employs (i) and (ii), BART employs (i), (ii), and (iv), and Mondrian forest employs (i) and (iii).

Elaborating Uncertainty Estimation

• The expectation and variance of an indicator for the existence of \mathbf{x}_i in a bootstrap sample \mathbf{B} are expressed as

$$\mathbb{E}[1_{\mathbf{x}_i \in \mathbf{B}}] = 1 - \left(1 - \frac{1}{N}\right)^M,$$

$$\operatorname{Var}[1_{\mathbf{x}_i \in \mathbf{B}}] = \left(1 - \frac{1}{N}\right)^M - \left(1 - \frac{1}{N}\right)^{2M},$$
where N is the size of \mathbf{X} and M is the size of a bootstrap sample.

• The distribution of unique original elements in a bootstrap sample ${f B}$ is:

$$\mathbb{E}[|\text{unique}(\mathbf{B})|] = N - \frac{(N-1)^M}{N^{M-1}},$$

$$\text{Var}[|\text{unique}(\mathbf{B})|] = (N-1)\frac{(N-2)^M}{N^{M-1}} + \frac{(N-1)^M}{N^{M-1}} - \frac{(N-1)^{2M}}{N^{2M-2}},$$

where $unique(\mathbf{B})$ filters duplicates.

Algorithm 1 Training BwO Forest

Require: Ensemble size B, training data and evaluations $\mathbf{X} \in \mathbb{R}^{N \times d}$ and $\mathbf{y} \in \mathbb{R}^{N}$, size of bootstrap sample $M = \alpha N$ for an oversampling rate $\alpha > 1$.

Ensure: Set of decision trees $\{\mathcal{T}_b\}_{b=1}^B$

- 1: Initialize a set of decision trees.
- 2: **for** b = 1, ..., B **do**
- 3: Sample a bootstrap sample $\mathbf{B}_b \in \mathbb{R}^{M \times d}$ from \mathbf{X} .
- 4: Set a root node τ_r that contains all the elements in \mathbf{B}_b , and τ_r is set as the current split node.
- 5: Train a decision tree using random feature selection and random split location.
- 6: end for
- 7: **return** A set of decision trees $\{\mathcal{T}_b\}_{b=1}^B$




Figure 2: Experimental results on various benchmark functions.

Available on arXiv/GitHub





arXiv

GitHub