

a
Self-labelling data engine
subject
o_{26}
w_1
w_2
w_3
o_g
shoot
goal o_g
label $p(o_g)$
bearing 222°
elevation −1°
occupancy 18%
centre 895,351
read off the projected mesh:
no reward, no human label
$(o_s, p(o_g)) \mapsto (a_{s:s+8}, o_{s+1:s+8})$
12 orbits × 32 frames / placement
91 scenes × 102 subjects → 150k
b
World action model
p
tok
profile prompt
o_s
$\mathcal{E}$
z^0
clean
$o_{s+1:s+8}$
τ
$z_\tau^{1:2}$
noisy
$\epsilon \sim \mathcal{N}(0, I)$
$a_\tau \in \mathbb{R}^{8\times 10}$
W_a
×8
T V A
attention mask
no KV cache across chunks
VLM expert
Qwen3-VL-8B · frozen
K, V
joint attn · $T\|V\|A$
Q, K, V
World-action expert
trained
W^G_{qkv}
FFN^G
$+ \mathrm{emb}(\tau)$
×36
$\hat{o}_{s+4}$, $\hat{o}_{s+8}$
$\hat{v}_z$
$\mathcal{D}$
$\hat{v}_a$
Δt
R_{6D}
shoot
$\hat{a}$: 8 tokens × 10-D
6 moves, then shoot
$\mathcal{L} = \|\hat{v}_z - v_z\|^2 + \|\hat{v}_a - v_a\|^2$
rectified flow, shared τ
c
Deployment: intent → shot profile → closed-loop motion
the goal image is never shown to the policy
user intent
"A wide shot from her back-left, full body, centred, eye level."
or a reference photo
LLM / VLM
off-the-shelf
shot profile p
wide · back-left · eye level
centred · full body
bearing 214°
elevation −7°
occupancy 10%
centre 468,364
world action model
panel (b)
$\hat{a}_{1:8}$
start o_0
after chunk 2
after chunk 3
chunk 4 · shoot
d 2.01
0.98
0.41
0.066
shoot
execute 6 steps, capture
re-render o_t, next chunk