



Computer Engineering  
ISSN 1000-3428,CN 31-1289/TP

NCS2

DOI 10.19678/j.issn.1000-3428.0056214  
2020-03-26


NCS2

. <https://doi.org/10.19678/j.issn.1000-3428.0056214>





# 基于 NCS2 神经计算棒的车辆检测方法



(OSID):



## Vehicle detection method based on NCS2 neural compute stick


Jiang Xiaoyu, Li Zhongbing, Zhang Junhao, Peng Jiao, Wen Ting.

(School of Electrical Engineering and Information, Southwest Petroleum University, Chengdu 610500, China)

**Abstract** At present, most methods of deep learning to detect vehicles have high accuracy, but the real-time performance depends on PC or GPU devices with excellent performance, which limits its practical applications in embedded devices with relatively low performance. Therefore, an embedded vehicle detection system based on raspberry PI 3b+ is designed in this paper, which uses NCS2 neural computing rod (a miniature deep learning hardware driver) to provide deep learning acceleration for low-performance devices. A Tiny-YOLO network model based on depth separable convolution is proposed for real-time vehicle detection to improve the accuracy of target detection of embedded devices. Real-time experiments show that the real-time performance of the proposed algorithm is twice that of the original Tiny-YOLO algorithm. After the retrained network model is deployed to the raspberry PI 3b+ with NCS2 neural stick, the processing speed can reach 12 frames per second. At the same time, the improved algorithm improves the average detection accuracy by 1.12% and 0.23% respectively in MS COCO and VOC207 vehicle data sets.

**Key words** Vehicle detection; Depth separable convolution; Deep learning; Tiny-YOLO; Embedded device;

DOI:10.19678/j.issn.1000-3428.0056214.



201810615094

201801006095

(1996—)

E-mail:ceroo1005@gmail.com

Joseph Redmon<sup>14</sup> YOLO  
Tiny-Yolo

15 Tiny-YOLO  
depthwise separable

convolutions 16 NCS2  
12

## 2 YOLOV3

YOLOV3 Darknet53  
17 Darknet53 53

18

416× 416 Drknet53  
13× 13 26× 26 52× 52

1×1×(B×(5+C 1× 1 B

5+C  
 $t_x, t_y, t_w, t_h$  objectness C

YOLOV3

K-means 19 3

3  
 $P_x, P_y$

$G_x, G_y, G_w, G_h$  ground truth

4  $t_x, t_y, t_w, t_h$

$$\begin{aligned} t_x &= G_x - P_x \\ t_y &= G_y - P_y \\ t_w &= \log(G_w / P_w) \\ t_h &= \log(G_h / P_h) \end{aligned} \quad (1)$$

ground truth

1




Fig.1 The offset between prior box and prediction box

$$\begin{pmatrix} c_x & c_y \end{pmatrix} \begin{pmatrix} c_x & c_y \end{pmatrix} P_x, P_y$$

$$b_x, b_y, b_w, b_h \quad 1$$

$$t_x, t_y, t_w, t_h \quad b_x = \sigma(t_x) + c_x$$

$$b_y = \sigma(t_y) + c_y$$

$$b_w = P_w e^{t_w} \quad (2)$$

$$b_h = P_h e^{t_h}$$

$\sigma$  sigmoid  $1 \times 1$   
sigmoid  $t_x, t_y$  0 1

$$G_w / P_w \quad G_h / P_h$$

$$P_w \quad P_h$$

objectness

$$C_{\text{Object}} = P_{\text{Object}} \times \text{IOU}_{\text{pred}}^{\text{truth}} \quad (3)$$

$$P_{\text{Object}}=1 \quad 0 \quad \text{IOU}$$

ground truth

YOLOV3 B 3 C 80

3 80


## 3 Tiny-YOLO

Tiny YOLO

13× 13 26× 26

MobileNet<sup>20</sup>

(depthwise convolution)  
convolution)



**Fig.2 The structure of deep separable convolution**

$$\mathbf{F} \in \mathbb{R}^{D_f \times D_f \times M}$$

$$\mathbf{K} \in \mathbb{R}^{D_k \times D_k \times M \times N} \quad D_k \times D_k$$

$$\mathbf{G}_{k,l,n} = \sum_{i,j,m} \mathbf{K}_{i,j,m,n} \cdot \mathbf{F}_{k+i-1,l+j-1,m} \quad (4)$$

$$O_{(\text{conv})} = D_K \cdot D_K \cdot M \cdot N \cdot D_f \cdot D_f$$

$$\mathbf{F} \in \mathbb{R}^{D_f \times D_f \times M}$$

$$\begin{aligned} \hat{\mathbf{K}} &\in \mathbb{R}^{D_k \times D_k \times 1 \times M} \\ \hat{\mathbf{G}}_{k,l,m} &= \sum_{i,j} \hat{\mathbf{K}}_{i,j,m} \cdot \mathbf{F}_{k+i-1,l+j-1,m} \end{aligned} \quad (5)$$

$$O'_{(\text{conv})} = D_K \cdot D_K \cdot M \cdot D_f \cdot D_f + M \cdot N \cdot D_f \cdot D_f$$

$$\frac{\dot{O}_{(\text{conv})}}{O_{(\text{conv})}} = \frac{D_K \cdot D_K \cdot M \cdot D_f \cdot D_f + M \cdot N \cdot D_f \cdot D_f}{D_K \cdot D_K \cdot M \cdot N \cdot D_f \cdot D_f} = \frac{1}{N} + \frac{1}{D_K^2} \quad (6)$$

### 3.2 Tiny-YOLO

Tiny-YOLO

3 " S Conv  $3 \times 3$ "

Tiny-YOLO

3 " Conv  $3 \times 3$ "

1

Tiny-YOLO

" Maxpool"


Tiny-YOLO

**1**


**3x3**

**Tab.1 3 x 3 convolution information in the original network**



|   |     |      |            |            |
|---|-----|------|------------|------------|
| 1 | 3x3 | 16   | 416x416x3  | 416x416x16 |
| 2 | 3x3 | 32   | 208x208x16 | 208x208x32 |
| 3 | 3x3 | 64   | 104x104x32 | 104x104x64 |
| 4 | 3x3 | 128  | 52x52x64   | 52x52x128  |
| 5 | 3x3 | 256  | 26x26x128  | 26x26x256  |
| 6 | 3x3 | 512  | 13x13x256  | 13x13x512  |
| 7 | 3x3 | 1024 | 13x13x512  | 13x13x1024 |
| 8 | 3x3 | 512  | 13x13x256  | 13x13x512  |
| 9 | 3x3 | 256  | 13x13x384  | 13x13x256  |




**3 Tiny-YOLO**  
**Fig.3 Original and improved Tiny-YOLO network structure**



4.1



(a) comparison of calculation amount before and after replacing structure



(b) total calculation  
Fig.5 (a) is the calculation amount of the replacement structure part, and (b) is the total calculation amount of the algorithm

2.74× 10^11  
0.39× 10^11  
86%

4.3

Average Precision MAP

$$m_{AP} = \int_0^1 P(R) dR \quad (7)$$

P R P(R)


Frames Per Second FPS

| Tab.2 Comparison between this algorithm and the original algorithm |        |        |      |     |
|--|--------|--------|------|-----|
| MAP  |        |        |      |     |
|  | VOC    | COOC   | MB   | FPS |
| Tiny-YOLO  | 55.66% | 33.10% | 34.6 | 2   |
|  | 55.89% | 34.22% | 22.4 | 4   |
| NCS2   | 54.12% | 34.21% | 13.2 | 12  |

4.2

Fig.4 Development flow chart

Tiny-YOLO 9  
5



6  
Fig.6 Effect contrast

Tiny-YOLO

- [1] Dalal, N, Triggs, B. Histograms of Oriented Gradients for Human Detection. In 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05); IEEE, 2005, Vol. 1, 886–893.
- [2] David G.Lowe. Object Recognition from Local Scale-Invariant Features. In Proceedings of the Seventh IEEE International Conference on Computer Vision; IEEE: 1999, vol. 2, 1150–1157.
- [3] Sánchez A, V. David. Advanced Support Vector Machines and Kernel Methods. Neurocomputing, 2003, 55 (1–2), 5–20.
- [4] Artue Ferreira, Mario Figueiredo. Boosting Algorithms: A Review of Methods, Theory, and Applications. In Ensemble Machine Learning, 2012, 35–85.
- [5] Friedman, Jerome. Greedy Function Approximation: A Gradient Boosting Machine. The Annals of Statistics. 2000
- [6] David E, Rumelhart, Geoffrey E, Hinton, Ronald J. Williams. Learning Representations by Back-Propagating Errors. 1986, 533–536
- [7] Shaoqing Ren, Kaiming He, Ross Girshick, Jian Sun. Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks. arXiv:1506.01497 [cs] 2015.
- [8] Tao Kong, Anbang Yao, Yurong Chen, Fuchun Sun. HyperNet: Towards Accurate Region Proposal Generation and Joint Object Detection. In 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR); IEEE, 2016, 845–853.
- [9] Ross Girshick, Jeff Donahue, Trevor Darrell, Jitendra Malik. Rich Feature Hierarchies for Accurate Object Detection and Semantic Segmentation. arXiv:1311.2524

- 
- [cs] 2013.
- [10] Ross Girshick. Fast R-CNN. arXiv:1504.08083 [cs] 2015.
- [11] Joseph Redmon, Santosh Divvala, Ross Girshick, Ali Farhadi. You Only Look Once Unified, Real-Time Object Dete. arXiv:1506.02640 [cs] 2015.
- [12] Joseph Redmon, Ali Farhadi. YOLO9000 Better, Faster, Stronger. arXiv:1612.08242 [cs] 2016.
- [13] Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy. SSD: Single Shot MultiBox Detector. arXiv:1512.02325 [cs] 2016.
- [14] Joseph Redmon, Ali Farhadi. YOLOv3: An Incremental Improvement. arXiv:1804.02767 [cs] 2018.
- [15] ZHANG Yangshuo, MIAO Zhuang, WANG Jiabao, LI Yang. Pedestrian detection method based on Movidius neural computing stick. Journal of Computer Applications[j], 2019, 39 (08), 2230–2234. ;  
; . Movidius  
2019, 39 (08), 2230–2234.
- [16] Francois Chollet. Xception: Deep Learning with Depthwise Separable Convolutions. In 2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR);IEEE,2017 1800–1807.
- [17] Jonathan Long, Evan Shelhamer, Trevor Darrell. Fully Convolutional Networks for Semantic Segmentation; IEEE, 2016, 640–651
- [18] Kaiming He, Xiangyu Zhang, Shaoqing Ren. Deep Residual Learning for Image Recognition. arXiv:1512.03385 [cs] 2015.
- [19] Kiri Wagstaff, Claire Cardie, Seth Rogers, Stefan Schroedl. Constrained K-Means Clustering with Background Knowledge. Proceedings of 18th International Conference on Machine Learning[j], 2001, 577-584
- [20] Andrew G. Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko. MobileNets: Efficient Convolutional Neural Networks for Mobile Vision Applications. arXiv:1704.04861 [cs] 2017.